FIBRILLOGENIC PROPENSITY - LAGTIME ESTIMATIONS

A PREPRINT

Shahin Zibaee*
Unaffiliated

October 23, 2026

ABSTRACT

I present the results of the calculated estimates of fibrillogenic propensity of proteins involved in the formation of amyloid fibrils in human diseases. The data processing and prediction model are presented in a new web application called Lagtime Estimator. The original form of this prediction model developed in a study alpha-synuclein fibrillogenesis *in vitro* completed over 15 years ago. The study focused on the earliest phase of fibril formation. Over the past 12 years, a significant amount of new structural data of mature amyloid fibrils has emerged, placing a strong focus on the A number of new disease-causing mutations have also been discovered. As such, the current study attempts to assess the place for examining the process of interpreting amyloid fibril formation from these three distinct modalities: sequence determinants for kinetics of fibrilloegensis, computational rationalisation and near-atomic structures of end-point amyloid fibrils. A holistic and speculative model that attempts to tie these together is presented.

Keywords sequence analysis · bioinformatics

1 Introduction

A Simple ALgorithm of Sliding Averages (SALSA) was originally designed for the purpose of estimating the propensity for β-sheets in amyloid formation by natively unfolded proteins. It uses a novel and relatively crude sliding window computation in which the property of interest is calculated for each window as an average over that window. There are three aspects of this algorithm which, in their combination, provide for an interesting and potentially more widely useful way to estimate a local properties within a sequence.

2 Implementation details

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. See Section 2.

2.1 Algorithm design

The design of SALSA was heavily influenced by (a) the specific process it was being designed for helping to elucidate. Namely, the rate at which the earliest stages of detectable amyloid fibrils were forming for recombinant Synuclein-constructs in vitro. (b) the mental model I was leaning towards regarding the very earliest stages of amyloid fibril formation was of a large number of candidate amyloid β-sheets rapidly nucleating, extending along the primary

*Use footnote for providing further information about author (webpage, alternative address)—*not* for acknowledging funding agencies.

structure, 'competing' with other nascent $beta$-sheets within the same cluster of proteins, and mostly then collapsing. This brought with it the notion of proteins' sampling a large variety of inter-protein cross-β structures, until eventually, one or more sufficiently stable forms were able to persist for long enough, while also being sufficiently fragile enough to fragment. The latter property being essential for the much faster template-driven growth cycle (also known as the heterogeneous nucleation phase). One of a few Synuclein constructs that appeared to demonstrate the impact of the length of an amyloid-favourable contiguous region (a property I later referred to as 'β-strand contiguity') was α-Synuclein(1-70). This C-terminally truncated construct displayed both an inability to assemble, as well as a potent ability to assembly with a very short lag time. In the latter, it displayed a stunted ability for assembly into typically amyloid fibrils. This was in stark contrast to Synuclein constructs that were just a few residues longer. For example α-syn(1-75) assembly into fibrils was both very fast and prolific. As such, the point of the detail above is to make clear that although SALSA is a relatively abstract and unsophisticated computation, the motivation governing its design was very much grounded in data from careful, detailed and rigorously repeated laboratory experiments. In other words, the design of SALSA was driven by adherence to a mental model of molecular events indirectly informed by the measured kinetics of those events.

I take this opportunity to shed light on it. A precursor sliding window algorithm was conceived by myself in 2002, using a fixed window size, the calculation for each window was the propensity for a protein sequence to form contiguous β-sheets, interspersed by turns. As such, this placed a pre-determined template on the primary structure of the candidate sequence. The motivation for this algorithm was to attempt to address the question of how different protein sequences sharing little to no identity with one another could share the propensity to form amyloid fibrils. The assumption I made was that, in the absence of sequence identity across the different amyloid forming protein, a quantitative rationale was the only measure that made sense - in other a thermodynamic propensity rather than a 'killer fold'. I was essentially of the view that the propensity for amyloid to start forming was dominated by thermodynamics more than determinants of protein folding. In 2003, the notion of

This was governed by a mental model of amyloid assembly in vitro, in that the very earliest stages of amyloid beta-sheet formation was highly dynamic and varied, with multiple rapidly forming inter-protein β-sheets starting, extending

$$\xi_{ij}(t) = P(x_t = i, x_{t+1} = j|y, v, w; \theta) = \frac{\alpha_i(t) a_{ij}^{w_t} \beta_j(t+1) b_j^{v_{t+1}}(y_{t+1})}{\sum_{i=1}^{N} \sum_{j=1}^{N} \alpha_i(t) a_{ij}^{w_t} \beta_j(t+1) b_j^{v_{t+1}}(y_{t+1})} \tag{1}$$

2.1.1 Headings: third level

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Paragraph Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

3 Examples of citations, figures, tables, references

3.1 Citations

Citations use `natbib`. The documentation may be found at

`http://mirrors.ctan.org/macros/latex/contrib/natbib/natnotes.pdf`

Here is an example usage of the two main commands (`citet` and `citep`): Some people thought a thing [Kour and Saabne, 2014a, Hadash et al., 2018] but other people thought something else [Kour and Saabne, 2014b]. Many people have speculated that if we knew exactly why Kour and Saabne [2014b] thought this...




Figure 1: Sample figure caption.

Table 1: Sample table title

	Part	
Name	Description	Size (μm)
Dendrite	Input terminal	$\sim$100
Axon	Output terminal	$\sim$10
Soma	Cell body	up to 10^6

3.2 Figures

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi. See Figure 1. Here is how you add footnotes. [2] Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

3.3 Tables

See awesome Table 1.

The documentation for `booktabs` ('Publication quality tables in LaTeX') is available from:

`https://www.ctan.org/pkg/booktabs`

3.4 Lists

- Lorem ipsum dolor sit amet
- consectetur adipiscing elit.
- Aliquam dignissim blandit est, in dictum tortor gravida eget. In ac rutrum magna.

References

George Kour and Raid Saabne. Real-time segmentation of on-line handwritten arabic script. In *Frontiers in Handwriting Recognition (ICFHR), 2014 14th International Conference on*, pages 417–422. IEEE, 2014a.

Guy Hadash, Einat Kermany, Boaz Carmeli, Ofer Lavi, George Kour, and Alon Jacovi. Estimate and replace: A novel approach to integrating deep neural networks with existing applications. *arXiv preprint arXiv:1804.09028*, 2018.

[2] Sample of the first footnote.

George Kour and Raid Saabne. Fast classification of handwritten on-line arabic characters. In *Soft Computing and Pattern Recognition (SoCPaR), 2014 6th International Conference of*, pages 312–318. IEEE, 2014b. doi:10.1109/SOCPAR.2014.7008025.