ICSV27 27th International Congress on Sound and Vibration
The annual congress of the International Institute of Acoustics and Vibration (IIAV)
11-16 July, 2021

Sound transmission through a curved sandwich panel

A solution to the coincidence and ring frequency effect

Zibo Liu, Wuzhou Yu, Qi Li

Content

- Introduction
- Sandwich panel and coincidence effect
- Curved panel and ring frequency effect
- Curved sandwich and design criteria
- Conclusion

Sound insulation

Noise reduction engineering

Isolation for sound transmission path

Sound insulation/sound transmission loss properties

Introduction to the sound transmission through panels







D'Alessandro, V., Petrone, G., Franco, F., & De Rosa, S. (2013). A review of the vibroacoustics of sandwich panels: Models and exp
of Sandwich Structures & Materials, *15*(5), 541-582.

Coincidence effect

$$\lambda_{\mathbf{trace}} = \lambda_{\mathbf{bending}}$$



Infinite panel



Variation of *TL* with frequency for a single angle of incidence



Sandwich panels



Advantage:
- low mass
- high stiffness

Disadvantage:
- bad acoustic properties (sound insulation)
  - ➢ Broad coincidence region
  - ➢ often drops to the low frequency range

Early works:
- move coincidence out of frequency range of interest
- metamaterial design





New solution:

Curved sandwich→ stiffness to stiffness

Moore, J. A., & Lyon, R. H. (1991). Sound transmission loss characteristics of sandwich panel constructions. The Journal of the Acoustical Society of Amer

Liu, Z., Rumpler, R., & Feng, L. (2018). Broadband locally resonant metamaterial sandwich plate for improved noise insulation in the coincidence region. Composite S

Sound transmission through a single-layer panel





$\varphi = 0; \theta = \frac{\pi}{3}$

$$\hat{p}_1 = \hat{p}_{\text{inc}} + \hat{p}_{\text{ref}}$$

$$\hat{p}_2 = \hat{p}_{\text{trans}}$$



- Continuity of Velocity: $\rho_0 \dfrac{\partial \vec{v}_z}{\partial t} = -\vec{\nabla}_z \hat{p}_1 = -\vec{\nabla}_z \hat{p}_2$

- Newton's second law:

For a limp wall: $\hat{p}_1 - \hat{p}_2 = \mathrm{j}\omega m \hat{v}$

For a thin plate: $\hat{p}_1 - \hat{p}_2 = \left(D\nabla^4 - \omega^2 m\right)\hat{v} / \mathrm{j}\omega$

Under the Thin Plate Assumption:



Sound transmission through a single-layer panel

- Transmission coefficient: $\tau = \left|\dfrac{\hat{p}_{\text{trans}}}{\hat{p}_{\text{inc}}}\right|^2 = \left|1 + \dfrac{Z\cos\theta}{2\rho_0 c_0}\right|^{-2}$ $\quad \text{STL} = 10\log\left(\dfrac{1}{\tau}\right)$

$Z = \dfrac{\hat{p}_1 - \hat{p}_2}{\hat{v}}$ is the corresponding plate impedance.

$$Z_0 = \mathrm{j}\omega m\left(1 - k^4\frac{D}{\omega^2 m}\sin^4\theta\right) = \mathrm{j}\omega m\left(1 - \frac{k^4}{\kappa^4}\sin^4\theta\right)$$

- Coincidence effect: $\kappa = k\sin\theta$ $\quad f_{\text{co}} = \dfrac{1}{2\pi}\dfrac{c_0^{\,2}}{\sin^2\theta}\sqrt{\dfrac{m}{D}}$

$$\Rightarrow \quad Z_0 = \mathrm{j}\omega m\left(1 - \frac{f^2}{f_{\text{co}}^{\,2}}\right)$$

When $Z = 0$, coincidence effect occurs, total transmission is induced.



Sound transmission through a sandwich panel



- **Equation of in-phase motion:**





In-phase Mode:



- $$-2D_S D_f \frac{\partial^6 w}{\partial x^6} + 2D_f I_S \frac{\partial^6 w}{\partial t^2 \partial x^4} - (D_S m + 2D_f m + I_S G_c t_c) \frac{\partial^4 w}{\partial t^2 \partial x^2} + G_c t_c \left(D_S \frac{\partial^4 w}{\partial x^4} + m \frac{\partial^2 w}{\partial t^2} \right) + I_S m \frac{\partial^4 w}{\partial t^4} = 0$$

Anti-phase Mode:



- $$2D_S D_f k_x^{\,6} - 2D_f I_S \omega^2 k_x^{\,4} - (D_S m + 2D_f m + I_S G_c t_c)\omega^2 k_x^{\,2} + G_c t_c (D_S k_x^{\,4} - m\omega^2) + I_S m \omega^2 = 0$$

$$D_f = \frac{E_f t_f^{\,3}}{12\left(1-\nu_f^{\,2}\right)}$$

$$D_S = \frac{E_c t_c^{\,3}}{12\left(1-\nu_c^{\,2}\right)} + \frac{E_f}{\left(1-\nu_f^{\,2}\right)} \left(\frac{t_c^{\,2} t_f}{2} + t_c t_f^{\,2} + \frac{2}{3} t_f^{\,3} \right)$$

$$G_c = \frac{E_c}{2\left(1+\nu_c\right)}$$

$$I_S = \frac{1}{12}\rho_c t_c^{\,3} + \rho_f \left(\frac{t_c^{\,2} t_f}{2} + t_c t_f^{\,2} + \frac{2}{3}$$

Sound transmission through a sandwich panel



- **Equation of in-phase motion:**





In-phase Mode:



- $-2D_S D_f \frac{\partial^6 w}{\partial x^6} + 2D_f I_S \frac{\partial^6 w}{\partial t^2 \partial x^4} - (D_S m + 2D_f m + I_S G_c t_c) \frac{\partial^4 w}{\partial t^2 \partial x^2} + G_c t_c \left(D_S \frac{\partial^4 w}{\partial x^4} + m \frac{\partial^2 w}{\partial t^2} \right) + I_S m \frac{\partial^4 w}{\partial t^4} = 0$

Anti-phase Mode:



- ➢ $2D_S D_f {k_x}^6 - 2D_f I_S \omega^2 {k_x}^4 - (D_S m + 2D_f m + I_S G_c t_c) \omega^2 {k_x}^2 + G_c t_c (D_S {k_x}^4 - m\omega^2) + I_S m \omega^2 = 0$



Sound transmission through a sandwich panel



Thin plate assumption

Bending wavenumber κ_2



- Sandwich plate impedance

$$Z_{\mathrm{Sa}} = \mathrm{j}\omega m\left(1-\frac{k^4}{\kappa_2^{\ 4}}\sin^4\theta\right) = \mathrm{j}\omega m\left(1-\frac{f^{\,2}}{f_{\mathrm{Sco}}^{\ \ 2}}\right)$$

$$f_{\mathrm{Sco}} = \frac{1}{2\pi}\frac{c_0}{\sin^2\theta}\frac{\kappa_2^{\ 2}}{k}$$

is a symbolic expression,
and is a function of frequency.



Sound transmission through a sandwich panel





Thin plate assumption

Bending wavenumber κ_2



- Sandwich plate impedance

$$Z_{\mathrm{Sa}} = \mathrm{j}\omega m\left(1-\frac{k^4}{\kappa_2{}^4}\sin^4\theta\right) = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{Sco}}{}^2}\right)$$

$$f_{\mathrm{Sco}} = \frac{1}{2\pi}\frac{c_0}{\sin^2\theta}\frac{\kappa_2{}^2}{k}$$

is a symbolic expression, and is a function of frequency.



Sound transmission through a sandwich panel



Thin plate assumption

Bending wavenumber κ_2



- Sandwich plate impedance

$$Z_{\mathrm{Sa}} = \mathrm{j}\omega m\left(1-\frac{k^4}{\kappa_2{}^4}\sin^4\theta\right) = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{Sco}}{}^2}\right)$$

$$f_{\mathrm{Sco}} = \frac{1}{2\pi}\frac{c_0}{\sin^2\theta}\frac{\kappa_2{}^2}{k}$$

is a symbolic expression,
and is a function of frequency.



Sound transmission through a sandwich panel







Single-leaf:

$$Z_0 = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{co}}^{\;2}}\right)$$

Sandwich:

$$Z_{\mathrm{Sa}} = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{Sco}}^{\;2}}\right)$$



Intention:

- **Integrate the ring frequency effect**

Curved panels





Curved panel:

- Aeronautical/aerospace engineering

Ring frequency effect

$$\textbf{circumference} = \lambda_{\textbf{longitudinal}}$$

Ring frequency effect



$$\lambda_{\mathbf{trace}} = \lambda_{\mathbf{bending}}$$





$$\mathbf{circumference} = \lambda_{\mathbf{longitudinal}}$$

Hard to overcome



Ring frequency effect



$$Z = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\text{co}}^{\;2}}\right)$$

$$Z_{\text{eff}} = Z + Z_{\text{eq}}^{\text{r}}$$





$$Z = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\text{co}}^{\;2}}-\frac{f_{\text{ri}}^{\;2}}{f^2}\right)$$

$$Z_{\text{eff}} = Z + Z_{\text{eq}}^{\text{r}}$$



- *Unlike for the coincidence effect*
- *‘Side effects’ are observed in the ring frequency region*

Impedance of curved panels

Impedance of a slightly curved shell:

$$Z = \mathrm{j}\omega m\left(1 - \frac{f^2}{f_{\mathrm{co}}^2} - \frac{f_{\mathrm{ri}}^2}{f^2}\right) \qquad f_{\mathrm{ri}} = \frac{c_l}{2\pi R}$$



Finite Element model of the section of the shell at the frequency where the worst sound transmission loss occurs:



- Mathematically: minimum impedance
- Physically: maximum radiation efficiency



Ring frequency effect



Recall: control region

Mass to stiffness

Stiffness to mass



Overcome the ring frequency effect







Overcome the ring frequency effect

Condition:

- *The impedance is enforced not equal to zero*

$$Z = \mathrm{j}\omega m\left(1 - \frac{f^2}{f_{\mathrm{co}}^{\;2}} - \frac{f_{\mathrm{ri}}^{\;2}}{f^2}\right) \neq 0$$

Such that

$$f_{\mathrm{ri}} > \frac{1}{2} f_{\mathrm{co}}$$

→ **Design criterion**

Overcome the ring frequency effect





Too thick, not realistic



Impedance of curved sandwich panels

recall

Single-leaf: $$Z_0 = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{co}}{}^2}\right)$$

Sandwich: $$Z_{\mathrm{Sa}} = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{Sco}}{}^2}\right)$$

Curved: $$Z = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{co}}{}^2}-\frac{f_{\mathrm{ri}}{}^2}{f^2}\right)$$



Therefore:

Curved sandwich: $$Z = \mathrm{j}\omega m\left(1-\frac{f^2}{f_{\mathrm{Sco}}{}^2}-\frac{f_{\mathrm{Sri}}{}^2}{f^2}\right)$$

$$f_{\mathrm{Sco}} = \frac{1}{2\pi}\frac{c_0}{\sin^2\theta}\frac{\kappa^2}{k}$$

$$f_{\mathrm{Sri}} = \frac{1}{2\pi R}\sqrt{\frac{2E_{\mathrm{f}}{}^*t_{\mathrm{f}} + E_{\mathrm{c}}{}^*t_{\mathrm{c}}}{m}}$$

→ **Design criterion applicable to sandwich** $f_{\mathrm{Sri}} > \frac{1}{2} f_{\mathrm{Sco}}$

Curved sandwich panels

Ef	nuf	rhof	Ec	nuc	rhoc	tf	tc	fco
6.9e10	0.3	2700	8e8	0.3	500	2mm	2cm	760 Hz

when $f_{\mathrm{ri}} < \frac{1}{2} f_{\mathrm{co}}$





Curved sandwich panels

Ef	nuf	rhof	Ec	nuc	rhoc	tf	tc	fco
6.9e10	0.3	2700	8e8	0.3	500	2mm	2cm	760 Hz

when $f_{\text{ri}} > \frac{1}{2} f_{\text{co}}$





Conclusion

- An impedance approach is developed

$$Z = \mathrm{j}\omega m\left(1 - \frac{f^2}{f_{\mathrm{Sco}}^2} - \frac{f_{\mathrm{Sri}}^2}{f^2}\right)$$

- A design criterion is proposed to overcome the coincidence and ring frequency effects

$$f_{\mathrm{ri}} > \frac{1}{2} f_{\mathrm{co}}$$

- Physical insights into coincidence and ring frequency effect is illustrated