Python Basics!

functions, scope

CS101 Lecture #4

Administrivia

Administrivia 1/25

Administrivia

- Register your i>clickers on the course Compass page-attendance counts from today!
- Complete Homework #1 before 5:00 p.m. today.
- ▶ Homework #2 is due Friday Sep. 9.
- No lab next week (Labor Day).

Administrivia 2/2:

Warmup Quiz

Warmup Quiz 3/25

```
x = "3"
y = 10 % 4
print(x * y)
```

What does this program print?

A 6

B 2

C 33

D 32

Warmup Quiz 4/25

```
c = (10 + 5j)
i = 25
r = c.real + i
What is the type and value of \mathbf{r}?
 A int, 35
 B complex, 35 + 5j
 C float, 35.0
 D complex, 35 + 0j
```

Warmup Quiz 5/2

Which of these expressions will cause an **overflow**?

```
A 10 ** 100000
```

B "10" * 100000

C 10.0 ** 100000

D "10" ** 100000

E None of the above

Warmup Quiz 6/25

```
x = "10"
v = "%i"
print( (x+y) % 2)
What does this program print?
 A 102
 B 1111
 C 1010
 D None of the above
```

Warmup Quiz 7/2

Strings Redux

Strings

- ♣ As a literal: text surrounded by quotes.
 - "DEEP"
- Each symbol is a character.
- Unlike numeric types, strings vary in length.

String operations

- **Concatenation**: combine two strings
 - Uses the + symbol
 - 'RACE' + 'CAR'
- Repetition: repeat a string
 - Uses the *
 - . 'HELLO '*10
- Formatting: used to encode other data as string
 - Uses % symbol

Formatting operator

- Creates string with value inserted
 - Formats nicely
 - Requires indicator of type inside of string "%i" int "%f" float "%e" float (scientific notation) "%s" str

Example

Strings Redux 12/2:

Indexing operator []

Extracts single character
a = "FIRE"
a[0]

- ➤ The integer is the index.
- We count from zero!
- ▶ If negative, counts down from end.

Extracts range of characters (substring)

- Extracts range of characters (substring)
- Range specified inside of indexing operator

- Extracts range of characters (substring)
- Range specified inside of indexing operatora = "FIREHOUSE"a[0:4]

- Extracts range of characters (substring)
- Range specified inside of indexing operatora = "FIREHOUSE"a[0:4]
- Can be a bit tricky at first:
 - Includes character at first index
 - Excludes character at last index

Example

```
alpha = "ABCDE"
x = alpha[1:3]
What is the value of x?
 A 'AB'
 B 'ABC'
 C'BC'
 D'BCD'
 E 'CD'
```

Functions

➤ A function is a small program (block of code) we can run within Python.

unctions 17/2s

- ► A function is a small program (block of code) we can run within Python.
 - Saves us from rewriting code
 - Don't reinvent the wheel!

- ► A function is a small program (block of code) we can run within Python.
 - Saves us from rewriting code
 - Don't reinvent the wheel!
- Analogy: Functions are more verbs.

unctions 17/2.

- ► A function is a small program (block of code) we can run within Python.
 - Saves us from rewriting code
 - Don't reinvent the wheel!
- Analogy: Functions are more verbs.
- Also called subroutine or procedure.

When we want to execute a function, we call or invoke it.

- When we want to execute a function, we call or invoke it.
- Use name of the function with parentheses.

- When we want to execute a function, we call or invoke it.
- Use name of the function with parentheses.

print()

- When we want to execute a function, we call or invoke it.
- Use name of the function with parentheses.
 - print()
- Many functions come built-in to Python or in the standard library.

- When we want to execute a function, we call or invoke it.
- Use name of the function with parentheses.
 - print()
- Many functions come built-in to Python or in the standard library.
- Others we will compose at need.

▶ Functions can act on data.

- Functions can act on data.
- ▶ Arguments are the input to functions.

- Functions can act on data.
- ▶ Arguments are the input to functions.
- Functions can return a value. (fruitful)

- Functions can act on data.
- ▶ Arguments are the input to functions.
- Functions can return a value. (fruitful)
- Return values are the output of a function.

unctions 19/2s

- Functions can act on data.
- ▶ Arguments are the input to functions.
- Functions can return a value. (fruitful)
- Return values are the output of a function.
 - print('10')
 - len('Rex Kwon Do')
 - abs(-123)

functions 19/2.

▶ Arguments are values passed to a function.

Functions 20/2:

- ▶ Arguments are values passed to a function.
- A function can accept zero to many arguments.

-unctions 20/2.

- ▶ Arguments are values passed to a function.
- A function can accept zero to many arguments.
- Multiple arguments are separated by commas:

```
min( 1,4,5 )
max( 1,4,5 )
```

unctions 20/25

Type conversion.

A set of built-in functions to convert data from one type to another.

-unctions 21/2.

Type conversion.

▶ A set of built-in functions to convert data from one type to another.

```
float( "0.3" )
str( 3 + 5j )
```

Type conversion.

▶ A set of built-in functions to convert data from one type to another.

```
float( "0.3" )
str( 3 + 5j )
```

▶ Be careful of nonsense:

```
int( "Rex" )
int( 3 + 5j )
```

Also called subroutine or procedure.

-unctions 21,

Userinput

• input is a built-in function.

Functions 22/2

Userinput

- **input** is a built-in function.
- Argument: string prompting user

Functions 22/2

Userinput

- **input** is a built-in function.
- Argument: string prompting user
- ▶ Return value: input from user (as str)

Functions 22/2.

Goal

▶ A program should achieve a goal.

Functions 23/25

Goal

- A program should achieve a goal.
- Next time we will write our first nontrivial program.

-unctions 23/25

Reminders

Reminders 24/25

Reminders

- ▶ Homework #1 due today, Aug. 31, 5:00 p.m.
- ► Homework #2 due Friday, Sep. 9, 5:00 p.m.
- No class Monday, Sep. 5 (Labor Day).
- No lab next week!

Reminders 25/25