

Python Basics!

functions, scope

CS101 Lecture #4

Administrivia

- ✦ Register your i>clickers on the course Compass page—attendance counts from today!

Administrivia

- ✚ Register your i>clickers on the course Compass page—attendance counts from today!
 - Don't panic!

- ✦ Register your i>clickers on the course Compass page—attendance counts from today!
 - Don't panic!
- ✦ Complete Homework #1 before 6:00 p.m. today.

- ✦ Register your i>clickers on the course Compass page—attendance counts from today!
 - Don't panic!
- ✦ Complete Homework #1 before 6:00 p.m. today.
- ✦ Homework #2 is due Friday Sep. 9.

- ❖ Register your i>clickers on the course Compass page—attendance counts from today!
 - ❖ Don't panic!
- ❖ Complete Homework #1 before 6:00 p.m. today.
- ❖ Homework #2 is due Friday Sep. 9.
- ❖ No lab next week (Labor Day).

Warmup Quiz

Question #1

```
x = "3"  
y = 10 % 4  
print(x * y)
```

What does this program print?

- A 6
- B 2
- C 33
- D 32

Question #2

```
c = (10 + 5j)
i = 25
r = c.real + i
```

What is the type and value of r?

- A int, 35
- B complex, 35 + 5j
- C float, 35.0
- D complex, 35 + 0j

Question #3

Which of these expressions is most likely to cause an **overflow**?

A `10 ** 100000`

B `"10" * 100000`

C `10.0 ** 100000`

D `"10" ** 100000`

E None of the above

Question #4

```
x = "10"  
y = "%i"  
print( (x+y) % 2)
```

What does this program print?

- A 102
- B 1111
- C 1010
- D None of the above

Data Types—A Few Points

Complex numbers, \mathbb{C}

- Represent numbers with an imaginary component.
- Use j for i :
 $z = 1.0 + 1j$

Complex numbers, \mathbb{C}

- Represent numbers with an imaginary component.
- Use j for i :
 $z = 1.0 + 1j$
- $z.\text{real} + z.\text{imag} * 1j$

Strings

- ❖ As a literal: text surrounded by quotes.
 - ❑ "DEEP"
- ❖ Each symbol is a character.
- ❖ Unlike numeric types, strings vary in length.

String operations

- **Concatenation:** combine two strings
 - Uses the + symbol
 - 'RACE' + 'CAR'
- **Repetition:** repeat a string
 - Uses the *
 - 'HELLO '*10
- **Formatting:** used to encode other data as string
 - Uses % symbol

Formatting operator

- Creates string with value inserted
 - Formats nicely
 - Requires indicator of type inside of string
 - `"%i"` `int`
 - `"%f"` `float`
 - `"%e"` `float` (scientific notation)
 - `"%s"` `str`

Example

```
print( "An integer:  %i" % 7 )  
print( "A float:     %f" % 7.0 )  
print( "A float:     %e" % 7.0 )  
print( "A string:    %s" % 'seven' )
```

Indexing operator `[]`

- ▣ Extracts single character

```
a = "FIRE"
```

```
a[0]
```

- ▣ The integer is the index.

Indexing operator `[]`

- ✦ Extracts single character
 `a = "FIRE"`
 `a[0]`
- ✦ The integer is the index.
- ✦ We count from zero!

Indexing operator `[]`

- ✦ Extracts single character
 `a = "FIRE"`
 `a[0]`
- ✦ The integer is the index.
- ✦ **We count from zero!**
- ✦ If negative, counts down from end.

Indexing operator `[]`

- ✦ Extracts single character

```
a = "FIRE"  
a[0]
```

- ✦ The integer is the index.
- ✦ **We count from zero!**
- ✦ If negative, counts down from end.
- ✦ Does this work on other data types like `int`?

Slicing operator:

- ▣ Extracts range of characters (substring)

Slicing operator:

- ▣ Extracts range of characters (substring)
- ▣ Range specified inside of indexing operator

Slicing operator:

- ✦ Extracts range of characters (substring)
- ✦ Range specified inside of indexing operator

```
a = "FIREHOUSE"  
a[0:4]
```

Slicing operator:

- ✦ Extracts range of characters (substring)
- ✦ Range specified inside of indexing operator

```
a = "FIREHOUSE"  
a[0:4]
```

- ✦ Can be a bit tricky at first:
 - ✦ Includes character at first index
 - ✦ Excludes character at last index

Example

```
alpha = "ABCDE"  
x = alpha[1:3]
```

What is the value of x?

- A 'AB'
- B 'ABC'
- C 'BC'
- D 'BCD'
- E 'CD'

Functions

And now for something different...

- ✦ A function is a small program (block of code) we can run within Python.

And now for something different...

- A function is a small program (block of code) we can run within Python.
 - Saves us from rewriting code
 - Don't reinvent the wheel!

And now for something different...

- A function is a small program (block of code) we can run within Python.
 - Saves us from rewriting code
 - Don't reinvent the wheel!
- Analogy: Functions are more verbs.

And now for something different...

- ✦ A function is a small program (block of code) we can run within Python.
 - ✦ Saves us from rewriting code
 - ✦ Don't reinvent the wheel!
- ✦ Analogy: Functions are more verbs.
- ✦ Also called subroutine or procedure.

Function calls

- ✦ When we want to execute a function, we call or invoke it.

Function calls

- ✦ When we want to execute a function, we call or invoke it.
- ✦ Use name of the function with parentheses.

Function calls

- ❖ When we want to execute a function, we call or invoke it.
- ❖ Use name of the function with parentheses.
 - ❖ `print()`

Function calls

- ❖ When we want to execute a function, we call or invoke it.
- ❖ Use name of the function with parentheses.
 - ❖ `print()`
- ❖ Many functions come built-in to Python or in the standard library.

Function calls

- ❖ When we want to execute a function, we call or invoke it.
- ❖ Use name of the function with parentheses.
 - ❖ `print()`
- ❖ Many functions come built-in to Python or in the standard library.
- ❖ Others we will compose at need.

Arguments

- ▣ Functions can act on data.

Arguments

- ▣ Functions can act on data.
- ▣ Arguments are the input to functions.

Arguments

- ❖ Functions can act on data.
- ❖ Arguments are the input to functions.
- ❖ Functions can return a value. (fruitful)

Arguments

- ❖ Functions can act on data.
- ❖ Arguments are the input to functions.
- ❖ Functions can return a value. (fruitful)
- ❖ Return values are the output of a function.

Arguments

- ❖ Functions can act on data.
- ❖ Arguments are the input to functions.
- ❖ Functions can return a value. (fruitful)
- ❖ Return values are the output of a function.
 - ❑ `print('10')`

Arguments

- ❖ Functions can act on data.
- ❖ Arguments are the input to functions.
- ❖ Functions can return a value. (fruitful)
- ❖ Return values are the output of a function.
 - ❑ `print('10')`
 - ❑ `len('Rex Kwon Do')`

Arguments

- ❖ Functions can act on data.
- ❖ Arguments are the input to functions.
- ❖ Functions can return a value. (fruitful)
- ❖ Return values are the output of a function.
 - ❑ `print('10')`
 - ❑ `len('Rex Kwon Do')`
 - ❑ `abs(-123)`

Arguments

- ❖ Functions can act on data.
- ❖ Arguments are the input to functions.
- ❖ Functions can return a value. (fruitful)
- ❖ Return values are the output of a function.
 - ❑ `print('10')`
 - ❑ `len('Rex Kwon Do')`
 - ❑ `abs(-123)`

Arguments

- Arguments are values passed to a function.

Arguments

- Arguments are values passed to a function.
- A function can accept zero to many arguments.

Arguments

- Arguments are values passed to a function.
- A function can accept zero to many arguments.
- Multiple arguments are separated by commas:
 - `min(1,4,5)`
 - `max(1,4,5)`

Type conversion.

- A set of built-in functions to convert data from one type to another.

Type conversion.

- A set of built-in functions to convert data from one type to another.
 - `float("0.3")`
 - `str(3 + 5j)`

Type conversion.

- ✦ A set of built-in functions to convert data from one type to another.
 - ✦ `float("0.3")`
 - ✦ `str(3 + 5j)`
- ✦ Be careful of nonsense:
 - ✦ `int("Rex")`
 - ✦ `int(3 + 5j)`
- ✦ Also called subroutine or procedure.

User input

- ▣ `input` is a built-in function.

User input

- `input` is a built-in function.
- Argument: string prompting user

User input

- `input` is a built-in function.
- Argument: string prompting user
- Return value: input from user (as `str`)

Goal

- ✦ A program should achieve a goal.

Goal

- ❖ A program should achieve a goal.
- ❖ Next time we will write our first nontrivial program.

Reminders

Reminders

- ❖ Homework #1 due today, Aug. 31, 5:00 p.m.
- ❖ Homework #2 due Friday, Sep. 9, 5:00 p.m.
- ❖ No class Monday, Sep. 5 (Labor Day).
- ❖ No lab next week!