

Python Applications

manipulating listss

CS101 Lecture #13

Administrivia

- ❖ Homework #7 is due Friday, Nov. 25.
- ❖ Use the `split(' ', '')` approach.
- ❖ Midterm reflection exercise on website for extra credit.

Warmup Quiz (No Real Quiz Today)

Mutability Question

Which of the following sets of `list` methods *all* change the function in place (have no return value)?

A `split`, `append`, `extend`

B `del`, `index`, `upper`

C `read`, `readlines`, `close`

D `sort`, `reverse`, `append`, `extend`

Mutability Question

Which of the following sets of list methods *all* change the function in place (have no return value)?

A split, append, extend

B del, index, upper

C read, readlines, close

D sort, reverse, append, extend ★

Working with Containers

lists and dicts

list	
modifies in place	returns value
append	index
extend	count
reverse	upper
sort	isupper
del (not method)	etc.

lists and dicts

`dict`

modifies in place

returns value

`del` (not method)

values
keys

lists and dicts

`dict`

`modifies in place`

`returns value`

`del (not method)`

`values`
`keys`

❖ Note that there isn't a `sort` method!

Sorting a dict by value

```
# remember me?
def sortDictAsList( d ):
    items = list( d.items() )
    items.sort( key=lambda x:x[1] )
    return items

d = { 'a':2, 'b':1, 'c':-1, 'd':14 }
sortDictAsList( d )
```

Sorting a dict by value

We want to know which plankton species has the largest population.

Sorting a dict by value

We want to know which plankton species has the largest population.

```
from csv import DictReader
reader = DictReader( open( 'plankton.csv' ) )
plankdata = {}
for row in reader:
    plankdata[ row['Species'] ] = \
        max( float( row['Near-shore, May-93'] ),
              float( row['Near-shore, Aug-93'] ),
              float( row['Off-shore, May-93'] ),
              float( row['Off-shore, Aug-93'] ) )
sortDictAsList( plankdata )
```

Accessing *lists*

- Sometimes we have two lists that correspond to each other.
- If we want to loop over both together, we have two approaches open:

```
qs = [ 'name', 'quest', 'favourite colour' ]  
as = [ 'Lancelot', 'the Holy Grail', 'blue' ]  
# method 1:  
for i in range(len(qs)):  
    print( 'What is your %s? It is %s.'%(qs[i],as[i]) )
```

Accessing *lists*

- Sometimes we have two lists that correspond to each other.
- If we want to loop over both together, we have two approaches open:

```
qs = [ 'name', 'quest', 'favourite colour' ]
as = [ 'Lancelot', 'the Holy Grail', 'blue' ]

# method 1:
for i in range(len(qs)):
    print( 'What is your %s?  It is %s.'%(qs[i],as[i]) )

# method 2:
for q,a in zip(qs,as):
    print( 'What is your %s?  It is %s.'%(q,a) )
```

Accessing *lists*

- ❖ `zip` makes two lists *jointly iterable*.
- ❖ Consider a function which compares two lists of measurements and determines for each pair of measurements which is larger:

```
def pickLarger( a,b ):
    result = [ ] # a list of largest values
    for i,j in zip(a,b):
        result.append( max( i,j ) )
    return result
```


Accessing lists

- ❖ What if you need to know both an item and the index of the item?

```
my_list = [ 'meter', 'kilogram', 'second' ]  
# one way  
for i in range( len(my_list) ):  
    print( '%s is the %sth item.' % (my_list[i]
```

Accessing *lists*

- What if you need to know both an item and the index of the item?

```
my_list = [ 'meter', 'kilogram', 'second' ]
```

```
# one way
```

```
for i in range( len(my_list) ):
```

```
    print( '%s is the %sth item.' % (my_list[i]
```

```
# another way
```

```
for i,item in enumerate( my_list ):
```

```
    print( '%s is the %sth item.' % (item,i) )
```

Accessing *lists*

- ❖ Both `zip` and `enumerate` are *convenience* functions!
- ❖ There are multiple approaches!

Accessing *lists*

- ❖ *Permutations* are used in statistics to analyze all possible configurations of a group of things.
- ❖ In engineering, for instance, you see them used in experimental design.

one way

```
for i in 'ABCD':  
    for j in 'ABCD':  
        if i == j:  
            continue  
        print( i, j )
```

Accessing lists

- *Permutations* are used in statistics to analyze all possible configurations of a group of things.
- In engineering, for instance, you see them used in experimental design.

```
# one way
```

```
for i in 'ABCD':  
    for j in 'ABCD':  
        if i == j:  
            continue  
        print( i, j )
```

```
# another way
```

```
from itertools import permutations  
for doublet in permutations( 'ABCD',2 ):  
    print( doublet )
```

Homework debugging

```
# how to figure out what directory Python is in
import os
os.getcwd() # Get Current Working Directory

# how to figure out what's in that directory
os.listdir('.')

# when submitting, use:
open( 'batting.csv' ) #(since in same dir)
```

Reminders

Reminders

- ❖ Homework #7 is due Friday, Nov. 25.
- ❖ Use the `split(' ', '')` approach.
- ❖ Midterm reflection exercise on website for extra credit.