**Table 1. WorkBuddy-Bench.** Two executor models, each under two open-source initial harnesses. Harness$^2$ uses one improvement step (k = 1) and has the highest average score in all four settings.

| Method | Code | | Web | | Office | | Avg. | |
|---|---|---|---|---|---|---|---|---|
| | Score ↑ | #Steps ↓ | Score ↑ | #Steps ↓ | Score ↑ | #Steps ↓ | Score ↑ | #Steps ↓ |
| *Gemini 3.5 Flash · initial harness OpenCode* | | | | | | | | |
| OpenCode (initial) | 73.4 (3.6) | 29.6 (1.0) | 69.9 (4.2) | 19.2 (0.8) | 74.0 (2.2) | 27.3 (3.3) | 72.4 (0.9) | 25.4 (0.4) |
| ReasoningBank | 72.6 (3.1) | 28.7 (2.6) | 70.7 (6.9) | 18.8 (0.7) | 76.8 (2.1) | 27.1 (1.2) | 73.4 (2.5) | 24.9 (1.0) |
| Meta-Harness$^\dagger$ | 75.5 (1.7) | 31.5 (0.8) | 75.1 (0.6) | 26.4 (1.1) | 78.6 (1.4) | 28.6 (2.4) | 76.4 (0.7) | 28.8 (0.8) |
| Harness Scaling | 74.0 (1.1) | 26.1 (0.9) | 74.0 (1.9) | **16.6** (1.5) | 77.9 (1.3) | **24.3** (1.4) | 75.3 (0.7) | 22.3 (0.4) |
| Harness$^2$ | **76.5** (1.3) | **22.8** (1.3) | **76.4** (4.5) | 17.7 (0.7) | **79.5** (3.1) | 25.1 (1.7) | **77.5** (2.5) | **21.9** (0.4) |
| + Recursion (k=5) | +4.3 | −0.4 | +1.9 | +0.4 | +3.9 | −2.2 | +3.3 | −0.8 |
| *Gemini 3.5 Flash · initial harness Codex* | | | | | | | | |
| Codex (initial) | 74.0 (1.7) | 31.8 (0.9) | 72.5 (1.2) | 22.6 (0.9) | 77.0 (2.2) | 30.6 (1.2) | 74.5 (1.6) | 28.3 (0.7) |
| ReasoningBank | 73.5 (3.3) | 32.8 (1.7) | 65.7 (2.2) | 22.7 (2.2) | 78.4 (0.9) | 32.1 (2.3) | 72.5 (2.2) | 29.2 (1.1) |
| Meta-Harness$^\dagger$ | 74.6 (3.3) | 33.5 (1.1) | 67.8 (1.5) | 22.1 (2.8) | 77.6 (1.6) | 30.1 (1.9) | 73.3 (0.8) | 28.6 (1.2) |
| Harness Scaling | 75.5 (2.1) | 32.4 (0.6) | 69.3 (3.8) | 23.5 (0.9) | 76.7 (3.8) | 34.0 (2.6) | 73.8 (1.7) | 30.0 (1.0) |
| Harness$^2$ | **79.4** (3.6) | **26.6** (2.8) | **74.7** (3.8) | **19.5** (1.1) | **78.5** (2.4) | **25.6** (1.3) | **77.5** (2.0) | **23.9** (0.6) |
| + Recursion (k=5) | +1.6 | −2.0 | +2.6 | 0.0 | +4.3 | +1.3 | +2.9 | −0.2 |
| *GLM-5 · initial harness OpenCode* | | | | | | | | |
| OpenCode (initial) | 58.4 (5.2) | 19.2 (1.8) | 59.2 (6.9) | 9.2 (1.2) | 75.1 (3.2) | **12.0** (1.1) | 64.2 (1.4) | 13.5 (0.5) |
| ReasoningBank | 63.3 (4.3) | 18.6 (0.6) | 61.4 (4.2) | 10.3 (2.5) | 72.0 (0.9) | 14.3 (0.4) | 65.6 (1.2) | 14.4 (0.7) |
| Meta-Harness$^\dagger$ | 69.0 (1.2) | 22.4 (1.6) | 61.9 (4.1) | 10.0 (1.9) | 78.1 (1.3) | 13.6 (1.7) | 69.7 (0.6) | 15.3 (1.5) |
| Harness Scaling | 60.3 (2.6) | 16.0 (2.6) | 63.4 (2.2) | **9.0** (1.2) | 79.8 (3.0) | 12.8 (1.1) | 67.8 (1.3) | **12.6** (1.1) |
| Harness$^2$ | **77.1** (2.7) | **14.8** (2.1) | **69.1** (3.3) | 11.0 (2.0) | **80.8** (2.6) | 15.2 (1.8) | **75.7** (2.2) | 13.7 (0.2) |
| + Recursion (k=5) | +4.8 | −5.5 | +5.3 | −0.2 | +1.7 | −2.3 | +3.9 | −2.7 |
| *GLM-5 · initial harness Codex* | | | | | | | | |
| Codex (initial) | 56.8 (2.7) | 28.5 (1.8) | 59.6 (1.0) | 18.0 (0.9) | 76.9 (2.4) | 23.4 (1.4) | 64.4 (1.2) | 23.3 (0.3) |
| ReasoningBank | 50.2 (3.8) | 24.9 (0.6) | 66.3 (2.5) | **17.5** (1.6) | 75.8 (4.2) | **20.9** (0.5) | 64.1 (0.9) | **21.1** (0.7) |
| Meta-Harness$^\dagger$ | **76.8** (1.9) | 33.0 (2.1) | 67.8 (4.1) | 24.7 (0.5) | 77.9 (2.8) | 31.4 (2.8) | 74.2 (1.6) | 29.7 (1.2) |
| Harness Scaling | 49.5 (3.9) | 24.2 (1.0) | 60.9 (1.7) | 18.9 (1.4) | 78.2 (2.4) | 22.0 (2.8) | 62.9 (1.3) | 21.7 (1.2) |
| Harness$^2$ | 74.9 (1.5) | **19.7** (1.3) | **70.0** (4.3) | 22.4 (2.2) | **81.1** (2.0) | 21.8 (1.5) | **75.3** (1.3) | 21.3 (1.3) |
| + Recursion (k=5) | +2.3 | −1.4 | +3.3 | −2.5 | +3.2 | +0.1 | +3.0 | −1.3 |

Mean over runs with SD in parentheses; Avg. is the macro-average of the three domains. + Recursion is the change after parallel task-level recursion at k = 5 (green better, red worse, following each column's arrow). $^\dagger$ Offline method optimized on separate training tasks. Bold: best before recursion within each block. Shaded: Harness$^2$.