Table 1. Task success and inference cost at two token budgets. Adaptive routing is best on every suite within each budget and costs less than Verifier, the strongest baseline.

	Task success (%) ↑					Cost ↓	
Method	**Math** n=250	**Code** n=200	**Docs** n=150	**Tools** n=100	**Avg.** macro	**Tokens** mean	**Latency** ms
16k-token budget							
Direct	65.6	61.5	73.3	54.0	63.6	**4,800**	**410**
Chain of thought	72.0	68.0	77.3	61.0	69.6	6,200	521
Search	78.8	74.0	82.0	65.0	75.0	10,150	811
Verifier	78.0	75.5	83.3	64.0	75.2	11,280	953
Adaptive routing	**80.4**	**77.5**	**85.3**	**69.0**	**78.1**	9,800	754
Δ vs. Verifier	+2.4	+2.0	+2.0	+5.0	+2.9	−1,480	−198
32k-token budget							
Chain of thought	73.6	70.5	80.7	64.0	72.2	**9,700**	**743**
Search	82.8	77.5	87.3	71.0	79.7	17,200	1,236
Verifier	83.2	79.0	88.7	72.0	80.7	18,400	1,403
Adaptive routing	**84.8**	**81.5**	**90.0**	**76.0**	**83.1**	15,100	1,128
Δ vs. Verifier	+1.6	+2.5	+1.3	+4.0	+2.4	−3,300	−274

Synthetic data. Success = successes / n; Avg. is the unweighted mean of the four rates. Δ is Adaptive routing minus Verifier, from unrounded values; green marks an improvement. Bold: best within a budget. Shaded: proposed method.