Table 5. Memory systems for agents. Mechanisms each system implements, the memory types it stores, and end-task success and cost on one benchmark.

	Mechanism			Memory				Results	
Method	**Str.**	**Ret.**	**Rea.**	**E**	**S**	**P**	**Agn.**	**Success** % ↑	**Cost** rel. ↓
Task-agnostic memory									
Vector retrieval	✗	✓	✗	✓	✗	✗	✓	61.2	**1.0**×
Summary memory	✓	✗	✗	✓	✓	✗	✓	63.5*	1.4×
Graph memory	✓	✓	~	✓	✓	✗	✓	66.8	3.2×†
Task-specific memory									
Workflow memory	✓	✓	✗	✗	✗	✓	✗	68.1	1.9×
Skill library	✓	✗	✓	✗	✗	✓	✗	67.4*	2.6×
Ours									
Plugin memory (ours)	✓	✓	✓	✓	✓	✓	✓	**71.9**	1.3×

Synthetic data. Str./Ret./Rea. = structuring, retrieval, reasoning; E/S/P = episodic, semantic, procedural memory; Agn. = task-agnostic. Cost is relative to vector retrieval. Bold: best in each results column. Shaded: the proposed system. * reported by the original authors. † measured on a 500-task subset. ✓ supported, ✗ not supported, ~ partial.