Table 1. WorkBuddy-Bench. Results under two open-source initial harnesses for two executor models. Harness^2 uses one improvement step (k = 1).

Method	Code		Web		Office		Avg.	
	Score ↑	#Steps ↓	Score ↑	#Steps ↓	Score ↑	#Steps ↓	Score ↑	#Steps ↓
Gemini 3.5 Flash · initial harness OpenCode								
OpenCode (initial)	73.4 (3.6)	29.6 (1.0)	69.9 (4.2)	19.2 (0.8)	74.0 (2.2)	27.3 (3.3)	72.4 (0.9)	25.4 (0.4)
ReasoningBank	72.6 (3.1)	28.7 (2.6)	70.7 (6.9)	18.8 (0.7)	76.8 (2.1)	27.1 (1.2)	73.4 (2.5)	24.9 (1.0)
Meta-Harness†	75.5 (1.7)	31.5 (0.8)	75.1 (0.6)	26.4 (1.1)	78.6 (1.4)	28.6 (2.4)	76.4 (0.7)	28.8 (0.8)
Harness Scaling	74.0 (1.1)	26.1 (0.9)	74.0 (1.9)	**16.6** (1.5)	77.9 (1.3)	**24.3** (1.4)	75.3 (0.7)	22.3 (0.4)
Harness^2	**76.5** (1.3)	**22.8** (1.3)	**76.4** (4.5)	17.7 (0.7)	**79.5** (3.1)	25.1 (1.7)	**77.5** (2.5)	**21.9** (0.4)
+ Recursion (k=5)	+4.3	−0.4	+1.9	+0.4	+3.9	−2.2	+3.3	−0.8
Gemini 3.5 Flash · initial harness Codex								
Codex (initial)	74.0 (1.7)	31.8 (0.9)	72.5 (1.2)	22.6 (0.9)	77.0 (2.2)	30.6 (1.2)	74.5 (1.6)	28.3 (0.7)
ReasoningBank	73.5 (3.3)	32.8 (1.7)	65.7 (2.2)	22.7 (2.2)	78.4 (0.9)	32.1 (2.3)	72.5 (2.2)	29.2 (1.1)
Meta-Harness†	74.6 (3.3)	33.5 (1.1)	67.8 (1.5)	22.1 (2.8)	77.6 (1.6)	30.1 (1.9)	73.3 (0.8)	28.6 (1.2)
Harness Scaling	75.5 (2.1)	32.4 (0.6)	69.3 (3.8)	23.5 (0.9)	76.7 (3.8)	34.0 (2.6)	73.8 (1.7)	30.0 (1.0)
Harness^2	**79.4** (3.6)	**26.6** (2.8)	**74.7** (3.8)	**19.5** (1.1)	**78.5** (2.4)	**25.6** (1.3)	**77.5** (2.0)	**23.9** (0.6)
+ Recursion (k=5)	+1.6	−2.0	+2.6	0.0	+4.3	+1.3	+2.9	−0.2
GLM-5 · initial harness OpenCode								
OpenCode (initial)	58.4 (5.2)	19.2 (1.8)	59.2 (6.9)	9.2 (1.2)	75.1 (3.2)	**12.0** (1.1)	64.2 (1.4)	13.5 (0.5)
ReasoningBank	63.3 (4.3)	18.6 (0.6)	61.4 (4.2)	10.3 (2.5)	72.0 (0.9)	14.3 (0.4)	65.6 (1.2)	14.4 (0.7)
Meta-Harness†	69.0 (1.2)	22.4 (1.6)	61.9 (4.1)	10.0 (1.9)	78.1 (1.3)	13.6 (1.7)	69.7 (0.6)	15.3 (1.5)
Harness Scaling	60.3 (2.6)	16.0 (2.6)	63.4 (2.2)	**9.0** (1.2)	79.8 (3.0)	12.8 (1.1)	67.8 (1.3)	**12.6** (1.1)
Harness^2	**77.1** (2.7)	**14.8** (2.1)	**69.1** (3.3)	11.0 (2.0)	**80.8** (2.6)	15.2 (1.8)	**75.7** (2.2)	13.7 (0.2)
+ Recursion (k=5)	+4.8	−5.5	+5.3	−0.2	+1.7	−2.3	+3.9	−2.7
GLM-5 · initial harness Codex								
Codex (initial)	56.8 (2.7)	28.5 (1.8)	59.6 (1.0)	18.0 (0.9)	76.9 (2.4)	23.4 (1.4)	64.4 (1.2)	23.3 (0.3)
ReasoningBank	50.2 (3.8)	24.9 (0.6)	66.3 (2.5)	**17.5** (1.6)	75.8 (4.2)	**20.9** (0.5)	64.1 (0.9)	**21.1** (0.7)
Meta-Harness†	**76.8** (1.9)	33.0 (2.1)	67.8 (4.1)	24.7 (0.5)	77.9 (2.8)	31.4 (2.8)	74.2 (1.6)	29.7 (1.2)
Harness Scaling	49.5 (3.9)	24.2 (1.0)	60.9 (1.7)	18.9 (1.4)	78.2 (2.4)	22.0 (2.8)	62.9 (1.3)	21.7 (1.2)
Harness^2	74.9 (1.5)	**19.7** (1.3)	**70.0** (4.3)	22.4 (2.2)	**81.1** (2.0)	21.8 (1.5)	**75.3** (1.3)	21.3 (1.3)
+ Recursion (k=5)	+2.3	−1.4	+3.3	−2.5	+3.2	+0.1	+3.0	−1.3

Mean over runs with SD in parentheses; Avg. is the macro-average of the three domains. + Recursion is the change after parallel task-level recursion at k = 5 (green better, red worse, following each column's arrow). † Offline method optimized on separate training tasks. Bold: best before recursion within each block. Shaded: Harness^2.