

Taiga REST API

Table of Contents

1. General notes	1
1.1. Authentication.....	1
1.2. OCC - Optimistic concurrency control	6
1.3. Pagination	6
1.4. Internationalization.....	6
1.5. Throttling	7
2. Endpoints Summary	7
2.1. Auth	7
2.2. Applications	7
2.3. Application Tokens.....	7
2.4. Resolver	8
2.5. Searches	8
2.6. User storage	8
2.7. Project templates	8
2.8. Projects	9
2.9. Memberships/Invitations	10
2.10. Milestones	11
2.11. User stories	11
2.12. User story status.....	13
2.13. Points.....	13
2.14. User story custom attribute	13
2.15. User story custom attributes values	14
2.16. Tasks	14
2.17. Task status	15
2.18. Task custom attribute	16
2.19. Task custom attributes values.....	16
2.20. Issues.....	16
2.21. Issue status.....	17
2.22. Issue types	18
2.23. Priorities.....	18
2.24. Severities	19
2.25. Issue custom attribute.....	19
2.26. Issue custom attributes values	20
2.27. Wiki pages	20
2.28. Wiki links	21
2.29. History	21

2.30. Users	22
2.31. Notify policies	22
2.32. Feedback	23
2.33. Export/Import	23
2.34. Webhooks	23
2.35. Timelines	24
2.36. Locales	24
2.37. Stats	24
3. Auth	24
3.1. Normal login	24
3.2. Github login	25
3.3. Public registry	25
3.4. Private registry	26
4. Applications	27
4.1. Get	27
4.2. Get token	27
5. Application tokens	27
5.1. List	27
5.2. Get	28
5.3. Delete	28
5.4. Authorize	28
5.5. Validate	29
6. Resolver	29
6.1. Projects	29
6.2. User stories	30
6.3. Issues	30
6.4. Tasks	31
6.5. Milestones	31
6.6. Wiki pages	32
6.7. Multiple resolution	32
6.8. By ref value	33
7. Searches	33
7.1. Search	33
8. User storage	34
8.1. List	34
8.2. Create	34
8.3. Get	35
8.4. Edit	35

8.5. Delete.....	35
9. Project templates	35
9.1. List	36
9.2. Create	36
9.3. Get	46
9.4. Edit.....	46
9.5. Delete.....	46
10. Projects.....	47
10.1. List	47
10.2. Create	48
10.3. Get	49
10.4. Get by slug	49
10.5. Edit.....	50
10.6. Delete	50
10.7. Bulk update order	50
10.8. Get modules configuration	51
10.9. Edit modules configuration	51
10.10. Stats	52
10.11. Issue stats.....	52
10.12. Issue filters data	52
10.13. Tag colors.....	52
10.14. Like a project.....	53
10.15. Unlike a project	53
10.16. List project fans	53
10.17. Watch a project.....	54
10.18. Stop watching project	54
10.19. List project watchers.....	54
10.20. Create template	54
10.21. Leave.....	55
10.22. Change logo	55
10.23. Remove logo	55
10.24. Transfer request.....	56
10.25. Transfer start	56
10.26. Transfer accept.....	56
10.27. Transfer reject	57
11. Memberships/Invitations.....	57
11.1. List	57
11.2. Create	58

11.3. Bulk creation	58
11.4. Get	59
11.5. Edit	59
11.6. Delete	60
11.7. Resend invitation	60
11.8. Get Invitation (by token)	60
12. Milestones	60
12.1. List	60
12.2. Create	61
12.3. Get	62
12.4. Edit	63
12.5. Delete	63
12.6. Stats	63
12.7. Watch a milestone	63
12.8. Stop watching a milestone	64
12.9. List milestone watchers	64
13. User stories	64
13.1. List	64
13.2. Create	65
13.3. Get	67
13.4. Get by ref	67
13.5. Edit	67
13.6. Delete	68
13.7. Bulk creation	68
13.8. Bulk update backlog order	68
13.9. Bulk update kanban order	69
13.10. Bulk update sprint order	70
13.11. Vote a user story	71
13.12. Remove vote from a user story	71
13.13. Get user story voters list	72
13.14. Watch a user story	72
13.15. Stop watching a user story	72
13.16. List user story watchers	72
13.17. List attachments	73
13.18. Create attachment	73
13.19. Get attachment	73
13.20. Edit attachment	74
13.21. Delete attachment	74

14. User story status	74
14.1. List	74
14.2. Create	75
14.3. Get	76
14.4. Edit	76
14.5. Delete	76
14.6. Bulk update order	77
15. Points	77
15.1. List	77
15.2. Create	78
15.3. Get	79
15.4. Edit	79
15.5. Delete	79
15.6. Bulk update order	79
16. User story custom attribute	80
16.1. List	80
16.2. Create	80
16.3. Get	81
16.4. Edit	82
16.5. Delete	82
16.6. Bulk update order	82
17. User story custom attributes values	83
17.1. Get	83
17.2. Edit	83
18. Tasks	84
18.1. List	84
18.2. Create	84
18.3. Get	86
18.4. Get by ref	86
18.5. Edit	86
18.6. Delete	87
18.7. Bulk creation	87
18.8. Vote a task	88
18.9. Remove vote from a task	88
18.10. Get task voters list	88
18.11. Watch a task	88
18.12. Stop watching a task	89
18.13. List task watchers	89

18.14. List attachments	89
18.15. Create attachment	89
18.16. Get attachment	90
18.17. Edit attachment	90
18.18. Delete attachment	91
19. Task status	91
19.1. List	91
19.2. Create	91
19.3. Get	92
19.4. Edit	92
19.5. Delete	93
19.6. Bulk update order	93
20. Task custom attribute	94
20.1. List	94
20.2. Create	94
20.3. Get	95
20.4. Edit	95
20.5. Delete	96
20.6. Bulk update order	96
21. Task custom attributes values	97
21.1. Get	97
21.2. Edit	97
22. Issues	97
22.1. List	97
22.2. Create	99
22.3. Get	100
22.4. Get by ref	101
22.5. Edit	101
22.6. Delete	101
22.7. Vote an issue	102
22.8. Remove vote from an issue	102
22.9. Get issue voters list	102
22.10. Watch an issue	102
22.11. Stop watching an issue	103
22.12. List issue watchers	103
22.13. List attachments	103
22.14. Create attachment	104
22.15. Get attachment	104

22.16. Edit attachment	104
22.17. Delete attachment	105
23. Issue status	105
23.1. List	105
23.2. Create	105
23.3. Get	106
23.4. Edit	106
23.5. Delete	107
23.6. Bulk update order	107
24. Issue types	108
24.1. List	108
24.2. Create	108
24.3. Get	109
24.4. Edit	109
24.5. Delete	110
24.6. Bulk update order	110
25. Priorities	111
25.1. List	111
25.2. Create	111
25.3. Get	112
25.4. Edit	112
25.5. Delete	113
25.6. Bulk update order	113
26. Severities	114
26.1. List	114
26.2. Create	114
26.3. Get	115
26.4. Edit	115
26.5. Delete	116
26.6. Bulk update order	116
27. Issue custom attribute	117
27.1. List	117
27.2. Create	117
27.3. Get	118
27.4. Edit	118
27.5. Delete	119
27.6. Bulk update order	119
28. Issue custom attributes values	120

28.1. Get	120
28.2. Edit.....	120
29. Wiki pages	120
29.1. List	120
29.2. Create	121
29.3. Get	122
29.4. Get by slug	122
29.5. Edit.....	122
29.6. Delete	123
29.7. Watch a wiki page	123
29.8. Stop watching a wiki page	123
29.9. List wiki page watchers	124
29.10. List attachments.....	124
29.11. Create attachment	124
29.12. Get attachment.....	125
29.13. Edit attachment	125
29.14. Delete attachment	125
30. Wiki links.....	126
30.1. List	126
30.2. Create	126
30.3. Get	127
30.4. Edit.....	127
30.5. Delete	128
31. History	128
31.1. Get user story, task, issue or wiki page history	128
31.2. Delete comment	128
31.3. Undelete comment.....	129
32. Users	129
32.1. List	129
32.2. Get	130
32.3. Me	130
32.4. Get user stats.....	130
32.5. Get watched content	130
32.6. Get liked content	131
32.7. Get voted content.....	131
32.8. Edit.....	132
32.9. Delete	132
32.10. Get contacts	133

32.11. Cancel	133
32.12. Change avatar	133
32.13. Remove avatar	133
32.14. Change email	134
32.15. Change password	134
32.16. Password recovery	134
32.17. Change password from recovery	135
33. Notify policies	135
33.1. List	135
33.2. Get	136
33.3. Edit	136
34. Feedback	136
34.1. Create	136
35. Export/Import	137
35.1. Export	137
35.2. Import	137
36. Webhooks	138
36.1. List	138
36.2. Create	138
36.3. Get	139
36.4. Edit	139
36.5. Delete	140
36.6. Test	140
36.7. Logs list	140
36.8. Log get	141
36.9. Resend request	141
37. Timelines	141
37.1. List user timeline	141
37.2. List profile timeline	141
37.3. List project timeline	142
38. Locales	142
38.1. List	142
39. Stats	142
39.1. Get discover stats	143
39.2. Get system stats	143
40. Objects Summary	143
40.1. Attachment	143
40.2. Application object	144

40.3. Application token object	144
40.4. Authorization code object	145
40.5. Cyphered token object	145
40.6. User detail	145
40.7. User contact detail	146
40.8. User authentication-detail	147
40.9. User stats detail	147
40.10. Search results detail	148
40.11. User storage data	150
41. Project templates detail	150
41.1. Project list entry	158
41.2. Project detail	168
41.3. Project modules configuration	188
41.4. Project stats detail	188
41.5. Project issue stats detail	193
41.6. Project issue filters data detail	206
41.7. Project tag colors data detail	219
41.8. Project voter detail	222
41.9. Project watcher detail	222
41.10. Project template detail	222
41.11. Membership detail	232
41.12. Milestone detail	232
41.13. Milestone watcher detail	233
41.14. Milestone stats detail	233
41.15. User story detail	234
41.16. User story detail (GET)	236
41.17. User story detail (LIST)	238
41.18. User story voter detail	239
41.19. User story watcher detail	239
41.20. User story status detail	240
41.21. Point detail	240
41.22. User story custom attribute detail	240
41.23. User story custom attributes values detail	241
41.24. Task detail	241
41.25. Task detail (GET)	243
41.26. Task detail (LIST)	244
41.27. Task voter detail	246
41.28. Task watcher detail	246

41.29. Project voter detail	246
41.30. Project watcher detail.....	246
41.31. Task status detail	246
41.32. Task custom attribute detail	247
41.33. Task custom attributes values detail.....	247
41.34. Issue detail.....	247
41.35. Issue detail (GET)	249
41.36. Issue detail (LIST)	251
41.37. Issue voters detail	253
41.38. Issue watchers detail	253
41.39. Issue status detail.....	253
41.40. Issue type detail	253
41.41. Priority detail	254
41.42. Severity detail.....	254
41.43. Issue custom attribute detail.....	254
41.44. Issue custom attributes values detail	255
41.45. Wiki page	255
41.46. Wiki page watcher detail.....	256
41.47. Wiki link.....	257
41.48. History entry.....	257
41.49. Notify policy	258
41.50. Feedback	258
41.51. Export detail for synch mode	259
41.52. Export accepted response	259
41.53. Import accepted response	259
41.54. Webhook	259
41.55. Webhook log	259
41.56. Timeline entry detail.....	260
41.57. Locale	261
41.58. Watched	262
41.59. Liked	262
41.60. Voted	263
41.61. Discover stats	264
41.62. System stats.....	264
42. Contrib plugins.....	266

1. General notes

About Taiga instance and URLs used in this document

NOTE All API calls used in the documentation are referred to Taiga.io instance, so if you use another instance remember to change the url.

For example, if you have installed Taiga on your own PC, you must perform the tests using <http://localhost:8000/api/v1> instead of <https://taiga.io/api/v1>.

1.1. Authentication

1.1.1. Standard token authentication

To authenticate requests an http header called "Authorization" should be added. Its format should be:

```
Authorization: Bearer ${AUTH_TOKEN}
```

This token can be received through the [login API](#)

To provide an example, the following can be used within a Bash script running on Ubuntu - customise as appropriate for your system configuration.

- Install `jq` (a command-line JSON processor):

```
$ sudo apt-get install jq
```

- Bash snippet:

```

#!/bin/bash
# Request username and password for connecting to Taiga
read -p "Username or email: " USERNAME
read -s -p "Password: " PASSWORD

# Get AUTH_TOKEN
USER_AUTH_DETAIL=$( curl -X POST \
-H "Content-Type: application/json" \
-d '{
    "type": "normal",
    "username": "'${USERNAME}'",
    "password": "'${PASSWORD}'"
}' \
https://api.taiga.io/api/v1/auth 2>/dev/null )

AUTH_TOKEN=$( echo ${USER_AUTH_DETAIL} | jq -r '.auth_token' )

# Exit if AUTH_TOKEN is not available
if [ -z ${AUTH_TOKEN} ]; then
    echo "Error: Incorrect username and/or password supplied"
    exit 1
else
    echo "auth_token is ${AUTH_TOKEN}"
fi

# Proceed to use API calls as desired
...

```

- If unable to install `jq`, it is possible (but not recommended) to use `grep` and `cut` to extract the value of `auth_token` from the JSON `user auth detail object` - use the following line instead:

```

AUTH_TOKEN=$( echo ${USER_AUTH_DETAIL} | grep -Po '"auth_token":.*?[^\\"], ' | cut -d\" -f4 )

```

1.1.2. Application token authentication

This kind of tokens are designed for allowing external apps use the Taiga API, they are associated to an existing user and an Application. They can be manually created via the django ADMIN or programmatically created via API.

They work in the same way than standard Taiga authentication tokens but the "Authorization" header change slightly. Its format should be:

```
Authorization: Application ${AUTH_TOKEN}
```

The process for obtaining a valid token consists in:

- [Checking if there is an existing application token for the requesting user](#)
- [Requesting an authorization code for the requesting user if it doesn't exist yet](#)
- [Validating the authorization code to obtain the final token](#)
- [Decyphering the token](#)

Checking if there is an existing application token for the requesting user

A GET request must be done to the applications resource including the application id in the url and specifying the token endpoint:

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer {AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/applications/5c8515c2-4fc4-11e5-9a5e-68f72800aadd/token
```

The API will answer with info about the application and the token:

```
{
  "user": 4,
  "id": null,
  "application": {
    "id": "a60c3208-5234-11e5-96df-68f72800aadd",
    "name": "Testing application",
    "web": "http://taiga.io",
    "description": "Testing external app",
    "icon_url": "https://tree.taiga.io/images/beta.png"
  },
  "auth_code": null,
  "next_url": "http://tree.taiga.io/redirect?auth_code=None"
}
```

If id and auth_code are null it means there is no application token generated and you need to [authorize one](#). If they are not null you can jump to the [validation step](#).

Requesting an authorization code for the requesting user if it doesn't exist yet

The request should include:

- application: the application id for the requested token

- state: an unguessable random string. It is used to protect against cross-site request forgery attacks. The API will include this value when the validation process is completed so the final app can verify it matches the original one.

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer
eyJ1c2VyX2F1dGhbnRpY2F0aW9uX2lkIjo0fQ:1ZX33b:QnAN3EcuChLoRVf3CdybWEi20Eg" \
-d '{
    "application": "a60c3208-5234-11e5-96df-68f72800aadd",
    "state": "random-state"
}' \
https://api.taiga.io/api/v1/application-tokens/authorize
```

The API answer will be something like:

```
{
  "auth_code": "c8bfacba-5236-11e5-b8f6-68f72800aadd",
  "state": "random-state",
  "next_url": "asd?auth_code=c8bfacba-5236-11e5-b8f6-68f72800aadd"
}
```

The obtained auth_code must be validated as described in the [validation step](#).

Validating the authorization code to obtain the final token

Now the external app must validate the auth_code obtained in the previous steps with a request including:

- application: the application id for the requested token
- state: an unguessable random string. It is used to protect against cross-site request forgery attacks. The API will include this value when the validation process is completed so the final app can verify it matches the original one.
- auth_code: the authorization code received on previous the steps.

```

curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer
eyJ1c2VyX2F1dGhbnRpY2F0aW9uX2lkIjo0fQ:1ZX33b:QnAN3EcuChLoRVf3CdybWEi20Eg" \
-d '{
    "application": "a60c3208-5234-11e5-96df-68f72800aadd",
    "auth_code": "21ce08c4-5237-11e5-a8a3-68f72800aadd",
    "state": "random-state"
}' \
https://api.taiga.io/api/v1/application-tokens/validate

```

The API answer will be something like:

```
{
  "cyphered_token": "eyJlbmMi0iJBmjU2R0NNIiwiYWxnIjoiQTEyOEtXIn0.E-Ee1cRgG0JEd90yJu-
DgI_vwKHTHdPy2YHRbCsMvfiJx00vR12E8g.kGwJPnWQJecFPEae.ebQtpRNPbKh6FBS-
LSUhw1xNARl0Q5loC04fAk00LHFqcDpAwba7LHeR3MPx9T9LfA.KM-Id_041g80dWaseGyV8g"
}
```

Decyphering the token

The token is cyphered using JWE with A128KW as algorythm and A256GCM as encryption. Both parts (Taiga and the external application requesting the token) must know about the encryption key used in the process (in Taiga it's an attribute of the application model).

- A python snippet for decyphering the token:

```

from jwkest.jwk import SYMKey
from jwkest.jwe import JWE
key ="this-is-the-secret-key"
cyphered_token="eyJlbmMi0iJBmjU2R0NNIiwiYWxnIjoiQTEyOEtXIn0.H5jWzzXQISSh_QPC05mWhT0EI9RRV
45xA7vbWoxeBIjiCL3qwAmlzg.bBWVkwGTkta5y99c.ArycfFtr1mWgyZ4lwXw_JiSVmkn9YF6Xw1h8nVDku0BLW8
kvaxNy3XRbbb17MtZ7mg.pDkpgDwffCyCy4sYNQI6zA"
sym_key = SYMKey(key=key, alg="A128KW")
token=JWE().decrypt(cyphered_token, keys=[sym_key])
print(token)

```

When decyphering it correctly you will obtain a json containing the application token that can be used in the Authorization headers

```
{  
  "token": "95db1710-5238-11e5-a86e-68f72800aadd"  
}
```

1.2. OCC - Optimistic concurrency control

In taiga multiple operations can be happening at the same time for an element so every modifying request should include a valid version parameter. You can think about two different users updating the same user story, there are two possible scenarios here:

- They are updating the same attributes on the element. In this situation the API will accept the first request and deny the second one because the version parameter will be considered as invalid.
- They are updating different attributes on the element. In this situation the API is smart enough for accepting both requests, the second one would have an invalid version but the changes are not affecting modified attributes so they can be applied safely

The version parameter is considered valid if it contains the current version for the element, it will be incremented automatically if the modification is successful.

1.3. Pagination

By default the API will always return paginated results and includes the following headers in the response:

- x-paginated: boolean indicating if pagination is being used for the request
- x-paginated-by: number of results per page
- x-pagination-count: total number of results
- x-pagination-current: current page
- x-pagination-next: next results
- x-pagination-prev: previous results

Disabling pagination can be accomplished by setting an extra http header:

```
x-disable-pagination: True
```

1.4. Internationalization

The API returns some content translated, you can specify the language with an extra http header:

```
Accept-Language: {LanguageId}
```

The LanguageId can be chosen from the value list of available languages. You can get them using the [locales API](#).

1.5. Throttling

If the api is configured with throttling you have to take care on responses with 429 (Too many requests) status code, that mean you reach the throttling limit.

2. Endpoints Summary

2.1. Auth

URL	Method	Functionality
/api/v1/auth	POST	Login
/api/v1/auth/register	POST	Register user

2.2. Applications

URL	Method	Functionality
/api/v1/applications/{applicationId}	GET	Get application
/api/v1/applications/{applicationId}/token	GET	Get application token

2.3. Application Tokens

URL	Method	Functionality
/api/v1/application-tokens	GET	List application tokens
/api/v1/application-tokens/{applicationTokenId}	GET	Get application token
/api/v1/application-tokens/{applicationTokenId}	DELETE	Delete application token
/api/v1/application-tokens/authorize	POST	Authorize application token

URL	Method	Functionality
/api/v1/application-tokens/validate	POST	Validate application token

2.4. Resolver

URL	Method	Functionality
/api/v1/resolver	GET	Resolve references and slugs

2.5. Searches

URL	Method	Functionality
/api/v1/search	GET	Search in a project

2.6. User storage

URL	Method	Functionality
/api/v1/user-storage	GET	List user storage data
/api/v1/user-storage	POST	Create user storage data
/api/v1/user-storage/{key}	GET	Get user storage data
/api/v1/user-storage/{key}	PUT	Modify user storage data
/api/v1/user-storage/{key}	PATCH	Modify partially an user storage data
/api/v1/user-storage/{key}	DELETE	Delete user storage data

2.7. Project templates

URL	Method	Functionality
/api/v1/project-templates	GET	List project templates
/api/v1/project-templates	POST	Create project template
/api/v1/project-templates/{projectTemplateId}	GET	Get project template
/api/v1/project-templates/{projectTemplateId}	PUT	Modify project template

URL	Method	Functionality
/api/v1/project-templates/{projectTemplateId}	PATCH	Modify partially an project template
/api/v1/project-templates/{projectTemplateId}	DELETE	Delete an project template

2.8. Projects

URL	Method	Functionality
/api/v1/projects	GET	List projects
/api/v1/projects	POST	Create project
/api/v1/projects/{projectId}	GET	Get project
/api/v1/projects/by_slug?slug={projectSlug}	GET	Get project
/api/v1/projects/{projectId}	PUT	Modify project
/api/v1/projects/{projectId}	PATCH	Modify partially a project
/api/v1/projects/{projectId}	DELETE	Delete a project
/api/v1/projects/bulk_update_order	POST	Update projects order for logged in user
/api/v1/projects/{projectId}/modules	GET	Get project modules configuration
/api/v1/projects/{projectId}/modules	PATCH	Modify partially a project modules configuration
/api/v1/projects/{projectId}/stats	GET	Get project stats
/api/v1/projects/{projectId}/issues_stats	GET	Get project issue stats
/api/v1/projects/{projectId}/issues_filters_data	GET	Get project issue filters data
/api/v1/projects/{projectId}/tags_colors	GET	Get project tags colors
/api/v1/projects/{projectId}/like	POST	Like a project
/api/v1/projects/{projectId}/unlike	POST	Unlike a project
/api/v1/projects/{projectId}/fans	GET	Get project fans

URL	Method	Functionality
/api/v1/projects/{projectId}/watch	POST	Watch a project
/api/v1/projects/{projectId}/unwatch	POST	Unwatch a project
/api/v1/projects/{projectId}/watchers	GET	Get project watchers
/api/v1/projects/{projectId}/create_template	POST	Create project template
/api/v1/projects/{projectId}/leave	POST	Leave project
/api/v1/projects/{projectId}/change_logo	POST	Change logo
/api/v1/projects/{projectId}/remove_logo	POST	Remove logo
/api/v1/projects/{projectId}/transfer_validate_token	POST	Transfer validate token
/api/v1/projects/{projectId}/transfer_request	POST	Transfer request
/api/v1/projects/{projectId}/transfer_start	POST	Transfer start
/api/v1/projects/{projectId}/transfer_accept	POST	Transfer accept
/api/v1/projects/{projectId}/transfer_reject	POST	Transfer reject

2.9. Memberships/Invitations

URL	Method	Functionality
/api/v1/memberships	GET	List memberships
/api/v1/memberships	POST	Create membership
/api/v1/memberships/bulk_create	POST	Create a bulk of memberships
/api/v1/memberships/{membershipId}	GET	Get membership
/api/v1/memberships/{membershipId}	PUT	Modify membership

URL	Method	Functionality
/api/v1/memberships/{membershipId}	PATCH	Modify partially a membership
/api/v1/memberships/{membershipId}	DELETE	Delete a membership
/api/v1/memberships/{membershipId}/resend_invitation	POST	Resend invitation
/api/v1/invitations/{invitationUuid}	POST	Get invitation by anonymous user

2.10. Milestones

URL	Method	Functionality
/api/v1/milestones	GET	List milestones
/api/v1/milestones	POST	Create milestone
/api/v1/milestones/{milestoneId}	GET	Get milestone
/api/v1/milestones/{milestoneId}	PUT	Modify milestone
/api/v1/milestones/{milestoneId}	PATCH	Modify partially a milestone
/api/v1/milestones/{milestoneId}	DELETE	Delete a milestone
/api/v1/milestones/{milestoneId}/stats	GET	Get a milestone stats
/api/v1/milestones/{milestoneId}/watch	POST	Watch a milestone
/api/v1/milestones/{milestoneId}/unwatch	POST	Stop watching a milestone
/api/v1/milestones/{milestoneId}/watchers	GET	Get milestone watchers

2.11. User stories

URL	Method	Functionality
/api/v1/userstories	GET	List user stories
/api/v1/userstories	POST	Create user story
/api/v1/userstories/{userStoryId}	GET	Get user story

URL	Method	Functionality
/api/v1/userstories/by_ref?ref={userStoryRef}&project={userStoryId}	GET	Get user story
/api/v1/userstories/{userStoryId}	PUT	Modify user story
/api/v1/userstories/{userStoryId}	PATCH	Modify partially a user story
/api/v1/userstories/{userStoryId}	DELETE	Delete a user story
/api/v1/userstories/bulk_create	POST	Create user stories un bulk mode
/api/v1/userstories/bulk_update_backlog_order	POST	Update user stories order for backlog in bulk mode
/api/v1/userstories/bulk_update_kanban_order	POST	Update user stories order for kanban in bulk mode
/api/v1/userstories/bulk_update_sprint_order	POST	Update user stories order for sprint in bulk mode
/api/v1/userstories/{userStoryId}/upvote	POST	Add star to a user story
/api/v1/userstories/{userStoryId}/downvote	POST	Remove star from user story
/api/v1/userstories/{userStoryId}/voters	GET	Get user story voters
/api/v1/userstories/{userStoryId}/watch	POST	Watch a user story
/api/v1/userstories/{userStoryId}/unwatch	POST	Unwatch a user story
/api/v1/userstories/{userStoryId}/watchers	GET	Get user story watchers
/api/v1/userstories/attachments	GET	List user story attachments
/api/v1/userstories/attachments	POST	Create user story attachments
/api/v1/userstories/attachments/{userStoryAttachmentId}	GET	Get user story attachments
/api/v1/userstories/attachments/{userStoryAttachmentId}	PUT	Modify user story attachments
/api/v1/userstories/attachments/{userStoryAttachmentId}	PATCH	Modify partially a user story attachments
/api/v1/userstories/attachments/{userStoryAttachmentId}	DELETE	Delete a user story attachments

2.12. User story status

URL	Method	Functionality
/api/v1/userstory-statuses	GET	List user story status
/api/v1/userstory-statuses	POST	Create user story status
/api/v1/userstory-statuses/{userStoryStatusId}	GET	Get user story status
/api/v1/userstory-statuses/{userStoryStatusId}	PUT	Modify user story status
/api/v1/userstory-statuses/{userStoryStatusId}	PATCH	Modify partially a user story status
/api/v1/userstory-statuses/{userStoryStatusId}	DELETE	Delete a user story status
/api/v1/userstory-statuses/bulk_update_order	POST	Update user story statuses order in bulk mode

2.13. Points

URL	Method	Functionality
/api/v1/points	GET	List points
/api/v1/points	POST	Create point
/api/v1/points/{pointId}	GET	Get point
/api/v1/points/{pointId}	PUT	Modify point
/api/v1/points/{pointId}	PATCH	Modify partially a point
/api/v1/points/{pointId}	DELETE	Delete a point
/api/v1/points/bulk_update_order	POST	Update points order in bulk mode

2.14. User story custom attribute

URL	Method	Functionality
/api/v1/userstory-custom-attributes	GET	List user story custom attributes
/api/v1/userstory-custom-attributes	POST	Create user story custom attribute

URL	Method	Functionality
/api/v1/userstory-custom-attributes/{userStoryCustomAttributeId}	GET	Get user story custom attribute
/api/v1/userstory-custom-attributes/{userStoryCustomAttributeId}	PUT	Modify user story custom attribute
/api/v1/userstory-custom-attributes/{userStoryCustomAttributeId}	PATCH	Modify partially a user story custom attribute
/api/v1/userstory-custom-attributes/{userStoryCustomAttributeId}	DELETE	Delete a user story custom attribute
/api/v1/userstory-custom-attributes/bulk_update_order	POST	Update user story custom attributes order in bulk mode

2.15. User story custom attributes values

URL	Method	Functionality
/api/v1/userstories/custom-attributes-values/{userStoryId}	GET	Get user story custom attributes values
/api/v1/userstories/custom-attributes-values/{userStoryId}	PUT	Modify user story custom attributes values
/api/v1/userstories/custom-attributes-values/{userStoryId}	PATCH	Modify partially a user story custom attributes values

2.16. Tasks

URL	Method	Functionality
/api/v1/tasks	GET	List tasks
/api/v1/tasks	POST	Create task
/api/v1/tasks/{taskId}	GET	Get task
/api/v1/tasks/by_ref?ref={taskRef}&project={projectId}	GET	Get task
/api/v1/tasks/{taskId}	PUT	Modify task
/api/v1/tasks/{taskId}	PATCH	Modify partially a task

URL	Method	Functionality
/api/v1/tasks/{taskId}	DELETE	Delete a task
/api/v1/tasks/bulk_create	POST	Create tasks on bulk mode
/api/v1/tasks/{taskId}/upvote	POST	Add star to a task
/api/v1/tasks/{taskId}/downvote	POST	Remove star from task
/api/v1/tasks/{taskId}/voters	GET	Get task voters
/api/v1/tasks/{taskId}/watch	POST	Watch a task
/api/v1/tasks/{taskId}/unwatch	POST	Unwatch a task
/api/v1/tasks/{taskId}/watchers	GET	Get task watchers
/api/v1/tasks/attachments	GET	List task attachments
/api/v1/tasks/attachments	POST	Create task attachments
/api/v1/tasks/attachments/{taskAttachmentId}	GET	Get task attachments
/api/v1/tasks/attachments/{taskAttachmentId}	PUT	Modify task attachments
/api/v1/tasks/attachments/{taskAttachmentId}	PATCH	Modify partially a task attachments
/api/v1/tasks/attachments/{taskAttachmentId}	DELETE	Delete a task attachments

2.17. Task status

URL	Method	Functionality
/api/v1/task-statuses	GET	List task statuses
/api/v1/task-statuses	POST	Create task status
/api/v1/task-statuses/{taskStatusId}	GET	Get task status
/api/v1/task-statuses/{taskStatusId}	PUT	Modify task status
/api/v1/task-statuses/{taskStatusId}	PATCH	Modify partially a task status
/api/v1/task-statuses/{taskStatusId}	DELETE	Delete a task status

URL	Method	Functionality
/api/v1/task-statuses/bulk_update_order	POST	Update task statuses order in bulk mode

2.18. Task custom attribute

URL	Method	Functionality
/api/v1/task-custom-attributes	GET	List task custom attributes
/api/v1/task-custom-attributes	POST	Create task custom attribute
/api/v1/task-custom-attributes/{taskCustomAttributeId}	GET	Get task custom attribute
/api/v1/task-custom-attributes/{taskCustomAttributeId}	PUT	Modify task custom attribute
/api/v1/task-custom-attributes/{taskCustomAttributeId}	PATCH	Modify partially a task custom attribute
/api/v1/task-custom-attributes/{taskCustomAttributeId}	DELETE	Delete a task custom attribute
/api/v1/task-custom-attributes/bulk_update_order	POST	Update task custom attributes order in bulk mode

2.19. Task custom attributes values

URL	Method	Functionality
/api/v1/tasks/custom-attributes-values/{taskId}	GET	Get task custom attributes values
/api/v1/tasks/custom-attributes-values/{taskId}	PUT	Modify task custom attributes values
/api/v1/tasks/custom-attributes-values/{taskId}	PATCH	Modify partially a task custom attributes values

2.20. Issues

URL	Method	Functionality
/api/v1/issues	GET	List issues
/api/v1/issues	POST	Create issue
/api/v1/issues/{issueId}	GET	Get issue
/api/v1/issues/by_ref?ref={issueRef}&project={projectId}	GET	Get issue
/api/v1/issues/{issueId}	PUT	Modify issue
/api/v1/issues/{issueId}	PATCH	Modify partially an issue
/api/v1/issues/{issueId}	DELETE	Delete an issue
/api/v1/issues/bulk_create	POST	Create issues un bulk mode
/api/v1/issues/{issueId}/upvote	POST	Add a vote to an issue
/api/v1/issues/{issueId}/downvote	POST	Remove your vote to an issue
/api/v1/issues/{issueId}/voters	GET	Get issue voters list
/api/v1/issues/{issueId}/watch	POST	Watch an issue
/api/v1/issues/{issueId}/unwatch	POST	Unwatch an issue
/api/v1/issues/{issueId}/watchers	GET	Get issue watchers
/api/v1/issues/attachments	GET	List issue attachments
/api/v1/issues/attachments	POST	Create issue attachments
/api/v1/issues/attachments/{issueAttachmentId}	GET	Get issue attachments
/api/v1/issues/attachments/{issueAttachmentId}	PUT	Modify issue attachments
/api/v1/issues/attachments/{issueAttachmentId}	PATCH	Modify partially an issue attachments
/api/v1/issues/attachments/{issueAttachmentId}	DELETE	Delete an issue attachments

2.21. Issue status

URL	Method	Functionality
/api/v1/issue-statuses	GET	List issue statuses
/api/v1/issue-statuses	POST	Create issue status

URL	Method	Functionality
/api/v1/issue-statuses/{issueStatusId}	GET	Get issue status
/api/v1/issue-statuses/{issueStatusId}	PUT	Modify issue status
/api/v1/issue-statuses/{issueStatusId}	PATCH	Modify partially a issue status
/api/v1/issue-statuses/{issueStatusId}	DELETE	Delete a issue status
/api/v1/issue-statuses/bulk_update_order	POST	Update issue statuses order in bulk mode

2.22. Issue types

URL	Method	Functionality
/api/v1/issue-types	GET	List issue types
/api/v1/issue-types	POST	Create issue type
/api/v1/issue-types/{issueTypeId}	GET	Get issue type
/api/v1/issue-types/{issueTypeId}	PUT	Modify issue type
/api/v1/issue-types/{issueTypeId}	PATCH	Modify partially a issue type
/api/v1/issue-types/{issueTypeId}	DELETE	Delete a issue type
/api/v1/issue-types/bulk_update_order	POST	Update issue types order in bulk mode

2.23. Priorities

URL	Method	Functionality
/api/v1/priorities	GET	List priorities
/api/v1/priorities	POST	Create priority
/api/v1/priorities/{priorityId}	GET	Get priority
/api/v1/priorities/{priorityId}	PUT	Modify priority
/api/v1/priorities/{priorityId}	PATCH	Modify partially a priority
/api/v1/priorities/{priorityId}	DELETE	Delete a priority

URL	Method	Functionality
/api/v1/priorities/bulk_update_order	POST	Update priorities order in bulk mode

2.24. Severities

URL	Method	Functionality
/api/v1/severities	GET	List severities
/api/v1/severities	POST	Create severity
/api/v1/severities/{severityId}	GET	Get severity
/api/v1/severities/{severityId}	PUT	Modify severity
/api/v1/severities/{severityId}	PATCH	Modify partially a severity
/api/v1/severities/{severityId}	DELETE	Delete a severity
/api/v1/severities/bulk_update_order	POST	Update severities order in bulk mode

2.25. Issue custom attribute

URL	Method	Functionality
/api/v1/issue-custom-attributes	GET	List issue custom attributes
/api/v1/issue-custom-attributes	POST	Create issue custom attribute
/api/v1/issue-custom-attributes/{issueCustomAttributeId}	GET	Get issue custom attribute
/api/v1/issue-custom-attributes/{issueCustomAttributeId}	PUT	Modify issue custom attribute
/api/v1/issue-custom-attributes/{issueCustomAttributeId}	PATCH	Modify partially a issue custom attribute
/api/v1/issue-custom-attributes/{issueCustomAttributeId}	DELETE	Delete a issue custom attribute
/api/v1/issue-custom-attributes/bulk_update_order	POST	Update issue custom attributes order in bulk mode

2.26. Issue custom attributes values

URL	Method	Functionality
/api/v1/issues/custom-attributes-values/{issueId}	GET	Get issue custom attributes values
/api/v1/issues/custom-attributes-values/{issueId}	PUT	Modify issue custom attributes values
/api/v1/issues/custom-attributes-values/{issueId}	PATCH	Modify partially a issue custom attributes values

2.27. Wiki pages

URL	Method	Functionality
/api/v1/wiki	GET	List wiki pages
/api/v1/wiki	POST	Create wiki page
/api/v1/wiki/{wikiId}	GET	Get wiki page
/api/v1/wiki/by_slug?slug={wikiPageSlug}&project={projectId}	GET	Get wiki page
/api/v1/wiki/{wikiPageId}	PUT	Modify wiki page
/api/v1/wiki/{wikiPageId}	PATCH	Modify partially an wiki page
/api/v1/wiki/{wikiPageId}	DELETE	Delete an wiki page
/api/v1/wiki/{wikiPageId}/watch	POST	Watch a wiki page
/api/v1/wiki/{wikiPageId}/unwatch	POST	Stop watching a wiki page
/api/v1/wiki/{wikiPageId}/watchers	GET	Get wiki page watchers
/api/v1/wiki/attachments	GET	List wiki page attachments
/api/v1/wiki/attachments	POST	Create wiki page attachments
/api/v1/wiki/attachments/{wikiPageAttachmentId}	GET	Get wiki page attachments
/api/v1/wiki/attachments/{wikiPageAttachmentId}	PUT	Modify wiki page attachments
/api/v1/wiki/attachments/{wikiPageAttachmentId}	PATCH	Modify partially an wiki page attachments

URL	Method	Functionality
/api/v1/wiki/attachments/{wikiPageAttachmentId}	DELETE	Delete an wiki page attachments

2.28. Wiki links

URL	Method	Functionality
/api/v1/wiki-links	GET	List wiki links
/api/v1/wiki-links	POST	Create wiki link
/api/v1/wiki-links/{wikiLinkId}	GET	Get wiki link
/api/v1/wiki-links/{wikiLinkId}	PUT	Modify wiki link
/api/v1/wiki-links/{wikiLinkId}	PATCH	Modify partially an wiki link
/api/v1/wiki-links/{wikiLinkId}	DELETE	Delete an wiki link

2.29. History

URL	Method	Functionality
/api/v1/history/userstory/{usId}	GET	Get user story history
/api/v1/history/userstory/{usId}/delete_comment?id={commentId}	POST	Delete user story comment
/api/v1/history/userstory/{usId}/undelete_comment?id={commentId}	POST	Undelete user story comment
/api/v1/history/issue/{issueId}	GET	Get issue history
/api/v1/history/issue/{usId}/delete_comment?id={commentId}	POST	Delete issue comment
/api/v1/history/issue/{usId}/undelete_comment?id={commentId}	POST	Undelete issue comment
/api/v1/history/task/<taskId>	GET	Get task history
/api/v1/history/task/{usId}/delete_comment?id={commentId}	POST	Delete task comment
/api/v1/history/task/{usId}/undelete_comment?id={commentId}	POST	Undelete task comment
/api/v1/history/wiki/{wikiId}	GET	Get wiki history

URL	Method	Functionality
/api/v1/history/wiki/{usId}/delete_comment?id={commentId}	POST	Delete wiki comment
/api/v1/history/wiki/{usId}/undelete_comment?id={commentId}	POST	Undelete wiki comment

2.30. Users

URL	Method	Functionality
/api/v1/users	GET	List users
/api/v1/users/{userId}	GET	Get user
/api/v1/users/me	GET	Get myself
/api/v1/users/{userId}	PUT	Modify user
/api/v1/users/{userId}	PATCH	Modify partially a user
/api/v1/users/{userId}/stats	GET	Get user stats
/api/v1/users/{userId}/watched	GET	Get user watched content
/api/v1/users/{userId}/liked	GET	Get user liked content
/api/v1/users/{userId}/voted	GET	Get user voted content
/api/v1/users/{userId}	DELETE	Delete a user
/api/v1/users/{userId}/contacts	GET	Get user contacts
/api/v1/users/cancel	POST	Cancel user
/api/v1/users/change_avatar	POST	Change avatar
/api/v1/users/remove_avatar	POST	Remove avatar
/api/v1/users/change_email	POST	Change email
/api/v1/users/change_password	POST	Change password
/api/v1/users/password_recovery	POST	Password recovery
/api/v1/users/change_password_from_recovery	POST	Change password from recovery

2.31. Notify policies

URL	Method	Functionality
/api/v1/notify-policies	GET	List notify policies

URL	Method	Functionality
/api/v1/notify-policies/{policyId}	GET	Get notify policy
/api/v1/notify-policies/{policyId}	PUT	Modify notify policy
/api/v1/notify-policies/{policyId}	PATCH	Modify partially a notify policy

2.32. Feedback

URL	Method	Functionality
/api/v1/feedback	POST	Send feedback

2.33. Export/Import

URL	Method	Functionality
/api/v1/exporter/{projectId}	GET	Export a project dump
/api/v1/importer/load_dump	POST	Import a project dump

2.34. Webhooks

URL	Method	Functionality
/api/v1/webhooks	GET	List webhooks
/api/v1/webhooks	POST	Create webhook
/api/v1/webhooks/{webhookId}	GET	Get webhook
/api/v1/webhooks/{webhookId}	PUT	Modify webhook
/api/v1/webhooks/{webhookId}	PATCH	Modify partially an webhook
/api/v1/webhooks/{webhookId}	DELETE	Delete an webhook
/api/v1/webhooks/{webhookId}/test	POST	Test webhook
/api/v1/webhooklogs	GET	List webhooks logs
/api/v1/webhooklogs/{webhookLogId}	GET	Get webhook log
/api/v1/webhooklogs/{webhookLogId}/resend	POST	Resend webhook log request

2.35. Timelines

URL	Method	Functionality
/api/v1/timeline/user/{userId}	GET	List user timeline
/api/v1/timeline/profile/{userId}	GET	List profile timeline
/api/v1/timeline/project/{projectId}	GET	List project timeline

2.36. Locales

URL	Method	Functionality
/api/v1/locales	GET	List locales

2.37. Stats

URL	Method	Functionality
/api/v1/stats/discover	GET	Get discover stats
/api/v1/stats/system	GET	Get system stats

3. Auth

3.1. Normal login

To login a user send a POST request containing the following data:

- **type** with value "normal"
- **username** (required): this field also supports the user email
- **password** (required)

```
curl -X POST \
  -H "Content-Type: application/json" \
  -d '{
    "type": "normal",
    "username": "'${USERNAME}'",
    "password": "'${PASSWORD}'"
  }' \
  https://api.taiga.io/api/v1/auth
```

When the login is successful, the HTTP response is a 200 OK and the response body is a JSON [user auth detail object](#)

3.2. Github login

To login a user via GitHub send a POST request containing the following data:

- **type** with value "github"
- **code** (required): your github authentication code
- **token**: generated when creating a project's membership (for accept invitations to projects)

```
curl -X POST \
  -H "Content-Type: application/json" \
  -d '{
    "type": "github",
    "code": "${GITHUB_CODE}"
  }' \
  https://api.taiga.io/api/v1/auth
```

When the login is successful, the HTTP response is a 200 OK and the response body is a JSON [user auth detail object](#)

NOTE

Get GitHub authorized code

To get the GitHub code you have to follow the first step *Redirect users to request GitHub access* described in [GitHub Documentation for Developers - API - OAuth - Web Application Flow](#).

Taiga needs privileges to get the user email from Github so you have to use the scope `user:email`.

3.3. Public registry

To register a user without invitation send a POST request containing the following data:

- **type** with value "public"
- **username** (required)
- **password** (required)
- **email** (required)
- **full_name** (required)

```
curl -X POST \
-H "Content-Type: application/json" \
-d '{
    "type": "public",
    "username": "'${USERNAME}'",
    "password": "'${PASSWORD}'",
    "email": "'${EMAIL}'",
    "full_name": "'${FULL_NAME}'"
}' \
https://api.taiga.io/api/v1/auth/register
```

When the registration is successful, the HTTP response is a 201 CREATED and the response body is a JSON [user auth detail object](#)

3.4. Private registry

To add a user into a project via invitation send a POST request containing the following data:

- **type** with value "private"
- **existing** (required): indicates if the user is member or not
- **token** (required): generated when creating a project's membership
- **username** (required)
- **password** (required)
- **email** (required only if the user doesn't exist in the platform)
- **full_name** (required only if the user doesn't exist in the platform)

```
curl -X POST \
-H "Content-Type: application/json" \
-d '{
    "type": "private",
    "existing": false,
    "token": "e8ea658e-6655-11e4-9d95-b499ba562790",
    "username": "'${USERNAME}'",
    "password": "'${PASSWORD}'",
    "email": "'${EMAIL}'",
    "full_name": "'${FULL_NAME}'"
}' \
https://api.taiga.io/api/v1/auth/register
```

When the registration is successful, the HTTP response is a 201 CREATED and the response body is a JSON [user auth detail object](#)

4. Applications

4.1. Get

To get an application send a GET request specifying the application id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/applications/a60c3208-5234-11e5-96df-68f72800aadd
```

The HTTP response is a 200 OK and the response body is a JSON [application object](#)

4.2. Get token

To get an application token send a GET request specifying the application id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/applications/a60c3208-5234-11e5-96df-68f72800aadd/token
```

The HTTP response is a 200 OK and the response body is a JSON [application token object](#)

5. Application tokens

5.1. List

To list the application tokens for an authenticated user send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/application-tokens
```

The HTTP response is a 200 OK and the response body is a JSON list of [application token objects](#)

5.2. Get

To get an application token send a GET request specifying the application token id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/application-tokens/1
```

The HTTP response is a 200 OK and the response body is a JSON [application token object](#)

5.3. Delete

To delete application tokens send a DELETE specifying the application token id in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/application-tokens/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

5.4. Authorize

To request an authorization code send a POST request with the following data:

- **application**: the application id for the requested token
- **state**: an unguessable random string. It is used to protect against cross-site request forgery attacks. The API will include this value when the validation process is completed so the final app can verify it matches the original one.

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer
eyJ1c2VyX2F1dGhbnRpY2F0aW9uX2lkIjo0fQ:1ZX33b:QnAN3EcuChLoRVf3CdybWEi20Eg" \
-d '{
    "application": "a60c3208-5234-11e5-96df-68f72800aadd",
    "state": "random-state"
}' \
https://api.taiga.io/api/v1/application-tokens/authorize
```

When the creation is successful, the HTTP response is a 200 and the response body is a JSON [authorization code object](#)

5.5. Validate

To validate an authorization code send a POST request with the following data:

- **application**: the application id for the requested token
- **state**: an unguessable random string. It is used to protect against cross-site request forgery attacks. The API will include this value when the validation process is completed so the final app can verify it matches the original one.
- **auth_code**: the authorization code received on previous the steps.

```
curl -X POST \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer
eyJ1c2VyX2F1dGhbnRpY2F0aW9uX21kIjo0fQ:1ZX33b:QnAN3EcuChLoRVf3CdybWEi20Eg" \
-d '{
    "application": "a60c3208-5234-11e5-96df-68f72800aadd",
    "auth_code": "21ce08c4-5237-11e5-a8a3-68f72800aadd",
    "state": "random-state"
}' \
https://api.taiga.io/api/v1/application-tokens/validate
```

When the creation is successful, the HTTP response is a 200 and the response body is a JSON [cyphered token object](#)

6. Resolver

6.1. Projects

To resolve the id of a project send a GET request with the following parameters:

- **project** (required): the project slug trying to be resolved

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/resolver?project=taiga
```

The response body is a JSON object containing the project id

```
{  
  "project": 1  
}
```

6.2. User stories

To resolve the id of a user story send a GET request with the following parameters:

- **project** (required): the project slug trying to be resolved
- **us** (required): the user story ref trying to be resolved

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/resolver?project=taiga&us=1
```

The response body is a JSON object containing the project and the user story ids

```
{  
  "us": 26,  
  "project": 1  
}
```

6.3. Issues

To resolve the id of an issue send a GET request with the following parameters:

- **project** (required): the project slug trying to be resolved
- **issue** (required): the issue ref trying to be resolved

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/resolver?project=taiga&issue=1485
```

The response body is a JSON object containing the project and the issue ids

```
{  
  "issue": 5209,  
  "project": 1  
}
```

6.4. Tasks

To resolve the id of a task send a GET request with the following parameters:

- **project** (required): the project slug trying to be resolved
- **task** (required): the task ref trying to be resolved

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/resolver?project=taiga\&task=915
```

The response body is a JSON object containing the project and the task ids

```
{  
  "task": 1336,  
  "project": 1  
}
```

6.5. Milestones

To resolve the id of a milestone send a GET request with the following parameters:

- **project** (required): the project slug trying to be resolved
- **milestone** (required): the milestone slug trying to be resolved

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/resolver?project=taiga\&milestone=sprint-0
```

The response body is a JSON object containing the project and the milestone ids

```
{  
  "milestone": 1,  
  "project": 1  
}
```

6.6. Wiki pages

To resolve the id of a wiki page send a GET request with the following parameters:

- **project** (required): the project slug trying to be resolved
- **wikipage**(required): the wiki-page slug trying to be resolved

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/resolver?project=taiga\&wikipage=home
```

The response body is a JSON object containing the project and the wiki page ids

```
{  
  "wikipage": 2,  
  "project": 1  
}
```

6.7. Multiple resolution

To resolve the multiple ids you can send a GET mixing parameters from the previous examples:

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/resolver?project=taiga\&task=915\&us=1\&wikipage=home
```

The response body is a JSON object containing the project and the task ids

```
{  
  "project": 1,  
  "task": 1336,  
  "us": 26,  
  "wikipage": 2  
}
```

6.8. By ref value

To resolve an object if we don't know its type we have to use `ref` GET parameter:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/resolver?project=taiga&ref=915
```

The response body is a JSON object containing the project and the story, task or issue id.

```
{  
  "project": 1,  
  "task": 1336  
}
```

Incompatibility between GET params

IMPORTANT

Be careful because `ref` is incompatible with `us`, `task` and `issue` parameters in requests with multiple resolutions.

7. Searches

7.1. Search

To search send a GET request with the following get parameters:

- **project** (required): project id
- **text**: string

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/search?project=1&text=design
```

The HTTP response is a 200 OK and the response body is a JSON list of [search results detail objects](#)

8. User storage

8.1. List

To list user storage data send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/user-storage
```

The HTTP response is a 200 OK and the response body is a JSON list of [user storage data objects](#)

8.2. Create

To create user storage data send a POST request with the following data:

- **key**: string
- **value**: string

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "key": "favorite-forest",  
    "value": "Taiga"  
' \  
https://api.taiga.io/api/v1/user-storage
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [user storage data object](#)

8.3. Get

To get a user storage data send a GET request specifying the user storage key in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/user-storage/favorite-forest
```

The HTTP response is a 200 OK and the response body is a JSON [user storage data object](#)

8.4. Edit

To edit user storage data send a PUT or a PATCH specifying the user storage key in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "value": "Russian Taiga"
}' \
https://api.taiga.io/api/v1/user-storage/favorite-forest
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [user storage data object](#)

8.5. Delete

To delete user storage data send a DELETE specifying the user storage key in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/user-storage/favorite-forest
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

9. Project templates

9.1. List

To list project templates send a GET request with the following parameters:

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/project-templates
```

The HTTP response is a 200 OK and the response body is a JSON list of [project template detail objects](#)

9.2. Create

To create project templates send a POST request with the following data:

- **name** (required): string
- **slug**: slug
- **description** (required): string
- **default_owner_role** (required):
- **is_backlog_activated**: boolean
- **is_kanban_activated**: boolean
- **is_wiki_activated**: boolean
- **is_issues_activated**: boolean
- **videoconferences**: (talky|appear-in)
- **videoconferences_extra_data**: string
- **default_options**: a json with a list of objects with:
 - **points**: slug
 - **us_status**: slug
 - **task_status**: slug
 - **issue_status**: slug
 - **issue_type**: slug
 - **priority**: slug
 - **severity**: slug
- **us_statuses**: a json with a list of objects with:
 - **name**: string

- **slug**: slug
 - **is_closed**: boolean
 - **color**: #rgb color
 - **wip_limit**: integer or none
 - **order**: integer
- **points**: a json with a list of objects with:
 - **name**: string
 - **value**: integer or none
 - **order**: integer
- **task_statuses**: a json with a list of objects with:
 - **name**: string
 - **slug**: slug
 - **is_closed**: boolean
 - **color**: #rgb color
 - **order**: integer
- **issue_statuses**: a json with a list of objects with:
 - **name**: string
 - **slug**: slug
 - **is_closed**: boolean
 - **color**: #rgb color
 - **order**: integer
- **issue_types**: a json with a list of objects with:
 - **name**: string
 - **color**: #rgb color
 - **order**: integer
- **priorities**: a json with a list of objects with:
 - **name**: string
 - **color**: #rgb color
 - **order**: integer
- **severities**: a json with a list of objects with:
 - **name**: string

- **color**: #rgb color
- **order**: integer
- **roles**: a json with a list of objects with:
 - **name**: string
 - **slug**: slug
 - **permissions**: list of permissions
 - **order**: integer
 - **computable**: boolean

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "default_options": {
    "us_status": "New",
    "points": "?",
    "priority": "Normal",
    "severity": "Normal",
    "task_status": "New",
    "issue_type": "Bug",
    "issue_status": "New"
  },
  "us_statuses": [
    {
      "wip_limit": null,
      "color": "#999999",
      "name": "New",
      "order": 1,
      "is_closed": false
    },
    {
      "wip_limit": null,
      "color": "#f57900",
      "name": "Ready",
      "order": 2,
      "is_closed": false
    },
    {
      "wip_limit": null,
      "color": "#729fcf",
      "name": "In progress",
      "order": 3,
      "is_closed": false
    }
  ]
}'
```

```
},
{
  "wip_limit": null,
  "color": "#4e9a06",
  "name": "Ready for test",
  "order": 4,
  "is_closed": false
},
{
  "wip_limit": null,
  "color": "#cc0000",
  "name": "Done",
  "order": 5,
  "is_closed": true
}
],
"points": [
  {
    "value": null,
    "name": "?",
    "order": 1
  },
  {
    "value": 0.0,
    "name": "0",
    "order": 2
  },
  {
    "value": 0.5,
    "name": "1/2",
    "order": 3
  },
  {
    "value": 1.0,
    "name": "1",
    "order": 4
  },
  {
    "value": 2.0,
    "name": "2",
    "order": 5
  },
  {
    "value": 3.0,
    "name": "3",
    "order": 6
  },
  {
    "value": 4.0,
    "name": "4",
    "order": 7
  }
]
```

```
        "value": 5.0,
        "name": "5",
        "order": 7
    },
    {
        "value": 8.0,
        "name": "8",
        "order": 8
    },
    {
        "value": 10.0,
        "name": "10",
        "order": 9
    },
    {
        "value": 15.0,
        "name": "15",
        "order": 10
    },
    {
        "value": 20.0,
        "name": "20",
        "order": 11
    },
    {
        "value": 40.0,
        "name": "40",
        "order": 12
    }
],
"task_statuses": [
    {
        "color": "#999999",
        "name": "New",
        "order": 1,
        "is_closed": false
    },
    {
        "color": "#729fcf",
        "name": "In progress",
        "order": 2,
        "is_closed": false
    },
    {
        "color": "#f57900",
        "name": "Ready for test",
        "order": 3,
        "is_closed": true
    }
]
```

```
},
{
  "color": "#4e9a06",
  "name": "Closed",
  "order": 4,
  "is_closed": true
},
{
  "color": "#cc0000",
  "name": "Needs Info",
  "order": 5,
  "is_closed": false
}
],
"issue_statuses": [
  {
    "color": "#999999",
    "name": "New",
    "order": 1,
    "is_closed": false
  },
  {
    "color": "#729fcf",
    "name": "In progress",
    "order": 2,
    "is_closed": false
  },
  {
    "color": "#f57900",
    "name": "Ready for test",
    "order": 3,
    "is_closed": true
  },
  {
    "color": "#4e9a06",
    "name": "Closed",
    "order": 4,
    "is_closed": true
  },
  {
    "color": "#cc0000",
    "name": "Needs Info",
    "order": 5,
    "is_closed": false
  },
  {
    "color": "#d3d7cf",
    "name": "Rejected",
    "order": 6,
    "is_closed": false
  }
]
```

```
        "order": 6,
        "is_closed": true
    },
    {
        "color": "#75507b",
        "name": "Postponed",
        "order": 7,
        "is_closed": false
    }
],
"issue_types": [
    {
        "color": "#cc0000",
        "name": "Bug",
        "order": 1
    },
    {
        "color": "#729fcf",
        "name": "Question",
        "order": 2
    },
    {
        "color": "#4e9a06",
        "name": "Enhancement",
        "order": 3
    }
],
"priorities": [
    {
        "color": "#999999",
        "name": "Low",
        "order": 1
    },
    {
        "color": "#4e9a06",
        "name": "Normal",
        "order": 3
    },
    {
        "color": "#CC0000",
        "name": "High",
        "order": 5
    }
],
"severities": [
    {
        "color": "#999999",
        "name": "Wishlist",
        "order": 1
    }
]
```

```

        "order": 1
    },
    {
        "color": "#729fcf",
        "name": "Minor",
        "order": 2
    },
    {
        "color": "#4e9a06",
        "name": "Normal",
        "order": 3
    },
    {
        "color": "#f57900",
        "name": "Important",
        "order": 4
    },
    {
        "color": "#CC0000",
        "name": "Critical",
        "order": 5
    }
],
"roles": [
    {
        "permissions": [
            "add_issue", "modify_issue", "delete_issue",
            "view_issues", "add_milestone", "modify_milestone",
            "delete_milestone", "view_milestones", "view_project",
            "add_task", "modify_task", "delete_task", "view_tasks",
            "add_us", "modify_us", "delete_us", "view_us",
            "add_wiki_page", "modify_wiki_page", "delete_wiki_page",
            "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
            "view_wiki_links"
        ],
        "order": 10,
        "computable": true,
        "slug": "ux",
        "name": "UX"
    },
    {
        "permissions": [
            "add_issue", "modify_issue", "delete_issue",
            "view_issues", "add_milestone", "modify_milestone",
            "delete_milestone", "view_milestones", "view_project",
            "add_task", "modify_task", "delete_task", "view_tasks",
            "add_us", "modify_us", "delete_us", "view_us",
            "add_wiki_page", "modify_wiki_page", "delete_wiki_page",
            "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
            "view_wiki_links"
        ]
    }
]

```

```
        "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
        "view_wiki_links"
    ],
    "order": 20,
    "computable": true,
    "slug": "design",
    "name": "Design"
},
{
    "permissions": [
        "add_issue", "modify_issue", "delete_issue",
        "view_issues", "add_milestone", "modify_milestone",
        "delete_milestone", "view_milestones", "view_project",
        "add_task", "modify_task", "delete_task", "view_tasks",
        "add_us", "modify_us", "delete_us", "view_us",
        "add_wiki_page", "modify_wiki_page", "delete_wiki_page",
        "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
        "view_wiki_links"
    ],
    "order": 30,
    "computable": true,
    "slug": "front",
    "name": "Front"
},
{
    "permissions": [
        "add_issue", "modify_issue", "delete_issue",
        "view_issues", "add_milestone", "modify_milestone",
        "delete_milestone", "view_milestones", "view_project",
        "add_task", "modify_task", "delete_task", "view_tasks",
        "add_us", "modify_us", "delete_us", "view_us",
        "add_wiki_page", "modify_wiki_page", "delete_wiki_page",
        "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
        "view_wiki_links"
    ],
    "order": 40,
    "computable": true,
    "slug": "back",
    "name": "Back"
},
{
    "permissions": [
        "add_issue", "modify_issue", "delete_issue",
        "view_issues", "add_milestone", "modify_milestone",
        "delete_milestone", "view_milestones", "view_project",
        "add_task", "modify_task", "delete_task", "view_tasks",
        "add_us", "modify_us", "delete_us", "view_us",
        "add_wiki_page", "modify_wiki_page", "delete_wiki_page",
        "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
        "view_wiki_links"
    ]
}
```

```

        "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
        "view_wiki_links"
    ],
    "order": 50,
    "computable": false,
    "slug": "product-owner",
    "name": "Product Owner"
},
{
    "permissions": [
        "add_issue", "modify_issue", "delete_issue",
        "view_issues", "view_milestones", "view_project",
        "view_tasks", "view_us", "modify_wiki_page",
        "view_wiki_pages", "add_wiki_link", "delete_wiki_link",
        "view_wiki_links"
    ],
    "order": 60,
    "computable": false,
    "slug": "stakeholder",
    "name": "Stakeholder"
}
],
"id": 2,
"name": "Kanban",
"slug": "kanban",
"description": "Sample description",
"default_owner_role": "product-owner",
"is_backlog_activated": false,
"is_kanban_activated": true,
"is_wiki_activated": false,
"is_issues_activated": false,
"videoconferences": null,
"videoconferences_extra_data": ""
}' \
https://api.taiga.io/api/v1/project-templates

```

```

curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-D '{
    "name": "Kanban",
    "description": "Sample description",
    "default_owner_role": "product-owner"
}' \
https://api.taiga.io/api/v1/project-templates

```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [project template detail object](#)

9.3. Get

To get a project template send a GET request specifying the project template id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/project-templates/1
```

The HTTP response is a 200 OK and the response body is a JSON [project template detail object](#)

9.4. Edit

To edit project templates send a PUT or a PATCH specifying the project template id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "description": "New description"
}' \
https://api.taiga.io/api/v1/project-templates/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [project template detail object](#)

9.5. Delete

To delete project template send a DELETE specifying the project template id in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/project-templates/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

10. Projects

10.1. List

To list projects send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects
```

The HTTP response is a 200 OK and the response body is a JSON list of [project list entry objects](#)

The results can be filtered using the following parameters:

- **member**: member id
- **members**: member ids
- **is_looking_for_people**: the project is looking for new members
- **is_featured**: the project has been highlighted by the instance staff
- **is_backlog_activated**: backlog is active
- **is_kanban_activated**: kanban is active

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects?member=1
```

The results can be ordered using the `order_by` parameter with the values:

- **memberships_user_order**: the project order specified by the user
- **total_fans**: total fans for the project
- **total_fans_last_week**: number of new fans in the last week
- **total_fans_last_month**: number of new fans in the last month
- **total_fans_last_year**: number of new fans in the last year
- **total_activity**: number of history entries for the project
- **total_activity_last_week**: number of history entries generated in the last week
- **total_activity_last_month**: number of history entries generated in the last month
- **total_activity_last_year**: number of history entries generated in the last year

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects?member=1&order_by=memberships__user_order
```

10.2. Create

To create projects send a POST request with the following data:

- **name** (required)
- **description** (required)
- **creation_template**: base template for the project
- **is_backlog_activated**
- **is_issues_activated**
- **is_kanban_activated**
- **is_private**
- **is_wiki_activated**
- **videoconferences**: appear-in or talky, the third party used for meetups if enabled
- **videoconferences_extra_data**: string used for the videoconference chat url generation
- **total_milestones**
- **total_story_points**

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Beta project",  
    "description": "Beta description"  
}' \  
https://api.taiga.io/api/v1/projects
```

```
curl -v -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "name": "Beta project",
  "description": "Taiga",
  "creation_template": 1,
  "is_backlog_activated": false,
  "is_issues_activated": true,
  "is_kanban_activated": true,
  "is_private": false,
  "is_wiki_activated": true,
  "videoconferences": "appear-in",
  "videoconferences_extra_data": null,
  "total_milestones": 3,
  "total_story_points": 20.0
}' \
https://api.taiga.io/api/v1/projects
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [project detail object](#)

10.3. Get

To get a project send a GET request specifying the project id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1
```

The HTTP response is a 200 OK and the response body is a JSON [project detail object](#)

10.4. Get by slug

To get a project send a GET request specifying the project slug as parameter:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/by_slug?slug=test
```

The HTTP response is a 200 OK and the response body is a JSON [project detail object](#)

10.5. Edit

To edit projects send a PUT or a PATCH specifying the project id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PUT \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Beta project put",
    "description": "Beta description"
}' \
https://api.taiga.io/api/v1/projects/1
```

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Beta project patch"
}' \
https://api.taiga.io/api/v1/projects/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [project detail object](#)

10.6. Delete

To delete projects send a DELETE specifying the project id in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

10.7. Bulk update order

To update the projects order for the logged in user send a POST request with a json list where each element is a json object with two attributes, the project id and the new order

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '[
  {
    "project_id": 123,
    "order": 2
  },
  {
    "project_id": 456,
    "order": 2
  }
]' \
https://api.taiga.io/api/v1/projects/bulk_update_order
```

When the update is successful, the HTTP response is a 200 OK and the response body is empty

10.8. Get modules configuration

To get a project modules configuration send a GET request specifying the project id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/modules
```

The HTTP response is a 200 OK and the response body is a JSON [project modules configuration object](#)

10.9. Edit modules configuration

To edit a project modules configuration send a PATCH specifying the project id in the url.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "github": {
    "secret": "new_secret"
  }
}' \
https://api.taiga.io/api/v1/projects/1/modules
```

When edition succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

10.10. Stats

To get a project stats send a GET request specifying the project id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/stats
```

The HTTP response is a 200 OK and the response body is a JSON [project stats object](#)

10.11. Issue stats

To get a project issue stats send a GET request specifying the project id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/issues_stats
```

The HTTP response is a 200 OK and the response body is a JSON [project issue stats object](#)

10.12. Issue filters data

To get a project issue filters data send a GET request specifying the project id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/issue_filters_data
```

The HTTP response is a 200 OK and the response body is a JSON [project issue filters data object](#)

10.13. Tag colors

To get a project tag colors stats send a GET request specifying the project id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects/1/tags_colors
```

The HTTP response is a 200 OK and the response body is a JSON [project tag colors](#) object

10.14. Like a project

To like a project send a POST request specifying the project id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects/1/like
```

The HTTP response is a 200 OK with an empty body response

10.15. Unlike a project

To unlike a project send a POST request specifying the project id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects/1/unlike
```

The HTTP response is a 200 OK with an empty body response

10.16. List project fans

To get the list of fans from a project send a GET request specifying the project id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/projects/1/fans
```

The HTTP response is a 200 OK and the response body is a JSON list of [project voter](#) object

10.17. Watch a project

To watch a project send a POST request specifying the project id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "notify_level": 3
}' \
https://api.taiga.io/api/v1/projects/1/watch
```

The HTTP response is a 200 OK with an empty body response

10.18. Stop watching project

To stop watching a project send a POST request specifying the project id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/unwatch
```

The HTTP response is a 200 OK with an empty body response

10.19. List project watchers

To get the list of watchers from a project send a GET request specifying the project id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/watchers
```

The HTTP response is a 200 OK and the response body is a JSON list of [project watcher object](#)

10.20. Create template

To create a template from a selected project send a POST request specifying the project id in the url with the following parameters:

- **name** (required)
- **description** (required)

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "template_name": "Beta template",
    "template_description": "Beta template description"
}' \
https://api.taiga.io/api/v1/projects/1/create_template
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [project template detail object](#)

10.21. Leave

To leave a project send a POST request specifying the project id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/leave
```

The HTTP response is a 200 OK with an empty body response

10.22. Change logo

To change your project logo send a POST with the following data

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-F "logo=@/tmp/test.png" \
https://api.taiga.io/api/v1/projects/1/change_logo
```

When the change is successful, the HTTP response is a 200 OK and the response body is a JSON [project detail object](#)

10.23. Remove logo

To remove your project logo send a POST with the following data

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/remove_logo
```

When the change is successful, the HTTP response is a 200 OK and the response body is a JSON [project detail object](#)

10.24. Transfer request

To request to the owner the transfer of a project send a POST request specifying the project id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/projects/1/transfer_request
```

The HTTP response is a 200 OK with an empty body response

10.25. Transfer start

To start the transfer of one of your projects to another user send a POST request specifying the project id in the url and containing the following data:

- **user**: user id of other admin member of the project.

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "user": "${USER_ID}",
}' \
https://api.taiga.io/api/v1/projects/1/transfer_start
```

The HTTP response is a 200 OK with an empty body response

10.26. Transfer accept

To accept the transfer of one project to your user send a POST request specifying the project id in the url and containing the following data:

- **token**: valid transfer token received by email.
- **reason**: text included in the email response to the project owner.

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "token": "${TRANSFER_TOKEN}",
  "reason": "testing"
}' \
https://api.taiga.io/api/v1/projects/1/transfer_accept
```

The HTTP response is a 200 OK with an empty body response

10.27. Transfer reject

To reject the transfer of one project to your user send a POST request specifying the project id in the url and containing the following data:

- **token**: valid transfer token received by email.
- **reason**: text included in the email response to the project owner.

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "token": "${TRANSFER_TOKEN}",
  "reason": "testing"
}' \
https://api.taiga.io/api/v1/projects/1/transfer_reject
```

The HTTP response is a 200 OK with an empty body response

11. Memberships/Invitations

11.1. List

To list memberships send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/memberships
```

The HTTP response is a 200 OK and the response body is a JSON list of **membership detail** objects

The results can be filtered using the following parameters:

- **project**: project id
- **role**: role id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/memberships?project=1
```

11.2. Create

To create memberships/invitations send a POST request with the following data:

- **project** (required)
- **role** (required): Role to the membership
- **email** (required): user email

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project": 3,  
    "role": 12,  
    "email": "test@test.com"  
}' \  
https://api.taiga.io/api/v1/memberships
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [membership detail object](#)

11.3. Bulk creation

To create multiple memberships at the same time send a POST request with the following data:

- **project_id** (required)
- **bulk_memberships** (required): a list of dicts with
 - **role_id**
 - **email**
- **invitation_extra_text**: string

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_memberships": [
        {"role_id": 10, "email": "test@test.com"},
        {"role_id": 12, "email": "john@doe.com"}
    ]
}' \
https://api.taiga.io/api/v1/memberships/bulk_create
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [membership detail object](#)

11.4. Get

To get a membership send a GET request specifying the membership id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/memberships/1
```

The HTTP response is a 200 OK and the response body is a JSON [membership detail object](#)

11.5. Edit

To edit memberships send a PUT or a PATCH specifying the membership id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "role": 10
}' \
https://api.taiga.io/api/v1/memberships/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [membership detail object](#)

11.6. Delete

To delete memberships/invitations send a DELETE specifying the membership id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/memberships/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

11.7. Resend invitation

To resend an invitation send a POST request specifying the membership id in the url

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/memberships/1/resend_invitation
```

The HTTP response is a 200 OK and the response body is a JSON [membership detail object](#)

11.8. Get Invitation (by token)

To get an invitation send a GET request specifying the invitation id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/invitations/8e3af6bcd4
```

The HTTP response is a 200 OK and the response body is a JSON [membership detail object](#)

12. Milestones

12.1. List

To list milestones send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/milestones
```

The HTTP response is a 200 OK and the response body is a JSON list of [milestone detail objects](#)

The results can be filtered using the following parameters:

- **project**: project ID
- **closed**: `true` to get only closed milestones or `false` to get only opened ones.

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/milestones?project=1
```

When you filter milestones by project ID ([/api/v1/milestones?project=<projectID>](#)) the response has two new headers:

NOTE

- **Taiga-Info-Total-Opened-Milestones**: the number of opened milestones for this project.
- **Taiga-Info-Total-Closed-Milestones**: the number of closed milestones for this project.

12.2. Create

To create milestone send a POST request with the following data:

- **project** (required): project id
- **name** (required): string
- **estimated_start** (required): iso date (YYYY-MM-DD)
- **estimated_finish** (required): iso date (YYYY-MM-DD)
- **disponibility**: float
- **slug**: slug
- **order**: integer
- **watchers**: array of watcher id's

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 3,
  "name": "Sprint 1",
  "estimated_start": "2014-10-20",
  "estimated_finish": "2014-11-04",
  "disponibility": 30,
  "slug": "sprint-1",
  "order": 1,
  "watchers": []
}' \
https://api.taiga.io/api/v1/milestones
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 3,
  "name": "Sprint 3",
  "estimated_start": "2014-10-20",
  "estimated_finish": "2014-11-04"
}' \
https://api.taiga.io/api/v1/milestones
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [milestone detail object](#)

12.3. Get

To get a milestone send a GET request specifying the milestone id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/milestones/1
```

The HTTP response is a 200 OK and the response body is a JSON [milestone detail object](#)

12.4. Edit

To edit milestones send a PUT or a PATCH specifying the milestone id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "name": "Sprint 2"
  }' \
  https://api.taiga.io/api/v1/milestones/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [milestone detail object](#)

12.5. Delete

To delete milestones send a DELETE specifying the milestone id in the url

```
curl -X DELETE \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/milestones/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

12.6. Stats

To get the milestone stats send a GET request specifying the milestone id in the url

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/milestones/1/stats
```

The HTTP response is a 200 OK and the response body is a JSON [milestone stats detail object](#)

12.7. Watch a milestone

To watch a milestone send a POST request specifying the milestone id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/milestones/1/watch
```

The HTTP response is a 200 OK with an empty body response

12.8. Stop watching a milestone

To stop watching an milestone send a POST request specifying the milestone id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/milestones/1/unwatch
```

The HTTP response is a 200 OK with an empty body response

12.9. List milestone watchers

To get the list of watchers from a milestone send a GET request specifying the milestone id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/milestones/1/watchers
```

The HTTP response is a 200 OK and the response body is a JSON list of [milestone watcher](#) object

13. User stories

13.1. List

To list user stories send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstories
```

The HTTP response is a 200 OK and the response body is a JSON list of [user story](#) list objects

The results can be filtered using the following parameters:

- **project**: project id
- **milestone**: milestone id
- **milestone_isnull**: (true | false) if you are looking for user stories associated with a milestone or not
- **status**: status id
- **status_is_archived**: (true | false)
- **watchers**: watching user id
- **assigned_to**: assigned to user id
- **status_is_closed**: (true | false)

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/userstories?project=1
```

13.2. Create

To create user stories send a POST request with the following data:

- **assigned_to**: user id
- **backlog_order**: order in the backlog
- **blocked_note**: reason why the user story is blocked
- **client_requirement**: boolean
- **description**: string
- **is_blocked**: boolean
- **is_closed**: boolean
- **kanban_order**: order in the kanban
- **milestone**: milestone id
- **points**: dictionary of points
- **project** (required): project id
- **sprint_order**: order in the milestone
- **status**: status id
- **subject** (required)
- **tags**: array of strings

- **team_requirement**: boolean
- **watchers**: array of watcher id's

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "assigned_to": null,
    "backlog_order": 2,
    "blocked_note": "blocking reason",
    "client_requirement": false,
    "description": "Implement API CALL",
    "is_blocked": false,
    "is_closed": true,
    "kanban_order": 37,
    "milestone": null,
    "points": {
        "129": 361,
        "130": 361,
        "131": 361,
        "132": 364
    },
    "project": 3,
    "sprint_order": 2,
    "status": 13,
    "subject": "Customer personal data",
    "tags": [
        "service catalog",
        "customer"
    ],
    "team_requirement": false,
    "watchers": []
}' \
https://api.taiga.io/api/v1/userstories
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project": 3,
    "subject": "Customer personal data"
}' \
https://api.taiga.io/api/v1/userstories
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON

[user story detail object](#)

13.3. Get

To get a user story send a GET request specifying the user story id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1
```

The HTTP response is a 200 OK and the response body is a JSON [user story detail \(GET\) object](#)

13.4. Get by ref

To get a user story send a GET request specifying the user story reference and the project id as parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/by_ref?ref=1&project=1
```

The HTTP response is a 200 OK and the response body is a JSON [user story detail \(GET\) object](#)

13.5. Edit

To edit user stories send a PUT or a PATCH specifying the user story id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "subject": "Patching subject"
}' \
https://api.taiga.io/api/v1/userstories/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [user story detail object](#)

13.6. Delete

To delete user stories send a DELETE specifying the user story id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstories/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

13.7. Bulk creation

To create multiple user stories at the same time send a POST request with the following data:

- **project_id** (required)
- **status_id**
- **bulk_stories**: user story subjects, one per line

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_stories": "US 1 \n US 2 \n US 3"  
}' \  
https://api.taiga.io/api/v1/userstories/bulk_create
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON list of [user story detail object](#)

13.8. Bulk update backlog order

To update the backlog order of multiple user stories at the same time send a POST request with the following data:

- **project_id** (required)
- **bulk_stories**: list where each element is a json object with two attributes, the user story id and the new order

```

curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_stories": [
        {
            "us_id": 123,
            "order": 2
        },
        {
            "us_id": 456,
            "order": 2
        }
    ]
}' \
https://api.taiga.io/api/v1/userstories/bulk_update_backlog_order

```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON list of [user story detail object](#)

13.9. Bulk update kanban order

To update the kanban order of multiple user stories at the same time send a POST request with the following data:

- **project_id** (required)
- **bulk_stories**: list where each element is a json object with two attributes, the user story id and the new order

```

curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_stories": [
        {
            "us_id": 123,
            "order": 2
        },
        {
            "us_id": 456,
            "order": 2
        }
    ]
}' \
https://api.taiga.io/api/v1/userstories/bulk_update_kanban_order

```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON list of [user story detail object](#)

13.10. Bulk update sprint order

To update the sprint order of multiple user stories at the same time send a POST request with the following data:

- **project_id** (required)
- **bulk_stories**: list where each element is a json object with two attributes, the user story id and the new order

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project_id": 3,
  "bulk_stories": [
    {
      "us_id": 123,
      "order": 2
    },
    {
      "us_id": 456,
      "order": 2
    }
  ]
}' \
https://api.taiga.io/api/v1/userstories/bulk_update_sprint_order
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON list of [user story detail object](#)

13.11. Vote a user story

To add a vote to a user story send a POST request specifying the user story id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1/upvote
```

The HTTP response is a 200 OK with an empty body response

13.12. Remove vote from a user story

To remove a vote from a user story send a POST request specifying the user story id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1/downvote
```

When remove of the vote succeeded, the HTTP response is a 200 OK with an empty body response

13.13. Get user story voters list

To get the list of voters from a user story send a GET request specifying the user story id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1/voters
```

The HTTP response is a 200 OK and the response body is a JSON list of [user story voter object](#)

13.14. Watch a user story

To watch a user story send a POST request specifying the project id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1/watch
```

The HTTP response is a 200 OK with an empty body response

13.15. Stop watching a user story

To stop watching a user story send a POST request specifying the user story id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1/unwatch
```

The HTTP response is a 200 OK with an empty body response

13.16. List user story watchers

To get the list of watchers from a user story send a GET request specifying the user story id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/1/watchers
```

The HTTP response is a 200 OK and the response body is a JSON list of [user story watcher object](#)

13.17. List attachments

To list user story attachments send a GET request with the following parameters:

- **project**: project id
- **object_id**: user story id

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/attachments?object_id=81&project=3
```

The HTTP response is a 200 OK and the response body is a JSON list of [attachment detail objects](#)

13.18. Create attachment

To create user story attachments send a POST request with the following data:

- **object_id** (required): user story id
- **project** (required): project id
- **attached_file** (required): attaching file
- **description**
- **is_DEPRECATED**

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-F "object_id=81" \
-F "project=3" \
-F "attached_file=@/tmp/test.png" \
https://api.taiga.io/api/v1/userstories/attachments
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [attachment detail object](#)

13.19. Get attachment

To get a user story attachment send a GET request specifying the user story attachment id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstories/attachments/415
```

The HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

13.20. Edit attachment

To edit user story attachments send a PUT or a PATCH specifying the user story attachment id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-F "description=patching description" \  
https://api.taiga.io/api/v1/userstories/attachments/417
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

13.21. Delete attachment

To delete user story attachments send a DELETE specifying the user story attachment id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstories/attachments/415
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

14. User story status

14.1. List

To list user story status send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstory-statuses
```

The HTTP response is a 200 OK and the response body is a JSON list of [user story status detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstory-statuses?project=1
```

14.2. Create

To create user story statuses send a POST request with the following data:

- **color**: in hexadecimal
- **is_closed**: (true | false)
- **name** (required)
- **order**: integer
- **project**: (required): project id
- **wip_limit**: integer representing the max number of user stories in this status

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "color": "#AAAAAA",  
    "is_closed": true,  
    "name": "New status",  
    "order": 8,  
    "project": 3,  
    "wip_limit": 6  
' \  
https://api.taiga.io/api/v1/userstory-statuses
```

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project": 3,  
    "name": "New status name"  
}' \  
https://api.taiga.io/api/v1/userstory-statuses
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [user story status detail object](#)

14.3. Get

To get a user story status send a GET request specifying the user story status id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstory-statuses/1
```

The HTTP response is a 200 OK and the response body is a JSON [user story status detail object](#)

14.4. Edit

To edit user story statuses send a PUT or a PATCH specifying the user story status id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Patch status name"  
}' \  
https://api.taiga.io/api/v1/userstory-statuses/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [user story status detail object](#)

14.5. Delete

To delete user story statuses send a DELETE specifying the user story status id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/userstory-statuses/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

14.6. Bulk update order

To update the order of multiple user story statuses at the same time send a POST request with the following data:

- **project** (required)
- **bulk_userstory_statuses**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_userstory_statuses": [[1,10], [2,5]]  
}' \  
https://api.taiga.io/api/v1/userstory-statuses/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

15. Points

15.1. List

To list points send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/points
```

The HTTP response is a 200 OK and the response body is a JSON list of [point detail objects](#)

The results can be filtered using the following parameters:

- **project:** project id

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/points?project=1
```

15.2. Create

To create points send a POST request with the following data:

- **color:** in hexadecimal
- **name** (required)
- **order:** integer
- **value** (required): integer
- **project:** (required): project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "color": "#AAAAAA",
    "name": "Huge",
    "order": 8,
    "value": 40,
    "project": 3
}' \
https://api.taiga.io/api/v1/points
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project": 3,
    "name": "Very huge"
}' \
https://api.taiga.io/api/v1/points
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [point detail object](#)

15.3. Get

To get a point send a GET request specifying the point id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/points/1
```

The HTTP response is a 200 OK and the response body is a JSON [point detail object](#)

15.4. Edit

To edit points send a PUT or a PATCH specifying the point id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Patch name"
}' \
https://api.taiga.io/api/v1/points/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [point detail object](#)

15.5. Delete

To delete points send a DELETE specifying the point id in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/points/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

15.6. Bulk update order

To update the order of multiple points at the same time send a POST request with the following data:

- **project** (required)

- **bulk_points**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_points": [[1,10], [2,5]]
}' \
https://api.taiga.io/api/v1/points/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

16. User story custom attribute

16.1. List

To list user story custom attributes send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstory-custom-attributes
```

The HTTP response is a 200 OK and the response body is a JSON list of [user story custom attribute detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstory-custom-attributes?project=1
```

16.2. Create

To create user story custom attributes send a POST request with the following data:

- **name**: (required) text

- **description:** text
- **order:** integer
- **project:** (required) integer, project id

```
curl -X POST \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "name": "Duration",
    "description": "Duration in minutes",
    "order": 8,
    "project": 3
  }' \
  https://api.taiga.io/api/v1/userstory-custom-attributes
```

```
curl -X POST \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "name": "Duration",
    "project": 3
  }' \
  https://api.taiga.io/api/v1/userstory-custom-attributes
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [user story custom attribute detail object](#)

16.3. Get

To get a user story custom attribute send a GET request specifying the user story custom attribute id in the url

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/userstory-custom-attributes/1
```

The HTTP response is a 200 OK and the response body is a JSON [user story custom attribute detail object](#)

16.4. Edit

To edit user story custom attributes send a PUT or a PATCH specifying the user story custom attribute id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "name": "Duration"
  }' \
  https://api.taiga.io/api/v1/userstory-custom-attributes/1
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON [user story custom attribute detail object](#)

16.5. Delete

To delete user story custom attributes send a DELETE specifying the user story custom attribute id in the url

```
curl -X DELETE \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/userstory-custom-attributes/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

16.6. Bulk update order

To update the order of multiple user story custom attributes at the same time send a POST request with the following data:

- **project** (required)
- **bulk_userstory_custom_attributes**: list where each element is a list, the first element is the custom attribute id and the second the new order

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_userstory_custom_attributes": [[1,10], [2,5]]
}' \
https://api.taiga.io/api/v1/userstory-custom-attributes/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

17. User story custom attributes values

17.1. Get

To get a user story custom attribute send a GET request specifying the user story custom attribute id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/userstories/custom-attributes-values/1
```

The HTTP response is a 200 OK and the response body is a JSON [user story custom attribute detail object](#)

17.2. Edit

To edit user story custom attributes values send a PUT or a PATCH specifying the user story id in the url. "attribute_values" must be a JSON object with pairs user story custom attribute id - value. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "attribute_values": {"1": "240 min"},
    "version": 2
}' \
https://api.taiga.io/api/v1/userstories/custom-attributes-values/1
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON [user story custom attribute detail object](#)

18. Tasks

18.1. List

To list tasks send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks
```

The HTTP response is a 200 OK and the response body is a JSON list of [task list objects](#)

The results can be filtered using the following parameters:

- **project**: project id
- **user_story**: user story id
- **milestone**: milestone id
- **watchers**: watching user id
- **assigned_to**: assigned to user id
- **status_is_closed**: (true | false)

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks?project=1
```

18.2. Create

To create tasks send a POST request with the following data:

- **assigned_to**: user id
- **blocked_note**: reason why the task is blocked
- **description**: string
- **is_blocked**: boolean
- **is_closed**: boolean

- **milestone**: milestone id
- **project** (required): project id
- **user_story**: user story id
- **status**: status id
- **subject** (required)
- **tags**: array of strings
- **us_order**: order in the user story,
- **taskboard_order**: order in the taskboard,
- **is_iocaine**: boolean,
- **external_reference**: tuple of ("service", serviceId),
- **watchers**: array of watcher id's

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "assigned_to": null,
    "blocked_note": "blocking reason",
    "description": "Implement API CALL",
    "is_blocked": false,
    "is_closed": true,
    "milestone": null,
    "project": 3,
    "user_story": 17,
    "status": 13,
    "subject": "Customer personal data",
    "tags": [
        "service catalog",
        "customer"
    ],
    "us_order": 1,
    "taskboard_order": 1,
    "is_iocaine": false,
    "external_reference": null,
    "watchers": []
}' \
https://api.taiga.io/api/v1/tasks
```

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project": 3,  
    "subject": "Customer personal data"  
}' \  
https://api.taiga.io/api/v1/tasks
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [task detail object](#)

18.3. Get

To get a task send a GET request specifying the task id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/tasks/1
```

The HTTP response is a 200 OK and the response body is a JSON [task detail \(GET\) object](#)

18.4. Get by ref

To get a task send a GET request specifying the task reference and the project id as parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/tasks/by_ref?ref=1&project=1
```

The HTTP response is a 200 OK and the response body is a JSON [task detail \(GET\) object](#)

18.5. Edit

To edit tasks send a PUT or a PATCH specifying the task id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "subject": "Patching subject"  
}' \  
https://api.taiga.io/api/v1/tasks/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [task detail object](#)

18.6. Delete

To delete tasks send a DELETE specifying the task id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/tasks/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

18.7. Bulk creation

To create multiple tasks at the same time send a POST request with the following data:

- **project_id** (required)
- **status_id**
- **sprint_id**: milestone id (optional)
- **us_id**: user story id (optional)
- **bulk_tasks**: task subjects, one per line

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_tasks": "Task 1 \n Task 2 \n Task 3"  
}' \  
https://api.taiga.io/api/v1/tasks/bulk_create
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON list of

18.8. Vote a task

To vote tasks send a POST request specifying the task id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/1/upvote
```

The HTTP response is a 200 OK with an empty body response

18.9. Remove vote from a task

To remove a vote from a task send a POST request specifying the task id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/1/downvote
```

When remove of the vote succeeded, the HTTP response is a 200 OK with an empty body response

18.10. Get task voters list

To get the list of voters from a task send a GET request specifying the task id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/1/voters
```

The HTTP response is a 200 OK and the response body is a JSON list of [task voter object](#)

18.11. Watch a task

To watch a task send a POST request specifying the task id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/1/watch
```

The HTTP response is a 200 OK with an empty body response

18.12. Stop watching a task

To stop watching a task send a POST request specifying the task id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/1/unwatch
```

The HTTP response is a 200 OK with an empty body response

18.13. List task watchers

To get the list of watchers from a task send a GET request specifying the task id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/1/watchers
```

The HTTP response is a 200 OK and the response body is a JSON list of [task watcher object](#)

18.14. List attachments

To list task attachments send a GET request with the following parameters:

- **project**: project id
- **object_id**: task id

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/tasks/attachments?object_id=81&project=3
```

The HTTP response is a 200 OK and the response body is a JSON list of [attachment detail objects](#)

18.15. Create attachment

To create task attachments send a POST request with the following data:

- **object_id** (required): task id
- **project** (required): project id
- **attached_file** (required): attaching file
- **description**
- **is_DEPRECATED**

```
curl -X POST \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -F "object_id=81" \
  -F "project=3" \
  -F "attached_file=@/tmp/test.png" \
  https://api.taiga.io/api/v1/tasks/attachments
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [attachment detail object](#)

18.16. Get attachment

To get a task attachment send a GET request specifying the task attachment id in the url

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/tasks/attachments/415
```

The HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

18.17. Edit attachment

To edit task attachments send a PUT or a PATCH specifying the task attachment id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -F "description=patching description" \
  https://api.taiga.io/api/v1/tasks/attachments/417
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

18.18. Delete attachment

To delete task attachments send a DELETE specifying the task attachment id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/tasks/attachments/415
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

19. Task status

19.1. List

To list task status send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/task-statuses
```

The HTTP response is a 200 OK and the response body is a JSON list of [task status detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/task-statuses?project=1
```

19.2. Create

To create task statuses send a POST request with the following data:

- **color**: in hexadecimal
- **is_closed**: (true | false)
- **name** (required)
- **order**: integer

- **project:** (required): project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "color": "#AAAAAA",
    "is_closed": true,
    "name": "New status",
    "order": 8,
    "project": 3
}' \
https://api.taiga.io/api/v1/task-statuses
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project": 3,
    "name": "New status name"
}' \
https://api.taiga.io/api/v1/task-statuses
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [task status detail object](#)

19.3. Get

To get a task status send a GET request specifying the task status id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/task-statuses/1
```

The HTTP response is a 200 OK and the response body is a JSON [task status detail object](#)

19.4. Edit

To edit task statuses send a PUT or a PATCH specifying the task status id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Patch status name"
}' \
https://api.taiga.io/api/v1/task-statuses/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [task status detail object](#)

19.5. Delete

To delete task satuses send a DELETE specifying the task status id in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/task-statuses/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

19.6. Bulk update order

To update the order of multiple task statuses at the same time send a POST request with the following data:

- **project** (required)
- **bulk_task_statuses**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_task_statuses": [[1,10], [2,5]]
}' \
https://api.taiga.io/api/v1/task-statuses/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

20. Task custom attribute

20.1. List

To list task custom attributes send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/task-custom-attributes
```

The HTTP response is a 200 OK and the response body is a JSON list of [task custom attribute detail objects](#)

The results can be filtered using the following parameters:

- **project:** project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/task-custom-attributes?project=1
```

20.2. Create

To create task custom attributes send a POST request with the following data:

- **name:** (required) text
- **description:** text
- **order:** integer
- **project:** (required) integer, project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "name": "Duration",
  "description": "Duration in minutes",
  "order": 8,
  "project": 3
}' \
https://api.taiga.io/api/v1/task-custom-attributes
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "name": "Duration",
  "project": 3
}' \
https://api.taiga.io/api/v1/task-custom-attributes
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [task custom attribute detail object](#)

20.3. Get

To get a task custom attribute send a GET request specifying the task custom attribute id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/task-custom-attributes/1
```

The HTTP response is a 200 OK and the response body is a JSON [task custom attribute detail object](#)

20.4. Edit

To edit task custom attributes send a PUT or a PATCH specifying the task custom attribute id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Duration"  
}' \  
https://api.taiga.io/api/v1/task-custom-attributes/1
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON [task custom attribute detail object](#)

20.5. Delete

To delete task custom attributes send a DELETE specifying the task custom attribute id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/task-custom-attributes/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

20.6. Bulk update order

To update the order of multiple task custom attributes at the same time send a POST request with the following data:

- **project** (required)
- **bulk_task_custom_attributes**: list where each element is a list, the first element is the custom attribute id and the second the new order

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_task_custom_attributes": [[1,10], [2,5]]  
}' \  
https://api.taiga.io/api/v1/task-custom-attributes/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

21. Task custom attributes values

21.1. Get

To get a task custom attribute send a GET request specifying the task custom attribute id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/tasks/custom-attributes-values/1
```

The HTTP response is a 200 OK and the response body is a JSON [task custom attribute detail object](#)

21.2. Edit

To edit task custom attributes values send a PUT or a PATCH specifying the task id in the url. "attribute_values" must be a JSON object with pairs task custom attribute id - value. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "attribute_values": {"1": "240 min"},  
    "version": 2  
}' \  
https://api.taiga.io/api/v1/tasks/custom-attributes-values/1
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON [task custom attribute detail object](#)

22. Issues

22.1. List

To list issues send a GET request with the following parameters:

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/issues
```

The HTTP response is a 200 OK and the response body is a JSON list of [issue detail list objects](#)

The results can be filtered using the following parameters:

- **project**: project id
- **status**: status id
- **severity**: severity id
- **priority**: priority id
- **owner**: owner user id
- **assigned_to**: assigned to user id
- **tags**: separated by ","
- **type**: issue type id
- **watchers**: watching user id
- **status_is_closed**: (true | false)

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/issues?project=1
```

The results can be ordered using the **order_by** parameter with the values:

- **type**
- **severity**
- **status**
- **priority**
- **created_date**
- **modified_date**
- **owner**
- **assigned_to**
- **subject**

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues?project=1&order_by=priority
```

22.2. Create

To create issues send a POST request with the following data:

- **assigned_to**: user id
- **blocked_note**: reason why the issue is blocked
- **description**: string
- **is_blocked**: boolean
- **is_closed**: boolean
- **milestone**: milestone id
- **project** (required): project id
- **status**: status id
- **severity**: severity id
- **priority**: priority id
- **type**: type id
- **subject** (required)
- **tags**: array of strings
- **watchers**: array of watcher id's

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "assigned_to": null,
    "blocked_note": "blocking reason",
    "description": "Implement API CALL",
    "is_blocked": false,
    "is_closed": true,
    "milestone": null,
    "project": 3,
    "status": 13,
    "severity": 2,
    "priority": 3,
    "type": 1,
    "subject": "Customer personal data",
    "tags": [
        "service catalog",
        "customer"
    ],
    "watchers": []
}' \
https://api.taiga.io/api/v1/issues
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project": 3,
    "subject": "Customer personal data"
}' \
https://api.taiga.io/api/v1/issues
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [issue detail object](#)

22.3. Get

To get an issue send a GET request specifying the issue id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1
```

The HTTP response is a 200 OK and the response body is a JSON [issue detail \(GET\) object](#)

22.4. Get by ref

To get an issue send a GET request specifying the issue reference end project id as parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/by_ref?ref=1&project=1
```

The HTTP response is a 200 OK and the response body is a JSON [issue detail \(GET\) object](#)

22.5. Edit

To edit issues send a PUT or a PATCH specifying the issue id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "subject": "Patching subject"  
}' \  
https://api.taiga.io/api/v1/issues/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [issue detail object](#)

22.6. Delete

To delete issues send a DELETE specifying the issue id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

22.7. Vote an issue

To vote issues send a POST specifying the issue id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1/upvote
```

When vote succeeded, the HTTP response is a 200 OK with an empty body response

22.8. Remove vote from an issue

To remove a vote from an issue send a POST specifying the issue id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1/downvote
```

When remove of the vote succeeded, the HTTP response is a 200 OK with an empty body response

22.9. Get issue voters list

To get the list of voters from an issue send a GET request specifying the issue id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1/voters
```

The HTTP response is a 200 OK and the response body is a JSON [issue voters detail object](#)

22.10. Watch an issue

To watch an issue send a POST request specifying the issue id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1/watch
```

The HTTP response is a 200 OK with an empty body response

22.11. Stop watching an issue

To stop watching an issue send a POST request specifying the issue id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1/unwatch
```

The HTTP response is a 200 OK with an empty body response

22.12. List issue watchers

To get the list of watchers from an issue send a GET request specifying the issue id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/1/watchers
```

The HTTP response is a 200 OK and the response body is a JSON list of [issue watcher object](#)

22.13. List attachments

To list issue attachments send a GET request with the following parameters:

- **project**: project id
- **object_id**: issue id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/attachments?object_id=81&project=3
```

The HTTP response is a 200 OK and the response body is a JSON list of [attachment detail objects](#)

22.14. Create attachment

To create issue attachments send a POST request with the following data:

- **object_id** (required): issue id
- **project** (required): project id
- **attached_file** (required): attaching file
- **description**
- **is_DEPRECATED**

```
curl -X POST \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -F "object_id=81" \
  -F "project=3" \
  -F "attached_file=@/tmp/test.png" \
  https://api.taiga.io/api/v1/issues/attachments
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [attachment detail object](#)

22.15. Get attachment

To get an issue attachment send a GET request specifying the issue attachment id in the url

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/issues/attachments/415
```

The HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

22.16. Edit attachment

To edit issue attachments send a PUT or a PATCH specifying the issue attachment id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -F "description=patching description" \
  https://api.taiga.io/api/v1/issues/attachments/417
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

22.17. Delete attachment

To delete issue attachments send a DELETE specifying the issue attachment id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/attachments/415
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

23. Issue status

23.1. List

To list issue status send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-statuses
```

The HTTP response is a 200 OK and the response body is a JSON list of [issue status detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-statuses?project=1
```

23.2. Create

To create issue statuses send a POST request with the following data:

- **color**: in hexadecimal
- **is_closed**: (true | false)

- **name** (required)
- **order**: integer
- **project**: (required): project id

```
curl -X POST \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "color": "#AAAAAA",
    "is_closed": true,
    "name": "New status",
    "order": 8,
    "project": 3
  }' \
  https://api.taiga.io/api/v1/issue-statuses
```

```
curl -X POST \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "project": 3,
    "name": "New status name"
  }' \
  https://api.taiga.io/api/v1/issue-statuses
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [issue status detail object](#)

23.3. Get

To get a issue status send a GET request specifying the issue status id in the url

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/issue-statuses/1
```

The HTTP response is a 200 OK and the response body is a JSON [issue status detail object](#)

23.4. Edit

To edit issue statuses send a PUT or a PATCH specifying the issue status id in the url. In a PATCH

request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Patch status name"  
}' \  
https://api.taiga.io/api/v1/issue-statuses/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [issue status detail object](#)

23.5. Delete

To delete issue satuses send a DELETE specifying the issue status id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-statuses/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

23.6. Bulk update order

To update the order of multiple issue statuses at the same time send a POST request with the following data:

- **project** (required)
- **bulk_issue_statuses**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_issue_statuses": [[1,10], [2,5]]  
}' \  
https://api.taiga.io/api/v1/issue-statuses/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

24. Issue types

24.1. List

To list issue types send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-types
```

The HTTP response is a 200 OK and the response body is a JSON list of [issue type detail objects](#)

The results can be filtered using the following parameters:

- **project:** project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-types?project=1
```

24.2. Create

To create issue types send a POST request with the following data:

- **color:** in hexadecimal
- **name** (required)
- **order:** integer
- **project:** (required): project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "color": "#AAAAAA",
    "name": "New type",
    "order": 8,
    "project": 3
}' \
https://api.taiga.io/api/v1/issue-types
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project": 3,
    "name": "New type name"
}' \
https://api.taiga.io/api/v1/issue-types
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [issue type detail object](#)

24.3. Get

To get an issue type send a GET request specifying the issue type id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/issue-types/1
```

The HTTP response is a 200 OK and the response body is a JSON [issue type detail object](#)

24.4. Edit

To edit issue types send a PUT or a PATCH specifying the issue type id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Patch type name"  
}' \  
https://api.taiga.io/api/v1/issue-types/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [issue type detail object](#)

24.5. Delete

To delete issue statuses send a DELETE specifying the issue type id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-types/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

24.6. Bulk update order

To update the order of multiple issue types at the same time send a POST request with the following data:

- **project** (required)
- **bulk_issue_types**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_issue_types": [[1,10], [2,5]]  
}' \  
https://api.taiga.io/api/v1/issue-types/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

25. Priorities

25.1. List

To list priorities send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/priorities
```

The HTTP response is a 200 OK and the response body is a JSON list of [priority detail objects](#)

The results can be filtered using the following parameters:

- **project:** project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/priorities?project=1
```

25.2. Create

To create priorities send a POST request with the following data:

- **color:** in hexadecimal
- **name** (required)
- **order:** integer
- **project:** (required): project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "color": "#AAAAAA",
  "name": "New priority",
  "order": 8,
  "project": 3
}' \
https://api.taiga.io/api/v1/priorities
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 3,
  "name": "New priority name"
}' \
https://api.taiga.io/api/v1/priorities
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [priority detail object](#)

25.3. Get

To get a priority send a GET request specifying the priority id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/priorities/1
```

The HTTP response is a 200 OK and the response body is a JSON [priority detail object](#)

25.4. Edit

To edit priorities send a PUT or a PATCH specifying the priority id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Patch name"  
}' \  
https://api.taiga.io/api/v1/priorities/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [priority detail object](#)

25.5. Delete

To delete priorities send a DELETE specifying the priority id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/priorities/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

25.6. Bulk update order

To update the order of multiple priorities at the same time send a POST request with the following data:

- **project** (required)
- **bulk_priorities**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_priorities": [[1,10], [2,5]]  
}' \  
https://api.taiga.io/api/v1/priorities/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

26. Severities

26.1. List

To list severities send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/severities
```

The HTTP response is a 200 OK and the response body is a JSON list of [severity detail objects](#)

The results can be filtered using the following parameters:

- **project:** project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/severities?project=1
```

26.2. Create

To create severities send a POST request with the following data:

- **color:** in hexadecimal
- **name** (required)
- **order:** integer
- **project:** (required): project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "color": "#AAAAAA",
  "name": "New severity",
  "order": 8,
  "project": 3
}' \
https://api.taiga.io/api/v1/severities
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 3,
  "name": "New severity name"
}' \
https://api.taiga.io/api/v1/severities
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [severity detail object](#)

26.3. Get

To get a severity send a GET request specifying the severity id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/severities/1
```

The HTTP response is a 200 OK and the response body is a JSON [severity detail object](#)

26.4. Edit

To edit severities send a PUT or a PATCH specifying the severity id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Patch name"
}' \
https://api.taiga.io/api/v1/severities/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [severity detail object](#)

26.5. Delete

To delete severities send a DELETE specifying the severity id in the url

```
curl -X DELETE \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/severities/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

26.6. Bulk update order

To update the order of multiple severities at the same time send a POST request with the following data:

- **project** (required)
- **bulk_severities**: list where each element is a list, the first element is the status id and the second the new order

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "project_id": 3,
    "bulk_severities": [[1,10], [2,5]]
}' \
https://api.taiga.io/api/v1/severities/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

27. Issue custom attribute

27.1. List

To list issue custom attributes send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-custom-attributes
```

The HTTP response is a 200 OK and the response body is a JSON list of [issue custom attribute detail objects](#)

The results can be filtered using the following parameters:

- **project:** project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-custom-attributes?project=1
```

27.2. Create

To create issue custom attributes send a POST request with the following data:

- **name:** (required) text
- **description:** text
- **order:** integer
- **project:** (required) integer, project id

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Duration",
    "description": "Duration in minutes",
    "order": 8,
    "project": 3
}' \
https://api.taiga.io/api/v1/issue-custom-attributes
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "name": "Duration",
    "project": 3
}' \
https://api.taiga.io/api/v1/issue-custom-attributes
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [issue custom attribute detail object](#)

27.3. Get

To get a issue custom attribute send a GET request specifying the issue custom attribute id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/issue-custom-attributes/1
```

The HTTP response is a 200 OK and the response body is a JSON [issue custom attribute detail object](#)

27.4. Edit

To edit issue custom attributes send a PUT or a PATCH specifying the issue custom attribute id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "name": "Duration"  
}' \  
https://api.taiga.io/api/v1/issue-custom-attributes/1
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON [issue custom attribute detail object](#)

27.5. Delete

To delete issue custom attributes send a DELETE specifying the issue custom attribute id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issue-custom-attributes/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

27.6. Bulk update order

To update the order of multiple issue custom attributes at the same time send a POST request with the following data:

- **project** (required)
- **bulk_issue_custom_attributes**: list where each element is a list, the first element is the custom attribute id and the second the new order

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project_id": 3,  
    "bulk_issue_custom_attributes": [[1,10], [2,5]]  
}' \  
https://api.taiga.io/api/v1/issue-custom-attributes/bulk_update_order
```

When the update is successful, the HTTP response is a 204 NO CONTENT with an empty body response

28. Issue custom attributes values

28.1. Get

To get a issue custom attribute send a GET request specifying the issue custom attribute id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/issues/custom-attributes-values/1
```

The HTTP response is a 200 OK and the response body is a JSON [issue custom attribute detail object](#)

28.2. Edit

To edit issue custom attributes values send a PUT or a PATCH specifying the issue id in the url. "attribute_values" must be a JSON object with pairs issue custom attribute id - value. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "attribute_values": {"1": "240 min"},  
    "version": 2  
}' \  
https://api.taiga.io/api/v1/issues/custom-attributes-values/1
```

When the update is successful, the HTTP response is a 200 OK and the response body is a JSON [issue custom attribute detail object](#)

29. Wiki pages

29.1. List

To list wiki pages send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki
```

The HTTP response is a 200 OK and the response body is a JSON list of [wiki page detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki?project=1
```

29.2. Create

To create wiki pages send a POST request with the following data:

- **project** (required): project id
- **slug** (required): slug
- **content** (required): string
- **watchers**: array of watcher id's

```
curl -X POST \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "project": 1,  
    "slug": "home",  
    "content": "Lorem ipsum dolor.",  
    "watchers": []  
}' \  
https://api.taiga.io/api/v1/wiki
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 1,
  "slug": "home",
  "content": "Lorem ipsum dolor."
}' \
https://api.taiga.io/api/v1/wiki
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [wiki page detail object](#)

29.3. Get

To get a wiki page send a GET request specifying the wiki page id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/wiki/1
```

The HTTP response is a 200 OK and the response body is a JSON [wiki page detail object](#)

29.4. Get by slug

To get a wiki page send a GET request specifying the wiki page slug and the project id as parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/wiki/by_slug?slug=home\&project=1
```

The HTTP response is a 200 OK and the response body is a JSON [wiki page detail object](#)

29.5. Edit

To edit wiki pages send a PUT or a PATCH specifying the wiki page id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "subject": "Patching subject"  
}' \  
https://api.taiga.io/api/v1/wiki/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [wiki page detail object](#)

29.6. Delete

To delete wiki page send a DELETE specifying the wiki page id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

29.7. Watch a wiki page

To watch a wiki page send a POST request specifying the wiki page id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki/1/watch
```

The HTTP response is a 200 OK with an empty body response

29.8. Stop watching a wiki page

To stop watching a wiki page send a POST request specifying the wiki page id in the url

```
curl -X POST \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki/1/unwatch
```

The HTTP response is a 200 OK with an empty body response

29.9. List wiki page watchers

To get the list of watchers from a wiki page send a GET request specifying the wiki page id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/wiki/1/watchers
```

The HTTP response is a 200 OK and the response body is a JSON list of [wiki page watcher object](#)

29.10. List attachments

To list wiki page attachments send a GET request with the following parameters:

- **project**: project id
- **object_id**: wiki page id

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/wiki/attachments?object_id=81\&project=3
```

The HTTP response is a 200 OK and the response body is a JSON list of [attachment detail objects](#)

29.11. Create attachment

To create wiki page attachments send a POST request with the following data:

- **object_id** (required): wiki page id
- **project** (required): project id
- **attached_file** (required): attaching file
- **description**
- **is_DEPRECATED**

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-F "object_id=81" \
-F "project=3" \
-F "attached_file=@/tmp/test.png" \
https://api.taiga.io/api/v1/wiki/attachments
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [attachment detail object](#)

29.12. Get attachment

To get an wiki page attachment send a GET request specifying the wiki page attachment id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/wiki/attachments/415
```

The HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

29.13. Edit attachment

To edit wiki page attachments send a PUT or a PATCH specifying the wiki page attachment id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-F "description=patching description" \
https://api.taiga.io/api/v1/wiki/attachments/417
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [attachment detail object](#)

29.14. Delete attachment

To delete wiki page attachments send a DELETE specifying the wiki page attachment id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki/attachments/415
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

30. Wiki links

30.1. List

To list wiki links send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki-links
```

The HTTP response is a 200 OK and the response body is a JSON list of [wiki link detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki-links?project=1
```

30.2. Create

To create wiki links send a POST request with the following data:

- **project** (required): project id
- **title** (required): string
- **href** (required): wiki page slug
- **order**: integer

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 1,
  "title": "Home page",
  "href": "home",
  "order": 1
}' \
https://api.taiga.io/api/v1/wiki-links
```

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 1,
  "title": "Home page",
  "href": "home"
}' \
https://api.taiga.io/api/v1/wiki-links
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [wiki link detail object](#)

30.3. Get

To get a wiki link send a GET request specifying the wiki link id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/wiki-links/1
```

The HTTP response is a 200 OK and the response body is a JSON [wiki link detail object](#)

30.4. Edit

To edit wiki links send a PUT or a PATCH specifying the wiki link id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "subject": "Patching subject"  
}' \  
https://api.taiga.io/api/v1/wiki-links/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [wiki link detail object](#)

30.5. Delete

To delete wiki link send a DELETE specifying the wiki link id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/wiki-links/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

31. History

31.1. Get user story, task, issue or wiki page history

To get the history of a user story, task, issue or wiki page send a GET request specifying the id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/history/userstory/1
```

The HTTP response is a 200 OK and the response body is a JSON of a list of [history entry detail objects](#)

31.2. Delete comment

To delete history comment send a POST specifying the history entry id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/history/userstory/1/delete_comment?id=10
```

When deleted successfully, the HTTP response is a 204 NO CONTENT with an empty body response

31.3. Undelete comment

To undelete history comment send a POST specifying the history entry id in the url

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/history/userstory/1/undelete_comment?id=10
```

When deleted successfully, the HTTP response is a 204 NO CONTENT with an empty body response

32. Users

32.1. List

To list users send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/users
```

The HTTP response is a 200 OK and the response body is a JSON list of [user detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/users?project=1
```

32.2. Get

To get a user send a GET request specifying the user id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/users/1
```

The HTTP response is a 200 OK and the response body is a JSON [user detail object](#)

32.3. Me

To get your own user send a GET request to the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/users/me
```

The HTTP response is a 200 OK and the response body is a JSON [user detail object](#)

32.4. Get user stats

To get the stats from a user send a GET request specifying the user id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/users/1/stats
```

The HTTP response is a 200 OK and the response body is a JSON [user stats object](#)

32.5. Get watched content

To get the user watched content send a GET request specifying the user id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1/watched
```

The HTTP response is a 200 OK and the response body is a list of JSON [watched detail object](#)

The results can be filtered using the following parameters:

- **type**: of the content. Possible values: project, userstory, task and issue
- **q**: text to search in the subject of the element

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1/watched?type=project&q=test
```

32.6. Get liked content

To get the user liked content send a GET request specifying the user id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1/liked
```

The HTTP response is a 200 OK and the response body is a list of JSON [liked detail object](#)

The results can be filtered using the following parameters:

- **q**: text to search in the subject of the element

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1/liked?q=test
```

32.7. Get voted content

To get the user voted content send a GET request specifying the user id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1/voted
```

The HTTP response is a 200 OK and the response body is a list of JSON [voted detail object](#)

The results can be filtered using the following parameters:

- **type**: of the content. Possible values: userstory, task and issue
- **q**: text to search in the subject of the element

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1/liked?type=userstory&q=test
```

32.8. Edit

To edit users send a PUT or a PATCH specifying the user id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
-d '{  
    "username": "patchedusername"  
}' \  
https://api.taiga.io/api/v1/users/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [user detail object](#)

32.9. Delete

To delete users send a DELETE specifying the user id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/users/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

32.10. Get contacts

To get a user contacts send a GET request specifying the user id in the url

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/users/1/contacts
```

The HTTP response is a 200 OK and the response body is a list of JSON [contact detail object](#)

32.11. Cancel

To cancel a user account send a POST with the following data

```
curl -X POST \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "cancel_token": "${CANCEL_TOKEN}"
  }' \
  https://api.taiga.io/api/v1/users/cancel
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

32.12. Change avatar

To change your user avatar send a POST with the following data

```
curl -X POST \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -F "avatar=@/tmp/test.png" \
  https://api.taiga.io/api/v1/users/change_avatar
```

When the change is successful, the HTTP response is a 200 OK and the response body is a JSON [user detail object](#)

32.13. Remove avatar

To remove your user avatar send a POST with the following data

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/users/remove_avatar
```

When the change is successful, the HTTP response is a 200 OK and the response body is a JSON [user detail object](#)

32.14. Change email

To change your user email send a POST with the following data

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "email_token": "'${EMAIL_TOKEN}'"
}' \
https://api.taiga.io/api/v1/users/change_email
```

When the change is successful, the HTTP response is a 200 OK and the response body is a JSON [user detail object](#)

32.15. Change password

To change your user password send a POST with the following data

```
curl -X POST \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
    "current_password": "'${CURRENT_PASSWORD}'",
    "password": "'${NEW_PASSWORD}'"
}' \
https://api.taiga.io/api/v1/users/change_password
```

When the change succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

32.16. Password recovery

To request a user password recovery send a POST with the following data:

- **username** (required): this field also supports the user email

```
curl -X POST \
-d '{
    "username": "${USERNAME_OR_EMAIL}"
}' \
https://api.taiga.io/api/v1/users/password_recovery
```

When the password recovery request succeeded, the HTTP response is a 200 OK and the response body is a JSON object:

```
{
  "detail": "Mail sended successfully!",
  "email": "${USER_EMAIL}"
}
```

32.17. Change password from recovery

To change a user password from a request recovery send a POST with the following data

```
curl -X POST \
-d '{
    "token": "${CHANGE_PASSWORD_TOKEN}",
    "password": "${NEW_TOKEN}"
}' \
https://api.taiga.io/api/v1/users/change_password_from_recovery
```

When the password change succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

33. Notify policies

33.1. List

To list the notify policies of the current user send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/notify-policies
```

The HTTP response is a 200 OK and the response body is a JSON list of [notify policy detail objects](#)

33.2. Get

To get a notify policy send a GET request specifying the notify policy id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/notify-policies/1
```

The HTTP response is a 200 OK and the response body is a JSON [notify policy detail object](#)

33.3. Edit

To edit notify policies send a PUT or a PATCH specifying the notify policy id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "notify_level": 2
}' \
https://api.taiga.io/api/v1/notify-policies/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [notify policy detail object](#)

34. Feedback

34.1. Create

To create feedback send a POST request with the following data:

- **comment** (required)

```
curl -X POST \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  -d '{
    "comment": "Testing feedback"
}' \
https://api.taiga.io/api/v1/feedback
```

When created successfully, the HTTP response is a 201 Created and the response body is a JSON [feedback object](#)

35. Export/Import

35.1. Export

To get a project dump send a GET request with the project id:

```
curl -X GET \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ${AUTH_TOKEN}" \
  https://api.taiga.io/api/v1/exporter/1
```

Depending on server configuration it can return two results:

- If taiga is working in synchronous mode the json file is directly generated, the result is a 200 OK and as response body a JSON of [export detail for synch mode](#).
- If taiga is working in asynchronous mode the result is a 202 Accepted and as response body a JSON of [export request accepted](#). The export_id can be used to build the URL to download the exported file when the file generation is complete, those urls look like: MEDIA_URL/exports/PROJECT_ID/PROJECT_SLUG-export_id.json.

35.2. Import

To load a project dump send a POST request with the following file:

- **dump** (required)

```
curl -X POST \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  -F 'dump=@my-dump-file.json' \  
  https://api.taiga.io/api/v1/importer/load_dump
```

Depending on server configuration it can return two results:

- A 202 Accepted and as response body a JSON of [import request accepted](#).
- A 201 Created and the response body is a JSON of [project detail object](#)

36. Webhooks

36.1. List

To list webhooks send a GET request with the following parameters:

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/webhooks
```

The HTTP response is a 200 OK and the response body is a JSON list of [webhook detail objects](#)

The results can be filtered using the following parameters:

- **project**: project id

```
curl -X GET \  
  -H "Content-Type: application/json" \  
  -H "Authorization: Bearer ${AUTH_TOKEN}" \  
  https://api.taiga.io/api/v1/webhooks?project=1
```

36.2. Create

To create webhook send a POST request with the following data:

- **project** (required): project id
- **name** (required): string
- **url** (required): payload url

- **key** (required): secret key

```
curl -X POST \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "project": 1,
  "name": "My service webhook",
  "url": "http://myservice.com/webhooks",
  "key": "my-very-secret-key"
}' \
https://api.taiga.io/api/v1/webhooks
```

When the creation is successful, the HTTP response is a 201 Created and the response body is a JSON [webhook detail object](#)

36.3. Get

To get a webhook send a GET request specifying the webhook id in the url

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/webhooks/1
```

The HTTP response is a 200 OK and the response body is a JSON [webhook detail object](#)

36.4. Edit

To edit a webhook send a PUT or a PATCH specifying the webhook id in the url. In a PATCH request you just need to send the modified data, in a PUT one the whole object must be sent.

```
curl -X PATCH \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
-d '{
  "name": "My service name"
}' \
https://api.taiga.io/api/v1/webhooks/1
```

When the creation is successful, the HTTP response is a 200 OK and the response body is a JSON [webhook detail object](#)

36.5. Delete

To delete a webhook send a DELETE specifying the webhook id in the url

```
curl -X DELETE \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/webhooks/1
```

When delete succeeded, the HTTP response is a 204 NO CONTENT with an empty body response

36.6. Test

To test a webhook send a POST request specifying the webhook id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/webhooks/1/test
```

The HTTP response is a 200 OK and the response body is a JSON [webhook log detail object](#) with the result of the test.

36.7. Logs list

To list webhook logs send a GET request to the url:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/webhooklogs
```

The HTTP response is a 200 OK and the response body is a JSON list of [webhook log detail objects](#)

The results can be filtered using the following parameters:

- **webhook**: webhook id

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/webhooklogs?webhook=1
```

36.8. Log get

To get a webhook log send a GET request specifying the webhook log id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/webhooklogs/1
```

The HTTP response is a 200 OK and the response body is a JSON [webhook log detail object](#)

36.9. Resend request

To resend a request from a webhook log send a POST request specifying the webhook log id in the url

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/webhooklogs/1/resend
```

The HTTP response is a 200 OK and the response body is a JSON [webhook log detail object](#) with the result of the resend.

37. Timelines

37.1. List user timeline

To list a user timeline send a GET request with the following parameters:

```
curl -X GET \  
-H "Content-Type: application/json" \  
-H "Authorization: Bearer ${AUTH_TOKEN}" \  
https://api.taiga.io/api/v1/timeline/user/1
```

This API call returns only actions directly executed by the specified user.

The HTTP response is a 200 OK and the response body is a JSON list of [timeline entry detail](#)

37.2. List profile timeline

To list a profile timeline send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/timeline/profile/1
```

This API call returns actions executed by the specified user and related to them, watching objects, actions by related team members, belonging to projects...

The HTTP response is a 200 OK and the response body is a JSON list of [timeline entry detail](#)

37.3. List project timeline

To list a project timeline send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/timeline/project/1
```

This API call returns actions executed by different users related to the specified project.

The HTTP response is a 200 OK and the response body is a JSON list of [timeline entry detail](#)

38. Locales

38.1. List

To list the available locales send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/locales
```

The HTTP response is a 200 OK and the response body is a JSON list of [locale objects](#)

39. Stats

39.1. Get discover stats

To get the discover stats send a GET request with the following parameters:

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/stats/discover
```

The HTTP response is a 200 OK and the response body is a JSON [discover stats object](#)

39.2. Get system stats

To get the discover stats send a GET request with the following parameters:

NOTE This API will only work if your instance has system stats enabled

```
curl -X GET \
-H "Content-Type: application/json" \
-H "Authorization: Bearer ${AUTH_TOKEN}" \
https://api.taiga.io/api/v1/stats/system
```

The HTTP response is a 200 OK and the response body is a JSON [system stats object](#)

40. Objects Summary

40.1. Attachment

```
{
  "id": 415,
  "project": 3,
  "owner": 2,
  "name": "img_20141102_214512.jpg",
  "attached_file":
  "attachments/8/1/6/e/68a8e4edb4ba422d201d65406b161be03e052d9b63e265aaa826179497c8/img_201
  41102_214512.jpg",
  "size": 173780,
  "url":
  "https://media.taiga.io/attachments/8/1/6/e/68a8e4edb4ba422d201d65406b161be03e052d9b63e26
  5aaa826179497c8/img_20141102_214512.jpg",
  "description": "asdasd",
  "is_DEPRECATED": false,
  "created_date": "2014-11-11T14:22:29+0000",
  "modified_date": "2014-11-11T14:22:43+0000",
  "object_id": 81,
  "order": 0,
  "sha1": "da2631d805f12a1b533738a0912e9b9c2261dbef",
  "thumbnail_card_url":
  "https://media.taiga.io/8/1/6/e/68a8e4edb4ba422d201d65406b161be03e052d9b63e265aaa82617949
  7c8/img_20141102_214512.300x200_q85_crop.jpg"
}
```

40.2. Application object

```
{
  "id": "a60c3208-5234-11e5-96df-68f72800aadd",
  "name": "test",
  "web": "qweqweqwe",
  "description": "asdasdasdasd",
  "icon_url": "http://www.iconarchive.com/icons/yellowicon/game-stars/256/Mario-
  icon.png"
}
```

40.3. Application token object

```
{
  "user": 4,
  "id": 5,
  "application": {
    "id": "a60c3208-5234-11e5-96df-68f72800aadd",
    "name": "Testing application",
    "web": "http://taiga.io",
    "description": "Testing external app",
    "icon_url": "https://tree.taiga.io/images/beta.png"
  },
  "auth_code": "5a6e869a-52e6-11e5-ad57-68f72800aadd",
  "next_url": "http://tree.taiga.io/redirect?auth_code=5a6e869a-52e6-11e5-ad57-68f72800aadd"
}
```

If id and auth_code are null it means there is no application token generated and you need to authorize one.

40.4. Authorization code object

```
{
  "auth_code": "5a6e869a-52e6-11e5-ad57-68f72800aadd",
  "state": "random-state",
  "next_url": "http://tree.taiga.io/redirect?auth_code=5a6e869a-52e6-11e5-ad57-68f72800aadd"
}
```

40.5. Cyphered token object

```
{
  "cyphered_token": "eyJlbmMiOiJBmjU2R0NNIiwiYWxnIjoiQTEyOEtXIn0.E-Ee1cRgG0JEd90yJu-Dgl_vwKTHdPy2YHRbCsMvfiJx00vR12E8g.kGwJPnWQJecFPEae.ebQtpRNPbKh6FBS-LSUhwxNARl0Q5loC04fAk00LHFqcDpAwba7LHeR3MPx9T9LfA.KM-Id_041g80dWaseGyV8g"
}
```

40.6. User detail

```
{  
  "id": 7,  
  "username": "beta.tester",  
  "full_name": "Beta testing",  
  "full_name_display": "Beta testing",  
  "email": "beta.testing@taiga.io",  
  "color": "#FC8EAC",  
  "bio": "",  
  "lang": "en",  
  "theme": "taiga",  
  "timezone": "",  
  "is_active": true,  
  "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",  
  "big_photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=300",  
  "max_private_projects": null,  
  "max_public_projects": null,  
  "max_memberships_private_projects": 3,  
  "max_memberships_public_projects": 10,  
  "total_private_projects": 11,  
  "total_public_projects": 2  
}
```

NOTE The attributes: email, max_private_projects, max_public_projects, max_memberships_private_projects, max_memberships_public_projects, total_private_projects, total_public_projects will only be included in the json only if the user requested and the requesting one are the same or if the requesting user is a super user.

40.7. User contact detail

```
{
  "id": 32090,
  "username": "beta.tester",
  "full_name": "Beta testing",
  "full_name_display": "Beta testing",
  "color": "#2c3e58",
  "bio": "",
  "lang": "",
  "timezone": "",
  "is_active": true,
  "photo": "http://www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80",
  "big_photo": "http://www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80",
  "roles": [
    "Product Owner"
  ],
  "projects_with_me": []
}
```

40.8. User authentication-detail

```
{
  "auth_token": "eyJ1c2VyX2F1dGh1bnRpY2F0aW9uX2lkIjo3fq:1XmPud:LKXVD9Z0rmHJjiyy0m4YaaHlQS1",
  "bio": "",
  "is_active": true,
  "email": "beta.testing@taiga.io",
  "github_id": null,
  "color": "#FC8EAC",
  "lang": "",
  "full_name_display": "Beta testing",
  "timezone": "",
  "id": 7,
  "full_name": "Beta testing",
  "photo": "//www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80",
  "username": "beta.tester",
  "big_photo": "//www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80"
}
```

40.9. User stats detail

```
{  
  "roles": [  
    "Back"  
  ],  
  "total_num_closed_userstories": 0,  
  "total_num_contacts": 8,  
  "total_num_projects": 1  
}
```

40.10. Search results detail

```
{  
  "wikipages": [  
    {  
      "id": 1,  
      "slug": "wiki-page",  
      "content": "wiki content"  
    },  
    ...  
  ],  
  "userstories": [  
    {  
      "id": 1,  
      "ref": 10,  
      "subject": "User story subject",  
      "status": 23,  
      "total_points": 12.5,  
      "milestone_name": "Sprint name",  
      "milestone_slug": "sprint-name"  
    },  
    ...  
  ],  
  "issues": [  
    {  
      "id": 1,  
      "ref": 20,  
      "subject": "Issue subject",  
      "status": 10,  
      "assigned_to": 12  
    },  
    ...  
  ],  
  "tasks": [  
    {  
      "id": 1,  
      "ref": 30,  
      "subject": "Task subject",  
      "status": 15,  
      "assigned_to": 54  
    },  
    ...  
  ],  
  "count": 8  
}
```

40.11. User storage data

```
{  
  "key": "favorite-forest",  
  "value": "Taiga",  
  "created_date": "2014-11-13T16:58:35+0000",  
  "modified_date": "2014-11-13T16:58:35+0000"  
}
```

41. Project templates detail

```
{  
  "default_options": {  
    "us_status": "New",  
    "points": "?",  
    "priority": "Normal",  
    "severity": "Normal",  
    "task_status": "New",  
    "issue_type": "Bug",  
    "issue_status": "New"  
  },  
  "us_statuses": [  
    {  
      "wip_limit": null,  
      "color": "#999999",  
      "name": "New",  
      "slug": "new",  
      "order": 1,  
      "is_closed": false  
    },  
    {  
      "wip_limit": null,  
      "color": "#f57900",  
      "name": "Ready",  
      "slug": "ready",  
      "order": 2,  
      "is_closed": false  
    },  
    {  
      "wip_limit": null,  
      "color": "#729fcf",  
      "name": "In progress",  
      "slug": "in-progress",  
      "order": 3,  
    }  
  ]  
}
```

```
        "is_closed": false
    },
    {
        "wip_limit": null,
        "color": "#4e9a06",
        "name": "Ready for test",
        "slug": "ready-for-test",
        "order": 4,
        "is_closed": false
    },
    {
        "wip_limit": null,
        "color": "#cc0000",
        "name": "Done",
        "slug": "done",
        "order": 5,
        "is_closed": true
    }
],
"points": [
    {
        "value": null,
        "name": "?",
        "order": 1
    },
    {
        "value": 0.0,
        "name": "0",
        "order": 2
    },
    {
        "value": 0.5,
        "name": "1/2",
        "order": 3
    },
    {
        "value": 1.0,
        "name": "1",
        "order": 4
    },
    {
        "value": 2.0,
        "name": "2",
        "order": 5
    },
    {
        "value": 3.0,
        "name": "3",
        "order": 6
    }
]
```

```
        "order": 6
    },
    {
        "value": 5.0,
        "name": "5",
        "order": 7
    },
    {
        "value": 8.0,
        "name": "8",
        "order": 8
    },
    {
        "value": 10.0,
        "name": "10",
        "order": 9
    },
    {
        "value": 15.0,
        "name": "15",
        "order": 10
    },
    {
        "value": 20.0,
        "name": "20",
        "order": 11
    },
    {
        "value": 40.0,
        "name": "40",
        "order": 12
    }
],
"task_statuses": [
    {
        "color": "#999999",
        "name": "New",
        "slug": "new",
        "order": 1,
        "is_closed": false
    },
    {
        "color": "#729fcf",
        "name": "In progress",
        "slug": "in-progress",
        "order": 2,
        "is_closed": false
    },
    {
        "color": "#2e6b2e",
        "name": "Completed",
        "slug": "completed",
        "order": 3,
        "is_closed": true
    }
]
```

```
{  
  "color": "#f57900",  
  "name": "Ready for test",  
  "slug": "ready-for-test",  
  "order": 3,  
  "is_closed": true  
},  
{  
  "color": "#4e9a06",  
  "name": "Closed",  
  "slug": "closed",  
  "order": 4,  
  "is_closed": true  
},  
{  
  "color": "#cc0000",  
  "name": "Needs Info",  
  "slug": "needs-info",  
  "order": 5,  
  "is_closed": false  
}  
],  
"issue_statuses": [  
  {  
    "color": "#999999",  
    "name": "New",  

```

```
        "order": 4,
        "is_closed": true
    },
    {
        "color": "#cc0000",
        "name": "Needs Info",
        "slug": "needs-info",
        "order": 5,
        "is_closed": false
    },
    {
        "color": "#d3d7cf",
        "name": "Rejected",
        "slug": "rejected",
        "order": 6,
        "is_closed": true
    },
    {
        "color": "#75507b",
        "name": "Postponed",
        "slug": "postponed",
        "order": 7,
        "is_closed": false
    }
],
"issue_types": [
    {
        "color": "#cc0000",
        "name": "Bug",
        "order": 1
    },
    {
        "color": "#729fcf",
        "name": "Question",
        "order": 2
    },
    {
        "color": "#4e9a06",
        "name": "Enhancement",
        "order": 3
    }
],
"priorities": [
    {
        "color": "#999999",
        "name": "Low",
        "order": 1
    },
    {
        "color": "#007bff",
        "name": "Medium",
        "order": 2
    },
    {
        "color": "#28a745",
        "name": "High",
        "order": 3
    }
]
```

```
{
  "color": "#4e9a06",
  "name": "Normal",
  "order": 3
},
{
  "color": "#CC0000",
  "name": "High",
  "order": 5
}
],
"severities": [
  {
    "color": "#999999",
    "name": "Wishlist",
    "order": 1
  },
  {
    "color": "#729fcf",
    "name": "Minor",
    "order": 2
  },
  {
    "color": "#4e9a06",
    "name": "Normal",
    "order": 3
  },
  {
    "color": "#f57900",
    "name": "Important",
    "order": 4
  },
  {
    "color": "#CC0000",
    "name": "Critical",
    "order": 5
  }
],
"roles": [
  {
    "permissions": [
      "add_issue", "modify_issue", "delete_issue", "view_issues",
      "add_milestone", "modify_milestone", "delete_milestone",
      "view_milestones", "view_project", "add_task", "modify_task",
      "delete_task", "view_tasks", "add_us", "modify_us",
      "delete_us", "view_us", "add_wiki_page", "modify_wiki_page",
      "delete_wiki_page", "view_wiki_pages", "add_wiki_link",
      "delete_wiki_link", "view_wiki_links"
    ]
  }
]
```

```
],
  "order": 10,
  "computable": true,
  "slug": "ux",
  "name": "UX"
},
{
  "permissions": [
    "add_issue", "modify_issue", "delete_issue", "view_issues",
    "add_milestone", "modify_milestone", "delete_milestone",
    "view_milestones", "view_project", "add_task", "modify_task",
    "delete_task", "view_tasks", "add_us", "modify_us",
    "delete_us", "view_us", "add_wiki_page", "modify_wiki_page",
    "delete_wiki_page", "view_wiki_pages", "add_wiki_link",
    "delete_wiki_link", "view_wiki_links"
  ],
  "order": 20,
  "computable": true,
  "slug": "design",
  "name": "Design"
},
{
  "permissions": [
    "add_issue", "modify_issue", "delete_issue", "view_issues",
    "add_milestone", "modify_milestone", "delete_milestone",
    "view_milestones", "view_project", "add_task", "modify_task",
    "delete_task", "view_tasks", "add_us", "modify_us",
    "delete_us", "view_us", "add_wiki_page", "modify_wiki_page",
    "delete_wiki_page", "view_wiki_pages", "add_wiki_link",
    "delete_wiki_link", "view_wiki_links"
  ],
  "order": 30,
  "computable": true,
  "slug": "front",
  "name": "Front"
},
{
  "permissions": [
    "add_issue", "modify_issue", "delete_issue", "view_issues",
    "add_milestone", "modify_milestone", "delete_milestone",
    "view_milestones", "view_project", "add_task", "modify_task",
    "delete_task", "view_tasks", "add_us", "modify_us",
    "delete_us", "view_us", "add_wiki_page", "modify_wiki_page",
    "delete_wiki_page", "view_wiki_pages", "add_wiki_link",
    "delete_wiki_link", "view_wiki_links"
  ],
  "order": 40,
  "computable": true,
```

```

        "slug": "back",
        "name": "Back"
    },
    {
        "permissions": [
            "add_issue", "modify_issue", "delete_issue", "view_issues",
            "add_milestone", "modify_milestone", "delete_milestone",
            "view_milestones", "view_project", "add_task", "modify_task",
            "delete_task", "view_tasks", "add_us", "modify_us",
            "delete_us", "view_us", "add_wiki_page", "modify_wiki_page",
            "delete_wiki_page", "view_wiki_pages", "add_wiki_link",
            "delete_wiki_link", "view_wiki_links"
        ],
        "order": 50,
        "computable": false,
        "slug": "product-owner",
        "name": "Product Owner"
    },
    {
        "permissions": [
            "add_issue", "modify_issue", "delete_issue", "view_issues",
            "view_milestones", "view_project", "view_tasks", "view_us",
            "modify_wiki_page", "view_wiki_pages", "add_wiki_link",
            "delete_wiki_link", "view_wiki_links"
        ],
        "order": 60,
        "computable": false,
        "slug": "stakeholder",
        "name": "Stakeholder"
    }
],
"id": 2,
"name": "Kanban",
"slug": "kanban",
"description": "Sample description",
"created_date": "2014-04-22T14:50:19+0000",
"modified_date": "2014-07-25T13:11:42+0000",
"default_owner_role": "product-owner",
"is_backlog_activated": false,
"is_kanban_activated": true,
"is_wiki_activated": false,
"is_issues_activated": false,
"videoconferences": null,
"videoconferences_extra_data": ""
}

```

41.1. Project list entry

```
{  
  "is_fan": true,  
  "is_watcher": true,  
  "total_watchers": 200,  
  "anon_permissions": [  
    "view_project",  
    "view_milestones",  
    "view_us",  
    "view_tasks",  
    "view_issues"  
,  
  "public_permissions": [  
    "view_project",  
    "view_milestones",  
    "view_us",  
    "view_tasks",  
    "view_issues"  
,  
  "my_permissions": [  
    "delete_us",  
    "view_project",  
    "add_comments_to_us",  
    "delete_milestone",  
    "modify_task",  
    "modify_milestone",  
    "remove_member",  
    "delete_project",  
    "add_comments_to_issue",  
    "modify_issue",  
    "delete_task",  
    "modify_us",  
    "delete_issue",  
    "add_wiki_link",  
    "view_tasks",  
    "view_milestones",  
    "add_milestone",  
    "modify_wiki_link",  
    "add_comments_to_task",  
    "delete_wiki_page",  
    "add_member",  
    "add_task",  
    "view_wiki_pages",  
    "view_us",  
    "delete_wiki_link",  
  ]  
}
```

```
"add_issue",
"view_issues",
"modify_project",
"modify_wiki_page",
"add_wiki_page",
"request_membership",
"add_us_to_project",
"add_us",
"admin_roles",
"admin_project_values",
"view_wiki_links"
],
"owner": {
  "id": 33,
  "username": "beta.tester",
  "full_name_display": "Beta Tester",
  "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
  "big_photo":
  "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
  "is_active": true
},
"i_am_owner": true,
"i_am_admin": true,
"i_am_member": true,
"tags": [
  "angular",
  "python",
  "django",
  "project manager"
],
"tags_colors": {
  "python": "#5c3566",
  "angular": "#3465a4",
  "project manager": "#fcaf3e",
  "django": "#888a85"
},
"notify_level": 2,
"total_closed_milestones": 16,
"logo_small_url":
"http://localhost:8000/media/project/c/4/9/4/eb6354d601e95a7813a3394d0b0b656eefe684721c85
a01692143b381c23/1_imggr2__mg_6521.jpg.80x80_q85_crop.jpg",
"logo_big_url":
"http://localhost:8000/media/project/c/4/9/4/eb6354d601e95a7813a3394d0b0b656eefe684721c85
a01692143b381c23/1_imggr2__mg_6521.jpg.300x300_q85_crop.jpg",
"id": 1,
"default_points": 1,
"default_us_status": 27,
"default_task_status": 1,
```

```
"default_priority": 2,
"default_severity": 3,
"default_issue_status": 1,
"default_issue_type": 1,
"name": "Taiga",
"slug": "taiga",
"description": "Free. Open Source. Powerful. Taiga is a project management platform for startups and agile developers & designers who want a simple, beautiful tool that makes work truly enjoyable.",
"created_date": "2013-10-23T11:45:58+0000",
"modified_date": "2016-01-14T08:22:14+0000",
"total_milestones": 20,
"total_story_points": 380.0,
"is_backlog_activated": false,
"is_kanban_activated": true,
"is_wiki_activated": true,
"is_issues_activated": true,
"videoconferences": null,
"videoconferences_extra_data": null,
"creation_template": null,
"is_private": true,
"is_featured": true,
"is_looking_for_people": false,
"looking_for_people_note": "",
"totals_updated_datetime": "2016-01-13T11:56:02+0000",
"total_fans": 42,
"total_fans_last_week": 2,
"total_fans_last_month": 11,
"total_fans_last_year": 42,
"total_activity": 20538,
"total_activity_last_week": 142,
"total_activity_last_month": 506,
"total_activity_last_year": 12264,
"members": [
  7119,
  7,
  17,
  8,
  15,
  11,
  19,
  21921,
  9,
  24,
  16318,
  3,
  2,
  111,
```

```
  6,
  38,
  18,
  18231,
  4,
  5,
  16,
  13,
  14
]
},
{
  "is_fan": false,
  "is_watcher": true,
  "total_watchers": 1,
  "anon_permissions": [],
  "public_permissions": [],
  "my_permissions": [
    "delete_us",
    "view_project",
    "add_comments_to_us",
    "delete_milestone",
    "modify_task",
    "modify_milestone",
    "remove_member",
    "delete_project",
    "add_comments_to_issue",
    "modify_issue",
    "delete_task",
    "modify_us",
    "delete_issue",
    "add_wiki_link",
    "view_tasks",
    "view_milestones",
    "add_milestone",
    "modify_wiki_link",
    "add_comments_to_task",
    "delete_wiki_page",
    "add_member",
    "add_task",
    "view_wiki_pages",
    "view_us",
    "delete_wiki_link",
    "add_issue",
    "view_issues",
    "modify_project",
    "modify_wiki_page",
    "add_wiki_page",
```

```

    "request_membership",
    "add_us_to_project",
    "add_us",
    "admin_roles",
    "admin_project_values",
    "view_wiki_links"
],
"owner": {
    "username": "beta.tester",
    "full_name_display": "Beta Tester",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80",
    "big_photo":
    "//www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80",
    "is_active": true
},
"i_am_owner": true,
"i_am_admin": true,
"i_am_member": true,
"tags": [],
"tags_colors": {},
"notify_level": 1,
"total_closed_milestones": [],
"logo_small_url": null,
"logo_big_url": null,
"id": 83524,
"default_points": 1002480,
"default_us_status": 479163,
"default_task_status": 417984,
"default_priority": 250953,
"default_severity": 416784,
"default_issue_status": 584816,
"default_issue_type": 251876,
"name": "Taiga support",
"slug": "alejandroalonso-taiga-support",
"description": "Questions and answers, howto's, sample emails...\n\nUseful stuff for the support team",
"created_date": "2015-11-19T06:14:24+0000",
"modified_date": "2016-01-05T11:27:53+0000",
"total_milestones": null,
"total_story_points": null,
"is_backlog_activated": false,
"is_kanban_activated": false,
"is_wiki_activated": true,
"is_issues_activated": true,
"videoconferences": null,
"videoconferences_extra_data": null,
"creation_template": 1,
"is_private": true

```

```
"is_featured": false,
"is_looking_for_people": false,
"looking_for_people_note": "",
"totals_updated_datetime": "2016-01-05T11:27:53+0000",
"total_fans": 0,
"total_fans_last_week": 0,
"total_fans_last_month": 0,
"total_fans_last_year": 0,
"total_activity": 35,
"total_activity_last_week": 6,
"total_activity_last_month": 10,
"total_activity_last_year": 35,
"members": [
  7
]
},
{
  "is_fan": false,
  "is_watcher": true,
  "total_watchers": 27,
  "anon_permissions": [],
  "public_permissions": [],
  "my_permissions": [
    "delete_us",
    "view_project",
    "add_comments_to_us",
    "delete_milestone",
    "modify_task",
    "modify_milestone",
    "remove_member",
    "delete_project",
    "add_comments_to_issue",
    "modify_issue",
    "delete_task",
    "modify_us",
    "delete_issue",
    "add_wiki_link",
    "view_tasks",
    "view_milestones",
    "add_milestone",
    "modify_wiki_link",
    "add_comments_to_task",
    "delete_wiki_page",
    "add_member",
    "add_task",
    "view_wiki_pages",
    "view_us",
    "delete_wiki_link",
  ]
}
```

```
"add_issue",
"view_issues",
"modify_project",
"modify_wiki_page",
"add_wiki_page",
"request_membership",
"add_us_to_project",
"add_us",
"admin_roles",
"admin_project_values",
"view_wiki_links"
],
"owner": {
  "id": 33,
  "username": "beta.tester",
  "full_name_display": "Beta Tester",
  "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
  "big_photo":
  "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
  "is_active": true
},
"i_am_owner": true,
"i_am_admin": true,
"i_am_member": true,
"tags": [],
"tags_colors": {
  "perfil": "#ef2929",
  "keywords": "#88fc09",
  "do the gig": "#e338c5",
  "404": "#c35a9f",
  "cases": "#f9063c",
  "challenge": "#edd400",
  "question": "#3b2be2",
  "abuse": "#39ca1c",
  "illustration": "#6573ac",
  "teams": "#462938",
  "steps": "#657891",
  "naming": "#9c388c",
  "back": "#ad7fa8",
  "login": "#2736fa",
  "ofertas": "#2e3436",
  "legal": "#73d216",
  "errors": "#570043",
  "bug": "#75507b",
  "profile": "#888a85",
  "moneda": "#f1f114",
  "button": "#7b7fcc",
  "confirmation": "#38bd34",
```

```
"url": "#817363",
"taiga": "#4e9a06",
"transversal": "#fce94f",
"suggest": "#fd0a49",
"mensajer\u00eda": "#a40000",
"import": "#3465a4",
"gig": "#12f295",
"cancel": "#4fd065",
"header": "#594fd1",
"localStorage": "#45a2e6",
"edit profile": "#d3fab0",
"copy": "#f84e2e",
"mail": "#1d6e1c",
"paypal": "#0b4e48",
"home": "#ce5c00",
"anonymous": "#0a92fa",
"account": "#ca2072",
"translation": "#efd7fd",
"crear gig": "#cdf0da",
"design": "#d3d7cf",
"report": "#a27297",
"seo": "#6170ca",
"share": "#aab90d",
"closed": "#ea88fb",
"403": "#8980dc",
"form": "#5c3566",
"external": "#59d8f3",
"support": "#5bdcd3",
"messages": "#17f346",
"settings": "#3cc1d5",
"web": "#c4a000",
"timeline": "#16c004",
"integration": "#f57900",
"location": "#6469ac",
"search": "#3559d7",
"baja": "#0d9c30",
"status": "#48a366",
"cancel account": "#aa3066",
"help": "#92005e",
"gig icon": "#ce42e1",
"contacts": "#9db49a",
"items": "#7316c8",
"core": "#cc0000",
"copies": "#475f96",
"footer": "#d7eb6b",
"front": "#1b78eb",
"applied": "#c0b885",
"gig detail": "#e49bc6",
```

```
"icon": "#f8995b",
"sincronizar": "#8296a4",
"mobile": "#83d631",
"refactor": "#90b816",
"autenticaci\u00f3n": "#204a87",
"users": "#5b7dcd",
"not lucy": "#0c59f5",
"survey": "#62380f",
".po": "#c8269d",
"typo": "#020f67",
"sign up": "#6acc13",
"links": "#379e75",
"tab": "#e97460",
"rating": "#3c2d68",
"notifications": "#1b60d2",
"setting": "#d6df1a",
"backlog": "#ff9e8f",
"offer": "#729fcf",
"avatar": "#9c3bb4",
"review": "#61e62b",
"email": "#a88b7d",
"skills": "#816f2b",
"big": "#95c4be",
"notification": "#310ec4",
"owner": "#8ae234",
"gig done": "#8724ae",
"created": "#21c508",
"javascript": "#fcacf3e",
"fee": "#9c15cd",
"ux": "#796384"
},
"notify_level": 1,
"total_closed_milestones": [
  "Sprint Zero",
  "Sprint 1",
  "Sprint 2",
  "Sprint 3",
  "Sprint 4",
  "Sprint 5",
  "Sprint 6",
  "Sprint 7",
  "Sprint 8",
  "Sprint 9",
  "Sprint 10",
  "Sprint 11",
  "Sprint 12",
  "Sprint 13",
  "Sprint 14",
```

```
        "Sprint 15",
        "Sprint 16"
    ],
    "logo_small_url": null,
    "logo_big_url": null,
    "id": 25682,
    "default_points": 308217,
    "default_us_status": 130291,
    "default_task_status": 128468,
    "default_priority": 76985,
    "default_severity": 128265,
    "default_issue_status": 179622,
    "default_issue_type": 77033,
    "name": "Taiga Tribe",
    "slug": "taiga-tribe",
    "description": "Taiga Tribe Project",
    "created_date": "2015-02-04T12:40:46+0000",
    "modified_date": "2016-01-07T15:34:28+0000",
    "total_milestones": 18,
    "total_story_points": 315.0,
    "is_backlog_activated": true,
    "is_kanban_activated": false,
    "is_wiki_activated": true,
    "is_issues_activated": true,
    "videoconferences": null,
    "videoconferences_extra_data": null,
    "creation_template": 1,
    "is_private": true,
    "is_featured": false,
    "is_looking_for_people": false,
    "looking_for_people_note": "",
    "totals_updated_datetime": "2016-01-07T15:34:28+0000",
    "total_fans": 4,
    "total_fans_last_week": 0,
    "total_fans_last_month": 1,
    "total_fans_last_year": 4,
    "total_activity": 10141,
    "total_activity_last_week": 108,
    "total_activity_last_month": 140,
    "total_activity_last_year": 10141,
    "members": [
        7,
        17,
        8,
        15,
        11,
        19,
        9,
```

```
24,  
16318,  
2,  
111,  
6,  
38,  
18,  
4,  
5,  
16,  
20,  
13,  
14  
]  
}
```

41.2. Project detail

```
{  
  "is_fan": true,  
  "is_watcher": true,  
  "total_watchers": 200,  
  "anon_permissions": [  
    "view_project",  
    "view_wiki_links",  
    "view_tasks",  
    "view_milestones",  
    "view_issues",  
    "view_wiki_pages",  
    "view_us"  
,  
  "public_permissions": [  
    "view_project",  
    "view_wiki_links",  
    "view_tasks",  
    "view_milestones",  
    "view_issues",  
    "view_wiki_pages",  
    "view_us"  
,  
  "my_permissions": [  
    "modify_project",  
    "view_issues",  
    "add_comments_to_task",  
    "delete_project",  
    "delete_wiki_link",  
  ]  
}
```

```
"add_wiki_link",
"view_project",
"add_issue",
"delete_issue",
"modify_issue",
"admin_project_values",
"view_wiki_links",
"add_us_to_project",
"add_task",
"delete_us",
"view_us",
"add_milestone",
"remove_member",
"delete_milestone",
"request_membership",
"add_comments_to_issue",
"modify_wiki_link",
"modify_wiki_page",
"view_tasks",
"modify_us",
"delete_wiki_page",
"add_member",
"view_milestones",
"add_comments_to_us",
"add_us",
"view_wiki_pages",
"modify_task",
"admin_roles",
"delete_task",
"modify_milestone",
"add_wiki_page"
],
"owner": {
  "username": "eposner",
  "full_name_display": "Enrique Posner",
  "photo": "https://www.gravatar.com/avatar/4d0461f202e33a82a1b810cbfed81361?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "big_photo": "https://www.gravatar.com/avatar/4d0461f202e33a82a1b810cbfed81361?size=300&default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png",
  "is_active": true,
  "id": 24
},
"i_am_owner": true,
"i_am_admin": true,
"i_am_member": true,
"tags": [
```

```
        "angular",
        "python",
        "django",
        "project manager"
    ],
    "tags_colors": {
        "django": "#4e9a06",
        "angular": "#d3d7cf",
        "project manager": "#888a85",
        "python": "#2e3436"
    },
    "notify_level": 2,
    "total_closed_milestones": 16,
    "logo_small_url": null,
    "logo_big_url": null,
    "us_statuses": [
        {
            "id": 27,
            "name": "Icebox",
            "slug": "icebox",
            "order": 0,
            "is_closed": false,
            "is_archived": false,
            "color": "#729fcf",
            "wip_limit": null,
            "project": 1
        },
        {
            "id": 29,
            "name": "Defining",
            "slug": "defining",
            "order": 1,
            "is_closed": false,
            "is_archived": false,
            "color": "#ef2929",
            "wip_limit": null,
            "project": 1
        },
        {
            "id": 1,
            "name": "Ready",
            "slug": "ready",
            "order": 2,
            "is_closed": false,
            "is_archived": false,
            "color": "#a40000",
            "wip_limit": null,
            "project": 1
        }
    ]
}
```

```
},
{
  "id": 57858,
  "name": "UX",
  "slug": "ux",
  "order": 3,
  "is_closed": false,
  "is_archived": false,
  "color": "#ad7fa8",
  "wip_limit": null,
  "project": 1
},
{
  "id": 211690,
  "name": "UX feedback",
  "slug": "ux-feedback",
  "order": 4,
  "is_closed": false,
  "is_archived": false,
  "color": "#75507b",
  "wip_limit": null,
  "project": 1
},
{
  "id": 57859,
  "name": "UX done",
  "slug": "ux-done",
  "order": 5,
  "is_closed": false,
  "is_archived": false,
  "color": "#5c3566",
  "wip_limit": null,
  "project": 1
},
{
  "id": 57860,
  "name": "Design",
  "slug": "design",
  "order": 6,
  "is_closed": false,
  "is_archived": false,
  "color": "#8ae234",
  "wip_limit": null,
  "project": 1
},
{
  "id": 211691,
  "name": "Design feedback",
```

```
"slug": "design-feedback",
"order": 7,
"is_closed": false,
"is_archived": false,
"color": "#73d216",
"wip_limit": null,
"project": 1
},
{
  "id": 57861,
  "name": "Design done",
  "slug": "design-done",
  "order": 8,
  "is_closed": false,
  "is_archived": false,
  "color": "#4e9a06",
  "wip_limit": null,
  "project": 1
},
{
  "id": 38,
  "name": "Development",
  "slug": "development",
  "order": 9,
  "is_closed": false,
  "is_archived": false,
  "color": "#fcacf3e",
  "wip_limit": null,
  "project": 1
},
{
  "id": 57868,
  "name": "Ready For Test",
  "slug": "ready-for-test",
  "order": 10,
  "is_closed": false,
  "is_archived": false,
  "color": "#ce5c00",
  "wip_limit": null,
  "project": 1
},
{
  "id": 57876,
  "name": "Testing",
  "slug": "testing",
  "order": 11,
  "is_closed": false,
  "is_archived": false,
```

```
        "color": "#fce94f",
        "wip_limit": null,
        "project": 1
    },
    {
        "id": 57870,
        "name": "Done",
        "slug": "done",
        "order": 13,
        "is_closed": false,
        "is_archived": false,
        "color": "#73d216",
        "wip_limit": null,
        "project": 1
    },
    {
        "id": 2,
        "name": "Released",
        "slug": "released",
        "order": 14,
        "is_closed": true,
        "is_archived": true,
        "color": "#3465a4",
        "wip_limit": null,
        "project": 1
    }
],
"points": [
    {
        "id": 1,
        "name": "?",
        "order": 1,
        "value": null,
        "project": 1
    },
    {
        "id": 2,
        "name": "0",
        "order": 2,
        "value": 0.0,
        "project": 1
    },
    {
        "id": 3,
        "name": "1/2",
        "order": 3,
        "value": 0.5,
        "project": 1
    }
]
```

```
},
{
  "id": 4,
  "name": "1",
  "order": 4,
  "value": 1.0,
  "project": 1
},
{
  "id": 5,
  "name": "2",
  "order": 5,
  "value": 2.0,
  "project": 1
},
{
  "id": 6,
  "name": "3",
  "order": 6,
  "value": 3.0,
  "project": 1
},
{
  "id": 7,
  "name": "5",
  "order": 7,
  "value": 5.0,
  "project": 1
},
{
  "id": 8,
  "name": "8",
  "order": 8,
  "value": 8.0,
  "project": 1
},
{
  "id": 9,
  "name": "10",
  "order": 9,
  "value": 10.0,
  "project": 1
},
{
  "id": 10,
  "name": "15",
  "order": 10,
  "value": 15.0,
```

```
        "project": 1
    },
    {
        "id": 11,
        "name": "20",
        "order": 11,
        "value": 20.0,
        "project": 1
    },
    {
        "id": 12,
        "name": "40",
        "order": 12,
        "value": 40.0,
        "project": 1
    }
],
"task_statuses": [
    {
        "id": 1,
        "name": "New",
        "slug": "new",
        "order": 0,
        "is_closed": false,
        "color": "#999999",
        "project": 1
    },
    {
        "id": 2,
        "name": "In progress",
        "slug": "in-progress",
        "order": 1,
        "is_closed": false,
        "color": "#ff9900",
        "project": 1
    },
    {
        "id": 4,
        "name": "Closed",
        "slug": "closed",
        "order": 3,
        "is_closed": true,
        "color": "#669900",
        "project": 1
    },
    {
        "id": 5,
        "name": "Needs Info",
        "slug": "needs-info",
        "order": 4,
        "is_closed": false,
        "color": "#999999",
        "project": 1
    }
]
```

```
        "slug": "needs-info",
        "order": 4,
        "is_closed": false,
        "color": "#999999",
        "project": 1
    },
    {
        "id": 217,
        "name": "Rejected",
        "slug": "rejected",
        "order": 5,
        "is_closed": true,
        "color": "#804eff",
        "project": 1
    }
],
"issue_statuses": [
    {
        "id": 1,
        "name": "New",
        "slug": "new",
        "order": 1,
        "is_closed": false,
        "color": "#8C2318",
        "project": 1
    },
    {
        "id": 2,
        "name": "In progress",
        "slug": "in-progress",
        "order": 2,
        "is_closed": false,
        "color": "#5E8C6A",
        "project": 1
    },
    {
        "id": 4,
        "name": "Closed",
        "slug": "closed",
        "order": 4,
        "is_closed": true,
        "color": "#BFB35A",
        "project": 1
    },
    {
        "id": 5,
        "name": "Needs Info",
        "slug": "needs-info",
        "order": 5,
        "is_closed": false,
        "color": "#999999",
        "project": 1
    }
]
```

```
        "order": 5,
        "is_closed": false,
        "color": "#89BAB4",
        "project": 1
    },
    {
        "id": 6,
        "name": "Rejected",
        "slug": "rejected",
        "order": 6,
        "is_closed": true,
        "color": "#CC0000",
        "project": 1
    },
    {
        "id": 7,
        "name": "Postponed",
        "slug": "postponed",
        "order": 7,
        "is_closed": true,
        "color": "#666666",
        "project": 1
    }
],
"issue_types": [
    {
        "id": 1,
        "name": "Bug",
        "order": 0,
        "color": "#cc0000",
        "project": 1
    },
    {
        "id": 6,
        "name": "Enhancement",
        "order": 1,
        "color": "#729fcf",
        "project": 1
    },
    {
        "id": 65033,
        "name": "Refactors",
        "order": 2,
        "color": "#f57900",
        "project": 1
    },
    {
        "id": 68773,
```

```
        "name": "Question",
        "order": 3,
        "color": "#5c3566",
        "project": 1
    }
],
"priorities": [
    {
        "id": 1,
        "name": "Low",
        "order": 1,
        "color": "#888a85",
        "project": 1
    },
    {
        "id": 2,
        "name": "Normal",
        "order": 3,
        "color": "#4e9a06",
        "project": 1
    },
    {
        "id": 3,
        "name": "High",
        "order": 5,
        "color": "#a40000",
        "project": 1
    }
],
"severities": [
    {
        "id": 1,
        "name": "Wishlist",
        "order": 1,
        "color": "#888a85",
        "project": 1
    },
    {
        "id": 2,
        "name": "Minor",
        "order": 2,
        "color": "#4e9a06",
        "project": 1
    },
    {
        "id": 3,
        "name": "Normal",
        "order": 3,
        "color": "#4e9a06",
        "project": 1
    }
]
```

```
        "color": "#204a87",
        "project": 1
    },
    {
        "id": 4,
        "name": "Important",
        "order": 4,
        "color": "#ce5c00",
        "project": 1
    },
    {
        "id": 5,
        "name": "Critical",
        "order": 5,
        "color": "#a40000",
        "project": 1
    }
],
"userstory_custom_attributes": [],
"task_custom_attributes": [],
"issue_custom_attributes": [],
"roles": [
    {
        "id": 43,
        "name": "UX",
        "slug": "ux",
        "order": 10,
        "computable": true
    },
    {
        "id": 44,
        "name": "Design",
        "slug": "design",
        "order": 20,
        "computable": true
    },
    {
        "id": 45,
        "name": "Front",
        "slug": "front",
        "order": 30,
        "computable": true
    },
    {
        "id": 46,
        "name": "Back",
        "slug": "back",
        "order": 40,
        "computable": true
    }
]
```

```
        "computable": true
    },
    {
        "id": 47,
        "name": "Product Owner",
        "slug": "product-owner",
        "order": 50,
        "computable": false
    },
    {
        "id": 48,
        "name": "Stakeholder",
        "slug": "stakeholder",
        "order": 60,
        "computable": false
    },
    {
        "id": 88176,
        "name": "Reader",
        "slug": "reader",
        "order": 61,
        "computable": false
    }
],
"members": [
    {
        "id": 7,
        "username": "alejandro.alonso",
        "full_name": "Alejandro Alonso",
        "full_name_display": "Alejandro Alonso",
        "color": "#FC8EAC",
        "photo": "https://www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
        "is_active": true,
        "role_name": "Back",
        "user": 7,
        "role": 46,
        "is_admin": true
    },
    {
        "id": 17,
        "username": "alonso.torres",
        "full_name": "Alonso Torres",
        "full_name_display": "Alonso Torres",
        "color": "#FFFF00",
        "photo": "https://www.gravatar.com/avatar/83aa5245de5659cdcaa1e5d025e320ae?default=https%3A%2F%2Fstatic.
```

```
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Stakeholder",
  "user": 17,
  "role": 48,
  "is_admin": false
},
{
  "id": 7119,
  "username": "acs",
  "full_name": "Alvaro",
  "full_name_display": "Alvaro",
  "color": "#67e326",
  "photo":
"//www.gravatar.com/avatar/e934740e4ac77c1100bb9abd289fad44?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Reader",
  "user": 7119,
  "role": 88176,
  "is_admin": false
},
{
  "id": 21921,
  "username": "astagi",
  "full_name": "Andrea Stagi",
  "full_name_display": "Andrea Stagi",
  "color": "#04a7db",
  "photo":
"//www.gravatar.com/avatar/2c01fbda58ccbae404f853c9e587407c?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Reader",
  "user": 21921,
  "role": 88176,
  "is_admin": false
},
{
  "id": 18231,
  "username": "myfunnyandy",
  "full_name": "andr\u00e9s gonz\u00e1lez fern\u00e1ndez",
  "full_name_display": "andr\u00e9s gonz\u00e1lez fern\u00e1ndez",
  "color": "#fcfd96",
  "photo":
"//www.gravatar.com/avatar/679fec642599c93d4f6affba963a57a4?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "UX",
```

```

    "user": 18231,
    "role": 43,
    "is_admin": false
  },
  {
    "id": 15,
    "username": "andres.moya",
    "full_name": "Andr\u00e1s Moya",
    "full_name_display": "Andr\u00e1s Moya",
    "color": "#669933",
    "photo":
      "https://www.gravatar.com/avatar/d4775abf3e36c119f0127e29da6adf12?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "is_active": true,
    "role_name": "Stakeholder",
    "user": 15,
    "role": 48,
    "is_admin": false
  },
  {
    "id": 8,
    "username": "andrei.antoukh",
    "full_name": "Andrey Antukh",
    "full_name_display": "Andrey Antukh",
    "color": "#A5694F",
    "photo":
      "https://www.gravatar.com/avatar/e6b6ab0f2fa0fde797dd2c80b188a6ef?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "is_active": true,
    "role_name": "Back",
    "user": 8,
    "role": 46,
    "is_admin": true
  },
  {
    "id": 11,
    "username": "anler.hernandez",
    "full_name": "Anler Hern\u00e1ndez Peral",
    "full_name_display": "Anler Hern\u00e1ndez Peral",
    "color": "#8f0030",
    "photo":
      "https://www.gravatar.com/avatar/a3d9202a1e1f5809bd399b9c50631a45?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "is_active": true,
    "role_name": "Back",
    "user": 11,
    "role": 46,
    "is_admin": false
  }

```

```
},
{
  "id": 19,
  "username": "antonio.delatorre",
  "full_name": "Antonio de la Torre",
  "full_name_display": "Antonio de la Torre",
  "color": "#67CF00",
  "photo":
  "://www.gravatar.com/avatar/bc4618611c4315311cfba45679681084?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Stakeholder",
  "user": 19,
  "role": 48,
  "is_admin": false
},
{
  "id": 9,
  "username": "bameda",
  "full_name": "David Barrag\u00e1n Merino",
  "full_name_display": "David Barrag\u00e1n Merino",
  "color": "#FFF8E7",
  "photo":
  "://www.gravatar.com/avatar/ca3f184c1e11414128d75b06509535bf?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Back",
  "user": 9,
  "role": 46,
  "is_admin": true
},
{
  "id": 24,
  "username": "eposner",
  "full_name": "Enrique Posner",
  "full_name_display": "Enrique Posner",
  "color": "#d9ff2f",
  "photo":
  "://www.gravatar.com/avatar/4d0461f202e33a82a1b810cbfed81361?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Product Owner",
  "user": 24,
  "role": 47,
  "is_admin": true
},
{
  "id": 16318,
```

```
"username": "esther.moreno",
"full_name": "Esther Moreno",
"full_name_display": "Esther Moreno",
"color": "#a9fd11",
"photo": null,
"is_active": true,
"role_name": "UX",
"user": 16318,
"role": 43,
"is_admin": true
},
{
"id": 3,
"username": "ivan.lopez",
"full_name": "Iv\u00e1n López",
"full_name_display": "Iv\u00e1n López",
"color": "#4B0082",
"photo": null,
"is_active": true,
"role_name": "Stakeholder",
"user": 3,
"role": 48,
"is_admin": false
},
{
"id": 2,
"username": "jesus.espino",
"full_name": "Jes\u00f3s Espino",
"full_name_display": "Jes\u00f3s Espino",
"color": "#007000",
"photo":
"//www.gravatar.com/avatar/571f7fd524c93a2958689e1594c8f1cb?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
"is_active": true,
"role_name": "Back",
"user": 2,
"role": 46,
"is_admin": true
},
{
"id": 111,
"username": "juan.delacruz",
"full_name": "Juan de la Cruz García",
"full_name_display": "Juan de la Cruz García",
"color": "#6427c0",
"photo":
"//www.gravatar.com/avatar/e53c2d8dc6df0cb22cc74d6bc0a8a2db?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
```

```
        "is_active": true,
        "role_name": "Design",
        "user": 111,
        "role": 44,
        "is_admin": true
    },
{
    "id": 6,
    "username": "juanfran.alcantara",
    "full_name": "Juanfran",
    "full_name_display": "Juanfran",
    "color": "#40826D",
    "photo":
    "//www.gravatar.com/avatar/cf51e428ddf4490dcc540991be905ee6?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
        "is_active": true,
        "role_name": "Front",
        "user": 6,
        "role": 45,
        "is_admin": true
    },
{
    "id": 38,
    "username": "mario.garcia",
    "full_name": "Mario Garcia",
    "full_name_display": "Mario Garcia",
    "color": "#FF9900",
    "photo":
    "//www.gravatar.com/avatar/fae470694dbb476f996a6ffd481883c4?default=https%3A%2F%2Fstatic.
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
        "is_active": true,
        "role_name": "Stakeholder",
        "user": 38,
        "role": 48,
        "is_admin": false
    },
{
    "id": 18,
    "username": "miguel.delacruz",
    "full_name": "Miguel de la Cruz",
    "full_name_display": "Miguel de la Cruz",
    "color": "#C0FF33",
    "photo": null,
    "is_active": true,
    "role_name": "Stakeholder",
    "user": 18,
    "role": 48,
    "is_admin": false
}
```

```
},
{
  "id": 4,
  "username": "pablo.alba",
  "full_name": "Pablo Alba",
  "full_name_display": "Pablo Alba",
  "color": "#708090",
  "photo":
  "://www.gravatar.com/avatar/31e5964e859dc66b52d76dcfea9bd94d?default=https%3A%2F%2Fstatic.
  taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Stakeholder",
  "user": 4,
  "role": 48,
  "is_admin": false
},
{
  "id": 5,
  "username": "pablo.ruiz",
  "full_name": "Pablo Ruiz M\u00f3nica",
  "full_name_display": "Pablo Ruiz M\u00f3nica",
  "color": "#761CEC",
  "photo": null,
  "is_active": true,
  "role_name": "Product Owner",
  "user": 5,
  "role": 47,
  "is_admin": true
},
{
  "id": 16,
  "username": "ramiro.sanchez",
  "full_name": "Ramiro Sanchez Balo",
  "full_name_display": "Ramiro Sanchez Balo",
  "color": "#FFCC00",
  "photo":
  "://www.gravatar.com/avatar/3709c545d8488043ee6e4517996ab7cb?default=https%3A%2F%2Fstatic.
  taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "is_active": true,
  "role_name": "Stakeholder",
  "user": 16,
  "role": 48,
  "is_admin": false
},
{
  "id": 13,
  "username": "xavier.julian",
  "full_name": "Xavier Juli\u00f3n",
  "full_name_display": "Xavier Juli\u00f3n",
```

```

    "full_name_display": "Xavier Juli\u00e1n",
    "color": "#CC0000",
    "photo": null,
    "is_active": true,
    "role_name": "Front",
    "user": 13,
    "role": 45,
    "is_admin": true
  },
  {
    "id": 14,
    "username": "yamila.moreno",
    "full_name": "",
    "full_name_display": "yamila.moreno",
    "color": "#669933",
    "photo": "//www.gravatar.com/avatar/0ec2ec5c6a1c55e1414865f03ea96b16?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "is_active": true,
    "role_name": "Stakeholder",
    "user": 14,
    "role": 48,
    "is_admin": false
  }
],
"is_private_extra_info": {
  "can_be_updated": false,
  "reason": "max_private_projects_memberships"
},
"max_memberships": 13,
"total_memberships": 24,
"id": 1,
"default_points": 1,
"default_us_status": 27,
"default_task_status": 1,
"default_priority": 2,
"default_severity": 3,
"default_issue_status": 1,
"default_issue_type": 1,
"name": "Taiga",
"slug": "taiga",
"description": "Free. Open Source. Powerful. Taiga is a project management platform for startups and agile developers & designers who want a simple, beautiful tool that makes work truly enjoyable.",
"created_date": "2013-10-23T11:45:58+0000",
"modified_date": "2016-03-18T12:00:43+0000",
"total_milestones": null,
"total_story_points": null

```

```

    "is_backlog_activated": false,
    "is_kanban_activated": true,
    "is_wiki_activated": true,
    "is_issues_activated": true,
    "videoconferences": null,
    "videoconferences_extra_data": null,
    "creation_template": null,
    "is_private": true,
    "is_featured": false,
    "is_looking_for_people": false,
    "looking_for_people_note": "",
    "userstories_csv_uuid": "PpJYgCqEIPpJYgCqEIPpJYgCqEI",
    "tasks_csv_uuid": "6m0oYhJJ6m0oYhJJ6m0oYhJJ",
    "issues_csv_uuid": "FomNu8YtNi",
    "transfer_token": "24:1agoMW:WQUE79W2s",
    "totals_updated_datetime": "2016-03-15T13:01:12+0000",
    "total_fans": 42,
    "total_fans_last_week": 0,
    "total_fans_last_month": 0,
    "total_fans_last_year": 42,
    "total_activity": 20508,
    "total_activity_last_week": 2,
    "total_activity_last_month": 2,
    "total_activity_last_year": 8703,
    "blocked_code": null
}

```

NOTE The attributes: is_private_extra_info, max_memberships, total_memberships, userstories_csv_uuid, tasks_csv_uuid, issues_csv_uuid, and transfer_token will only be included in the json only if the request is done by a project admin user.

41.3. Project modules configuration

```
{
  "github": {
    "secret": "b7a95570051a49ad8fb9482b5ef40262",
    "webhooks_url": "https://api.taiga.io/api/v1/github-hook?project=3"
  }
}
```

41.4. Project stats detail

```
{
```

```
"assigned_points": 331.5,
"assigned_points_per_role": {
    "43": 3.0,
    "44": 10.5,
    "45": 140.0,
    "46": 178.0
},
"closed_points": 310.5,
"closed_points_per_role": {
    "43": 3.0,
    "44": 7.5,
    "45": 133.0,
    "46": 167.0
},
"defined_points": 342.5,
"defined_points_per_role": {
    "43": 3.5,
    "44": 12.0,
    "45": 146.0,
    "46": 181.0
},
"milestones": [
    {
        "client-increment": 0,
        "evolution": 400.0,
        "name": "Sprint 0",
        "optimal": 400.0,
        "team-increment": 0
    },
    {
        "client-increment": 0,
        "evolution": 400.0,
        "name": "Sprint 1",
        "optimal": 380.0,
        "team-increment": 0
    },
    {
        "client-increment": 0,
        "evolution": 388.5,
        "name": "Sprint 2",
        "optimal": 360.0,
        "team-increment": 0
    },
    {
        "client-increment": 0,
        "evolution": 373.5,
        "name": "Sprint 3",
        "optimal": 340.0,
        "team-increment": 0
    }
]
```

```
        "team-increment": 0.5
    },
    {
        "client-increment": 0,
        "evolution": 361.5,
        "name": "Sprint 4",
        "optimal": 320.0,
        "team-increment": 0.5
    },
    {
        "client-increment": 0,
        "evolution": 357.0,
        "name": "Sprint 5",
        "optimal": 300.0,
        "team-increment": 3.5
    },
    {
        "client-increment": 0,
        "evolution": 351.5,
        "name": "Sprint 6",
        "optimal": 280.0,
        "team-increment": 5.0
    },
    {
        "client-increment": 0,
        "evolution": 347.0,
        "name": "Sprint 7",
        "optimal": 260.0,
        "team-increment": 5.0
    },
    {
        "client-increment": 0,
        "evolution": 346.5,
        "name": "Sprint 8",
        "optimal": 240.0,
        "team-increment": 5.0
    },
    {
        "client-increment": 0,
        "evolution": 325.5,
        "name": "Sprint 9",
        "optimal": 220.0,
        "team-increment": 6.0
    },
    {
        "client-increment": 0,
        "evolution": 308.0,
        "name": "Sprint 10 (new-taiga)",
```

```
        "optimal": 200.0,
        "team-increment": 7.0
    },
    {
        "client-increment": 0,
        "evolution": 199.5,
        "name": "Sprint 11 (new-taiga)",
        "optimal": 180.0,
        "team-increment": 7.0
    },
    {
        "client-increment": 0,
        "evolution": 192.5,
        "name": "Sprint 13 (new-taiga)",
        "optimal": 160.0,
        "team-increment": 7.0
    },
    {
        "client-increment": 0,
        "evolution": 157.0,
        "name": "Sprint 14",
        "optimal": 140.0,
        "team-increment": 8.0
    },
    {
        "client-increment": 0,
        "evolution": 141.0,
        "name": "Sprint 15",
        "optimal": 120.0,
        "team-increment": 8.0
    },
    {
        "client-increment": 0,
        "evolution": 108.5,
        "name": "Sprint 16",
        "optimal": 100.0,
        "team-increment": 8.0
    },
    {
        "client-increment": [
            0
        ],
        "evolution": 89.5,
        "name": "Future sprint",
        "optimal": 80.0,
        "team-increment": [
            8.0
        ]
    }
]
```

```
},
{
  "client-increment": [
    0
  ],
  "evolution": null,
  "name": "Future sprint",
  "optimal": 60.0,
  "team-increment": [
    8.0
  ]
},
{
  "client-increment": [
    0
  ],
  "evolution": null,
  "name": "Future sprint",
  "optimal": 40.0,
  "team-increment": [
    8.0
  ]
},
{
  "client-increment": [
    0
  ],
  "evolution": null,
  "name": "Future sprint",
  "optimal": 20.0,
  "team-increment": [
    8.0
  ]
},
{
  "client-increment": [
    0
  ],
  "evolution": null,
  "name": "Project End",
  "optimal": 0.0,
  "team-increment": [
    8.0
  ]
}
],
{
  "name": "Taiga",
  "speed": 20.7,
```

```
        "total_milestones": 20,  
        "total_points": 400.0  
    }
```

41.5. Project issue stats detail

```
{  
    "closed_issues": 560,  
    "issues_per_assigned_to": {  
        "0": {  
            "color": "black",  
            "count": 185,  
            "id": 0,  
            "name": "Unassigned",  
            "username": "Unassigned"  
        },  
        "111": {  
            "color": "#6427c0",  
            "count": 2,  
            "id": 111,  
            "name": "Juan de la Cruz Garcia",  
            "username": "juan.delacruz"  
        },  
        "13": {  
            "color": "#CC0000",  
            "count": 100,  
            "id": 13,  
            "name": "Xavier Juli\u00f3n",  
            "username": "xavier.julian"  
        },  
        "2": {  
            "color": "#007000",  
            "count": 93,  
            "id": 2,  
            "name": "Jes\u00f3s Espino",  
            "username": "jesus.espino"  
        },  
        "24": {  
            "color": "#d9ff2f",  
            "count": 3,  
            "id": 24,  
            "name": "Enrique Posner",  
            "username": "eposner"  
        },  
        "38": {  
            "color": "#FF9900",  
            "count": 1,  
            "id": 38,  
            "name": "Jes\u00f3s Espino",  
            "username": "jesus.espino"  
        }  
    }  
}
```

```
"count": 8,
"id": 38,
"name": "Mario Garcia",
"username": "mario.garcia"
},
"5": {
"color": "#761CEC",
"count": 3,
"id": 5,
"name": "Pablo Ruiz M\u00f3fazquiz",
"username": "pablo.ruiz"
},
"6": {
"color": "#40826D",
"count": 85,
"id": 6,
"name": "Juanfran",
"username": "juanfran.alcantara"
},
"7": {
"color": "#FC8EAC",
"count": 76,
"id": 7,
"name": "Alejandro Alonso",
"username": "alejandro.alonso"
},
"8": {
"color": "#A5694F",
"count": 16,
"id": 8,
"name": "Andrey Antukh",
"username": "andrei.antoukh"
},
"9": {
"color": "#FFF8E7",
"count": 97,
"id": 9,
"name": "David Barrag\u00e1n Merino",
"username": "david.barragan"
}
},
"issues_per_owner": {
"11": {
"color": "#8f0030",
"count": 1,
"id": 11,
"name": "Anler Hern\u00e1ndez Peral",
"username": "anler.hernandez"
}
}
```

```
},
"111": {
  "color": "#6427c0",
  "count": 1,
  "id": 111,
  "name": "Juan de la Cruz Garcia",
  "username": "juan.delacruz"
},
"13": {
  "color": "#CC0000",
  "count": 64,
  "id": 13,
  "name": "Xavier Juli\u00f3n",
  "username": "xavier.julian"
},
"17": {
  "color": "#FFFF00",
  "count": 6,
  "id": 17,
  "name": "Alonso Torres",
  "username": "alonso.torres"
},
"18": {
  "color": "#C0FF33",
  "count": 14,
  "id": 18,
  "name": "Miguel de la Cruz",
  "username": "miguel.delacruz"
},
"19": {
  "color": "#67CF00",
  "count": 7,
  "id": 19,
  "name": "Antonio de la Torre",
  "username": "antonio.delatorre"
},
"2": {
  "color": "#007000",
  "count": 50,
  "id": 2,
  "name": "Jes\u00f3s Espino",
  "username": "jesus.espino"
},
"24": {
  "color": "#d9ff2f",
  "count": 135,
  "id": 24,
  "name": "Enrique Posner",
```

```
        "username": "eposner"
    },
    "3": {
        "color": "#4B0082",
        "count": 80,
        "id": 3,
        "name": "Iv\u00e1n López",
        "username": "ivan.lopez"
    },
    "38": {
        "color": "#FF9900",
        "count": 6,
        "id": 38,
        "name": "Mario García",
        "username": "mario.garcia"
    },
    "4": {
        "color": "#708090",
        "count": 13,
        "id": 4,
        "name": "Pablo Alba",
        "username": "pablo.alba"
    },
    "5": {
        "color": "#761CEC",
        "count": 16,
        "id": 5,
        "name": "Pablo Ruiz M\u00f3niz",
        "username": "pablo.ruiz"
    },
    "6": {
        "color": "#40826D",
        "count": 20,
        "id": 6,
        "name": "Juanfran",
        "username": "juanfran.alcantara"
    },
    "7": {
        "color": "#FC8EAC",
        "count": 106,
        "id": 7,
        "name": "Alejandro Alonso",
        "username": "alejandro.alonso"
    },
    "8": {
        "color": "#A5694F",
        "count": 11,
        "id": 8,
        "name": "Jesús Martínez",
        "username": "jesus.martinez"
    }
}
```

```
        "name": "Andrey Antukh",
        "username": "andrei.antoukh"
    },
    "9": {
        "color": "#FFF8E7",
        "count": 138,
        "id": 9,
        "name": "David Barrag\u00e1n Merino",
        "username": "david.barragan"
    }
},
"issues_per_priority": {
    "1": {
        "color": "#888a85",
        "count": 50,
        "id": 1,
        "name": "Low"
    },
    "2": {
        "color": "#4e9a06",
        "count": 397,
        "id": 2,
        "name": "Normal"
    },
    "3": {
        "color": "#a40000",
        "count": 221,
        "id": 3,
        "name": "High"
    }
},
"issues_per_severity": {
    "1": {
        "color": "#888a85",
        "count": 9,
        "id": 1,
        "name": "Wishlist"
    },
    "2": {
        "color": "#4e9a06",
        "count": 21,
        "id": 2,
        "name": "Minor"
    },
    "3": {
        "color": "#204a87",
        "count": 464,
        "id": 3,
        "name": "Major"
    }
}
```

```
        "name": "Normal"
    },
    "4": {
        "color": "#ce5c00",
        "count": 118,
        "id": 4,
        "name": "Important"
    },
    "5": {
        "color": "#a40000",
        "count": 56,
        "id": 5,
        "name": "Critical"
    }
},
"issues_per_status": {
    "1": {
        "color": "#8C2318",
        "count": 90,
        "id": 1,
        "name": "New"
    },
    "2": {
        "color": "#5E8C6A",
        "count": 7,
        "id": 2,
        "name": "In progress"
    },
    "3": {
        "color": "#88A65E",
        "count": 370,
        "id": 3,
        "name": "Ready for test"
    },
    "4": {
        "color": "#BFB35A",
        "count": 89,
        "id": 4,
        "name": "Closed"
    },
    "5": {
        "color": "#89BAB4",
        "count": 2,
        "id": 5,
        "name": "Needs Info"
    },
    "6": {
        "color": "#CC0000",
        "count": 1
    }
}
```

```
    "count": 101,
    "id": 6,
    "name": "Rejected"
},
"7": {
    "color": "#666666",
    "count": 9,
    "id": 7,
    "name": "Postponed"
}
},
"issues_per_type": {
    "1": {
        "color": "#f57900",
        "count": 501,
        "id": 1,
        "name": "Bug"
    },
    "6": {
        "color": "#4e9a06",
        "count": 167,
        "id": 6,
        "name": "Enhancement"
    }
},
"last_four_weeks_days": {
    "by_open_closed": {
        "closed": [
            8,
            3,
            2,
            0,
            0,
            4,
            5,
            2,
            3,
            3,
            0,
            0,
            2,
            4,
            4,
            10,
            6,
            0,
            0,
            12,
        ]
    }
}
```

```
0,  
4,  
5,  
5,  
0,  
0,  
0,  
0  
],  
"open": [  
7,  
3,  
2,  
0,  
0,  
4,  
9,  
8,  
1,  
1,  
3,  
0,  
5,  
4,  
5,  
17,  
4,  
6,  
0,  
9,  
6,  
10,  
9,  
10,  
0,  
0,  
0,  
0  
]  
},  
"by_priority": {  
"1": {  
"color": "#888a85",  
"data": [  
18,  
17,  
17,  
17,
```

```
17,  
17,  
17,  
17,  
17,  
17,  
17,  
17,  
17,  
17,  
18,  
18,  
19,  
18,  
18,  
18,  
18,  
18,  
19,  
22,  
22,  
22,  
22,  
22,  
22,  
22  
],  
"id": 1,  
"name": "Low"  
},  
"2": {  
"color": "#4e9a06",  
"data": [  
33,  
30,  
28,  
27,  
27,  
29,  
28,  
28,  
28,  
27,  
27,  
27,  
30,  
32,  
32,  
38,  
36,
```

```
  39,
  39,
  43,
  43,
  49,
  49,
  58,
  55,
  55,
  55,
  55
],
"id": 2,
"name": "Normal"
},
"3": {
  "color": "#a40000",
  "data": [
    23,
    22,
    23,
    22,
    22,
    24,
    30,
    33,
    32,
    31,
    31,
    31,
    33,
    33,
    33,
    33,
    40,
    35,
    33,
    33,
    38,
    32,
    35,
    37,
    33,
    31,
    31,
    31,
    31
  ],
  "id": 3,
```

```
        "name": "High"
    }
},
"by_severity": {
    "1": {
        "color": "#888a85",
        "data": [
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8,
            8
        ],
        "id": 1,
        "name": "Wishlist"
    },
    "2": {
        "color": "#4e9a06",
        "data": [
            6,
            3,
            3,
            3,
            3,
            3,
            3
        ]
    }
}
```

```
  3,  
  2,  
  2,  
  2,  
  2,  
  2,  
  2,  
  2,  
  3,  
  3,  
  3,  
  3,  
  3,  
  3,  
  3,  
  3,  
  4,  
  4,  
  4,  
  4,  
  4,  
  4,  
  4,  
  4  
],  
"id": 2,  
"name": "Minor"  
},  
"3": {  
  "color": "#204a87",  
  "data": [  
    52,  
    51,  
    48,  
    46,  
    46,  
    48,  
    48,  
    51,  
    51,  
    52,  
    52,  
    52,  
    55,  
    56,  
    54,  
    61,  
    59,  
    63,  
    63,  
    63,
```

```
    66,  
    63,  
    70,  
    74,  
    82,  
    79,  
    79,  
    79,  
    79  
  ],  
  "id": 3,  
  "name": "Normal"  
},  
"4": {  
  "color": "#ce5c00",  
  "data": [  
    7,  
    7,  
    8,  
    8,  
    8,  
    10,  
    13,  
    14,  
    13,  
    11,  
    10,  
    10,  
    12,  
    12,  
    13,  
    16,  
    12,  
    10,  
    10,  
    11,  
    14,  
    16,  
    16,  
    15,  
    14,  
    14,  
    14,  
    14  
  ],  
  "id": 4,  
  "name": "Important"  
},
```

```

    "5": {
      "color": "#a40000",
      "data": [
        1,
        0,
        1,
        1,
        1,
        1,
        1,
        3,
        3,
        3,
        2,
        3,
        3,
        3,
        3,
        4,
        5,
        8,
        8,
        6,
        6,
        11,
        5,
        5,
        6,
        4,
        3,
        3,
        3,
        3,
        3
      ],
      "id": 5,
      "name": "Critical"
    },
    "by_status": {}
  },
  "opened_issues": 108,
  "total_issues": 668
}

```

41.6. Project issue filters data detail

```

{
  "assigned_to": [

```

```
[ 10, 0 ], [ 6, 85 ], [ 3, 0 ], [ 15, 0 ], [ 1, 0 ], [ 7, 76 ], [ 19, 0 ], [ 17, 0 ], [ 8, 16 ], [ 24, 3 ], [ 25, 0 ], [ 9, 97 ], [
```

```
[  
  13,  
  100  
,  
 [  
  5,  
  3  
,  
 [  
  null,  
  185  
,  
 [  
  16,  
  0  
,  
 [  
  12623,  
  0  
,  
 [  
  111,  
  2  
,  
 [  
  38,  
  8  
,  
 [  
  4,  
  0  
,  
 [  
  18,  
  0  
,  
 [  
  2,  
  93  
,  
 [  
  11,  
  0  
,  
 [  
  26,  
  0  
]
```

```
],
"created_by": [
  [
    12623,
    0
  ],
  [
    10,
    0
  ],
  [
    7,
    106
  ],
  [
    11,
    1
  ],
  [
    13,
    64
  ],
  [
    24,
    135
  ],
  [
    26,
    0
  ],
  [
    16,
    0
  ],
  [
    4,
    13
  ],
  [
    18,
    14
  ],
  [
    6,
    20
  ],
  [
    3,
    0
  ]
]
```

```
  80
  ],
  [
    19,
    7
  ],
  [
    15,
    0
  ],
  [
    17,
    6
  ],
  [
    1,
    0
  ],
  [
    2,
    50
  ],
  [
    9,
    138
  ],
  [
    25,
    0
  ],
  [
    38,
    6
  ],
  [
    8,
    11
  ],
  [
    111,
    1
  ],
  [
    5,
    16
  ]
],
"owners": [
```

```
[ 12623,  
 0 ],  
[ 10,  
 0 ],  
[ 7,  
 106 ],  
[ 11,  
 1 ],  
[ 13,  
 64 ],  
[ 24,  
 135 ],  
[ 26,  
 0 ],  
[ 16,  
 0 ],  
[ 4,  
 13 ],  
[ 18,  
 14 ],  
[ 6,  
 20 ],  
[ 3,  
 80 ],
```

```
        ],
        19,
        7
    ],
    [
        15,
        0
    ],
    [
        17,
        6
    ],
    [
        1,
        0
    ],
    [
        2,
        50
    ],
    [
        9,
        138
    ],
    [
        25,
        0
    ],
    [
        38,
        6
    ],
    [
        8,
        11
    ],
    [
        111,
        1
    ],
    [
        5,
        16
    ]
],
"priorities": [
    [
        1,
```

```
  50
  ],
  [
    2,
    397
  ],
  [
    3,
    221
  ]
],
"severities": [
  [
    1,
    9
  ],
  [
    2,
    21
  ],
  [
    3,
    464
  ],
  [
    4,
    118
  ],
  [
    5,
    56
  ]
],
"statuses": [
  [
    1,
    90
  ],
  [
    2,
    7
  ],
  [
    3,
    370
  ],
  [
    4,
    1
  ]
]
```



```
[  
  "comments",  
  1  
,  
  [  
    "create",  
    1  
,  
    [  
      "design",  
      5  
,  
      [  
        "dise\u00f1o",  
        14  
,  
        [  
          "drag & drop",  
          1  
,  
          [  
            "edition",  
            2  
,  
            [  
              "email",  
              2  
,  
              [  
                "feedback",  
                41  
,  
                [  
                  "filters",  
                  2  
,  
                  [  
                    "font",  
                    3  
,  
                    [  
                      "form",  
                      1  
,  
                      [  
                        "forms",  
                        1  
,  
                        [  
                          ]  
                        ]  
                      ]  
                    ]  
                  ]  
                ]  
              ]  
            ]  
          ]  
        ]  
      ]  
    ]  
  ]  
]
```

```
[  "front", 72 ], [  "frontend", 1 ], [  "historico", 1 ], [  "home", 1 ], [  "hover", 1 ], [  "images", 1 ], [  "issues", 7 ], [  "kamban", 1 ], [  "kan", 1 ], [  "kanban", 5 ], [  "landing", 14 ], [  "layout", 1 ], ]
```

```
[  "lightbox", 3 ], [  "loading", 1 ], [  "login", 1 ], [  "logo", 2 ], [  "manage members", 1 ], [  "markdown", 2 ], [  "member", 1 ], [  "migraci\u00f3n redmine", 9 ], [  "notifications", 2 ], [  "ordering", 1 ], [  "paginacion", 1 ], [  "performance", 1 ], ]
```

```
[  
  "points",  
  1  
,  
  [  
    "register",  
    1  
,  
    [  
      "responsive",  
      1  
,  
      [  
        "spinner",  
        1  
,  
        [  
          "sprint",  
          1  
,  
          [  
            "style",  
            1  
,  
            [  
              "svg",  
              1  
,  
              [  
                "tags",  
                1  
,  
                [  
                  "taiga-web",  
                  1  
,  
                  [  
                    "task",  
                    1  
,  
                    [  
                      "taskboard",  
                      4  
,  
                      [  
                        "tasks",  
                        1  
,  
                        [  
                          ]  
                        ]  
                      ]  
                    ]  
                  ]  
                ]  
              ]  
            ]  
          ]  
        ]  
      ]  
    ]  
  ]  
]
```

```
[
  "title",
  1
],
[
  "us",
  3
],
[
  "user-settings",
  2
],
[
  "uss",
  1
],
[
  "ux",
  23
],
[
  "web",
  1
],
[
  "wiki",
  5
]
],
"types": [
  [
    1,
    501
  ],
  [
    6,
    167
  ]
]
}
```

41.7. Project tag colors data detail

```
{
  "667": "#74da61",
  "Back": "#b52b36",
```

"Backlog": "#1fe3af",
"Documentaci\u00f3n": "#60f92f",
"Taskboard": "#066725",
"activity": "#ce5c00",
"admin": "#d033e2",
"análisis": "#ac1d8e",
"analytics": "#66d9b5",
"api": "#a033a5",
"appearin": "#d3d7cf",
"attachment": "#ad7fa8",
"attachments": "#05cb34",
"back": "#73d216",
"backend": "#754a08",
"backlog": "#fce94f",
"block": "#0214b4",
"blog": "#169254",
"checksley": "#9d4cd6",
"coffeescript": "#4e9a06",
"comments": "#5b17a6",
"controllers": "#3465a4",
"create": "#2e3436",
"design": "#056f11",
"directive": "#3d981b",
"dise\u00f1o": "#65b784",
"doc": "#f7f029",
"documentaci\u00f3n": "#c4a000",
"drag & drop": "#4557ef",
"edition": "#194562",
"email": "#a88b7d",
"favicon": "#2ba3a0",
"feedback": "#ef15f4",
"filters": "#9ce5ff",
"font": "#464257",
"form": "#d00b39",
"forms": "#453ca9",
"front": "#a40000",
"front-refactor": "#edd400",
"frontend": "#9ecc84",
"general": "#75507b",
"graph": "#29a184",
"graphs": "#ef2929",
"histórico": "#59f4b6",
"history": "#66f79d",
"home": "#e83249",
"hover": "#fbc588",
"i18n": "#61d28b",
"icono": "#4b1726",
"images": "#19f49d",

```
"issue": "#f57900",
"issues": "#fcaf3e",
"kamban": "#9296c7",
"kan": "#6769db",
"kanban": "#4073e8",
"kk": "#2ed451",
"landing": "#b95618",
"layout": "#207b87",
"license": "#234571",
"lightbox": "#97a2af",
"loading": "#14b85f",
"login": "#2736fa",
"logo": "#5807dd",
"manage members": "#4ed477",
"markdown": "#90320b",
"member": "#6467ba",
"migraci\u00f3n redmine": "#eacd33",
"model": "#1d06a0",
"newsletter": "#755df5",
"notifications": "#1b60d2",
"ordering": "#428ac4",
"orm": "#e14417",
"paginacion": "#c17776",
"performance": "#476ee0",
"permisos": "#729fcf",
"points": "#819f41",
"questions": "#cc0000",
"refactor": "#90b816",
"register": "#13a282",
"relationship": "#6a73a9",
"responsive": "#786745",
"retrospectiva": "#6d4244",
"roles": "#037c88",
"spinner": "#6be317",
"sprint": "#b9f866",
"stats": "#e350d5",
"style": "#26ec8d",
"subida de ficheros": "#4c0568",
"summary": "#05535e",
"svg": "#8feba6",
"tags": "#9b6ef5",
"taiga reporting": "#1dae9d",
"taiga-web": "#12b429",
"task": "#7fbb72",
"taskboard": "#0f4b15",
"tasks": "#55d872",
"test": "#5c3566",
"text": "#372ea0",
```

```
"title": "#3c6de1",
"us": "#888a85",
"user-settings": "#c44e5a",
"uss": "#219112",
"ux": "#796384",
"ux/dise\u00f1o pendiente": "#94dfcb",
"videoconferencia": "#8ae234",
"web": "#ca84d1",
"wiki": "#204a87"
}
```

41.8. Project voter detail

```
{
  "full_name": "Silvia Soto",
  "id": 2,
  "username": "user6532909695705815086"
}
```

41.9. Project watcher detail

```
{
  "full_name": "Silvia Soto",
  "id": 2,
  "username": "user6532909695705815086"
}
```

41.10. Project template detail

```
{
  "created_date": "2014-11-11T09:58:35+0000",
  "default_options": {
    "issue_status": "New",
    "issue_type": "Bug",
    "points": "?",
    "priority": "Normal",
    "severity": "Normal",
    "task_status": "New",
    "us_status": "New"
  },
  "default_owner_role": "ux",
  "description": "Beta template description",
  "name": "Beta template"
}
```

```
"id": 3,
"is_backlog_activated": true,
"is_issues_activated": true,
"is_kanban_activated": false,
"is_wiki_activated": true,
"issue_statuses": [
  {
    "color": "#8C2318",
    "is_closed": false,
    "name": "New",
    "order": 1
  },
  {
    "color": "#5E8C6A",
    "is_closed": false,
    "name": "In progress",
    "order": 2
  },
  {
    "color": "#88A65E",
    "is_closed": true,
    "name": "Ready for test",
    "order": 3
  },
  {
    "color": "#BFB35A",
    "is_closed": true,
    "name": "Closed",
    "order": 4
  },
  {
    "color": "#89BAB4",
    "is_closed": false,
    "name": "Needs Info",
    "order": 5
  },
  {
    "color": "#CC0000",
    "is_closed": true,
    "name": "Rejected",
    "order": 6
  },
  {
    "color": "#666666",
    "is_closed": false,
    "name": "Postponed",
    "order": 7
  }
]
```

```
],
"issue_types": [
  {
    "color": "#89BAB4",
    "name": "Bug",
    "order": 1
  },
  {
    "color": "#ba89a8",
    "name": "Question",
    "order": 2
  },
  {
    "color": "#89a8ba",
    "name": "Enhancement",
    "order": 3
  }
],
"modified_date": "2014-11-11T09:58:35+0000",
"name": "Beta template",
"points": [
  {
    "name": "?",
    "order": 1,
    "value": null
  },
  {
    "name": "0",
    "order": 2,
    "value": 0.0
  },
  {
    "name": "1/2",
    "order": 3,
    "value": 0.5
  },
  {
    "name": "1",
    "order": 4,
    "value": 1.0
  },
  {
    "name": "2",
    "order": 5,
    "value": 2.0
  },
  {
    "name": "3",
    "order": 6,
    "value": 3.0
  }
]
```

```
        "order": 6,
        "value": 3.0
    },
    {
        "name": "5",
        "order": 7,
        "value": 5.0
    },
    {
        "name": "8",
        "order": 8,
        "value": 8.0
    },
    {
        "name": "10",
        "order": 9,
        "value": 10.0
    },
    {
        "name": "15",
        "order": 10,
        "value": 15.0
    },
    {
        "name": "20",
        "order": 11,
        "value": 20.0
    },
    {
        "name": "40",
        "order": 12,
        "value": 40.0
    }
],
"priorities": [
    {
        "color": "#666666",
        "name": "Low",
        "order": 1
    },
    {
        "color": "#669933",
        "name": "Normal",
        "order": 3
    },
    {
        "color": "#CC0000",
        "name": "High",
        "order": 5
    }
]
```

```
        "order": 5
    }
],
"roles": [
{
    "computable": true,
    "name": "UX",
    "order": 10,
    "permissions": [
        "add_issue",
        "modify_issue",
        "delete_issue",
        "view_issues",
        "add_milestone",
        "modify_milestone",
        "delete_milestone",
        "view_milestones",
        "view_project",
        "add_task",
        "modify_task",
        "delete_task",
        "view_tasks",
        "add_us",
        "modify_us",
        "delete_us",
        "view_us",
        "add_wiki_page",
        "modify_wiki_page",
        "delete_wiki_page",
        "view_wiki_pages",
        "add_wiki_link",
        "delete_wiki_link",
        "view_wiki_links"
    ],
    "slug": "ux"
},
{
    "computable": true,
    "name": "Design",
    "order": 20,
    "permissions": [
        "add_issue",
        "modify_issue",
        "delete_issue",
        "view_issues",
        "add_milestone",
        "modify_milestone",
        "delete_milestone",
        "view_milestones"
    ]
}]]
```

```
        "view_milestones",
        "view_project",
        "add_task",
        "modify_task",
        "delete_task",
        "view_tasks",
        "add_us",
        "modify_us",
        "delete_us",
        "view_us",
        "add_wiki_page",
        "modify_wiki_page",
        "delete_wiki_page",
        "view_wiki_pages",
        "add_wiki_link",
        "delete_wiki_link",
        "view_wiki_links"
    ],
    "slug": "design"
},
{
    "computable": true,
    "name": "Front",
    "order": 30,
    "permissions": [
        "add_issue",
        "modify_issue",
        "delete_issue",
        "view_issues",
        "add_milestone",
        "modify_milestone",
        "delete_milestone",
        "view_milestones",
        "view_project",
        "add_task",
        "modify_task",
        "delete_task",
        "view_tasks",
        "add_us",
        "modify_us",
        "delete_us",
        "view_us",
        "add_wiki_page",
        "modify_wiki_page",
        "delete_wiki_page",
        "view_wiki_pages",
        "add_wiki_link",
        "delete_wiki_link",
        "view_wiki_links"
    ]
}
```

```
        "view_wiki_links"
    ],
    "slug": "front"
},
{
    "computable": true,
    "name": "Back",
    "order": 40,
    "permissions": [
        "add_issue",
        "modify_issue",
        "delete_issue",
        "view_issues",
        "add_milestone",
        "modify_milestone",
        "delete_milestone",
        "view_milestones",
        "view_project",
        "add_task",
        "modify_task",
        "delete_task",
        "view_tasks",
        "add_us",
        "modify_us",
        "delete_us",
        "view_us",
        "add_wiki_page",
        "modify_wiki_page",
        "delete_wiki_page",
        "view_wiki_pages",
        "add_wiki_link",
        "delete_wiki_link",
        "view_wiki_links"
    ],
    "slug": "back"
},
{
    "computable": false,
    "name": "Product Owner",
    "order": 50,
    "permissions": [
        "add_issue",
        "modify_issue",
        "delete_issue",
        "view_issues",
        "add_milestone",
        "modify_milestone",
        "delete_milestone",
        "view_milestones"
    ]
}
```

```
        "view_milestones",
        "view_project",
        "add_task",
        "modify_task",
        "delete_task",
        "view_tasks",
        "add_us",
        "modify_us",
        "delete_us",
        "view_us",
        "add_wiki_page",
        "modify_wiki_page",
        "delete_wiki_page",
        "view_wiki_pages",
        "add_wiki_link",
        "delete_wiki_link",
        "view_wiki_links"
    ],
    "slug": "product-owner"
},
{
    "computable": false,
    "name": "Stakeholder",
    "order": 60,
    "permissions": [
        "add_issue",
        "modify_issue",
        "delete_issue",
        "view_issues",
        "view_milestones",
        "view_project",
        "view_tasks",
        "view_us",
        "modify_wiki_page",
        "view_wiki_pages",
        "add_wiki_link",
        "delete_wiki_link",
        "view_wiki_links"
    ],
    "slug": "stakeholder"
}
],
"severities": [
{
    "color": "#666666",
    "name": "Wishlist",
    "order": 1
},
```

```
{  
  "color": "#669933",  
  "name": "Minor",  
  "order": 2  
},  
{  
  "color": "#0000FF",  
  "name": "Normal",  
  "order": 3  
},  
{  
  "color": "#FFA500",  
  "name": "Important",  
  "order": 4  
},  
{  
  "color": "#CC0000",  
  "name": "Critical",  
  "order": 5  
}  
],  
"slug": "beta-template",  
"task_statuses": [  
  {  
    "color": "#999999",  

```

```
        "color": "#999999",
        "is_closed": false,
        "name": "Needs Info",
        "order": 5
    }
],
"us_statuses": [
{
    "color": "#999999",
    "is_closed": false,
    "name": "New",
    "order": 1,
    "wip_limit": null
},
{
    "color": "#ff8a84",
    "is_closed": false,
    "name": "Ready",
    "order": 2,
    "wip_limit": null
},
{
    "color": "#ff9900",
    "is_closed": false,
    "name": "In progress",
    "order": 3,
    "wip_limit": null
},
{
    "color": "#fcc000",
    "is_closed": false,
    "name": "Ready for test",
    "order": 4,
    "wip_limit": null
},
{
    "color": "#669900",
    "is_closed": true,
    "name": "Done",
    "order": 5,
    "wip_limit": null
}
],
"videoconferences": null,
"videoconferences_extra_data": null
}
```

41.11. Membership detail

```
{  
  "role_name": "Front",  
  "full_name": "Alicia Diaz",  
  "user_email": "accusamus@doloribus.net",  
  "email": "accusamus@doloribus.net",  
  "color": "#C0FF33",  
  "photo": "//www.gravatar.com/avatar/e2cc11c9138524224f87aa72c1a343db?size=80",  
  "project_name": "Project Example 0",  
  "project_slug": "user6532909695705815086-project-example-0",  
  "invited_by": null,  
  "id": 7,  
  "user": 8,  
  "project": 1,  
  "role": 3,  
  "is_admin": true,  
  "created_at": "2014-11-17T16:19:04+0000",  
  "invitation_extra_text": null  
}
```

41.12. Milestone detail

```
{  
  "is_watcher": false,  
  "total_watchers": 0,  
  "user_stories": [...],  
  "total_points": 172.5,  
  "closed_points": 57.0,  
  "client_increment_points": 0,  
  "team_increment_points": 0,  
  "id": 1,  
  "name": "Sprint 2015-8-7",  
  "slug": "sprint-2015-8-7",  
  "owner": 7,  
  "project": 1,  
  "estimated_start": "2015-08-07",  
  "estimated_finish": "2015-08-22",  
  "created_date": "2015-08-07T09:52:54+0000",  
  "modified_date": "2015-10-01T09:52:54+0000",  
  "closed": false,  
  "disponibility": 0.0,  
  "order": 10  
}
```

41.13. Milestone watcher detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.14. Milestone stats detail

```
{
  "name": "Sprint 1",
  "estimated_start": "2014-10-20",
  "estimated_finish": "2014-10-21",
  "total_points": {
    "11": 10,
    "12": 40,
    "13": 30,
    "14": 20
  },
  "completed_points": 40,
  "total_userstories": 10,
  "completed_userstories": 4,
  "total_tasks": 40,
  "completed_tasks": 12,
  "iocaine_doses": 3,
  "days": [
    {
      "day": "2014-10-20",
      "name": "21",
      "open_points": 100,
      "optimal_points": 50
    },
    {
      "day": "2014-10-21",
      "name": "21"
      "open_points": 60,
      "optimal_points": 0
    }
  ]
}
```

41.15. User story detail

```
{
  "is_voter": true,
  "total_voters": 2,
  "is_watcher": false,
  "total_watchers": 1,
  "watchers": [
    12
  ],
  "tags": [
    "officiis",
    "est",
    "est"
  ]
}
```

```

    "expedita"
],
"external_reference": null,
"points": {
    "2": 7,
    "3": 10,
    "4": 7,
    "1": 8
},
"total_points": 31.0,
"comment": "",
"milestone_slug": "sprint-2015-8-7",
"milestone_name": "Sprint 2015-8-7",
"origin_issue": null,
"blocked_note_html": "",
"description_html": "<p>Cum explicabo esse quis impedit earum dolore, voluptatibus atque provident vel, impedit mollitia eius debitis saepe veritatis praesentium recusandae rem consequuntur alias, recusandae architecto blanditiis odit nihil enim dolores? Ab rem totam et delectus blanditiis, numquam iusto accusamus blanditiis tempore asperiores odit dolor voluptatibus officiis perferendis sunt, tempora nihil nobis quo, dolores porro ducimus sapiente aperiam nesciunt exercitationem nam hic et deserunt saepe, et officia modi laboriosam reiciendis placeat quisquam nostrum eum? Iste corrupti repellat, nam voluptates architecto, in fugiat tempora, ex similique neque voluptatibus?</p>",
"status_extra_info": {
    "name": "Ready",
    "color": "#ff8a84"
},
"assigned_to_extra_info": {
    "username": "user8",
    "full_name_display": "Lourdes Aguilar",
    "photo": "//www.gravatar.com/avatar/dce0e8ed702cd85d5132e523121e619b?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "big_photo": "//www.gravatar.com/avatar/dce0e8ed702cd85d5132e523121e619b?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=300",
    "is_active": true
},
"owner_extra_info": {
    "username": "user2",
    "full_name_display": "Sofia Ramirez",
    "photo": "//www.gravatar.com/avatar/5c921c7bd676b7b4992501005d243c42?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "big_photo": "//www.gravatar.com/avatar/5c921c7bd676b7b4992501005d243c42?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=300",
    "is_active": true
}

```

```

},
"id": 1,
"version": 1,
"is_blocked": false,
"blocked_note": "",
"ref": 1,
"milestone": 1,
"project": 1,
"owner": 8,
"status": 2,
"is_closed": false,
"backlog_order": 10000,
"sprint_order": 10000,
"kanban_order": 10000,
"created_date": "2015-10-01T09:52:54+0000",
"modified_date": "2015-10-01T09:52:54+0000",
"finish_date": null,
"subject": "Create the html template",
"description": "Cum explicabo esse quis impedit earum dolore, voluptatibus atque  

provident vel, impedit mollitia eius debitis saepe veritatis praesentium recusandae rem  

consequuntur alias, recusandae architecto blanditiis odit nihil enim dolores? Ab rem  

totam et delectus blanditiis, numquam iusto accusamus blanditiis tempore asperiores odit  

dolor voluptatibus officiis perferendis sunt, tempora nihil nobis quo, dolores porro  

ducimus sapiente aperiam nesciunt exercitationem nam hic et deserunt saepe, et officia  

modi laboriosam reiciendis placeat quisquam nostrum eum? Iste corrupti repellat, nam  

voluptates architecto, in fugiat tempora, ex similique neque voluptatibus?",  

"assigned_to": 14,
"client_requirement": false,
"team_requirement": false,
"generated_from_issue": null,
"neighbors": {
  "next": {
    "id": 2,
    "ref": 7,
    "subject": "get_actions() does not check for 'delete_selected' in actions"
  },
  "previous": {}
}
}

```

NOTE | status_extra_info and assigned_to_extra_info are read only fields

41.16. User story detail (GET)

```
{
```

```
"assigned_to": 19,
"backlog_order": 2,
"blocked_note": "",
"blocked_note_html": "",
"client_requirement": false,
"comment": "",
"created_date": "2014-07-29T07:15:50+0000",
"description": "Implement API CALL",
"description_html": "<p>Implement API CALL</p>",
"finish_date": "2014-09-16T17:17:16+0000",
"generated_from_issue": null,
"id": 1149,
"is_blocked": false,
"is_closed": true,
"kanban_order": 37,
"milestone": 98,
"milestone_name": "Sprint 03",
"milestone_slug": "sprint-03",
"modified_date": "2014-10-10T12:07:13+0000",
"origin_issue": null,
"owner": 19,
"points": {
    "129": 361,
    "130": 361,
    "131": 361,
    "132": 364
},
"project": 31,
"ref": 31,
"sprint_order": 2,
"status": 83,
"subject": "Customer personal data",
"tags": [
    "service catalog",
    "customer"
],
"team_requirement": false,
"total_points": 1.0,
"version": 8,
"watchers": [],
"neighbors": {
    "previous": {
        "id": 10969,
        "ref": 1286,
        "subject": "US/Task/Issue Visualization and edition refactor"
    },
    "next": {
        "id": 9085,
        "ref": 1287,
        "subject": "US/Task/Issue Visualization and edition refactor"
    }
}
```

```

        "ref": 1212,
        "subject": "Limit sizes"
    }
},
"status_extra_info": {
    "name": "In progress",
    "color": "#5E8C6A"
},
"assigned_to_extra_info": {
    "username": "beta.tester",
    "full_name_display": "Beta testing",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
    "big_photo":
"//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80"
}
}
}

```

NOTE neighbors, status_extra_info and assigned_to_extra_info are read only fields

41.17. User story detail (LIST)

```

{
    "assigned_to": 19,
    "backlog_order": 2,
    "blocked_note": "",
    "blocked_note_html": "",
    "client_requirement": false,
    "comment": "",
    "created_date": "2014-07-29T07:15:50+0000",
    "finish_date": "2014-09-16T17:17:16+0000",
    "generated_from_issue": null,
    "id": 1149,
    "is_blocked": false,
    "is_closed": true,
    "kanban_order": 37,
    "milestone": 98,
    "milestone_name": "Sprint 03",
    "milestone_slug": "sprint-03",
    "modified_date": "2014-10-10T12:07:13+0000",
    "origin_issue": null,
    "owner": 19,
    "points": {
        "129": 361,
        "130": 361,
        "131": 361,
    }
}

```

```

    "132": 364
},
"project": 31,
"ref": 31,
"sprint_order": 2,
"status": 83,
"subject": "Customer personal data",
"tags": [
    "service catalog",
    "customer"
],
"team_requirement": false,
"total_points": 1.0,
"version": 8,
"watchers": [],
"status_extra_info": {
    "name": "In progress",
    "color": "#5E8C6A"
},
"assigned_to_extra_info": {
    "username": "beta.tester",
    "full_name_display": "Beta testing",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
    "big_photo":
    "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80"
}
}

```

NOTE | status_extra_info and assigned_to_extra_info are read only fields

41.18. User story voter detail

```
{
  "full_name": "Silvia Soto",
  "id": 2,
  "username": "user6532909695705815086"
}
```

41.19. User story watcher detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.20. User story status detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "is_archived": true,  
  "is_closed": false,  
  "name": "Open",  
  "order": 1,  
  "project": 40,  
  "wip_limit": null  
}
```

41.21. Point detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "name": "Huge",  
  "order": 8,  
  "value": 40,  
  "project": 3  
}
```

41.22. User story custom attribute detail

```
{  
  "id": 1,  
  "name": "Duration",  
  "description": "Duration in minutes",  
  "order": 1,  
  "project": 1  
}
```

41.23. User story custom attributes values detail

```
{  
  "user_story": 1,  
  "attributes_values": {  
    "1": "240 minutes"  
  },  
  "version": 2  
}
```

41.24. Task detail

```
{  
  "is_voter": false,  
  "total_voters": 3,  
  "is_watcher": false,  
  "total_watchers": 1,  
  "watchers": [  
    6  
  ],  
  "tags": [  
    "porro",  
    "placeat"  
  ],  
  "external_reference": null,  
  "comment": "",  
  "milestone_slug": "sprint-2015-8-7",  
  "blocked_note_html": "",  
  "description_html": "<p>Nostrum consequatur quasi odio, pariatur modi id distinctio  
sequi. Voluptatibus illo ratione eius necessitatibus ad quibusdam nulla reiciendis  
laborum doloribus, nostrum repudiandae asperiores eveniet libero consequuntur expedita  
velit accusantium a commodi blanditiis? Quaerat ipsum pariatur nulla maiores harum ipsa  
eveniet, vel omnis culpa quisquam nulla, minus iste ad modi aliquid inventore ab iusto  
optio tempora hic voluptas?</p>",  
  "is_closed": false,  
  "status_extra_info": {  
    "name": "Needs Info",  
    "color": "#999999"  
  },  
  "assigned_to_extra_info": {  
    "username": "user2",  
    "full_name_display": "Sofia Ramirez",  
    "photo":  
      "://www.gravatar.com/avatar/5c921c7bd676b7b4992501005d243c42?default=https%3A%2F%2Fstatic.
```

```
taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "big_photo": "http://www.gravatar.com/avatar/5c921c7bd676b7b4992501005d243c42?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=300",
    "is_active": true
},
"owner_extra_info": {
    "username": "user3",
    "full_name_display": "Concepcion Garrido",
    "photo": "http://www.gravatar.com/avatar/9971a763f5dfc5cbd1ce1d2865b4fcfa?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
    "big_photo": "http://www.gravatar.com/avatar/9971a763f5dfc5cbd1ce1d2865b4fcfa?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=300",
    "is_active": true
},
"id": 1,
"version": 1,
"is_blocked": false,
"blocked_note": "",
"user_story": 1,
"ref": 2,
"owner": 9,
"status": 5,
"project": 1,
"milestone": 1,
"created_date": "2015-10-01T09:52:54+0000",
"modified_date": "2015-10-01T09:52:55+0000",
"finished_date": "2015-08-16T15:54:13+0000",
"subject": "Create testsuite with matrix builds",
"us_order": 1,
"taskboard_order": 1,
"description": "Nostrum consequatur quasi odio, pariatur modi id distinctio sequi. Voluptatibus illo ratione eius necessitatibus ad quibusdam nulla reiciendis laborum doloribus, nostrum repudiandae asperiores eveniet libero consequuntur expedita velit accusantium a commodi blanditiis? Quaerat ipsum pariatur nulla maiores harum ipsa eveniet, vel omnis culpa quisquam nulla, minus iste ad modi aliquid inventore ab iusto optio tempora hic voluptas?",
"assigned_to": 8,
"is_iocaine": false,
"neighbors": {
    "next": {
        "id": 2,
        "ref": 3,
        "subject": "Lighttpd support"
    },
    "previous": {}
}
```

```
    }  
}
```

NOTE | status_extra_info and assigned_to_extra_info are read only fields

41.25. Task detail (GET)

```
{  
  "assigned_to": 19,  
  "blocked_note": "",  
  "blocked_note_html": "",  
  "comment": "",  
  "milestone_slug": "sprint-2014-11-1",  
  "created_date": "2014-07-29T07:15:50+0000",  
  "description": "Implement API CALL",  
  "description_html": "<p>Implement API CALL</p>",  
  "id": 1149,  
  "is_blocked": false,  
  "is_closed": true,  
  "milestone": 98,  
  "modified_date": "2014-10-10T12:07:13+0000",  
  "finished_date": null,  
  "is_voted": true,  
  "is_watched": true,  
  "owner": 19,  
  "project": 31,  
  "user_story": 17,  
  "ref": 31,  
  "status": 83,  
  "subject": "Customer personal data",  
  "tags": [  
    "service catalog",  
    "customer"  
,  
  "us_order": 1,  
  "taskboard_order": 1,  
  "version": 8,  
  "is_iocaine": false,  
  "external_reference": null,  
  "voters": 1,  
  "watchers": [],  
  "neighbors": {  
    "previous": {  
      "id": 57,  
      "ref": 74,  
    }  
  }  
}
```

```
        "subject": "get_actions() does not check for 'delete_selected' in actions"
    },
    "next": {
        "id": 59,
        "ref": 77,
        "subject": "Feature/improved image admin"
    }
},
"status_extra_info": {
    "name": "In progress",
    "color": "#5E8C6A"
},
"assigned_to_extra_info": {
    "username": "beta.tester",
    "full_name_display": "Beta testing",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80",
    "big_photo":
    "//www.gravatar.com/avatar/4648b6d514c3ecece1b87136ceeda1d1?size=80"
}
}
```

NOTE neighbors, us_extra_info and assigned_to_extra_info are read only fields

41.26. Task detail (LIST)

```
{
  "assigned_to": 19,
  "blocked_note": "",
  "blocked_note_html": "",
  "comment": "",
  "milestone_slug": "sprint-2014-11-1",
  "created_date": "2014-07-29T07:15:50+0000",
  "id": 1149,
  "is_blocked": false,
  "is_closed": true,
  "milestone": 98,
  "modified_date": "2014-10-10T12:07:13+0000",
  "finished_date": null,
  "owner": 19,
  "project": 31,
  "user_story": 17,
  "ref": 31,
  "status": 83,
  "subject": "Customer personal data",
  "tags": [
    "service catalog",
    "customer"
  ],
  "us_order": 1,
  "taskboard_order": 1,
  "version": 8,
  "is_iocaine": false,
  "external_reference": null,
  "watchers": [],
  "status_extra_info": {
    "name": "In progress",
    "color": "#5E8C6A"
  },
  "assigned_to_extra_info": {
    "username": "beta.tester",
    "full_name_display": "Beta testing",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
    "big_photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80"
  }
}
```

NOTE | status_extra_info and assigned_to_extra_info are read only fields

41.27. Task voter detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.28. Task watcher detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.29. Project voter detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.30. Project watcher detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.31. Task status detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "is_closed": false,  
  "name": "Open",  
  "order": 1,  
  "project": 40  
}
```

41.32. Task custom attribute detail

```
{  
  "id": 1,  
  "name": "Duration",  
  "description": "Duration in minutes",  
  "order": 1,  
  "project": 1  
}
```

41.33. Task custom attributes values detail

```
{  
  "task": 1,  
  "attributes_values": {  
    "1": "240 minutes"  
  },  
  "version": 2  
}
```

41.34. Issue detail

```
        "dolores",
        "eum",
        "amet"
    ],
    "external_reference": null,
    "is_closed": false,
    "comment": "",
    "generated_user_stories": [],
    "blocked_note_html": "",
    "description_html": "<p>Modi numquam esse qui sequi porro optio tenetur assumenda temporibus consequatur ad, aspernatur veniam perferendis quia asperiores dolorem nihil impedit, libero aperiam quis, perspiciatis soluta quis iste? Id quo assumenda distinctio? Cupiditate corporis distinctio placeat dolor commodi delectus eum recusandae, non autem maiores saepe quia cum quasi nisi, a accusantium laudantium nihil eum adipisci aut voluptas debitis enim. Voluptatum voluptas saepe perferendis, a similique saepe sint iure numquam sed voluptas aliquam, laboriosam voluptate sequi?</p>",
    "status_extra_info": {
        "name": "Needs Info",
        "color": "#89BAB4"
    },
    "assigned_to_extra_info": {
        "username": "user1",
        "full_name_display": "Purificacion Montero",
        "photo": "https://www.gravatar.com/avatar/aed1e43be0f69f07ce6f34a907bc6328?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
        "big_photo": "https://www.gravatar.com/avatar/aed1e43be0f69f07ce6f34a907bc6328?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=300",
        "is_active": true
    },
    "owner_extra_info": {
        "username": "user2",
        "full_name_display": "Sofia Ramirez",
        "photo": "https://www.gravatar.com/avatar/5c921c7bd676b7b4992501005d243c42?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
        "big_photo": "https://www.gravatar.com/avatar/5c921c7bd676b7b4992501005d243c42?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=300",
        "is_active": true
    },
    "id": 1,
    "version": 1,
    "is_blocked": false,
    "blocked_note": "",
    "ref": 43,
    "owner": 8,
```

```

"status": 5,
"severity": 3,
"priority": 3,
"type": 3,
"milestone": null,
"project": 1,
"created_date": "2015-10-01T09:53:06+0000",
"modified_date": "2015-10-01T09:53:07+0000",
"finished_date": null,
"subject": "Migrate to Python 3 and milk a beautiful cow",
"description": "Modi numquam esse qui sequi porro optio tenetur assumenda temporibus  
consequatur ad, aspernatur veniam preferendis quia asperiores dolorem nihil impedit,  
libero aperiam quis, perspiciatis soluta quis iste? Id quo assumenda distinctio?  
Cupiditate corporis distinctio placeat dolor commodi delectus eum recusandae, non autem  
maiores saepe quia cum quasi nisi, a accusantium laudantium nihil eum adipisci aut  
voluptas debit is enim. Voluptatum voluptas saepe preferendis, a simili que sint iure  
numquam sed voluptas aliquam, laboriosam voluptate sequi?",  
"assigned_to": 7,  
"neighbors": {  
    "next": {  
        "id": 35,  
        "ref": 83,  
        "subject": "Lighttpd support"  
    },  
    "previous": {  
        "id": 2,  
        "ref": 44,  
        "subject": "Lighttpd support"  
    }  
}  
}

```

NOTE status_extra_info and assigned_to_extra_info are read only fields

41.35. Issue detail (GET)

```
{
    "assigned_to": 19,
    "blocked_note": "",
    "blocked_note_html": "",
    "comment": "",
    "created_date": "2014-07-29T07:15:50+0000",
    "description": "Implement API CALL",
    "description_html": "<p>Implement API CALL</p>",
    "finish_date": "2014-09-16T17:17:16+0000",
    "id": 19,
    "label": "Implement API CALL"
}
```

```
"id": 1149,
"is_blocked": false,
"is_closed": true,
"milestone": 98,
"modified_date": "2014-10-10T12:07:13+0000",
"finished_date": null,
"is_voted": true,
"is_watched": true,
"owner": 19,
"project": 31,
"ref": 31,
"status": 83,
"severity": 2,
"priority": 3,
"type": 1,
"subject": "Customer personal data",
"tags": [
    "service catalog",
    "customer"
],
"version": 8,
"voters": 1,
"watchers": [
    7
],
"generated_user_stories": [
],
"votes": null,
"neighbors": {
    "next": {
        "id": 16,
        "ref": 126,
        "subject": "Support for bulk actions"
    },
    "previous": {}
},
"status_extra_info": {
    "name": "In progress",
    "color": "#5E8C6A"
},
"assigned_to_extra_info": {
    "username": "beta.tester",
    "full_name_display": "Beta testing",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
    "big_photo":
        "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80"
}
}
```

NOTE

neighbors, status_extra_info and assigned_to_extra_info are read only fields

41.36. Issue detail (LIST)

```
{
  "assigned_to": 19,
  "blocked_note": "",
  "blocked_note_html": "",
  "comment": "",
  "created_date": "2014-07-29T07:15:50+0000",
  "finish_date": "2014-09-16T17:17:16+0000",
  "id": 1149,
  "is_blocked": false,
  "is_closed": true,
  "milestone": 98,
  "modified_date": "2014-10-10T12:07:13+0000",
  "finished_date": null,
  "owner": 19,
  "project": 31,
  "ref": 31,
  "status": 83,
  "severity": 2,
  "priority": 3,
  "type": 1,
  "subject": "Customer personal data",
  "tags": [
    "service catalog",
    "customer"
  ],
  "version": 8,
  "watchers": [],
  "generated_user_stories": [
  ],
  "votes": null,
  "status_extra_info": {
    "name": "In progress",
    "color": "#5E8C6A"
  },
  "assigned_to_extra_info": {
    "username": "beta.tester",
    "full_name_display": "Beta testing",
    "photo": "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80",
    "big_photo":
      "//www.gravatar.com/avatar/4648b6d514c3ece1b87136ceeda1d1?size=80"
  }
}
```

NOTE status_extra_info and assigned_to_extra_info are read only fields

41.37. Issue voters detail

```
[  
  {  
    "id": 1,  
    "username": "user-1",  
    "full_name": "John Doe"  
  },  
  {  
    "id": 2,  
    "username": "user-2",  
    "full_name": "User 2"  
  }  
]
```

41.38. Issue watchers detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.39. Issue status detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "is_closed": false,  
  "name": "Open",  
  "order": 1,  
  "project": 40  
}
```

41.40. Issue type detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "name": "Enhancement",  
  "order": 1,  
  "project": 40  
}
```

41.41. Priority detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "name": "High",  
  "order": 1,  
  "project": 40  
}
```

41.42. Severity detail

```
{  
  "color": "#669933",  
  "id": 143,  
  "name": "Important",  
  "order": 1,  
  "project": 40  
}
```

41.43. Issue custom attribute detail

```
{  
  "id": 1,  
  "name": "Duration",  
  "description": "Duration in minutes",  
  "order": 1,  
  "project": 1  
}
```

41.44. Issue custom attributes values detail

```
{  
  "issue": 1,  
  "attributes_values": {  
    "1": "240 minutes"  
  },  
  "version": 2  
}
```

41.45. Wiki page

```
{  
  "is_watcher": true,  
  "total_watchers": 1,  
  "html": "<p>Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.</p>\n<p>Facilis molestias nulla est harum saepe maiores quisquam, adipisci voluptas debitibus, expedita aspernatur architecto obcaecati blanditiis, quae et delectus exercitationem pariatur minus modi debitibus placeat? Suscipit corrupti architecto eos provident quibusdam autem?</p>\n<p>Accusamus modi nesciunt nobis sapiente voluptate non et, non necessitatibus nobis est qui nam hic a quidem rerum? Nisi quia sit distinctio provident voluptatem dolores accusantium numquam, eos voluptatum distinctio cupiditate quisquam aspernatur itaque, consequatur suscipit aut tenetur eius amet error est corporis fuga, porro neque omnis ad tenetur fugit perspiciatis consequatur sit placeat, delectus non repudiandae inventore. Reprehenderit enim preferendis adipisci molestiae nobis error totam facilis excepturi, obcaecati pariatur itaque eius adipisci facilis saepe tempora unde, debitibus neque eaque laborum voluptates voluptas culpa, enim debitibus nemo at pariatur iure inventore saepe? Ipsam asperiores itaque blanditiis voluptas ipsa ipsum nesciunt vero quod eius exercitationem, asperiores repudiandae placeat cum hic accusamus preferendis blanditiis expedita quia eum nostrum, obcaecati sint eius totam eum veritatis dolorem fugiat?</p>\n<p>Fuga rem adipisci, provident labore quae nobis earum, at nemo aliquid aperiam autem libero laborum sit dolore dignissimos vel sunt, vitae aliquam exercitationem vero recusandae mollitia quod, ratione ducimus quas nesciunt recusandae?</p>\n<p>Voluptate temporibus vero, facilis doloribus nobis, atque ipsum accusantium beatae quas velit ut quisquam suscipit amet. Totam dolorum iusto obcaecati earum porro sunt nisi amet ipsam deserunt, nemo officia fugit sit neque ipsum assumenda eaque maxime quasi harum, repudiandae dicta aut autem accusamus doloribus ab, beatae necessitatibus at quasi quod tempora. Esse doloribus amet rem iusto, id quaerat vel voluptates quae corrupti enim? Dolorum quod excepturi itaque ratione aut iste placeat animi repellat quae?</p>","
```

```

"editions": 2,
"id": 1,
"version": 1,
"project": 1,
"slug": "home",
"content": "Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.\n\nFacilis molestias nulla est harum saepe maiores quisquam, adipisci voluptas debitibus, expedita aspernatur architecto obcaecati blanditiis, quae et delectus exercitationem pariatur minus modi debitibus placeat? Suscipit corrupti architecto eos provident quibusdam autem?\n\nAccusamus modi nesciunt nobis sapiente voluptate non et, non necessitatibus nobis est qui nam hic a quidem rerum? Nisi quia sit distinctio provident voluptatem dolores accusantium numquam, eos voluptatum distinctio cupiditate quisquam aspernatur itaque, consequatur suscipit aut tenetur eius amet error est corporis fuga, porro neque omnis ad tenetur fugit perspiciatis consequatur sit placeat, delectus non repudiandae inventore. Reprehenderit enim perferendis adipisci molestiae nobis error totam facilis excepturi, obcaecati pariatur itaque eius adipisci facilis saepe tempora unde, debitibus neque eaque laborum voluptates voluptas culpa, enim debitibus nemo at pariatur iure inventore saepe? Ipsam asperiores itaque blanditiis voluptas ipsa ipsum nesciunt vero quod eius exercitationem, asperiores repudiandae placeat cum hic accusamus perferendis blanditiis expedita quia eum nostrum, obcaecati sint eius totam eum veritatis dolorem fugiat?\n\nFuga rem adipisci, provident labore quae nobis earum, at nemo aliquid aperiam autem libero laborum sit dolore dignissimos vel sunt, vitae aliquam exercitationem vero recusandae mollitia quod, ratione ducimus quas nesciunt recusandae?\n\nVoluptate temporibus vero, facilis doloribus nobis, atque ipsum accusantium beatae quas velit ut quisquam suscipit amet. Totam dolorum iusto obcaecati earum porro sunt nisi amet ipsam deserunt, nemo officia fugit sit neque ipsum assumenda eaque maxime quasi harum, repudiandae dicta aut autem accusamus doloribus ab, beatae necessitatibus at quasi quod tempora. Esse doloribus amet rem iusto, id quaerat vel voluptates quae corrupti enim? Dolorum quod excepturi itaque ratione aut iste placeat animi repellat quae?",

"owner": 13,
"last_modifier": null,
"created_date": "2015-10-01T09:53:12+0000",
"modified_date": "2015-10-01T09:53:12+0000"
}

```

41.46. Wiki page watcher detail

```
{  
  "full_name": "Silvia Soto",  
  "id": 2,  
  "username": "user6532909695705815086"  
}
```

41.47. Wiki link

```
{  
  "id": 1,  
  "project": 2,  
  "title": "Test title",  
  "href": "test",  
  "order": 1  
}
```

41.48. History entry

```
{  
  "diff": {  
    "team_requirement": [  
      false,  
      true  
    ],  
    "finish_date": [  
      "None",  
      "2014-11-17 16:19:04.411139+00:00"  
    ],  
    "is_closed": [  
      false,  
      true  
    ]  
  },  
  "snapshot": null,  
  "values": {},  
  "values_diff": {  
    "team_requirement": [  
      false,  
      true  
    ],  
    "finish_date": [  
      "None",  
      "2014-11-17 16:19:04.411139+00:00"  
    ]  
  }  
}
```

```

        ],
        "is_closed": [
            false,
            true
        ]
    },
    "user": {
        "pk": 2,
        "username": "admin",
        "name": "admin",
        "photo": "//www.gravatar.com/avatar/64e1b8d34f425d19e1ee2ea7236d3028?size=80",
        "is_active": true
    },
    "delete_comment_user": null,
    "id": "9660411e-6fea-11e4-a5b3-b499ba565108",
    "created_at": "2014-11-19T12:50:06+0000",
    "type": 1,
    "key": "userstories.userstory:1",
    "comment": "",
    "comment_html": "",
    "delete_comment_date": null,
    "is_hidden": false,
    "is_snapshot": false
}

```

41.49. Notify policy

```
{
    "id": 97,
    "notify_level": 1,
    "project": 3,
    "project_name": "Testing project"
}
```

41.50. Feedback

```
{
    "comment": "testing feedback",
    "created_date": "2014-11-17T15:10:54+0000",
    "email": "testing@taiga.io",
    "id": 71,
    "full_name": "betatester"
}
```

41.51. Export detail for synch mode

```
{  
  "url": "https://media.taiga.io/exports/21313/50f38116f1654076b130d1026f579fae.json"  
}
```

41.52. Export accepted response

```
{  
  "export_id": "e338555a-3918-4203-8fc6-81b3f7933c79"  
}
```

41.53. Import accepted response

```
{  
  "import_id": "e338555a-3918-4203-8fc6-81b3f7933c79"  
}
```

41.54. Webhook

```
{  
  "logs_counter": 6,  
  "id": 1,  
  "project": 1,  
  "name": "webhook",  
  "url": "http://localhost:8080/test",  
  "key": "123"  
}
```

41.55. Webhook log

```
{
  "request_data": {... payload data ...},
  "request_headers": {
    "Content-Length": "1573",
    "X-TAIGA-WEBHOOK-SIGNATURE": "32b30381523eda3df76854e84865467574fcc085"
  },
  "response_headers": {
    "Content-Type": "text/html; charset=UTF-8",
    "Content-Length": "2",
    "Server": "WSGIServer/0.2 CPython/3.4.2",
    "Date": "Thu, 22 Jan 2015 10:43:56 GMT"
  },
  "id": 159,
  "webhook": 1,
  "url": "http://localhost:8080/test",
  "status": 200,
  "response_data": "OK",
  "duration": 0.002326,
  "created": "2015-01-22T10:43:56+0000"
}
```

41.56. Timeline entry detail

```
{
  "data": {
    "comment_html": "<p>Hic cum voluptatibus et quaerat suscipit incident, quasi enim porro corrupti, accusantium accusamus quam odit deserunt ducimus, atque libero inventore fuga numquam aspernatur dolorem pariatur fugiat cumque quas ad? Incidunt rem ut dolore quidem sequi non neque esse quos sunt ea, quisquam non officia quidem minima a est eaque dolorem esse impedit, minus deserunt repellendus. Quae dolores obcaecati iste voluptatum facilis delectus quod aperiam totam possimus eum, totam voluptas quis temporibus sint debitibus aliquid in quae nulla, aspernatur voluptate velit amet, incident recusandae repudiandae, culpa iure commodi corrupti modi excepturi? Omnis voluptas et assumenda, ex nostrum qui iste commodi adipisci laborum, quaerat quasi enim, corporis laborum aliquid eum.</p>",
    "values_diff": {
      "status": [
        "Rejected",
        "New"
      ]
    },
    "comment": "Hic cum voluptatibus et quaerat suscipit incident, quasi enim porro corrupti, accusantium accusamus quam odit deserunt ducimus, atque libero inventore fuga numquam aspernatur dolorem pariatur fugiat cumque quas ad? Incidunt rem ut dolore quidem sequi non neque esse quos sunt ea, quisquam non officia quidem minima a est eaque dolorem"
  }
}
```

esse impedit, minus deserunt repellendus. Quae dolores obcaecati iste voluptatum facilis delectus quod aperiam totam possimus eum, totam voluptas quis temporibus sint debitibus aliquid in quae nulla, aspernatur voluptate velit amet, incident recusandae repudiandae, culpa iure commodi corrupti modi excepturi? Omnis voluptas et assumenda, ex nostrum qui iste commodi adipisci laborum, quaerat quasi enim, corporis laborum aliquid eum.",

```

"user": {
  "id": 7,
  "photo": "//www.gravatar.com/avatar/aed1e43be0f69f07ce6f34a907bc6328?size=80&default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png",
  "big_photo": "//www.gravatar.com/avatar/aed1e43be0f69f07ce6f34a907bc6328?default=https%3A%2F%2Fstatic.taiga.io%2Fimg%2Fuser-noimage.png&size=80",
  "name": "Purificacion Montero",
  "username": "user1"
},
"project": {
  "description": "Project example 3 description",
  "id": 4,
  "slug": "user9-project-example-3",
  "name": "Project Example 3"
},
"issue": {
  "id": 83,
  "ref": 106,
  "subject": "Added file copying and processing of images (resizing)"
},
"id": 4336,
"content_type": 3,
"object_id": 7,
"namespace": "user:7",
"event_type": "issues.issue.change",
"project": 4,
"data_content_type": 39,
"created": "2015-04-16T06:57:21+0000"
}
}
```

41.57. Locale

```
{
  "name": "Español",
  "code": "es"
}
```

41.58. Watched

```
{  
  "type": "project",  
  "id": 6,  
  "ref": null,  
  "slug": "project-5",  
  "name": "Project Example 5",  
  "subject": null,  
  "description": "Project example 5 description",  
  "assigned_to": null,  
  "status": null,  
  "status_color": null,  
  "tags_colors": [],  
  "created_date": "2015-10-01T09:54:55+0000",  
  "is_private": true,  
  "logo_small_url": null,  
  "project": null,  
  "project_name": null,  
  "project_slug": null,  
  "project_is_private": null,  
  "assigned_to_username": null,  
  "assigned_to_full_name": null,  
  "assigned_to_photo": null,  
  "is_watcher": false,  
  "total_watchers": 2,  
  "is_fan": false,  
  "total_fans": 3  
}
```

NOTE

is_fan and total_fans only appear for results with type "project", for issues, tasks and user stories those attributes are replaced by is_voter and total_voters

41.59. Liked

```
{  
  "type": "project",  
  "id": 5,  
  "ref": null,  
  "slug": "project-4",  
  "name": "Project Example 4",  
  "subject": null,  
  "description": "Project example 4 description",  
  "assigned_to": null,  
  "status": null,  
  "status_color": null,  
  "tags_colors": [],  
  "created_date": "2015-10-01T09:54:55+0000",  
  "is_private": true,  
  "logo_small_url":  
    "http://localhost:8000/media/project/c/4/9/4/eb6354d601e95a7813a3394d0b0b656eefe684721c85  
    a01692143b381c23/1_imgr2__mg_6521.jpg.80x80_q85_crop.jpg",  
  "project": null,  
  "project_name": null,  
  "project_slug": null,  
  "project_is_private": null,  
  "assigned_to_username": null,  
  "assigned_to_full_name": null,  
  "assigned_to_photo": null,  
  "is_watcher": true,  
  "total_watchers": 14,  
  "is_fan": false,  
  "total_fans": 3  
}
```

41.60. Voted

```
{  
  "type": "userstory",  
  "id": 5,  
  "ref": null,  
  "slug": "project-4",  
  "name": "Project Example 4",  
  "subject": null,  
  "description": "Project example 4 description",  
  "assigned_to": null,  
  "status": null,  
  "status_color": null,  
  "tags_colors": [],  
  "created_date": "2015-10-01T09:54:55+0000",  
  "is_private": true,  
  "logo_small_url": null,  
  "project": null,  
  "project_name": null,  
  "project_slug": null,  
  "project_is_private": null,  
  "assigned_to_username": null,  
  "assigned_to_full_name": null,  
  "assigned_to_photo": null,  
  "is_watcher": true,  
  "total_watchers": 14,  
  "is_voter": false,  
  "total_voters": 3  
}
```

41.61. Discover stats

```
{  
  "projects": {  
    "total": 1028  
  }  
}
```

41.62. System stats

```
{  
  "users": {  
    "total": 94478,  
    "today": 131,  
    "average_last_seven_days": 334.7142857142857,  
  }
```

```
"average_last_five_working_days": 392.2,  
"counts_last_year_per_week": {  
    "2015-01-12": 20182,  
    "2015-01-19": 21356,  
    "2015-01-26": 22578,  
    "2015-02-02": 23877,  
    "2015-02-09": 24967,  
    "2015-02-16": 26192,  
    "2015-02-23": 27333,  
    "2015-03-02": 28437,  
    "2015-03-09": 29555,  
    "2015-03-16": 30935,  
    "2015-03-23": 32302,  
    "2015-03-30": 33416,  
    "2015-04-06": 34710,  
    "2015-04-13": 35927,  
    "2015-04-20": 37223,  
    "2015-04-27": 38300,  
    "2015-05-04": 39623,  
    "2015-05-11": 40947,  
    "2015-05-18": 42186,  
    "2015-05-25": 43312,  
    "2015-06-01": 44545,  
    "2015-06-08": 45692,  
    "2015-06-15": 47084,  
    "2015-06-22": 48357,  
    "2015-06-29": 49604,  
    "2015-07-06": 50918,  
    "2015-07-13": 52204,  
    "2015-07-20": 53435,  
    "2015-07-27": 54716,  
    "2015-08-03": 56058,  
    "2015-08-10": 57282,  
    "2015-08-17": 58618,  
    "2015-08-24": 60059,  
    "2015-08-31": 61728,  
    "2015-09-07": 63251,  
    "2015-09-14": 64743,  
    "2015-09-21": 66385,  
    "2015-09-28": 68062,  
    "2015-10-05": 69808,  
    "2015-10-12": 71387,  
    "2015-10-19": 73028,  
    "2015-10-26": 74543,  
    "2015-11-02": 76486,  
    "2015-11-09": 78334,  
    "2015-11-16": 80282,  
    "2015-11-23": 82208,  
}
```

```

        "2015-11-30": 84330,
        "2015-12-07": 86223,
        "2015-12-14": 88154,
        "2015-12-21": 89393,
        "2015-12-28": 90483,
        "2016-01-04": 92693,
        "2016-01-11": 94094
    }
},
"projects": {
    "total": 84547,
    "today": 115,
    "average_last_seven_days": 297.42857142857144,
    "average_last_five_working_days": 351.0,
    "total_with_backlog": 45516,
    "percent_with_backlog": 53.8351449489633,
    "total_with_kanban": 26903,
    "percent_with_kanban": 31.820171029131725,
    "total_with_backlog_and_kanban": 11735,
    "percent_with_backlog_and_kanban": 13.879853809123919
},
"userstories": {
    "total": 365414,
    "today": 891,
    "average_last_seven_days": 1794.4285714285713,
    "average_last_five_working_days": 2187.2
}
}

```

42. Contrib plugins

Taiga allows adding features through contrib plugins, each plugin can add new API endpoints, and has its own documentation.

Current supported contrib plugins that adding endpoints:

- taiga-contrib-slack: Slack integration ([documentation](#))
- taiga-contrib-hall: Hall.com integration ([documentation](#))