Basic Information Manufacturer Class Compact SUV Energy Type Engine Engine Class Compact SUV Maximum Power (kW) Digital Transmission Continuously Variable Transmission (CVT) with simulated continuously Variable quars Engine Body Structure Body Structure Body Maximum Speed (km/h) Body Body Length (mm) Body With (mm) Body With (mm) Body Height (mm) Body With (mm) Body With (mm) Body Height (mm) Body With (mm) Body Body With (mm) Body Body With (mm) Body Body With (mm) Body Body With (mm) Bo	Model	RAV4 Rongfang 2024 2.0L CVT Two-wheel
Manufacturer Class Compact SUV Energy Type Gasoline Engine 2.01 171 horsepower L4 Maximum Power (kW) 126(171Ps) Maximum Torque (N · m) 206 Engine Maximum Torque (N · m) 206 Transmission John Transmission Continuously Variable Transmission (CVT) with simulated continuously variable gears 4600×1855×1680 Body Structure 5-door 5-seat SUV Maximum Speed (km/h) 180 WLTC Combined Fuel Consumption (L/100km) 6.27 Body Body Length (mm) 4600 Body Width (mm) 1855 Body Height (mm) 1680 Wheelbase (mm) 2690 Front Track (mm) 1605 Rear Track (mm) 1605 Rear Track (mm) 1605 Roor Opening Method Side-hinged door Number of Door S Door Opening Method Side-hinged door Number of Seats 5 Curb Weight (kg) 1540 Gross Vehicle Weight (kg) 2115 Fuel Tank Capacity (L) 555 Luggage Compartment Volume (L) 580 Minimum Turning Radius 5.5m Engine Engine Model M20D Displacement (mL) 1987 Displacement (ML) 2 1987 Displacement (ML) 2 1987 Number of Valves per Cylinder 4 Compression Ratio 13 Valve Train DOHC Maximum Power (kW) 126 Maximum Power (kW) 126 Maximum Power (kW) 126 Maximum Power (kW) 126 Maximum Porque (N · m) 206 Maximum Torque (N · m) 206 Munication Toransission (CV	Model	Drive Urban Edition
Class Gasoline Energy Type Gasoline Engine 2.0L 171 horsepower L4 Maximum Power (kW) 126(171Ps) Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Continuously Variable Transmission (CVT) with simulated continuously variable qears Length x Width x Height (mm) 4600 x 185 x 1680 Body Structure 5-door 5-seat SUV Maximum Speed (km/h) 180 WLTC Combined Fuel Consumption (L/100km) 6.27 Body Body Length (mm) 4600 Body Width (mm) 1855 Body Height (mm) 1680 Wheelbase (mm) 2690 Front Track (mm) 1605 Rear Track (mm) 1605 Rear Track (mm) 1605 Roor Opening Method Side-hinged door Number of Seats 5 Curb Weight (kg) 1540 Gross Vehicle Weight (kg) 2115 Fuel Tank Capacity (L) 55 Luggage Compartment Volume (L) 380 Minimum Turning Radius 5.5m Engine Engine Engine Model M20D Displacement (mL) 1987 Displacement (mL) 1987 Displacement (ML) 1987 Displacement (ML) 1987 Number of Cylinders 4 Compression Ratio 13 Valve Train DOHC Maximum Horsepower (Ps) 171 Maximum Horsepower (Ps) 171 Maximum Power (kW) 126 Maximum Forque (N·m) 206 Maximum Torque Speed (rpm) 4600 Maximum Speed (rpm) 4600 Maximum Speed (rpm) 4600 Maximum Speed (rpm) 4600 Maximum		5000
Energy Type Engine Engine Engine Engine Engine Engine Engine 2.0.171 horsepower L4 Maximum Power (kW) 126(171Ps) Adaximum Torque (N · m) Engine Maximum Torque (N · m) Transmission Transmission Body Structure Maximum Speed (km/h) Body Structure Maximum Speed (km/h) Body Length (mm) Body Body Length (mm) Body Width (mm) Body Width (mm) Body Height (mm) Body Height (mm) Body Height (mm) Body Body Length (mm) Body Body Body Body Body Body Body Body		
Engine 2.0L 171 horsepower L4 Maximum Power (kW) 126(171Ps) Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Engine Maximum Torque (N·m) 206 Transmission Continuously Variable Transmission (CVT) with simulated continuously variable qears 4600×1855×1680 Body Structure 5-door 5-seat SUV Maximum Speed (km/h) 180 WLTC Combined Fuel Consumption (L/100km) 6.27 Body Body Length (mm) 4600 Body Width (mm) 1855 Body Height (mm) 1680 Wheelbase (mm) 2690 Front Track (mm) 1605 Rear Track (mm) 1605 Rear Track (mm) 1602 Number of Doors 5 Door Opening Method Side-hinged door Number of Seats 5 Curb Weight (kg) 1540 Gross Vehicle Weight (kg) 2115 Fuel Tank Capacity (L) 55 Luggage Compartment Volume (L) 580 Minimum Turning Radius 5.5m Engine Engine Engine Model M20D Displacement (mL) 1987 Displacement (L) 2 Intake Form Naturally aspirated Engine Layout Form Transversely mounted Cylinder Arnagement Form L Number of Cylinders 4 Number of Valves per Cylinder 4 Compression Ratio 13 Valve Train DOHC Maximum Power (kW) 126 Maximum Horsepower (Ps) 171 Maximum Horsepower (Ps) 171 Maximum Power (kW) 126 Maximum Torque Speed (rpm) 4600 Maximum Torque Speed (rpm) 4600 Maximum Torque Speed (rpm) Gasoline Fuel Grade Parsmission (CVT) with Simulated Continuously Variable Gears Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears		
Maximum Power (kW) 126(171Ps) Maximum Torque (N · m) 206 Engine Maximum Torque (N · m) 206 Transmission Continuously Variable Transmission (CVT) with simulated continuously variable gears Length x Width x Height (mm) 4600 x 1855 x 1680 Body Structure 5-door 5-seat SUV Maximum Speed (km/h) 180 WLTC Combined Fuel Consumption (L/100km) 6.27 Body Body Body Length (mm) 4600 Body Height (mm) 4680 Body Height (mm) 1680 Body Height (mm) 1680 Wheelbase (mm) 2690 Front Track (mm) 1605 Rear Track (mm) 1605 Rear Track (mm) 1605 Number of Doors 5 Door Opening Method Side-hinged door Number of Seats 5 Curb Weight (kg) 1540 Gross Vehicle Weight (kg) 2115 Fuel Tank Capacity (L) 55 Lugage Compartment Volume (L) 580 Minimum Turning Radius 5.		
Maximum Torque (N · m) 206		
Engine Maximum Torque (N · m) Transmission Continuously Variable Transmission (CVT) with simulated continuously variable gears Length × Width × Height (mm) Body Structure Maximum Speed (km/h) Body Body Length (mm) Body Body Length (mm) Body Height (mm) Body H	` ,	
Transmission Length × Width × Height (mm) Body Structure Maximum Speed (km/h) Body V Body Length (mm) Body WITC Combined Fuel Consumption (L/100km) Body WITC Combined Fuel Consumption (L/100km) Body Width (mm) Body Height (mm) Bodo Body Height (mm) Bodo Body Height (mm) Bodo Bodina Height (mm) Bodo Bodin		
Length × Width × Height (mm) Body Structure Body Structure Body Structure Body Structure Body Body Length (mm) Body Height (mm) Body Height (mm) Body Height (mm) Body Height (mm) Front Track (mm) Boor Opening Method Gross Vehicle Weight (kg) Fuel Tank Capacity (L) Lugage Compartment Volume (L) Brigine Engine Engine Layout Form Intake Form Number of Valves per Cylinder Awaimum Power (kw) Maximum Torque (N · m) Maximum Lardinal Form Transmission Environmental Protection Standard Transmission Number of Gears Simulated continuously variable gears 4600 1855 1850 5 - door 7 -		
Length × Width × Height (mm) S-door S-seat SUV	Transmission	* '
Body Structure Maximum Speed (km/h) WLTC Combined Fuel Consumption (L/100km) Body Body Length (mm) Body Length (mm) Body Width (mm) Body Height (km) Body	Length × Width × Height (mm)	4600×1855×1680
WLTC Combined Fuel Consumption (L/100km) Body Length (mm) 4600		5-door 5-seat SUV
Body Length (mm) 4600 Body Width (mm) 1855 Body Height (mm) 1680 Wheelbase (mm) 2690 Front Track (mm) 1605 Rear Track (mm) 1605 Rear Track (mm) 1620 Number of Doors 5 Door Opening Method Side-hinged door Number of Seats 5 Curb Weight (kg) 1540 Gross Vehicle Weight (kg) 2115 Fuel Tank Capacity (L) 55 Luggage Compartment Volume (L) 580 Minimum Turning Radius 5.5m Engine 161 Engine Model M20D Displacement (mL) 1987 Displacement (L) 2 1987 Displacement (L) 2 2 Intake Form Naturally aspirated Engine Layout Form Transversely mounted Cylinder Arrangement Form L Number of Valves per Cylinder Compression Ratio 13 Valve Train DOHC Maximum Horsepower (Ps) 171 Maximum Power (kW) 126 Maximum Torque (N·m) 206 Maximum Torque Speed (rpm) 4600 - 5000 Engine Specific Technology Fuel Form Gasoline Fuel Grade 92# Fuel Form Gasoline Fuel Form Gasoline Fuel Fuel Fuel Fuel Fuel Fuel Fuel Fuel		180
Body Length (mm) Body Width (mm) Body Height (mm) Body Body Body Body Body Body Body Body	WLTC Combined Fuel Consumption (L/100km)	6.27
Body Width (mm) Body Height (mm) Body Body Body Body Body Body Body Body	-	
Body Height (mm) 1680 Wheelbase (mm) 2690 Front Track (mm) 1605 Rear Track (mm) 1620 Number of Doors 5 Door Opening Method Side-hinged door Number of Seats 5 Curb Weight (kg) 1540 Gross Vehicle Weight (kg) 22115 Fuel Tank Capacity (L) 55 Luggage Compartment Volume (L) 580 Minimum Turning Radius 5.5m Engine Engine Model M20D Displacement (mL) 1987 Displacement (bL) 2 Intake Form Naturally aspirated Engine Layout Form Naturally aspirated Engine Layout Form Transversely mounted Cylinder Arrangement Form L Number of Valves per Cylinder 4 Compression Ratio 13 Valve Train DOHC Maximum Horsepower (Ps) 171 Maximum Horsepower (Ps) 171 Maximum Power Speed (rpm) 6600 Maximum Torque (N · m) 206 Maximum Foyer Speed (rpm) 4600 - 5000 Engine Specific Technology		
Wheelbase (mm) Front Track (mm) Rear Track (mm) Number of Doors Door Opening Method Side-hinged door Number of Seats Curb Weight (kg) Gross Vehicle Weight (kg) Fuel Tank Capacity (L) Lugage Compartment Volume (L) S80 Minimum Turning Radius Engine Engine Model Displacement (mL) Displacement (mL) Displacement (L) Cylinder Arrangement Form Number of Vglinders Number of Valves per Cylinder Compression Ratio Maximum Power (kW) Maximum Power (kW) Maximum Power (kW) Engine Specific Technology Fuel Form Fuel Grade Fuel Supply Method Cylinder Block Material Cylinder Block Material Environmental Protection Standard Number of Gears Number of Gears Continuously Variable Gears Continuously Variable		
Front Track (mm) Rear Track (m		
Rear Track (mm) Number of Doors Door Opening Method Number of Seats Curb Weight (kg) Fuel Tank Capacity (L) Fuel Tank Capacity (L) S5 Luggage Compartment Volume (L) Signinum Turning Radius Engine Engine Model M20D Displacement (mL) Displacement (L) Signine Layout Form Naturally aspirated Engine Layout Form Number of Valves per Cylinder Number of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque Speed (rpm) Maximum Torque Speed (rpm) Fuel Grade Fuel Supply Method Cylinder Block Material Cylinder Block Material Finit Gason Fuel Grade Fuel Grade Fuel Supply Method Cylinder Block Material Continuously Variable Gears Continuously Variable Gears Continuously Variable Gears Continuously Variable Continuously Variable Continuously Variable Continuously Variable Continuously Variable Continuously Variable	` ,	
Number of Doors Door Opening Method Side-hinged door Number of Seats Curb Weight (kg) Gross Vehicle Weight (kg) Fuel Tank Capacity (L) S55 Luggage Compartment Volume (L) Minimum Turning Radius Engine Engine Engine Engine Model Displacement (mL) Displacement (L) S1987 Displacement (L) S2 Intake Form Naturally aspirated Engine Layout Form Cylinder Arrangement Form Cylinder Arrangement Form Number of Cylinders Aumber of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power (kW) Maximum Torque (N · m) Fuel Grade Fuel Supply Method Cylinder Book Material Furion Potection Standard Furion Gasoline Fuel Grade Simulated Continuously Variable Gears Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable Gears		
Door Opening Method Number of Seats Curb Weight (kg) Gross Vehicle Weight (kg) Euglage Compartment Volume (L) Engine Engine Engine Engine Model Displacement (L) Intake Form Intake Form Number of Cylinders Avalve Train Maximum Horsepower (Ps) Maximum Horsepower (Pm) Maximum Torque Speed (rpm) Maximum Torque Speed (rpm) Fuel Grade Fuel Supply Method Cylinder Box Material Fuel Fornsersion Fuel Grade Fuel Supply Method Cylinder Box Material Engine Seed (roth output) For Displacement (L) Displacemen	, ,	
Number of Seats Curb Weight (kg) Gross Vehicle Weight (kg) Fuel Tank Capacity (L) Fuel Tank Capacity (L) S5 Luggage Compartment Volume (L) S80 Minimum Turning Radius Engine Engine Genine Model Displacement (mL) Displacement (mL) Displacement (L) Engine Layout Form Final Layout Form Transversely mounted Cylinder Arrangement Form Cylinder Arrangement Form Anumber of Cylinders Anumber of Valves per Cylinder Maximum Horsepower (Ps) Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N · m) Cylinder Speed (rpm) Fuel Grade Fuel		
Curb Weight (kg) Gross Vehicle Weight (kg) Fuel Tank Capacity (L) Luggage Compartment Volume (L) S80 Minimum Turning Radius Engine Engine Model Engine Model Displacement (LL) Intake Form Intake Form Sumber of Cylinder Arrangement Form Number of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power Speed (rpm) Maximum Torque (N · m) Engine Specific Technology Fuel Grade Fuel Grade Fuel Grade Full Grade Full Grade Full Tans Minimum Horse (L) S80 Maximum August Form Maximum Horsepower (Ps) Maximum Torque (N · m) Fuel Grade Fuel Form Gasoline Fuel Grade F		
Gross Vehicle Weight (kg) Fuel Tank Capacity (L) S5 Luggage Compartment Volume (L) Minimum Turning Radius Engine Engine Engine Engine Model Displacement (mL) Intake Form Engine Layout Form Cylinder Arrangement Form Number of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power Speed (rpm) Maximum Torque Speed (rpm) Fuel Grade Fuel Grade Fuel Grade Fuel Grade Fusive Luggage Compartment Volume (L) S80 Maximum Alloyable Sears Number of Mazinal Protection Standard Transmission Transmission Number of Gears Number of Gears Continuously Variable Gears Continuously Variable		
Fuel Tank Capacity (L) Luggage Compartment Volume (L) Minimum Turning Radius Engine Engine Engine Model Displacement (mL) Displacement (L) Intake Form Engine Layout Form Cylinder Arrangement Form Number of Cylinders Number of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque Speed (rpm) Engine Layout Form Maximum Fuel Grade Fuel Grade Fuel Grade Fuel Grade Transmission Transmission Number of Gears Continuously Variable Gears Number of Gears		
Luggage Compartment Volume (L) Minimum Turning Radius Engine Engine Engine Model Displacement (mL) Displacement (L) Intake Form Intake Form Cylinder Arrangement Form Number of Cylinders Aumber of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque Speed (rpm) Engine Layout Form Transversely mounted Teasource Alumin DOHC Maximum DOHC Maximum Power (Ps) 171 Maximum Power (Rw) 126 Maximum Power Speed (rpm) 6600 Maximum Torque (N · m) 206 Maximum Torque Speed (rpm) 4600 - 5000 Engine Specific Technology - Fuel Form Gasoline Fuel Grade 92# Fuel Supply Method Hybrid injection Cylinder Block Material Aluminum alloy Cylinder Block Material Aluminum alloy Cylinder Block Material Aluminum alloy Transmission Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		
Minimum Turning Radius Engine Engine Bengine Model M20D Displacement (mL) Displacement (l) Intake Form Intake Form Intake Form Engine Layout Form Cylinder Arrangement Form Anumber of Cylinders Anumber of Valves per Cylinder Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power (kW) Maximum Torque (N · m) Maximum Torque (N · m) Engine Specific Technology Fuel Form Fuel Grade Fuel Supply Method Cylinder Block Material Aluminum alloy Environmental Protection Standard Transmission Transmission Number of Gears Number of Gears M20D Naturally aspirated Aluminum Callo Maturally aspirated Aluminum Advantable Maturally aspirated Aluminum Bounted Maximum Torque (N · m) DOHC Maximum Fower (kW) 126 6600 Maximum Torque (N · m) DOHC Maximum Fower (kW) 126 Maximum Fower (kW) 126 Maximum Torque (N · m) DOHC Maximum Fower (kW) 126 Maximum Fower (kW) Aluminum alloy Aluminum alloy Aluminum alloy Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		
Engine Model M20D Displacement (mL) 1987 Displacement (L) 2 Intake Form Naturally aspirated Engine Layout Form Transversely mounted Cylinder Arrangement Form L Number of Cylinders 4 Compression Ratio 13 Valve Train DOHC Maximum Horsepower (Ps) 171 Maximum Power (kW) 126 Maximum Power Speed (rpm) 6600 Maximum Torque (N · m) 206 Maximum Torque Speed (rpm) 4600 - 5000 Engine Specific Technology - Fuel Form Gasoline Fuel Grade 92# Fuel Supply Method Hybrid injection Cylinder Block Material Aluminum alloy Cylinder Block Material Aluminum alloy Environmental Protection Standard Transmission Transmission Description Number of Gears Number of Gears Continuously Variable Gears Continuously Variable Gears		
Engine Model Displacement (mL) Displacement (L) Displace (L) Displacement (L) Displace		
Displacement (mL) Displacement (L) Intake Form Intake Form Engine Layout Form Sumber of Cylinders Number of Valves per Cylinder Compression Ratio Valve Train Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N ⋅ m) Engine Specific Technology Fuel Grade Fuel Supply Method Cylinder Block Material Transmission Pisson Number of Gears Number of Gears Number of Gears Naturally aspirated Naturally aspirated Naturally aspirated 12 Naturally aspirated Transwersely mounted 4 4 4 4 4 4 4 4 DOHC 4 4 6600 Maximum Torque (N ⋅ m) 206 Maximum Torque Speed (rpm) 4600 - 5000 Engine Specific Technology - Fuel Form Gasoline Fuel Supply Method Hybrid injection Aluminum alloy Cylinder Block Material Aluminum alloy Environmental Protection Standard Transmission Continuously Variable Transmission (CVT) with Simulated Continuously Variable	\mathcal{F}	M20D
Displacement (L) Intake Form Engine Layout Form Cylinder Arrangement Form Number of Cylinders Number of Valves per Cylinder Compression Ratio Valve Train Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N · m) Engine Specific Technology Fuel Grade Fuel Grade Fuel Grade Fuel Supply Method Cylinder Head Material Continuously Variable Continuously Variable Cylinder Heads Number of Gears Number of Gears Number of Gears		
Intake Form Engine Layout Form Cylinder Arrangement Form Number of Cylinders Number of Valves per Cylinder Compression Ratio Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N · m) Engine Specific Technology Fuel Grade Fuel Supply Method Cylinder Head Material Environmental Protection Standard Transmission Transmission Number of Gears Aluminum Transwersely mounted Transmission DOHC Advinum 13 13 DOHC 11 14 40 126 Maximum Power (kW) 126 6600 Maximum Torque (N · m) 206 Maximum Torque Speed (rpm) 4600 - 5000 Gasoline Gasoline Fuel Gasoline Fuel Supply Method Hybrid injection Aluminum alloy Aluminum alloy Cylinder Block Material Aluminum alloy Continuously Variable Transmission (CVT) with Simulated Continuously Variable		2
Cylinder Arrangement Form Number of Cylinders Number of Valves per Cylinder Compression Ratio Valve Train DOHC Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N · m) Engine Specific Technology Fuel Form Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Head Material Environmental Protection Standard Transmission Transmission Continuously Variable Gears Number of Gears L 4 4 4 4 4 4 4 4 4 4 4 4	Intake Form	Naturally aspirated
Number of Cylinders Number of Valves per Cylinder Compression Ratio 13 Valve Train DOHC Maximum Horsepower (Ps) Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N · m) Engine Specific Technology Fuel Form Fuel Form Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Block Material Environmental Protection Standard Transmission Transmission Transmission Description Number of Gears Aluminum sloy Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		Transversely mounted
Number of Valves per Cylinder Compression Ratio 13 Valve Train DOHC Maximum Horsepower (Ps) 171 Maximum Power (kW) 126 Maximum Power Speed (rpm) 6600 Maximum Torque (N · m) 206 Maximum Torque Speed (rpm) Engine Specific Technology Fuel Form Fuel Grade Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Block Material Aluminum alloy Cylinder Block Material Transmission Transmission Continuously Variable Transmission (CVT) with Simulated Continuously Variable Simulated Continuously Variable Continuously Variable		L
Compression Ratio13Valve TrainDOHCMaximum Horsepower (Ps)171Maximum Power (kW)126Maximum Power Speed (rpm)6600Maximum Torque (N · m)206Maximum Torque Speed (rpm)4600 - 5000Engine Specific Technology-Fuel FormGasolineFuel Grade92#Fuel Supply MethodHybrid injectionCylinder Head MaterialAluminum alloyCylinder Block MaterialAluminum alloyEnvironmental Protection StandardNational VITransmissionContinuously Variable Transmission (CVT) with Simulated Continuously Variable GearsNumber of GearsContinuously Variable		
Valve TrainDOHCMaximum Horsepower (Ps)171Maximum Power (kW)126Maximum Power Speed (rpm)6600Maximum Torque (N ⋅ m)206Maximum Torque Speed (rpm)4600 - 5000Engine Specific Technology-Fuel FormGasolineFuel Grade92#Fuel Supply MethodHybrid injectionCylinder Head MaterialAluminum alloyCylinder Block MaterialAluminum alloyEnvironmental Protection StandardNational VITransmissionContinuously Variable Transmission (CVT) with Simulated Continuously Variable GearsNumber of GearsContinuously Variable		
Maximum Horsepower (Ps)171Maximum Power (kW)126Maximum Power Speed (rpm)6600Maximum Torque (N · m)206Maximum Torque Speed (rpm)4600 - 5000Engine Specific Technology-Fuel FormGasolineFuel Grade92#Fuel Supply MethodHybrid injectionCylinder Head MaterialAluminum alloyCylinder Block MaterialAluminum alloyEnvironmental Protection StandardNational VITransmissionContinuously Variable Transmission (CVT) with Simulated Continuously VariableNumber of GearsContinuously Variable		
Maximum Power (kW) Maximum Power Speed (rpm) Maximum Torque (N · m) Engine Specific Technology Fuel Form Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Block Material Environmental Protection Standard Transmission Transmission Description Maximum Power (kW) 6600 A600 A600 A600 A600 A600 Gasoline Fuel Gasoline Fuel Supply Method Hybrid injection Aluminum alloy Aluminum alloy National VI Transmission Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		
Maximum Power Speed (rpm)6600Maximum Torque (N ⋅ m)206Maximum Torque Speed (rpm)4600 - 5000Engine Specific Technology-Fuel FormGasolineFuel Grade92#Fuel Supply MethodHybrid injectionCylinder Head MaterialAluminum alloyCylinder Block MaterialAluminum alloyEnvironmental Protection StandardNational VITransmissionContinuously Variable Transmission (CVT) with Simulated Continuously Variable GearsNumber of GearsContinuously Variable		
Maximum Torque (N ⋅ m)206Maximum Torque Speed (rpm)4600 - 5000Engine Specific Technology-Fuel FormGasolineFuel Grade92#Fuel Supply MethodHybrid injectionCylinder Head MaterialAluminum alloyCylinder Block MaterialAluminum alloyEnvironmental Protection StandardNational VITransmissionContinuously Variable Transmission (CVT) with Simulated Continuously Variable GearsNumber of GearsContinuously Variable	` ,	
Maximum Torque Speed (rpm) Engine Specific Technology Fuel Form Gasoline Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Block Material Environmental Protection Standard Transmission Transmission Transmission Number of Gears Aluminum alloy Aluminum alloy National VI Continuously Variable Transmission (CVT) with Simulated Continuously Variable		
Engine Specific Technology Fuel Form Gasoline Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Block Material Environmental Protection Standard Transmission Transmission Continuously Variable Transmission (CVT) with Simulated Continuously Variable Continuously Variable		
Fuel Form Fuel Grade Fuel Supply Method Cylinder Head Material Cylinder Block Material Environmental Protection Standard Transmission Transmission Number of Gears Gasoline 92# Hybrid injection Aluminum alloy Aluminum alloy National VI Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		4600 - 3000
Fuel Grade 92# Fuel Supply Method Hybrid injection Cylinder Head Material Aluminum alloy Cylinder Block Material Aluminum alloy Environmental Protection Standard National VI Transmission Transmission Description Transmission Description Number of Gears Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		Gasolino
Fuel Supply Method Cylinder Head Material Cylinder Block Material Environmental Protection Standard Transmission Transmission Transmission Description Number of Gears Hybrid injection Aluminum alloy National VI Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		
Cylinder Head Material Cylinder Block Material Aluminum alloy Aluminum alloy Environmental Protection Standard Transmission Transmission Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Number of Gears Continuously Variable		
Cylinder Block Material Aluminum alloy Environmental Protection Standard National VI Transmission Transmission Description Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Number of Gears Continuously Variable		
Environmental Protection Standard Transmission Transmission Description Number of Gears Environmental Protection Standard Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		1
Transmission Transmission Description Number of Gears Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		1
Transmission Description Number of Gears Continuously Variable Transmission (CVT) with Simulated Continuously Variable Gears Continuously Variable		
Number of Gears Simulated Continuously Variable Gears Continuously Variable		Continuously Variable Transmission (CVT) with
Number of Gears Continuously Variable	Transmission Description	
Transmission Type Continuously Variable Transmission (CVT)	Number of Gears	Continuously Variable
)	Transmission Type	Continuously Variable Transmission (CVT)

Cl. :	
Chassis	F + 1 15:
Drive Mode	Front - wheel Drive
Front Suspension Type	MacPherson Independent Suspension
Rear Suspension Type	Double - Wishbone Independent Suspension
Steering Type	Electric Power Assist
Vehicle Body Structure	Unibody
Wheels / Brakes	
Front Brake Type	Ventilated Disc
Rear Brake Type	Solid Disc
Parking Brake Type	Electric Parking Brake
Front Tire Specification	225/65 R17
Rear Tire Specification	225/65 R17
Spare Tire Specification	● Non - full - size
Spare Tire Placement Method	Hidden - type
Active Safety	
Anti - lock Braking System (ABS)	•
Brake Force Distribution (EBD/CBC, etc.)	•
Brake Assist (EBA/BA, etc.)	•
Traction Control (TCS/ASR, etc.)	•
Vehicle Stability System (ESP/DSC, etc.)	•
	Lane Departure Warning
Active Safety Warning System	Forward Collision Warning
Active Braking	•
Blind Spot Assist	-
Lane Keeping Assist System	•
Lane Centering Assist	•
Passive Safety	
Front Airbags	Driver's Seat
	Passenger's Seat
Side Airbags	Front Row
Side Curtain Airbags	•
Front Knee Airbags	Driver's Seat
Center Airbags	-
Seat Belt Unfastened Reminder	•
Tire Pressure Monitoring System	Tire Pressure Display
Child Seat Interface (ISOFIX)	•
Assistance / Control Configuration	
Driving Assistance Image	-
Cruise System	Constant - speed Cruise
	Adaptive Cruise
	'
	Full - speed Adaptive Cruise







