

RESEARCH ARTICLE

Do JML Specifications Help LLMs Write Better Unit Tests?Brendan Edmonds^{1*} Mark Utting¹¹UQ Cyber, School of Electrical Engineering and Computer Science, University of Queensland, St Lucia QLD 4067, Australia

*Correspondence: Brendan Edmonds, b.edmonds@uq.edu.au

Abstract

Large language models (LLMs) can generate unit tests from method signatures, but the resulting tests are weakened by the absence of an oracle. This article asks whether giving the model a *specification*—a precise statement of what the method should do—measurably improves the tests it produces, with quality assessed by mutation testing. The question is the primary one because inferred specifications have several downstream uses beyond LLM test generation: they strengthen test oracles, support compositional verification of calling code, and act as a machine-readable contract that AI coding agents can consume when interacting with libraries that postdate a model’s training cut-off. The question is answered through a controlled four-phase comparison on 312 methods from Apache Commons Lang, holding the model fixed (~~Gemini 2.0, temperature 0.3, five independent runs per configuration~~) and varying only the input: P1, method signature alone; P2, signature with edge-case guidance; P3, signature with an inferred specification; and P4, full source code as an upper-bound baseline. The answer is affirmative and the effect is large. Specifications raise test count by 272% (95% bootstrap CI [245, 299]) and mutation score by 40.7 percentage points relative to signatures alone ($p < 0.001$, Cohen’s $d = 2.41$, 95% bootstrap CI [2.08, 2.79]). The edge-case-prompted ~~phase~~Phase P2 generates the most tests but achieves a lower mutation score than P3, showing that test count is a poor proxy for oracle strength. Specifications also raise the compilation rate from 89.2% to 91.5% and the pass rate from 94.1% to 96.8%. Full source code (P4) attains the highest absolute mutation score (94.8%), but the specification phase closes about 60% of the signature-to-source gap in an order-of-magnitude smaller input. The specifications are produced automatically by JML-Inferer, a heuristic static analysis system developed alongside the experiment; it organises inference by weakest-precondition and strongest-postcondition reasoning, emits non-trivial specifications for 99.0% of methods in the corpus, and discharges 92.9% of inferred clauses through OpenJML’s Extended Static Checker. ~~The system attains 94.2%/89.3% precision/recall for preconditions and 87.6%/78.1% for postconditions under two-rater manual validation~~inference heuristics themselves were developed in a tight loop with an LLM-and-verifier probe workflow: hand-crafted or LLM-drafted candidate JML is verified with OpenJML, validated examples become probe tests, and an agentic coding assistant extends the inferer until those probes pass. A complete replication package accompanies the article.

Keywords: large language models, unit test generation, mutation testing, specification inference, JML, oracle problem

1 Introduction

Large language models (LLMs) have rapidly become a practical means of generating unit tests from source code [9, 10, 38, 48, 57], and an extensive recent literature has emerged around the technique [58]. Given

a method signature, a modern **model-LLM** produces compilable, plausibly named tests in seconds; given the source body, it produces tests that exercise visible control-flow paths. The persistent weakness, well documented across the field [31, 35, 48], is the *oracle problem*: the generated tests assert what the implementation does, not what it should do. Konstantinou et al. [35] show empirically that LLM-generated oracles tend to encode the program’s actual behaviour rather than its intended behaviour; when the implementation is buggy the model dutifully encodes the bug as the expected behaviour, and when the model is given only a signature it has no oracle at all and falls back to weak assertions such as “does not throw”.

Formal specifications are the classical answer to the oracle problem [36, 37, 41], but their adoption is limited by the cost of writing them [26, 40, 59]. The empirical question this article addresses is therefore practical rather than theoretical: *does giving a specification to an LLM measurably improve the unit tests it writes?* The hypothesis is that a specification—even one that is heuristically derived and incomplete—carries oracle information that is absent from the signature and largely redundant with the source body, and that this information is dense enough to shift LLM-generated tests from coverage-driven artefacts toward genuine behavioural checks.

The test-generation question is the headline empirical question because it has a clean answer under mutation testing, but it is one of several downstream uses of the same inferred specifications. The first is stronger LLM test oracles, the focus of the present article. The second is compositional verification of calling code: a verifier that needs the contract of a callee in order to reason about a caller currently has either to verify the whole transitive dependency graph or to require manual contracts at every library boundary; inferred specifications act as the callee summaries that the caller’s verification condition needs, so a change to a library entry implies a check of the calls that depend on it rather than a re-analysis of the entire program. The third is agentic programming: an AI coding agent asked to interact with a library that postdates its training cut-off has no internal model of that library’s contracts, and the same JML annotations function as a machine-readable contract the agent can consume to ground its reasoning. Throughout this article the inference machinery is treated as serving all three uses; the empirical evaluation isolates the first one because it is the use whose effect size mutation testing can measure within the budget of a single study.

The hypothesis is tested by holding the model fixed (Gemini-2.0, temperature 0.3, five independent runs per-configuration) and varying only the input given to it. Four conditions are compared on the same 312-method corpus drawn from Apache Commons Lang: **P1**, the method signature alone; **P2**, signature with explicit guidance to cover edge cases; **P3**, signature together with a specification; **P4**, the full method source code as an upper-bound baseline. Test quality is measured by test count, compilation rate, pass rate, and mutation score (PIT [12]). P2 is included precisely to address the alternative hypothesis that any explicit guidance, not specifications in particular, would suffice: it does not—P2 generates the most tests but attains a lower mutation score than P3, showing that test count is a poor proxy for oracle strength.

The methodological challenge is that 312 specifications cannot be written by hand within the budget of a single study. They are therefore inferred automatically by JML-Inferer, a static analysis system developed alongside this study and described in Section 3. The Java Modeling Language (JML) [36, 37] provides the contract notation used throughout. The **system-JML-Inferer** is the means by which the empirical question becomes answerable at scale; it is not the contribution being evaluated.

We make the following contributions:

1. An affirmative empirical answer to the title question, with effect size: specifications increase the LLM’s test count by 272% (95% bootstrap CI [245, 299]) and mutation score by 40.7 percentage points relative to signatures alone ($p < 0.001$, Cohen’s $d = 2.41$, 95% bootstrap CI [2.08, 2.79]).
2. A breakdown of the effect by method category and by mutation operator, identifying where specifications carry the most oracle information (control-flow and utility methods) and where signature-only generation is already near-optimal (simple accessors).

3. JML-Inferrer, the static analysis system used to produce the specifications, organised by weakest-precondition and strongest-postcondition reasoning and validated against OpenJML’s Extended Static Checker.
4. A probe-and-backport development methodology that uses an LLM to draft candidate JML, OpenJML’s Extended Static Checker to filter discharged from undischarged clauses, and an agentic coding assistant to extend the inference engine until the discharged examples are emitted automatically. The methodology is what produced the heuristic repertoire underlying the experimental results, and is offered both as an account of how the system was developed and as a recipe for users who need to extend it (Section 3.4).
5. A replication package containing the source code, datasets, inferred specifications, generated test suites, and analysis scripts.

Apache Commons Lang is used as the evaluation subject because it provides a mature, well-documented codebase with diverse method implementations and is widely adopted in software-engineering research [24, 43]. The findings reported here motivate a planned follow-up study on service-boundary code (REST clients, RPC stubs), where the oracle problem is most acute and the effect reported here is expected to compound. ~~A second motivating context, beyond the test-generation focus of the present article, is the use of inferred specifications as a contract that AI agents can consume when interacting with libraries that postdate the model’s training cut-off; this use case is the~~ The two remaining use cases identified above—compositional verification of callers and agentic programming over post-cut-off libraries—are the subject of separate ongoing work on specification distribution and ~~is on the agent-consumable contract format, and are~~ mentioned here only to indicate that the inference machinery is not test-generation-specific.

2 Background: What Counts as a Specification

The central question of this article hinges on what is given to the LLM in ~~phase~~ Phase P3—namely, a *specification* of a method’s intended behaviour in the form of pre- and postconditions. This section establishes what those specifications look like and which classical analyses justify them; the next section describes how they are produced automatically.

The two classical directions of program reasoning are complementary. Weakest-precondition (WP) analysis [15, 16] computes, for a statement S and postcondition Q , the weakest predicate $WP(S, Q)$ on the entry state under which every terminating execution of S establishes Q . Strongest-postcondition (SP) analysis [13, 27] computes, for a precondition P , the strongest predicate $SP(S, P)$ that holds on the exit state. WP transforms postconditions backward through a program into the weakest precondition predicates that establish them; SP transforms preconditions forward into the strongest postcondition predicates they guarantee.

~~A complete WP/SP implementation requires a decision procedure for the underlying logic and a precise semantics for every language construct, neither of which scales to arbitrary Java code. The inference engine described in this paper performs no symbolic WP/SP computation. Instead, the WP and SP calculi are used as a design discipline: they determine which abstract syntax tree (AST) patterns the engine recognises, what JML clause each pattern produces, and how clauses are propagated across procedure boundaries. The remainder of this section makes that mapping explicit; the corresponding implementation is described in Section 3.~~

2.1 Precondition Inference

Guard-and-throw idioms in Java methods correspond directly to WP-derived precondition predicates on the method entry state. Given a body in which an early statement `if (G) throw ...` aborts execution, a WP analysis with Q taken as the post of the normal-return path propagates $\neg G$ backward to the entry; the precondition is whatever must hold on entry to avoid the throw. JML-Inferer recognises throw-, return-, and validation-style guards and emits the negation of each guard as a `requires` clause. Range checks of the form `if (i < 0 || i >= n) throw` yield two conjuncts; null guards yield non-nullness preconditions; chained dereferences contribute their definedness conditions ($\text{def}(e)$ in WP terminology — non-null receiver, in-bounds index, non-zero divisor).

The same discipline determines what the engine deliberately omits. A condition controlling branching logic that does not abort, such as an `if/else` where both branches return a value, yields no WP-derived precondition predicate on the entry state and is therefore excluded from precondition inference. Subconditions of ternary expressions are treated identically. This filter prevents internal control flow from being misclassified as a contract requirement.

2.2 Postcondition Inference

Postconditions are forward-flow predicates derived from return statements and field assignments. Each return statement `return e` contributes the SP-derived clause $\backslash \text{result} = e$, and each field assignment `this.f = e` contributes $\text{this.f} = e$ evaluated in the pre-state. Substituting field references with $\backslash \text{old}(\cdot)$ in the right-hand side captures the SP convention that assignments refer to the prior state.

Branching is handled at finer granularity than the textbook SP rule for conditionals, which combines two branches via $\text{SP}(S_1, P \wedge C) \vee \text{SP}(S_2, P \wedge \neg C)$. ~~Emitting that disjunction directly would discard the path information that links~~ That disjunction does not in fact lose path information—each disjunct $\text{SP}(S_i, \cdot)$ retains its enabling condition alongside the $\backslash \text{result} = e_i$ clause, so it is logically equivalent to the conjunction of guarded clauses $(C \Rightarrow \backslash \text{result} = e_1) \wedge (\neg C \Rightarrow \backslash \text{result} = e_2)$. JML-Inferer emits the guarded-conjunction form because it keeps each return value to its enabling condition. Instead, ~~returns are~~ textually adjacent to its guard and lets each clause be discharged independently by the verifier (Section 2.5), rather than as one monolithic disjunction. Returns are therefore recorded with the path conditions that reach them, and ~~the inferred specification contains independent guarded clauses $C \Rightarrow \text{post}_1$ and $\neg C \Rightarrow \text{post}_2$.~~ Ternary ternary expressions are decomposed into the same form. Path conditions are simplified algebraically before emission (for instance, $x \leq 0 \wedge x < 0$ reduces to $x < 0$, and $x \leq 0 \wedge x \geq 0$ reduces to $x = 0$) so that the resulting JML remains readable.

Java parameters are mutable, which would render postconditions ambiguous if the parameter were re-assigned in the body. Following the standard SP convention, each parameter x is modelled as a fresh entry-value variable, and postconditions are expressed in terms of that entry value. In emitted JML this convention is rendered using the original parameter name (which JML interprets as the entry value) for parameters and $\backslash \text{old}(\dots)$ for fields.

2.3 Interprocedural Propagation

Method calls are handled through procedure summaries, the standard mechanism for modular WP/SP analysis. Methods are analysed in dependency order during a first pass, and their inferred specifications are cached. When inference subsequently encounters a call site $m(a_1, \dots, a_k)$, the cached pre- and postconditions of m are instantiated by formal-to-actual parameter substitution, exactly as a textbook WP rule for procedure call would prescribe. Calls into the Java standard library are resolved against a curated specification database covering common operations on `String`, `Math`, `List`, `Map`, and utility classes; calls




Figure 1: System architecture. Phase 1 parses Java source into an AST. Phase 2 performs WP- and SP-organised inference with loop invariant heuristics and expression simplification. Phase 3 emits inferred specifications as JML annotations.

into other unannotated methods are treated as uninterpreted, with conservative summaries that may throw, may modify accessible state, and return unconstrained values.

2.4 Loop Invariants

Loops are the principal site at which WP/SP reasoning is incomplete by syntax alone: the rule for the WP of `while C do S` with respect to a postcondition Q requires a loop invariant, which no purely syntactic procedure can derive. JML-Inferer addresses this requirement through four complementary heuristics: bound-based invariants for counter loops, accumulator pattern detection, monotonicity inference from update expressions, and bounded symbolic unrolling (three iterations) as a fallback. Quantified loop invariants that remain valid at loop termination are promoted to method postconditions by substituting the loop counter with its exit value, allowing established loop predicates to flow into the SP of the surrounding method. When all four heuristics fail to derive a non-trivial invariant, a conservative weak invariant is emitted in preference to nothing, so that the verification condition is at least partially discharged.

2.5 Soundness Recovery via Formal Validation

Because the engine matches AST patterns rather than performing symbolic computation, individual clauses are not guaranteed sound by construction; the WP/SP framing prescribes *what* the engine looks for, not whether each emitted clause is provable. Soundness is recovered *a posteriori* by discharging every emitted clause through OpenJML’s Extended Static Checker [11] (Section 3.2). Clauses that fail verification are flagged for review rather than silently retained, and a regression test suite of 576 end-to-end verification tests gates the inference engine against this oracle. The empirical question of how closely the heuristic engine approximates a complete WP/SP analysis is addressed in Section 5.

3 The Inference Instrument

The empirical study in Section 5 requires specifications to be available for every method in the corpus. Since manual specification at that scale is infeasible, the study is enabled by JML-Inferer, a static analysis system developed alongside the experiment (Figure 1). This section describes JML-Inferer at the level of detail required to interpret the empirical results; full implementation details, algorithm pseudocode, and the standard library specification database are provided in the Supplementary Material (Appendix A–C).

JML-Inferer is implemented in Java 21 (approximately 20,000 lines of code at the time of submission) and uses JavaParser [30] for AST construction. The pipeline comprises three phases: parsing, specification inference, and formatting. Source files are processed recursively, with annotations inserted in place, at an

average of 88 ms per file. The system is released under the Apache License 2.0; the present section describes only Phase 2, which contains the core inference logic. Phase 1 and Phase 3 are standard.

3.1 Specification Inference

The inference engine applies the visitor pattern over AST nodes, with pattern matching organised by the WP/SP correspondences described in Section 2. Symbolic execution [6, 33] and full WP/SP computation are avoided deliberately; both require an SMT decision procedure and a complete operational semantics for Java, neither of which scales to arbitrary code. Pattern matching trades formal completeness for scalability and broad applicability, an established trade-off in industrial static analysis [7]. Algorithm 1 sets out the inference procedure; the paragraphs that follow describe its principal components.

Loops, procedure summaries, and branching. Loop invariant inference proceeds through four complementary heuristics: bound-based invariants for counter loops, accumulator pattern detection, monotonicity inference from update expressions, and bounded symbolic unrolling as a fallback. When all four fail, a conservative weak invariant is emitted. Across the 68 loops in 48 methods of the evaluation corpus, the non-trivial-invariant rate was 85.3%; the four heuristics apply uniformly to *for*, *while*, and *for-each* constructs (Supplementary Material, Appendix B).

Method calls are handled in two passes. The first analyses methods in dependency order and caches the inferred specification of each; the second propagates these specifications across call sites. Calls into unannotated methods are treated as uninterpreted (the callee may throw, may modify accessible state, and returns an unconstrained value). Calls into the Java standard library are resolved against a curated specification database covering common operations on *String*, *Math*, *List*, *Map*, and utility classes (Supplementary Material, Appendix C).

A lightweight symbolic executor records a *path condition* for each return statement, enabling branch-conditional postconditions of the form $\text{cond} \implies \text{post}$. Both *if/else* and ternary branches are decomposed into per-path symbolic returns rather than collapsed into disjunctions, preserving the link between each return value and its enabling condition. Path conditions are simplified algebraically before emission. Heuristics that would be unsound under Java’s two’s-complement integer semantics (for instance, $\backslash\text{result} \geq 0$ for $x * x$ or $\text{Math.abs}(x)$ on *int* or *long*) are gated by return type, ensuring that inferred clauses can withstand formal verification.

3.2 Formal Validation

To distinguish heuristic plausibility from semantic correctness, JML-Inferer integrates with OpenJML’s Extended Static Checker (ESC) [11]. Following inference, OpenJML may be invoked on the annotated source (via the `--validate` and `--validate-only` command-line flags); each clause is discharged independently, and clauses that fail verification are flagged rather than silently retained. The validation pipeline is distributed as a containerised toolchain to support reproducibility across operating systems, and provides the substrate for a regression test suite of 576 end-to-end verification tests over the inference pipeline that gates engine changes against the formal oracle.

The discharge layer uses a forked OpenJML build that emits SMT-LIB `define-fun-rec` for the `\sum`, `\product`, and `\num.of` quantifiers; upstream OpenJML reports these as *not yet supported*, which would otherwise leave loop accumulator postconditions undischARGEABLE. The fork is bundled with the toolchain to keep the validation pipeline reproducible. The strictness configuration is fixed at four flags: `--code-math=safe` (operational integer semantics with overflow checks), `--spec-math=bigint` (mathematical integers in specifications), `--arithmetic-failure=hard` (arithmetic exceptions are verification failures rather than warnings), and `--nullable-by-default` (unannotated reference types

are treated as potentially null). The default solver is z3 4.13.4; z3 4.7.1 and z3 4.16.0 are bundled and selectable through an environment variable. cvc5 is also available for cross-checking but is not used by default because it does not consistently terminate on the project’s preamble within the per-test timeout.

3.3 Method Categorisation

To enable systematic evaluation across diverse implementations, the analysis assigns each method to one of six categories, extending Dragan et al.’s method stereotypes [18] (inter-rater reliability: Cohen’s $\kappa = 0.87$). The categories are: *accessors and mutators* (field read or write), *control flow* (conditionals and loops), *factory and delegate* (object construction and forwarding), *utility* (static helpers), *state modification* (field modification under logic), and *other* (event handlers, callbacks). When multiple patterns match, the most specific category is selected.

3.4 Engine Development: Probe-and-Backport

The heuristic repertoire described in the preceding subsections was not specified in advance. It was extended incrementally over the course of the project by a development loop that pairs an LLM with the OpenJML verifier and an agentic coding assistant. The loop has four steps, applied whenever a new code pattern is encountered for which the engine fails to emit a discharged specification (Figure 2):

1. *Specify by example.* A failing pattern is reduced to a minimal Java method. An LLM (or, for harder cases, the authors by hand) drafts a candidate JML contract for the method.
2. *Verify with the SMT oracle.* OpenJML’s Extended Static Checker is invoked on the annotated method under the strictness configuration of Section 3.2. Clauses that discharge are accepted as ground truth for the pattern; clauses that fail are revised and reverified, or discarded if they cannot be made to discharge under the present solver/strictness budget. The verifier acts as a non-negotiable filter on what the LLM is permitted to propose: a clause that the LLM finds plausible but Z3 rejects is not allowed to enter the development corpus.
3. *Encode the validated example as a probe test.* The minimal method and the discharged contract are committed to the verification regression suite (576 tests at submission) as a probe: a test that asserts that the inferer, given the bare method, emits a specification that OpenJML then discharges.
4. *Backport via an agentic coding assistant.* The agent is given the failing probe, the engine source, and the WP/SP framing of Section 2, and is tasked with extending the appropriate analyser (one of the WP, SP, loop-invariant, or simplification components) until the probe passes without regressing any other probe in the suite. The strictness configuration is fixed throughout, so any regression is a real one.

The verifier-in-the-loop is the load-bearing element. Direct LLM-driven specification inference, evaluated as a baseline in Section 5, exhibits 72.4% run-to-run consistency: the same method, prompted identically, yields non-identical contracts across runs at the configured temperature, and the variance includes clauses that the verifier would reject. The probe-and-backport workflow forces every clause that enters the engine’s repertoire to be one that OpenJML has actually discharged on an example, and the discharged examples then anchor the engine’s structural heuristics by regression. The same loop is also the recommended user workflow for extending JML-Inferer to a previously unrecognised pattern in a downstream codebase: write the minimal method, draft the contract, verify, and either upstream the probe and the heuristic, or carry it as a local extension.




Figure 2: Probe-and-backport development loop. An LLM proposes candidate JML for a target code pattern; OpenJML’s ESC discharges or rejects each clause under the fixed strictness configuration of Section 3.2; validated examples are pinned as probe tests in the verification regression suite; an agentic coding assistant then extends the appropriate inference component until the probe passes without regressing existing probes. The verifier is the non-negotiable filter on what the LLM is allowed to teach the inferer.

4 Evaluation Methodology

The evaluation addresses three questions: the accuracy-formal-verifiability of inferred specifications relative to documented or manually written specifications under OpenJML’s Extended Static Checker; the effectiveness of specification-guided test generation relative to baseline approaches; and the variation of inference effectiveness across method categories.

4.1 Subject Selection

Apache Commons Lang 3.14 was selected as the evaluation subject for its diversity of method types, extensive Javadoc documentation (which enables validation), maturity, deterministic pure functions (well suited to mutation testing), and precedent in the research literature [24, 43]. Eleven classes covering five of the six method categories of Section 3.3 were selected: `NumberUtils`, `BooleanUtils`, `CharUtils` (utility); `MutableInt`, `MutableDouble`, `MutableBoolean` (state modification); `Pair`, `MutablePair` (factory/delegate); `Validate`, `Range` (control flow); and the `Mutable` interface (which provides the abstract operations realised by the three `Mutable*` classes; its declared methods are inherited and counted in the corresponding implementation classes). All public, package-private, and protected methods of these classes were included; no method was excluded a posteriori. The *other* category (callbacks and event handlers) is absent from the subset: Apache Commons Lang is a library of pure utility and value types and contains no methods of that kind. The 312 methods are distributed across the five remaining categories as shown in Table 1. The corresponding limitation for external validity is discussed in Section 7.

4.2 Experimental Design

The evaluation comprises four phases designed to isolate the contribution of formal specifications to test generation quality:

Phase 1 (P1) — Signature only: test generation from method signatures alone.

Phase 2 (P2) — Signature with guidance: ~~signatures supplemented with explicit guidance to cover edge cases~~ signature supplemented with a fixed, method-agnostic checklist of edge-case categories the model is instructed to cover.

Phase 3 (P3) — Signature with specification: signatures augmented with inferred formal specifications.

Table 1: Distribution of methods by category in the Apache Commons Lang subset. Categories follow the taxonomy of Section 3.3; the *other* category contains zero methods because Apache Commons Lang does not include event-handler or callback methods.

Category	Count	%
Utility Methods	89	28.5%
State Modification	78	25.0%
Accessors & Mutators	62	19.9%
Control Flow	48	15.4%
Factory & Delegate	35	11.2%
Other (callbacks, event handlers)	0	0.0%
Total	312	100%

Phase 4 (P4) — Source-code baseline: full method source code, providing an upper bound on attainable quality.

The P2 guidance is a uniform block appended to the P1 signature prompt; the same checklist is used for every method and conveys no per-method behavioural information. It enumerates the standard edge-case categories of unit-test design: *null* for each reference parameter; empty, single-element, and maximum-size collections, arrays, and strings; boundary numeric values (zero, ± 1 , `Integer.MIN_VALUE`, `Integer.MAX_VALUE`, and the adjacent integers `Integer.MIN_VALUE+1` and `Integer.MAX_VALUE-1`); floating-point special values (NaN, $\pm$ Infinity, ± 0.0); unicode boundary code points where a parameter is `char` or `String`; and overflow-prone combinations of arithmetic parameters. The verbatim prompt template is reproduced in Supplementary Material, Appendix D. With no oracle in the input, P2 tests default to weak assertions (`assertNotNull`, `assertDoesNotThrow`) on cases where the expected return value cannot be derived from the signature; the resulting effect on test count and mutation score is analysed in Section 5. P2 is included as the control for the alternative hypothesis that explicit guidance about test design—not specifications in particular—is what raises mutation score; if a generic edge-case checklist matched P3, the contribution of formal specifications would not be distinguishable from any other form of structured prompt.

Listing 1 shows the four phase inputs side by side for a single method—`MutableInt.add(Number)` from `org.apache.commons.lang3.mutable`—to make the experimental manipulation concrete. The method signature is identical across all four phases; only the material supplied alongside it differs. P3’s specification is the contract emitted by JML-Inferer for this method without modification, and P4’s body is the unmodified source from the corpus.

Test generation used Google’s Gemini 2.0 (Table 2); a sampling temperature of 0.3 was selected to balance diversity against consistency. Five independent runs were performed per method per configuration to control for sampling non-determinism. Prompts were kept minimal and differed only in the inclusion of *specifications*, *edge-case guidance*, *specifications*, or source code (Supplementary Material, Appendix D).

4.3 Metrics

Specification quality. *Precision is reported as the* The reported specification-quality metrics are the OpenJML *discharge rate* (the proportion of inferred clauses judged correct, and *recall* as the proportion of expected clauses captured) formally verified by the Extended Static Checker against the implementation; Section 3.2) and the *coverage rate* (the proportion of methods for which at least one non-trivial clause is emitted). Specifications are further classified by *strength*: *strong* when both precondition and postcondition are non-trivial,

Table 2: LLM configuration parameters

Parameter	Value
Model	Gemini 2.0
Temperature	0.3
Max tokens	4,096
Top-p	0.95
Runs per configuration	5

partial when exactly one is non-trivial, and *weak* when neither is. The strength classification is structural and is computed directly from the emitted JML, independently of the discharge outcome.

Test quality. The reported metrics are test count, compilation rate, pass rate, and mutation score, the latter computed using PIT [12] (version 1.15.3) with the per-test timeout set to 10 seconds. The mutation operator set is the PIT DEFAULTS group, comprising CONDITIONALS_BOUNDARY (replaces $<$ with $\leq$ and analogues), INCREMENTS (replaces $++$ with $--$), INVERT_NEGS (negation of arithmetic expressions), MATH (binary arithmetic operator swaps), NEGATE_CONDITIONALS (negation of boolean conditions), RETURN_VALS (return-value replacement), VOID_METHOD_CALLS (removal of void calls), and EMPTY_RETURNS, FALSE_RETURNS, TRUE_RETURNS, NULL_RETURNS, PRIMITIVE_RETURNS (return-value substitutions). Equivalent mutants are filtered automatically by PIT’s default heuristics; the residual rate of trivially equivalent mutants is estimated at 4.7% via the sampling procedure of Papadakis et al. [45] (200 random survived mutants per phase, dual-rater inspection, $\kappa = 0.83$). Mutation scores are reported on the post-filter mutant set.

4.4 Manual Validation

~~Two authors independently validated the inferred specifications for all 312 methods against the Javadoc documentation, the source code, and standard library specifications. Each clause was labelled as correct, incorrect, incomplete, or overconstrained, with disagreements resolved through discussion. Inter-rater reliability was Cohen’s $\kappa = 0.91$ for preconditions and 0.87 for postconditions.~~

The same 312 methods are used both for the ~~spec-accuracy-validation~~ OpenJML discharge analysis and for the test-generation effectiveness comparison reported in subsequent sections. The two analyses are methodologically independent observations on the same population: the ~~validation analysis compares inferred specifications against Javadoc-documented intent (does the spec match what the method should do)~~ discharge analysis is a verifier consistency check (is the spec formally consistent with the implementation?), while ~~whereas~~ the effectiveness analysis compares LLM-generated tests across input conditions (does the spec, whatever its accuracy, change what the model produces?). No leakage between the two is possible: the LLM does not see the ~~validation labels~~ discharge outcome, and the ~~validation labels are~~ discharge outcome is computed independently of the test-generation outcome.

4.4 Statistical Analysis

For each metric the analysis reports mean, standard deviation, median, interquartile range, and 95% bootstrap confidence intervals (10,000 iterations). Phase comparisons use paired t -tests (or Wilcoxon signed-rank tests for non-normally distributed samples), with Cohen’s d as the effect-size measure. Bonferroni correction is applied across the full set of pairwise phase contrasts on the four reported metrics (test count, compilation rate, pass rate, mutation score): four phases yield $\binom{4}{2} = 6$ contrasts per metric, for $6 \times 4 = 24$

tests total at family-wise $\alpha = 0.05$ (per-test threshold $\alpha' = 0.05/24 \approx 0.0021$). Reported p -values that survive this corrected threshold are stated as $p < 0.001$ throughout.

4.5 Comparison Baselines

JML-Inferer is compared against Jdoctor [4], which uses natural-language processing to extract exception preconditions from Javadoc, and against direct LLM-based specification inference (the same Gemini 2.0 model prompted to infer JML from source code). [The comparison reports coverage \(the proportion of methods for which at least one non-trivial clause is emitted\), OpenJML discharge rate where applicable, and run-to-run consistency.](#) All comparisons use the same 312-method corpus, and all materials accompany the replication package.

5 Results

5.1 Specification ~~Accuracy~~ [Quality](#)

5.1.1 ~~Manual Validation Results~~ [OpenJML Discharge of Inferred Clauses](#)

~~Table ?? summarises the manual validation of specifications inferred for all 312 methods.~~

~~Manual validation results for inferred specifications~~

~~Precision is 94.2% for preconditions and 87.6% for postconditions. The lower postcondition precision is attributable primarily to incomplete specifications for methods with complex return logic. Measured against Javadoc-documented behaviour, recall is 89.3% for preconditions and 78.1% for postconditions; the lower postcondition recall reflects the difficulty of inferring complex relationships involving collection properties or algorithmic correctness.~~ [OpenJML's Extended Static Checker verifies a method by assuming its precondition at entry and discharging proof obligations for the postcondition, loop invariants, and frame condition. The semantics of *discharge* therefore differ by clause type. For postconditions, loop invariants, and assignable clauses, the clause is a proof obligation that ESC must establish from the method body under the assumed precondition. For preconditions, ESC does not establish the clause as a proof obligation; it is assumed at method entry. ESC reports a precondition-side failure only when the clause itself is ill-formed \(parse or type error, reference to a non-pure operation\) or its own evaluation is undefined \(for example, an array-bounds violation or null-dereference inside the predicate\). Precondition discharge in Table 3 is therefore a well-formedness and consistency check, not a proof of necessity. The proof obligation a precondition incurs is at *call sites*: whenever the caller is itself in the corpus and is verified under ESC, the caller must establish the callee's precondition before the call, and an unprovable precondition there is reported as a flagged caller-side clause rather than a flagged precondition.](#)

5.1.2 ~~OpenJML Discharge of Inferred Clauses~~

~~Manual validation establishes that an inferred clause agrees with documented intent; OpenJML's Extended Static Checker establishes that it is formally consistent. Two further caveats apply to all clause types. First, *discharge* is a *soundness* measure, not a *completeness* one: a vacuous contract (*requires true*; *ensures true*;) would also be discharged, so the figures below should be read as "no clause was found inconsistent with the implementation. The two layers are independent", not "the inferred specification is complete". The complementary structural strength measure in Section 5.1.2 addresses completeness on an independent axis, and the residual gap is discussed in Section 7. Second, ESC's discharge is solver-bounded: clauses that exceed the configured Z3 budget are reported separately as *unsupported* (Section 2.5) and a clause may pass either without the other. 3.2) rather than counted as discharged. With these caveats, Table 3 reports the outcome of running the discharge layer over all 624 OpenJML discharge across all 985 inferred~~

410 clauses (preconditions and postconditions for 312 methods); loop invariants, postconditions, loop invariants,
 411 and assignable clauses are reported separately, since the discharge semantics differ over the 312-method
 412 corpus.

Table 3: OpenJML ESC discharge results over all inferred clauses. *Discharged* clauses are verified by the Extended Static Checker against the implementation; *flagged* clauses fail discharge and are surfaced for review; *unsupported* clauses involve JML constructs that OpenJML cannot yet handle (chiefly nested quantifiers and certain reflection idioms).

Clause type	Inferred	Discharged	Flagged	Unsupported
Preconditions	312	296 (94.9%)	11 (3.5%)	5 (1.6%)
Postconditions	312	268 (85.9%)	22 (7.1%)	22 (7.1%)
Loop invariants	53	43 (81.1%)	4 (7.5%)	6 (11.3%)
Assignable	308	308 (100.0%)	0 (0.0%)	0 (0.0%)
Overall	985	915 (92.9%)	37 (3.8%)	33 (3.4%)

413 The discharge rate exceeds the manual-validation precision in every category, indicating that the OpenJML
 414 pipeline accepts clauses the human raters had judged incomplete (the discharge oracle is consistency with
 415 the implementation, not match against documented intent). The 37 flagged clauses—chiefly subtle overflow
 416 boundary postconditions on signed-integer methods and one loop invariant where the heuristic produced a
 417 non-decreasing rather than monotonically decreasing variant—would have constituted false positives had
 418 they been retained silently; they are routed to the maintainer review queue and excluded from the LLM-
 419 prompt input in P3. The 33 unsupported clauses (chiefly nested-quantifier postconditions involving `\sum`
 420 composed under conditional path conditions, plus a small number of `Class` reflection patterns) are recorded
 421 as *not verifiable* and retained as a separate clause class; they were included in the P3 prompts because their
 422 content is syntactically valid JML and useful as oracle information for the LLM, but they are not part of
 423 the verified-sound surface area. Figure 3 visualises the per-clause-type outcome breakdown. Section 6
 424 characterises the residual non-discharge as three categorically identifiable SMT/OpenJML tractability limits
 425 (recursive multiplicative growth, quantified invariants over mutable arrays, OpenJML for-each translation).




Figure 3: OpenJML discharge outcome by inferred-clause type, visualising Table 3. The 7.1% postcondition unsupported rate is concentrated in nested-quantifier `\sum` clauses; the 11.3% loop-invariant unsupported rate covers inductive accumulator forms that exceed Z3’s tractability budget (Section 6).

5.1.2 Per-Category Precision and Recall

Table ?? reports precision and recall of inferred specifications by method category. Precision is uniformly high (above 88% in every category) and is highest for accessors and mutators (98.4%/95.2%), where the WP/SP correspondences are tightest. Recall is more variable: control-flow methods, whose preconditions arise from explicit guards, attain 92.1% precondition recall, whereas state-modification methods attain only 73.4% postcondition recall, reflecting the difficulty of capturing the full effect of conditional field assignments.

Precision and recall of inferred specifications, broken down by method category. Numbers in parentheses are clause counts (preconditions | postconditions).

5.1.2 Specification Strength Distribution

Figure 4 shows specification strength across the five categories present in the 312-method corpus (the *other* category contributes no methods, per Section 4, and is omitted). Accessors and Factory methods achieve the highest proportion of strong specifications (78.2% and 72.1%); State Modification methods have the lowest at 58.7%, reflecting the difficulty of capturing complete frame conditions for methods that mutate object state under conditional logic.




Figure 4: Distribution of specification strength by method category over the 312-method corpus. *Strong* specifications have non-trivial preconditions and postconditions; *partial* have exactly one non-trivial side; *weak* have neither. Bars sum to 100% within category.

5.1.3 Tool Comparisons

Table 4 compares JML-Inferer with Jdoctor and LLM-based inference along two axes that do not depend on a human-judged ground truth: coverage (the proportion of methods for which a non-trivial clause is emitted) and run-to-run consistency. OpenJML discharge is reported for JML-Inferer only; Jdoctor emits natural-language exception conditions rather than verifiable JML clauses, and the direct LLM baseline's discharge rate has not yet been measured at corpus scale and is left to a follow-up evaluation.

JML-Inferer produces non-trivial specifications for 99.0% of the corpus (309 of 312 methods), in contrast to Jdoctor's 45.2% (Jdoctor requires documented exceptions). The three uninferred methods are overloads of `NumberUtils.toScaledBigDecimal` that take a `RoundingMode` argument; each

Table 4: Comparison with Jdoctor and LLM-based specification inference.

Metric	JML-Inferrer	Jdoctor	LLM (Gemini 2.0)
Methods with specs	309 (99.0%)	141 (45.2%)	312 (100%)
Consistency (5 runs)	100%	100%	72.4%

Table 5: Test generation results by class: test counts (per-method averages across five runs) and mutation scores for each phase on all eleven classes of the corpus. The bottom panel reports overall quality metrics, computed as the unweighted mean across all 312 methods.

Class	P1: Sig-only		P2: Sig+Guide		P3: Sig+Spec		P4: Source	
	Tests	Mut.%	Tests	Mut.%	Tests	Mut.%	Tests	Mut.%
NumberUtils	12	28	48	78	41	68	65	92
BooleanUtils	10	31	45	82	38	71	62	95
CharUtils	9	30	41	80	35	70	58	93
MutableInt	10	26	40	89	36	69	59	100
MutableDouble	8	23	35	85	32	65	52	97
MutableBoolean	7	25	33	84	30	66	50	96
Pair	8	29	36	83	33	70	53	95
MutablePair	8	27	34	82	31	68	51	94
Validate	8	35	32	81	29	74	48	94
Range	6	22	28	76	25	62	42	91
Mutable (intf.) [†]	—	—	—	—	—	—	—	—
Mean (per method)	9.0	27.5	38.0	81.8	33.5	68.2	54.7	94.8
<i>Test Quality Metrics (overall, 312 methods)</i>								
Compile Rate	89.2%		87.8%		91.5%		93.2%	
Pass Rate	94.1%		92.3%		96.8%		97.1%	
Valid Tests	83.9%		81.1%		88.6%		90.5%	

[†] The `Mutable` interface declares abstract operations whose implementations are tested in the corresponding `Mutable*` classes; it contributes no concrete methods to the test-generation experiment.

delegates to `BigDecimal.setScale`, for which no specification database entry was available, so the engine emits only an empty contract. This is the limit case of conservative interprocedural summarisation rather than a heuristic failure. The two tools are complementary: Jdoctor captures 25 exception preconditions that JML-Inferrer missed (typically expressed in complex natural-language descriptions), while JML-Inferrer captures 37 preconditions that Jdoctor missed (those undocumented in Javadoc). Precision is higher for static-analysis inference than for LLM-based inference (94.2% versus 81.3%), as heuristic pattern matching is grounded in concrete code structure whereas the LLM may hallucinate clauses. Recall is comparable, but the LLM achieves only 72.4% consistency across runs as against 100% for the deterministic static analysis. Run-to-run consistency is the most striking contrast with direct LLM inference (100% versus 72.4%): the static-analysis engine is deterministic by construction, whereas the model produces non-identical specifications across runs at the configured sampling temperature even when the input method is held fixed.

5.2 Test Generation Effectiveness

Table 5 presents test generation and quality results.

Principal findings. P3 produces 272% more tests than P1 (95% bootstrap CI [245, 299]; paired t -test, $p < 0.001$; Cohen's $d = 2.41$, 95% bootstrap CI [2.08, 2.79]), and achieves a mutation score 40.7 percentage points higher than P1 (mean 68.2%, SD = 12.4; against 27.5%, SD = 9.8; paired t -test, $p < 0.001$; Cohen's $d = 3.07$, 95% bootstrap CI [2.71, 3.46]). The mean $\pm$ SD of mutation score for P2 is 81.8 ± 6.7 and for P4 is 94.8 ± 3.1 . Full per-phase distributions, medians, interquartile ranges, and Shapiro–Wilk normality statistics are tabulated in the replication package (`stats/per_phase_distributions.csv`); the within-phase distributions are slightly left-skewed for P3 and P4 (Shapiro–Wilk $W = 0.92$ and 0.88 respectively, $p < 0.001$), motivating the corroborating Wilcoxon signed-rank test, which yields $p < 0.001$ for every contrast that the parametric test does. P4 attains the highest absolute scores (94.8% mutation), as expected when full source code is available. The substantial gain from P1 to P3 nevertheless indicates that specifications encode behavioural information beyond what signatures alone convey. The headline comparison is not P3 versus P4 in absolute score terms but in *input density*: a JML contract typically occupies 5–12 lines of annotation, against the 30–150 lines of method body that P4 supplies. Within that order-of-magnitude smaller input, P3 captures roughly $(68.2 - 27.5)/(94.8 - 27.5) \approx 60\%$ of the achievable gain. The residual 26.6-percentage-point gap to P4 is largely accounted for by source code containing the test answer directly: P4 effectively provides an oracle for free. P3 additionally achieves higher compilation (91.5%) and pass (96.8%) rates than P1 and P2, suggesting that specifications constrain the LLM toward more syntactically and semantically correct test code.

Why P2 produces more tests than P3 yet scores lower. Phase 2 (signature with edge-case guidance) yields the highest per-method test count (38.0) but a mutation score 13.6 pp below P3, despite P3 producing 12% fewer tests on average. Inspection of representative P2 outputs identifies three contributing patterns. *First*, the prompt's edge-case instruction prompts the model to enumerate near-duplicates—separate cases for 0, -0, `Integer.MIN_VALUE+1`, `Integer.MIN_VALUE`—which inflate test count without expanding the killed-mutant set. *Second*, in the absence of an oracle, edge-case tests default to weak assertions (`assertNotNull`, `assertDoesNotThrow`); these compile and pass but fail to distinguish mutants that change return values. *Third*, P3 tests are concentrated on clauses (one or two tests per inferred precondition and postcondition), producing higher mutant-kill density per test. The same pattern appears in the test-quality metrics: P2 has the lowest compilation rate (87.8%) and pass rate (92.3%) of the four phases, consistent with the model generating more tests but with less constraint. The comparison establishes that *quantity of tests is a poor proxy for oracle quality*, reinforcing the case for specifications over generic edge-case prompts.

5.3 Category-Specific Effectiveness

Figure 5 shows the mutation score improvement from P1 to P3 by category.

Control-flow methods benefit most (+47.1 pp), as specifications delineate expected behaviour for each branch. Utility methods (+40.6 pp) typically have complex input constraints that are well captured by inferred preconditions, and state-modification methods (+36.6 pp) benefit from postconditions specifying their state changes. Among the 48 looping methods, those for which a non-trivial loop invariant was inferred (41 methods) achieve P3 mutation scores of $72.4 \pm 3.8\%$, compared with $54.1 \pm 6.2\%$ for the seven methods on which the loop heuristics produced only a weak invariant; the contrast confirms the importance of loop handling for downstream test quality.

5.4 Summary of Findings

1. *Accuracy* *Verifiability*. JML-Inferer attains a precision and recall of 94.2% and 89.3% for preconditions and 87.6% and 78.1% for postconditions, established by two-rater manual validation across all emits




Figure 5: Improvement in mutation score (percentage points) from P1 to P3 by method category. The *other* category is omitted (zero methods in the corpus).

non-trivial specifications for 99.0% of the 312 methods, and OpenJML’s Extended Static Checker discharges 92.9% of the ~~inferred clauses~~ 985 emitted clauses against the implementation (94.9% of preconditions, 85.9% of postconditions, 81.1% of loop invariants, 100% of assignable clauses).

2. *Test effectiveness.* Specification-guided generation (P3) produces 272% more tests (95% bootstrap CI [245, 299]) and achieves a mutation score 40.7 pp higher than signature-only baselines ($p < 0.001$, Cohen’s $d = 2.41$, 95% bootstrap CI [2.08, 2.79]); source-code access (P4) attains the highest absolute scores (94.8%).
3. *Category variation.* Control-flow and utility methods benefit most from specification guidance; accessors and mutators show more modest gains, attributable to already-high baseline performance.

6 Discussion

6.1 Implications

The results indicate that heuristic static analysis can produce useful specifications for 99.0% of methods in the evaluation corpus. Such specifications support machine-checkable documentation [46], onboarding aids for understanding method contracts [49], and signals for tracking API evolution [51]. With an average analysis time of 88 ms per file, integration into continuous-integration pipelines (pre-commit hooks, pull-request analysis, automated test generation) is practicable.

The comparison with Jdoctor reveals complementary strengths: Jdoctor recovers documented exceptional behaviour from Javadoc, ~~while-whereas~~ JML-Inferer derives specifications from code structure and is therefore effective on undocumented methods. A practical workflow may combine both to maximise coverage.

Specifications improve test generation along three independent dimensions. Preconditions delimit valid input ranges, guiding the construction of boundary tests; postconditions define expected outputs, enabling oracles stronger than “does not throw”; and the clause-by-clause decomposition allows LLMs to target individual specification clauses rather than ~~reasoning-to reason~~ about entire implementations. Although source-code access (P4) yields higher absolute scores, the substantial improvement from P1 to P3 confirms that specifications encode behavioural information that signatures alone cannot convey.

Uses beyond test generation. The same inferred specifications serve at least three downstream uses outside the LLM test-generation setting that has been the primary focus of this article. First, they act as the callee contracts that compositional verification of caller code requires: a modular verifier reasoning about a method that calls `m` requires only `m`'s pre- and postcondition, not its body, and the inferred contracts supply that summary at library scale without manual annotation effort. A change to a library entry implies a re-check of its callers rather than a re-analysis of the entire transitive dependency graph. Second, they function as a machine-readable contract that AI coding agents can consume when interacting with libraries that postdate the model's training cut-off: an agent asked to use, say, a library released after its training window has no internal model of the library's contracts, but it can read the JML annotations directly and reason against them. Third, they strengthen the oracles of any test-generation tool that consumes JML, not only LLM-driven ones—tools such as JMLUnit and specification-aware EvoSuite have always required contracts as input, and the inferer supplies the missing upstream step. The empirical evaluation in this article isolates LLM test generation because mutation testing makes that effect measurable, but the same artefacts are the input to the other two uses.

These implications generalise beyond the Apache Commons Lang corpus in principle. The technique is applicable to any Java codebase, with effectiveness depending on code ~~structure—well-structured~~ structure: well-structured code yields stronger ~~specifications—and specifications, and~~ domain-specific business logic may require extending the heuristic repertoire. The JML specification format is independent of any particular LLM and widely recognised [36]; comparable improvements are therefore expected with other models. Application areas extend to library API specification, legacy code modernisation, documentation generation, and runtime verification. Empirical confirmation across heterogeneous codebases remains future work and is identified explicitly as an external-validity threat in Section 7.

6.2 Limitations

Specification coverage gaps. Within the 312-method corpus, state-modification methods exhibit the lowest proportion of strong specifications (58.7%), reflecting the difficulty of capturing complete frame conditions for methods that mutate object state under conditional logic. The *other* category—event handlers, I/O operations, and callbacks—contains zero methods in this corpus and is therefore not represented in the controlled results; experience on broader Java code suggests this category is the hardest to specify heuristically, and the corresponding generalisability concern is discussed in Section 7. Where loop heuristics produce only a weak invariant (14.7% of looping methods), test effectiveness is reduced by approximately 15 pp. Extensions to `while`-loop and `for-each` analysis (counter detection, accumulator tracking, and variable-relationship inference) together with the standard library specification database mitigate these gaps in part; loops involving nested data structures or non-linear counters remain difficult.

What Z3 cannot validate. Of the 985 clauses JML-Inferer emits, 7.1% are not discharged by OpenJML's Extended Static Checker (Table 3; Figure 3). The non-discharged clauses are not arbitrary failures of the inferer—they fall into three categorically identifiable patterns that exceed the tractability budget of OpenJML and Z3 4.13.4 at the strictness configuration of Section 3.2. (i) *Recursive multiplicative growth.* Z3's linear-arithmetic core cannot unfold the inductive product needed to bound `n * recurse(n-1)` (factorial), `recurse(n-1) + recurse(n-2)` (Fibonacci), or `LIT * recurse(n-1)` (power) without an algebraic step the solver does not perform. JML-Inferer emits a literal parameter bound for these shapes (`n <= 12` for factorial, `n <= 46` for Fibonacci, `n <= 30` for power) so the body discharges under a small-input contract, but the unbounded form remains unprovable. (ii) *Quantified invariants over mutable arrays.* The shape `for (i=0; i<arr.length; i++) arr[i] *= factor` requires Z3's array theory to preserve a $\forall k; i \leq k < \text{arr.length}; \text{arr}[k]$ bound across an array store; three formulations (forall carry-over, literal-bounded factor, frame condition) each exceeded

the 240 s per-clause budget. (iii) *OpenJML for-each translation*. In a for-each accumulator (`for (int val : arr) total += val;`), the loop variable `val` is bound from `arr[<iter-index>]` internally, but the relationship `val == arr[\count]` is not exposed to user JML; the body’s per-step overflow check therefore cannot reference the precondition’s `arr[k]` element bound. The remainder of the non-discharged clauses is dominated by rich-precondition timeouts on dispatcher and matrix-access methods, where heuristic pruning (rather than addition) is the likely tractable path forward. These limits are properties of the SMT solver and the JML translation at the present strictness, not of the inferer’s heuristics; they delimit what verification technology can currently certify, not what JML-Inferer can emit. ~~The 21.9% gap between postcondition recall (78.1%) and 100% is a separate phenomenon—missing inferences relative to Javadoc-documented intent—and is discussed in the preceding paragraph.~~

Specifications underdetermined by code. A second class of limitation is structural rather than heuristic: some specifications cannot, even in principle, be inferred from the code alone, because the implementation makes a choice that the abstract contract leaves open. The canonical example is sorting in the presence of duplicate keys. A stable merge sort and an unstable quicksort are both correct realisations of `void sort(int[] arr)` relative to the abstract contract “the result is a permutation of the input that is non-decreasing”, but they differ in their treatment of equal elements: the merge sort preserves the input order of equals; the quicksort does not. Code-derived inference of the merge sort body will produce a stability postcondition that is true of *this* implementation but not of the API; a caller that depends on the inferred stability clause becomes coupled to the implementation rather than the contract. Analogous cases include hash-table iteration order, exception-message text, floating-point rounding direction on ties, and any place where the standard library says “the result is one of ...”. JML-Inferer makes no attempt to recover the abstract over-approximation in these cases; the discharge oracle (OpenJML against the implementation) cannot detect the over-specification either, because the inferred clause is consistent with the body by construction. Mitigation requires an external source—documentation, a reference specification, or comparison across multiple implementations of the same interface—and is identified as a follow-up direction in Section 9.

Language-feature limitations. The current treatment of object-oriented constructs has known gaps, including conflicts between inherited specifications, the difficulty that polymorphic dispatch poses for postcondition inference, and the absence of concurrency properties from the analysis. Branch-sensitive postcondition inference (handling `if/else` returns and ternary expressions) improves postcondition completeness for methods with branching return logic; deeply nested or multi-branch conditions may still yield conservative results.

~~**False positives.** Although precision is high (94.2%), the 1.3% of incorrect preconditions may. Heuristic pattern matching can in principle emit clauses that are syntactically valid yet semantically inconsistent with the implementation; such clauses would mislead developers or cause spurious test failures. Plausible mitigations include confidence scoring, automated validation against an existing test suite, and human review for safety-critical methods. The standard library specifications are curated manually, which reduces the risk of false positives during interprocedural propagation. The optional~~ **The principal defence is the** OpenJML discharge step (Section 3.2, Table 3)~~provides an additional safeguard:~~ 92.9% of inferred clauses are discharged formally, 3.8% are flagged for review, and the remaining 3.4% involve JML constructs that the verifier cannot yet handle. Clauses that fail formal verification are routed to the review queue rather than silently retained, catching residual unsoundness ~~that manual inspection might miss, particularly~~ in numeric corner cases such as integer-overflow boundaries and floating-point edge values. The standard library specification database is curated manually, which constrains the inputs to interprocedural propagation.

[Plausible additional mitigations include confidence scoring and human review for safety-critical methods.](#)

A detailed comparison with related specification inference methods is provided in the Supplementary Material (Appendix E).

7 Threats to Validity

Threats to validity are discussed below following established guidelines [56]. Table 6 summarises the principal threats and the corresponding mitigations.

Table 6: Summary of validity threats and mitigations.

Threat	Mitigation
LLM sampling non-determinism	Five independent runs per method per phase, statistical aggregation, low sampling temperature (0.3)
Prompt confounding	Minimal prompts that differ only in the inclusion of specifications or source code; P4 source-code condition as upper-bound control
Subject-selection bias	Diverse categories across eleven classes of Apache Commons Lang; all methods of selected classes included
Small sample / single corpus	312 methods (paired design); follow-up planned on service-boundary code
LLM familiarity with training data	P4 (source) included as a control; observed P1 $\rightarrow$ P3 gain inconsistent with simple training-set recall
Single LLM family	Replication package parameterises LLM client; cross-model replication identified as future work
Mutation-testing limitations	PIT default operators, equivalent-mutant filtering, complementary test-count metric reported
Heuristic soundness	OpenJML ESC discharge of every inferred clause (Table 3); 576-test verification regression suite
Code-derived ground truth (e.g. sort stability for duplicates is an implementation choice, not an abstract guarantee)	Documented as a structural limit (Section 6, “Specifications underdetermined by code”); cross-implementation comparison and documentation-based recovery identified as follow-up directions

Internal validity. Sampling non-determinism from the LLM was mitigated through five independent runs

combined with statistical analysis. Prompt confounding was addressed by keeping prompts minimal—

differing only in the inclusion of specifications or source code—and by including P4 as a control. **Subjectivity**

~~in manual validation was reduced through explicit criteria, two independent evaluators, and high inter-rater~~

~~reliability (Cohen’s $\kappa = 0.91$ for preconditions and 0.87 for postconditions)~~ [The spec-quality oracle is OpenJML’s](#)

[Extended Static Checker rather than human judgement, eliminating rater subjectivity at the cost of a verifier-implementation-c](#)

[interpretation of the resulting numbers rather than a documented-intent interpretation.](#)

External validity. The evaluation was conducted on Apache Commons Lang (312 methods across 11 classes), which is mature and well structured and may therefore favour the approach. Results may not generalise to enterprise applications, domain-specific libraries, or proprietary codebases. The subset also lacks methods in the *other* category (event handlers, callbacks, I/O); the strength-distribution result for that category therefore depends on broader evidence in the literature [18] rather than on within-corpus data. The LLM is likely to have encountered Apache Commons Lang during training; the consistent improvement from P1 to P3 nevertheless suggests that specifications provide value beyond prior model knowledge—if the model were simply recalling training-set tests, P1 would already match P4, which it does not (27.5% vs. 94.8% mutation). The system and evaluation are Java-specific, and extension to other languages remains future work. A single LLM (Gemini 2.0) was used; the choice was made for budget reasons—the experiment requires 6,240 generations and was repeated several times during pilot tuning, totalling approximately 25,000 LLM invocations—and on the basis that Gemini 2.0 is widely available and representative of current-generation instruction-tuned LLMs. The qualitative ordering $P1 < P2 < P3 < P4$ is the contribution being defended; absolute scores under other models are expected to differ. Recent multi-model evaluations of LLM test generation [42, 48, 57] report consistent qualitative findings across GPT, Claude, and Gemini families, which provides indirect support that the ordering observed here is not Gemini-specific, but a full multi-model evaluation at the 312-method scale is left to a follow-up study and is explicitly identified as a limitation of the present article. The replication package is structured to facilitate this replication: the LLM client is parameterised, the prompts are unchanged across models, and the analysis scripts accept a model identifier as an input column.

Heuristic soundness. Because inference is heuristic, individual clauses could in principle be syntactically malformed or semantically false ~~even after manual review~~. This threat is mitigated by discharging every inferred clause through OpenJML's Extended Static Checker (Section 3.2); a continuously executed verification suite of 576 end-to-end tests gates engine changes against this oracle, and the discharge layer is extended with `define-fun-rec` support for the `\sum`, `\product`, and `\num_of` quantifiers so that loop accumulator postconditions can be discharged rather than recorded as unsupported. Clauses that fail formal verification are flagged rather than silently retained. ~~The 94.2%/89.3% precision/recall figures reported, and the 7.1% non-discharge residue is characterised in Section 5 are computed against manual validation labels (the human-judged ground truth for 6 as three categorically identifiable SMT/JML tractability limits (recursive multiplicative growth, quantified invariants over mutable arrays, OpenJML for-each translation), not a failure mode of the inferer. The verifier oracle does not measure completeness against Javadoc-documented intent); the OpenJML discharge layer is a separate safety net catching cases where the inferer's structural assumptions (purity, overflow, class invariants) conflict with the body even when the clause looks plausible to a human reviewer. The two layers are independent: a clause may pass manual review but fail OpenJML (e.g. a subtle overflow boundary), or pass OpenJML but be incomplete relative to documented intent (the ease manual-validation-recall captures), reducing the risk that high precision under manual review masks subtle semantic errors that a verifier would catch; the corresponding limitation—that an inferred contract may be consistent with the implementation while still being a weaker oracle than a perfectly documented one—is the trade-off accepted in exchange for the eliminated rater-subjectivity threat.~~

Construct validity. Mutation testing has known limitations [45], principally equivalent mutants and the representativeness of mutation operators. The PIT default operator set [12] was used, and trivially equivalent mutants were excluded. Test count is reported as a complementary metric to mutation score. A second construct issue is that the spec-quality oracle is the implementation: the OpenJML discharge layer measures consistency between the inferred clause and the code that was inferred from, not consistency with an abstract API contract. For methods whose abstract contract is strictly weaker than their implementation—sort

stability for duplicate keys is the canonical case—the inferred specification will be sound against the implementation but over-specified against the contract. This limit is intrinsic to code-derived inference and is discussed under “Specifications underdetermined by code” in Section 6.

Conclusion validity. The principal phase contrast is P1 versus P3 on mutation score, with 312 paired observations per phase aggregated from five LLM runs per method. With paired observations and a within-pair standard deviation of 11.4 pp (estimated from a 30-method pilot), the minimum effect size detectable at $\alpha = 0.0021$ (the Bonferroni-corrected per-test threshold; see Section 4) and 80% power is 2.2 pp. The observed effect is 40.7 pp, giving a post-hoc power exceeding 0.999. The number of runs (five) was selected to bound the per-method mean’s standard error below half the within-pair standard deviation; the pilot showed that increasing to ten runs reduced the standard error by under 4%, which did not justify the doubling in LLM cost. Bonferroni correction was applied across the family of 24 phase $\times$ metric contrasts, and all reported significant differences remain significant after correction.

8 Related Work

Automated specification inference sits at the intersection of formal methods, program analysis, and, more recently, large language models. The remainder of this section situates the present approach with respect to each of these strands.

From verification to inference. The theoretical foundations of this work lie in Hoare logic [27] and Dijkstra’s weakest-precondition calculus [15, 16]. Tools such as Boogie [3] and ESC/Java [8, 22] apply these formalisms to *verify* user-provided specifications, and OpenJML and KeY adopt a similar verify-not-generate stance. The closest precursor on the generation side is Houdini [21], which guesses candidate annotations from a fixed set of templates and prunes them by repeated calls to ESC/Java; the present approach extends this lineage by replacing the template guess with WP/SP-organised structural pattern matching and by extending the verification oracle to OpenJML with quantifier support. The present work inverts the verification problem, inferring contracts from code structure rather than checking given ones. This distinction matters in practice because manual specification remains the dominant cost in verification projects: in large-scale case studies it accounts for roughly 50% of total effort [1, 34, 40]. Automating the inference step targets the barrier identified by Zimmermann and Wehrheim [59] as the principal obstacle to lightweight specification adoption in modern development workflows.

Dynamic and static inference. Daikon [20] pioneered dynamic invariant detection by generalising from execution traces; its principal limitation is its dependence on test-suite quality, ~~since~~because invariants are “likely” rather than guaranteed and coverage gaps leave specifications incomplete. PreInfer [2] addresses this in part through symbolic analysis of path conditions collected from failing tests for C# (built on Microsoft’s Pex), but continues to require an execution infrastructure. By contrast, the approach described here operates purely statically—without test suites, execution traces, or an SMT solver—and therefore applies to any compilable Java codebase, including library code without an existing test suite. The corresponding trade-off is that heuristic pattern matching may miss specifications that would emerge from dynamic observation, particularly for complex numeric relationships.

Documentation-based approaches. A complementary line of work extracts specifications from natural-language documentation. Toradocu [25] and its successor Jdoctor [4] use natural-language processing to recover exception preconditions from Javadoc comments, ~~while~~whereas Pandita et al. [44] infer resource specifications from API documentation. Such approaches are effective when documentation is thorough

but silent on undocumented methods. The complementarity is quantified in Section 5: Jdoctor captures 25 exception preconditions that JML-Inferer misses (typically encoded in natural language), ~~while-whereas~~ JML-Inferer captures 37 that Jdoctor misses (undocumented in Javadoc). A practical workflow benefits from combining the two.

LLM-based specification inference. Large language models have recently been applied to specification inference [19, 39, 47, 50]. SpecGen [39] and the LLM-based approach of Endres et al. [19] prompt the model directly to emit formal contracts; Richter and Wehrheim [47] extend this to full pre/post pairs and report the resulting verifier false-alarm rates. Closest in target language to the present work, Teuber and Beckert [50] use LLMs to generate JML contracts for Java deductive verification. The comparison reported in Section 5 ~~exhibits a precision-recall trade-off relative to contrasts~~ direct LLM inference ~~÷ LLM-based inference achieves recall comparable to with JML-Inferer but substantially lower precision (81.3% versus 94.2%) and only along two axes that do not depend on a human-judged ground truth: methods covered (100% versus 99.0%, near-parity by construction) and run-to-run consistency (72.4% consistency across runs, because model outputs are not grounded in concrete code structure versus 100%, the deterministic advantage of pattern matching over sampled inference).~~ The same comparison motivates the probe-and-backport development methodology of Section 3.4: an LLM proposes candidate contracts, but a verifier filter and an agentic backport step are required before any proposal enters the engine’s repertoire, because the LLM’s plausibility judgement does not by itself meet the discharge bar.

LLM-based test generation and the oracle problem. LLM test generation is now an extensive subarea, recently surveyed in a systematic literature review by Zhang et al. [58] covering 115 publications. Foundational results include AthenaTest [52], which adapted transformer architectures to unit-test generation with focal context; CodaMOSA [38]; ChatTESTER [57]; CodeT [9]; and the empirical evaluation of Schäfer et al. [48]. Kang, Yoon, and Yoo [32] (LIBRO) demonstrated that LLMs can be effective few-shot testers when prompted with bug reports. The oracle problem in this setting has attracted concentrated attention. Dinella et al. [17] (TOGA) trained a neural model jointly to produce exceptional and assertion oracles, and Hossain and Dwyer [28] (TOGLL) showed that large general-purpose LLMs can produce stronger and more diverse oracles than the original neural baseline, detecting an order of magnitude more bugs. Konstantinou et al. [35] show that LLM-generated oracles tend to encode actual rather than expected program behaviour, motivating any approach that supplies the model with an externally grounded specification. Molinelli et al. [42] evaluate 13,866 LLM-generated oracles on an unbiased dataset of 135 Java projects and report a mean mutation score of 43% versus 45% for human-written oracles, providing a calibration point for the present results. Foster et al. [23] report industrial deployment of mutation-guided LLM test generation at Meta. Schäfer et al. [48] report a 70% compilation rate for LLM-generated tests; the specification-guided approach evaluated here raises this rate to 91.5%, suggesting that specifications constrain LLM outputs toward valid test code. Rather than positioning static analysis against LLMs, the present work shows that the two are synergistic: specifications inferred by static analysis improve LLM test-generation quality beyond what signatures or source code alone provide. The TOGA/TOGLL line of work is complementary in that it learns oracles from corpora, whereas the present approach derives them from program structure; the two could in principle be ensembled. Jiang et al. [31] survey LLMs for code generation more broadly.

Mutation testing as the evaluation methodology. Mutation testing remains the standard means of distinguishing tests that exercise behaviour from tests that merely cover code. Papadakis et al. [45] survey the field; PIT [12] provides the operator set used here. Recent work has begun to study LLMs and mutation testing in combination. Wang et al. [53] present a comprehensive empirical study of LLMs for mutation testing across 851 Java bugs, and Wang et al. [54] develop a mutation-guided LLM test generation technique,

reporting that 100% statement coverage can coexist with mutation scores as low as 4%—a quantitative motivation for the mutation-based evaluation adopted in this article.

Specification-based testing. Established test-generation tools—EvoSuite [24], Randoop [43], and Korat [5]—achieve high structural coverage but address the oracle problem only partially. Design by Contract [41] and JML [36, 37] address it by embedding expected behaviour in specifications, but require manual specification effort. Industrial static analysers such as Facebook Infer [7] and FindBugs [29] demonstrate the scalability of static analysis on large codebases, but focus on bug detection rather than specification generation. The structural distinction relevant to the present article is the direction of the arrow: existing JML-aware tools (including JMLUnit, EvoSuite when given JML, Randoop, and Korat) *consume* formal specifications to generate tests, whereas this work *infers* the specifications they consume. The two roles are complementary halves of a single pipeline; JML-Inferer supplies the upstream piece that the established tools have always required as input. The method categorisation taxonomy adopted here extends Dragan et al.’s method stereotypes [18] to identify which categories benefit most from inferred specifications.

9 Conclusion

This article asked whether specifications help LLMs write better unit tests. Across 312 methods from Apache Commons Lang the answer is yes, and the effect is large.

1. *Specifications substantially improve test quality.* LLM-generated tests guided by specifications produce 272% more tests and achieve a mutation score 40.7 pp higher than signature-only baselines ($p < 0.001$, Cohen’s $d = 2.41$, 95% bootstrap CI [2.08, 2.79]).
2. *The effect varies systematically across method categories.* Control-flow and utility methods benefit most; simpler accessors show modest gains, primarily because their signature-only baselines are already near the achievable ceiling.
3. *Specifications close most, but not all, of the gap to source code.* Full source access (P4) attains the highest absolute mutation score (94.8%); the specification phase reaches 68.2%, well above the signature-only baseline of 27.5%, while remaining materially more compact than full source.

The specifications used in this study were produced automatically by JML-Inferer, a heuristic static analysis system that ~~attains a precision and recall of 94.2% and 89.3% for preconditions and 87.6% and 78.1% for postconditions on the same corpus~~, with each inferred clause discharged emits non-trivial specifications for 99.0% of the corpus and discharges 92.9% of inferred clauses through OpenJML’s Extended Static Checker(~~92.9% of clauses discharged~~). The system is the means by which the empirical question above could be answered at scale, and addresses the principal barrier to specification adoption—manual effort [26, 59]—while remaining complementary to documentation-based approaches [4].

The result above is the headline use of inferred specifications, but it is not the only use. The same artefacts function as oracle-bearing input for any test-generation tool that consumes JML; as the callee contracts that compositional verification needs in order to check calling code without re-analysing the entire transitive dependency graph; and as a machine-readable contract that AI coding agents can consume when reasoning about a library, particularly one that postdates the model’s training cut-off. The agentic-programming case is itself the source of the development methodology used to build JML-Inferer: candidate JML produced by an LLM (or by hand) is verified with OpenJML, validated examples become probe tests, and an agentic coding assistant extends the inferer to make those probes pass. The same workflow is available to users of the tool who need it to recognise a new pattern in their own code.

The findings reported here motivate a planned follow-up study targeting service-boundary code. Methods that call REST endpoints or RPC stubs are precisely the setting in which the oracle problem is most acute: the implementation typically delegates to an external service, signatures convey nothing about status codes or retry semantics, and signature-only LLM test generation collapses into mock-the-call assertions. Whether inferred specifications retain or amplify the gain reported here in that setting is the central question of the planned follow-up. Further directions include strengthening loop invariant inference through machine-learning [55] or hybrid static–dynamic techniques [20], explicit treatment of object-oriented constructs (inheritance, polymorphism, class invariants), extension to languages beyond Java, ~~and~~ interactive refinement under developer guidance [14], and recovery of abstract-contract over-approximations in cases where the implementation makes a choice that the API leaves open (sort stability for duplicates being the canonical case)—a class of specification not derivable from a single implementation in isolation. The replication package, including all source code, data, generated test suites, and analysis scripts, accompanies this article.

Data Accessibility Statement

A complete replication package is available at <https://github.com/ziggyfish/jml-inferrer>. The package contains the tool source code (Apache 2.0 licence), the 312-method Apache Commons Lang 3.14 dataset with category labels, all inferred specifications (in both annotation and JML comment form), generated test suites for phases P1–P4 (five runs per phase per method, 6,240 LLM invocations in total), raw PIT mutation testing logs, the statistical analysis scripts (Python; SciPy 1.13, statsmodels 0.14), the OpenJML discharge transcripts, the prompt templates, and the ~~two-rater manual validation labels and discussion notes~~probe-and-backport test corpus that gates inference-engine changes. The accompanying containerised toolchain reproduces the full pipeline on Linux, macOS, and Windows hosts.

Acknowledgements

This research was supported by the University of Queensland Cyber initiative. The authors thank David Cok for technical correspondence on OpenJML.

Conflict of Interest

The authors declare no conflict of interest.

Author Contributions (CRediT)

Brendan Edmonds: Conceptualisation, Methodology, Software, Validation, Investigation, Data Curation, Writing – Original Draft, Visualisation. **Mark Utting:** Writing – Review & Editing, Supervision.

ORCID

Brendan Edmonds <https://orcid.org/0009-0007-9067-3186>

Mark Utting <https://orcid.org/0000-0001-6859-3060>

References

- [1] June Andronick, Ross Jeffery, Gerwin Klein, Rafal Kolanski, Mark Staples, He Zhang, and Liming Zhu. Large-scale formal verification in practice: A process perspective. In *34th International Conference on Software Engineering (ICSE)*, pages 1002–1011, 2012. doi: 10.1109/ICSE.2012.6227120.
- [2] Angello Astorga, Siwakorn Srisakaokul, Xusheng Xiao, and Tao Xie. PreInfer: Automatic inference of preconditions via symbolic analysis. In *48th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN)*, pages 678–689. IEEE, 2018. doi: 10.1109/DSN.2018.00074.
- [3] Mike Barnett and K. Rustan M. Leino. Weakest-precondition of unstructured programs. In *Workshop on Program Analysis for Software Tools and Engineering (PASTE)*, pages 82–87, 2005. doi: 10.1145/1108792.1108813.
- [4] Arianna Blasi, Alberto Goffi, Konstantin Kuznetsov, Alessandra Gorla, Michael D. Ernst, Mauro Pezzè, and Sergio Delgado Castellanos. Translating code comments to procedure specifications. In *Proceedings of the 27th ACM SIGSOFT International Symposium on Software Testing and Analysis, ISSTA '18*, pages 242–253. ACM, July 2018. doi: 10.1145/3213846.3213872. URL <http://dx.doi.org/10.1145/3213846.3213872>.
- [5] Chandrasekhar Boyapati, Sarfraz Khurshid, and Darko Marinov. Korat: Automated testing based on Java predicates. In *International Symposium on Software Testing and Analysis (ISSTA)*, pages 123–133, 2002. doi: 10.1145/566172.566191.
- [6] Cristian Cadar, Daniel Dunbar, and Dawson Engler. KLEE: Unassisted and automatic generation of high-coverage tests for complex systems programs. In *USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, pages 209–224, 2008.
- [7] Cristiano Calcagno, Dino Distefano, Jérémy Dubreil, Dominik Gabi, Pieter Hooimeijer, Martino Luca, Peter O’Hearn, Irene Papakonstantinou, Jim Purbrick, and Dulma Rodriguez. Moving fast with software verification. In *NASA Formal Methods Symposium (NFM)*, pages 3–11, 2015. doi: 10.1007/978-3-319-17524-9_1.
- [8] Patrice Chalin, Joseph R. Kiniry, Gary T. Leavens, and Erik Poll. Beyond assertions: Advanced specification and verification with JML and ESC/Java2. In *Formal Methods for Components and Objects (FMCO 2005)*, volume 4111 of *LNCS*, pages 342–363. Springer, 2006. doi: 10.1007/11804192_16.
- [9] Bei Chen, Fengji Zhang, Anh Nguyen, Daoguang Zan, Zeqi Lin, Jian-Guang Lou, and Weizhu Chen. CodeT: Code generation with generated tests. In *International Conference on Learning Representations (ICLR)*, 2023.
- [10] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, et al. Evaluating large language models trained on code, 2021. Preprint.
- [11] David R. Cok. OpenJML: Software verification for Java 7 using JML, OpenJDK, and Eclipse. In *1st Workshop on Formal Integrated Development Environment (F-IDE)*, volume 149 of *EPTCS*, pages 79–92, 2014. doi: 10.4204/EPTCS.149.8.
- [12] Henry Coles. PIT: Mutation testing system for Java. <https://pitest.org>, 2016. Accessed: 2025-01-15.

- [13] Patrick Cousot and Radhia Cousot. Abstract interpretation: A unified lattice model for static analysis of programs by construction or approximation of fixpoints. In *ACM Symposium on Principles of Programming Languages (POPL)*, pages 238–252, 1977. doi: 10.1145/512950.512973.
- [14] Patrick Cousot, Radhia Cousot, and Francesco Logozzo. Precondition inference from intermittent assertions and application to contracts on collections. In *International Conference on Verification, Model Checking, and Abstract Interpretation (VMCAI)*, pages 150–168, 2011. doi: 10.1007/978-3-642-18275-4_12.
- [15] Edsger W. Dijkstra. Guarded commands, nondeterminacy and formal derivation of programs. *Communications of the ACM*, 18(8):453–457, 1975. doi: 10.1145/360933.360975.
- [16] Edsger W. Dijkstra. *A Discipline of Programming*. Prentice-Hall, Englewood Cliffs, NJ, USA, 1976.
- [17] Elizabeth Dinella, Gabriel Ryan, Todd Mytkowicz, and Shuvendu K. Lahiri. TOGA: A neural method for test oracle generation. In *44th International Conference on Software Engineering (ICSE)*, pages 2130–2141, 2022. doi: 10.1145/3510003.3510141.
- [18] Natalia Dragan, Michael L. Collard, and Jonathan I. Maletic. Reverse engineering method stereotypes. In *22nd IEEE International Conference on Software Maintenance (ICSM)*, pages 24–34, 2006. doi: 10.1109/ICSM.2006.68.
- [19] Madeline Endres, Sarah Fakhoury, Saikat Chakraborty, and Shuvendu K. Lahiri. Can large language models transform natural language intent into formal method postconditions? *Proceedings of the ACM on Software Engineering (PACMSE)*, 1(FSE):1889–1912, 2024. doi: 10.1145/3660791.
- [20] Michael D. Ernst, Jeff H. Perkins, Philip J. Guo, Stephen McCamant, Carlos Pacheco, Matthew S. Tschantz, and Chen Xiao. The Daikon system for dynamic detection of likely invariants. *Science of Computer Programming*, 69(1–3):35–45, 2007. doi: 10.1016/j.scico.2007.01.015.
- [21] Cormac Flanagan and K. Rustan M. Leino. Houdini, an annotation assistant for ESC/Java. In *International Symposium of Formal Methods Europe (FME)*, volume 2021 of *LNCS*, pages 500–517. Springer, 2001. doi: 10.1007/3-540-45251-6_29.
- [22] Cormac Flanagan, K. Rustan M. Leino, Mark Lillibridge, Greg Nelson, James B. Saxe, and Raymie Stata. Extended static checking for Java. In *ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, pages 234–245, 2002. doi: 10.1145/512529.512558.
- [23] Christopher Foster, Abhishek Gulati, Mark Harman, Inna Harper, Ke Mao, Jillian Ritchey, Hervé Robert, and Shubho Sengupta. Mutation-guided LLM-based test generation at Meta. In *Companion Proceedings of the 33rd ACM International Conference on the Foundations of Software Engineering (FSE Industry)*, 2025. doi: 10.1145/3696630.3728544.
- [24] Gordon Fraser and Andrea Arcuri. EvoSuite: Automatic test suite generation for object-oriented software. In *19th ACM SIGSOFT Symposium and 13th European Conference on Foundations of Software Engineering (ESEC/FSE)*, pages 416–419, 2011. doi: 10.1145/2025113.2025179.
- [25] Alberto Goffi, Alessandra Gorla, Michael D. Ernst, and Mauro Pezzè. Automatic generation of oracles for exceptional behaviors. In *International Symposium on Software Testing and Analysis (ISSTA)*, pages 213–224, 2016. doi: 10.1145/2931037.2931061.
- [26] Anthony Hall. Seven myths of formal methods. *IEEE Software*, 7(5):11–19, 1990. doi: 10.1109/52.57887.

- [27] C. A. R. Hoare. An axiomatic basis for computer programming. *Communications of the ACM*, 12(10): 576–580, 1969. doi: 10.1145/363235.363259.
- [28] Soneya Binta Hossain and Matthew B. Dwyer. TOGLL: Correct and strong test oracle generation with LLMs. In *Proceedings of the IEEE/ACM 47th International Conference on Software Engineering (ICSE)*, pages 1475–1487, 2025. doi: 10.1109/ICSE55347.2025.00098.
- [29] David Hovemeyer and William Pugh. Finding bugs is easy. In *ACM SIGPLAN Conference on Object-Oriented Programming, Systems, Languages, and Applications (OOPSLA)*, pages 92–106, 2004. doi: 10.1145/1028664.1028717.
- [30] JavaParser Team. JavaParser: Java parser and abstract syntax tree. <https://javaparser.org>, 2024. Accessed: 2025-01-15.
- [31] Juyong Jiang, Fan Wang, Jiasi Shen, Sungju Kim, and Sunghun Kim. A survey on large language models for code generation. *ACM Transactions on Software Engineering and Methodology*, 2025. doi: 10.1145/3747588.
- [32] Sungmin Kang, Juyeon Yoon, and Shin Yoo. Large language models are few-shot testers: Exploring LLM-based general bug reproduction. In *45th IEEE/ACM International Conference on Software Engineering (ICSE)*, pages 2312–2323, 2023. doi: 10.1109/ICSE48619.2023.00194.
- [33] James C. King. Symbolic execution and program testing. *Communications of the ACM*, 19(7):385–394, 1976. doi: 10.1145/360248.360252.
- [34] Gerwin Klein, June Andronick, Kevin Elphinstone, Toby C. Murray, Thomas Sewell, Rafal Kolanski, and Gernot Heiser. Comprehensive formal verification of an OS microkernel. *ACM Transactions on Computer Systems*, 32(1):2:1–2:70, 2014. doi: 10.1145/2560537.
- [35] Michael Konstantinou, Renzo Degiovanni, and Mike Papadakis. Do LLMs generate test oracles that capture the actual or the expected program behaviour? In *2025 IEEE Conference on Software Testing, Verification and Validation (ICST)*, 2025.
- [36] Gary T. Leavens, Albert L. Baker, and Clyde Ruby. Preliminary design of JML: A behavioral interface specification language for Java. *ACM SIGSOFT Software Engineering Notes*, 31(3):1–38, 2006. doi: 10.1145/1127878.1127884.
- [37] Gary T. Leavens et al. JML reference manual. <http://www.jmlspecs.org>, 2013. Accessed: 2025-01-15.
- [38] Caroline Lemieux, Jeevana Priya Inala, Shuvendu K. Lahiri, and Siddhartha Sen. CodaMOSA: Escaping coverage plateaus in test generation with pre-trained large language models. In *45th International Conference on Software Engineering (ICSE)*, pages 919–931, 2023. doi: 10.1109/ICSE48619.2023.00085.
- [39] Lezhi Ma, Shangqing Liu, Yi Li, Xiaofei Xie, and Lei Bu. SpecGen: Automated generation of formal program specifications via large language models. In *Proceedings of the IEEE/ACM 47th International Conference on Software Engineering (ICSE)*, 2025. doi: 10.1109/ICSE55347.2025.00129.
- [40] Daniel Matichuk, Toby Murray, June Andronick, Ross Jeffery, Gerwin Klein, and Mark Staples. Empirical study towards a leading indicator for cost of formal software verification. In *37th IEEE International Conference on Software Engineering (ICSE)*, pages 722–732, 2015. doi: 10.1109/ICSE.2015.76.

- [41] Bertrand Meyer. Applying “design by contract”. *Computer*, 25(10):40–51, 1992. doi: 10.1109/2.161279.
- [42] Davide Molinelli, Luca Di Grazia, Alberto Martin-Lopez, Michael D. Ernst, and Mauro Pezzè. Do LLMs generate useful test oracles? an empirical study with an unbiased dataset. In *40th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 2025.
- [43] Carlos Pacheco, Shuvendu K. Lahiri, Michael D. Ernst, and Thomas Ball. Feedback-directed random test generation. In *29th International Conference on Software Engineering (ICSE)*, pages 75–84, 2007. doi: 10.1109/ICSE.2007.37.
- [44] Rahul Pandita, Xusheng Xiao, Hao Zhong, Tao Xie, Stephen Oney, and Amit Paradkar. Inferring method specifications from natural language API descriptions. In *34th International Conference on Software Engineering (ICSE)*, pages 815–825, 2012. doi: 10.1109/ICSE.2012.6227137.
- [45] Mike Papadakis, Marinos Kintis, Jie Zhang, Yue Jia, Yves Le Traon, and Mark Harman. Mutation testing advances: An analysis and survey. *Advances in Computers*, 112:275–378, 2019. doi: 10.1016/bs.adcom.2018.03.015.
- [46] Dennis K. Peters and David Lorge Parnas. Using test oracles generated from program documentation. *IEEE Transactions on Software Engineering*, 24(3):161–173, 1998. doi: 10.1109/32.667877.
- [47] Cedric Richter and Heike Wehrheim. Beyond postconditions: Can large language models infer formal contracts for automatic software verification?, 2025. Preprint, under submission.
- [48] Max Schäfer, Sarah Nadi, Aryaz Eghbali, and Frank Tip. An empirical evaluation of using large language models for automated unit test generation. *IEEE Transactions on Software Engineering*, 50(1):85–105, 2024. doi: 10.1109/TSE.2023.3334955.
- [49] Jonathan Sillito, Gail C. Murphy, and Kris De Volder. Asking and answering questions during a programming change task. *IEEE Transactions on Software Engineering*, 34(4):434–451, 2008. doi: 10.1109/TSE.2008.26.
- [50] Samuel Teuber and Bernhard Beckert. Next steps in LLM-supported Java verification. In *ICSE Workshop on Neuro-Symbolic SE (NSE)*, 2025.
- [51] Frank Tip, Peter F. Sweeney, Chris Laffra, Aldo Eisma, and David Streeter. Practical extraction techniques for Java. *ACM Transactions on Programming Languages and Systems*, 24(6):625–666, 2002. doi: 10.1145/586088.586090.
- [52] Michele Tufano, Dawn Drain, Alexey Svyatkovskiy, Shao Kun Deng, and Neel Sundaresan. Unit test case generation with transformers and focal context, 2020. Preprint.
- [53] Bo Wang, Mingda Chen, Ming Deng, Youfang Lin, Mark Harman, Mike Papadakis, and Jie M. Zhang. A comprehensive study on large language models for mutation testing. *ACM Transactions on Software Engineering and Methodology*, 2025. doi: 10.1145/3805038.
- [54] Guancheng Wang, Qinghua Xu, Lionel Briand, and Kui Liu. Mutation-guided unit test generation with a large language model, 2025. Preprint.
- [55] Yi Wei, Carlo A. Furia, Nikolay Kazmin, and Bertrand Meyer. Inferring better contracts. In *33rd International Conference on Software Engineering (ICSE)*, pages 191–200, 2011. doi: 10.1145/1985793.1985820.

- 1000 [56] [Claes Wohlin, Per Runeson, Martin Höst, Magnus C. Ohlsson, Björn Regnell, and Anders Wesslén.](#)
1001 [Experimentation in Software Engineering.](#) Springer, 2012. doi: 10.1007/978-3-642-29044-2.
- 1002 [57] [Zhiqiang Yuan, Mingwei Liu, Shiji Ding, Kaixin Wang, Yixuan Chen, Xin Peng, and Yiling Lou.](#)
1003 [Evaluating and improving ChatGPT for unit test generation.](#) *Proceedings of the ACM on Software*
1004 [Engineering](#), 1(FSE):1703–1726, 2024. doi: 10.1145/3660783.
- 1005 [58] [Quanjun Zhang, Chunrong Fang, Siqi Gu, Ye Shang, Zhenyu Chen, and Liang Xiao.](#) Large language
1006 [models for unit testing: A systematic literature review, 2025.](#) Preprint.
- 1007 [59] [Daniel Zimmermann and Heike Wehrheim.](#) Increasing the practicality of formal methods for devops
1008 [with lightweight specifications.](#) In *Formal Methods for Industrial Critical Systems (FMICS)*, volume
1009 [11815 of LNCS](#), pages 3–20. Springer, 2019. doi: 10.1007/978-3-030-30942-8_1.

Algorithm 1 Specification Inference via Pattern Matching**Require:** Method AST node M **Ensure:** Preconditions Pre , Postconditions $Post$, LoopInvariants LI

```

1:  $Pre \leftarrow \emptyset; Post \leftarrow \emptyset; LI \leftarrow \emptyset$ 
2: {Infer preconditions from early guards}
3: for each statement  $S$  in  $M.body$  do
4:   if  $S$  is null check if ( $p == null$ ) throw/return then
5:      $Pre \leftarrow Pre \cup \{p \neq null\}$ 
6:   else if  $S$  is range check if ( $p < 0 \parallel p \geq n$ ) throw then
7:      $Pre \leftarrow Pre \cup \{p \geq 0, p < n\}$ 
8:   end if
9: end for
10: {Infer postconditions from return statements}
11: for each return  $e$  in  $M.body$  do
12:   if  $e$  is field access  $this.f$  then
13:      $Post \leftarrow Post \cup \{\backslash result == this.f\}$ 
14:   else if  $e$  is new object  $new T(\dots)$  then
15:      $Post \leftarrow Post \cup \{\backslash result \neq null\}$ 
16:   else if  $e$  involves  $\backslash old$  pattern then
17:      $Post \leftarrow Post \cup \{\text{derive relationship}\}$ 
18:   end if
19: end for
20: {Infer branch-conditional postconditions via symbolic paths}
21: for each return  $r$  reached under path condition  $\pi$  (if/else or ternary) do
22:   simplify  $\pi$  algebraically
23:    $Post \leftarrow Post \cup \{\pi \implies spec(r)\}$ 
24: end for
25: for each conditional field assignment  $this.f = e$  under path  $\pi$  do
26:    $Post \leftarrow Post \cup \{\pi \implies this.f == e[\backslash old/.]\}$ 
27: end for
28: {Infer loop invariants}
29: for each loop  $L$  in  $M.body$  do
30:    $LI \leftarrow LI \cup \text{InferLoopInvariant}(L)$ 
31: end for
32: return ( $Pre, Post, LI$ )

```

P1 — Signature only:

```
public void add(Number operand);
```

P2 — Signature + edge-case checklist (identical block for every method):

```
public void add(Number operand);
%DIF >
// Test-design checklist:
// - null for each reference parameter
// - empty/single-element/maximum-size collections, arrays, strings
// - boundary numeric values (0, +/-1, Integer.MIN_VALUE,
//   Integer.MAX_VALUE, and adjacent integers)
// - floating-point specials (NaN, +/-Infinity, +/-0.0)
// - unicode boundary code points (for char/String parameters)
// - overflow-prone arithmetic combinations
```

P3 — Signature + inferred JML specification:

```
//@ requires operand != null;
//@ assignable this.value;
//@ ensures this.value == \old(this.value) + operand.intValue();
public void add(Number operand);
```

P4 — Full source code (upper-bound baseline):

```
public void add(Number operand) {
    this.value += operand.intValue();
}
```

Listing 1: Worked example of the four phase inputs supplied to the LLM, applied to `MutableInt.add(Number)` from Apache Commons Lang. The signature is held constant across phases; P2 adds a method-agnostic edge-case checklist, P3 adds the JML contract inferred by JML-Inferer, and P4 substitutes the full source body.