

Week 3 - Notes

John Zimmerman

2026:02:05

Contents

1	Element Review	1
1.1	Block-Level Elements	1
1.2	Inline Elements	2
2	Organizing Page Content	2
2.1	Head, Header, and Headings	3
3	Block-Level Element Examples	3
3.1	HTML Headings	3
3.2	Paragraph	3
3.3	Horizontal Rule & Line Break Elements	3
3.4	Preformatted text element	4
3.5	Lists	4
3.6	Description List	4
4	Inline Element Examples	5
4.1	Links and Images	5

1 Element Review

First, lets review on the difference between **block-level elements** and **in-line elements**.

1.1 Block-Level Elements

The important details that will help you visually identify **block-level elements** are:

- Renders content on a new line
- Renders content left-justified
- Renders content to expand the entire width of the document by creating a box around it with padding.
- Meant to structure the main parts of your page by dividing up content

1.2 Inline Elements

Sometimes called text-level or phrasing elements. These are the behaviors inherent to **inline Elements**:

- Does **not** render content on a new line.
- Renders in the flow of text by default (only takes up the space of the content it surrounds).
- Inline elements are meant to differentiate parts of the content or to give it a particular function or meaning.
- Inline elements usually comprise of a single or few words.

2 Organizing Page Content

`<nav></nav>` *Container for the navigation. Often the navigation contains an unordered list for the navbar elements.*

`<header></header>` *Container for introductory material like the logo, webpage title, and navigation.*

`<footer></footer>` *Container for end content, can also be used at the end of articles, asides, headers, or nav elements.*

`<main></main>` *Container for the primary content. Only one main element is allowed per webpage and cannot be a child of an article, aside, footer, header, or nav content.*

`<aside></aside>` *Container for complementary content. Often used a "sidebar" to pull quotes, background information, or related links.*

`<section></section>` *Defines a general content area. Used to divide up related content on the page. Often sections have headings associated with them.*

`<article></article>` *Defines stand-alone content. Often used for magazine articles, blog posts, or comments. This element must have a heading element.*

2.1 Head, Header, and Headings

The head element is where the metadata is stored in a page. Header is the top of document, more for organizing a document. A heading indicates the hierarchy of a page.

3 Block-Level Element Examples

3.1 HTML Headings

HTML has a "0 to many" hierarchy for heading tags. `h1` is a main heading, everything else is a sub-heading. Best practices for HTML is to always use headings in order. For example, if a sub-heading needs to be bigger than its parent heading, you don't change the element to match the heading. You use CSS to modify it visually.

```
<h1>This is a level 1 heading<\h1>
<h2>This is a level 2 heading<\h2>
```

3.2 Paragraph

Paragraphs are a block-level element. That means it will render on a new line like every other block-level element. Paragraph elements can contain **inline elements** like an image or span, but it cannot contain another block-level element.

```
<p>
  This is a paragraph.
<\p>
```

3.3 Horizontal Rule & Line Break Elements

The **horizontal rule** and **line break** feel similar, especially because they are both *self-closing* tags that are meant to separate content, but the line break element has some distinct features that differentiate it from block-level elements.

```
<!-- This is a Horizontal Rule --!>
<hr>
<!-- This is a line break --!>
<br>
```

- The horizontal rule is a block-level element that creates an empty container meant to separate document sections.
- The line break isn't a block-level or inline element. It's basically just a new-line character that doesn't create a box, and can go anywhere it wants, including inside the **paragraph element**.

3.4 Preformatted text element

The preformatted text element tells the DOM to render any space or line breaks. Without it, the DOM will ignore whitespace.

```
<pre>
    Inside this container, the DOM will respect whitespace. It will display the text as
    spaces, and line-returns. The default behavior will display the text in this contain
</pre>
```

3.5 Lists

Unordered List A list with bullet points:

```
<ul>
    <li>List item</li>
</ul>
```

Ordered List A list with numbers points

```
<ol>
    <li>List item</li>
</ol>
```

3.6 Description List

The **description list** is another list structure where it focuses on having key-value pairs. The idea is you have a *term* and a connected *description*.

```
<dl>
    <dt>Term</dt>
    <dd>Description</dd>
</dl>
```

4 Inline Element Examples

4.1 Links and Images

TBC