

```
<!DOCTYPE html>
<html lang="ar">
  <head>
    <meta charset="UTF-8">
    <meta name="viewport"
content="width=device-width, initial-
scale=1.0">
    <title>آلة حاسبة بروف</title>
    <style>
      body { display: flex; justify-content:
center; align-items: center; height: 100vh;
background: #121212; font-family: sans-
serif; margin: 0; }
      .calculator { background: #1e1e1e;
padding: 20px; border-radius: 20px; box-
shadow: 0px 10px 30px rgba(0,0,0,0.5);
width: 300px; }
      #display { width: 100%; height: 60px;
background: #2d2d2d; border: none;
border-radius: 10px; color: #fff; font-size:
2rem; text-align: right; padding: 10px; box-
```

```
sizing: border-box; margin-bottom: 20px; }
.buttons { display: grid; grid-template-
columns: repeat(4, 1fr); gap: 10px; }
    button { padding: 20px; font-size:
1.5rem; border: none; border-radius: 10px;
cursor: pointer; background: #333; color:
                                #fff; }
    button:active { filter: brightness(1.2); }
    .operator { background: #ff9f0a;
                                color: white; }
    .clear { background: #a5a5a5; color:
                                black; }
</style>
</head>
<body>
```

```
    <div class="calculator">
<input type="text" id="display" readonly>
    <div class="buttons">
        <button class="clear"
onclick="clearDisplay()">C</button>
```

```
<button onclick="appendValue('/')"  
    class="operator">/</button>  
<button onclick="appendValue('*)"  
    class="operator">*</button>  
<button onclick="appendValue('-)"  
    class="operator">-</button>  
    <button  
onclick="appendValue('7')">7</button>  
    <button  
onclick="appendValue('8')">8</button>  
    <button  
onclick="appendValue('9')">9</button>  
    <button onclick="appendValue('+)"  
        class="operator">+</button>  
    <button  
onclick="appendValue('4')">4</button>  
    <button  
onclick="appendValue('5')">5</button>  
    <button  
onclick="appendValue('6')">6</button>  
    <button onclick="calculate()"
```

```

style="grid-row: span 2; height: 100%;"
      class="operator">=</button>
      <button
onclick="appendValue('1')">1</button>
      <button
onclick="appendValue('2')">2</button>
      <button
onclick="appendValue('3')">3</button>
      <button onclick="appendValue('0')
style="grid-column: span 2;">0</button>
      <button onclick="appendValue('.')">.</
      button>
      </div>
      </div>

      <script>
          const display =
document.getElementById('display');
          function appendValue(val) {
              display.value += val; }
function clearDisplay() { display.value =

```

```
        { ;"  
function calculate() { try { display.value  
    = eval(display.value); } catch {  
    display.value = 'خطأ'; } }  
    </script>  
  
    </body>  
    </html>
```