



CSM3023 WEB BASED APPLICATION DEVELOPMENT (K1)

**BACHELOR OF COMPUTER SCIENCE (MOBILE COMPUTING) WITH
HONORS**

SEMESTER 2 2023/2024

LAB 6 – JSP: Saving and Retrieving Data from Database

Prepared by:

MUHAMMAD HAZIQ AIMAN BIN MUSTAFA (S67978)

Task 1:

Coding:

```
<%page contentType="text/html" pageEncoding="UTF-8"%>
<%page language="java"%>
<%page import="java.sql.*"%>
<@contentType html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>JSP Page</title>
</head>
<body>
<h1>Lab 6 - Task 1 - Sample Insertion records into MySQL through JSP's page</h1>
<%
    int result;

    //Step 1: Load JDBC Driver...
    Class.forName("com.mysql.cj.jdbc.Driver");
    out.println("Step 1: MySQL driver loaded...!");
    %>
<br>
<%
    //Step 2: Establish the connection...
    String myURL = "jdbc:mysql://localhost:3306/csm3021_lab6";
    Connection myConnection = DriverManager.getConnection(myURL, "root", "admin");
    out.println("Step 2: Database is connected...!");
    %>
<br>
<%
    //Step 3: Create a PreparedStatement object...
    out.println("Step 3: Prepared Statement created...!");

    //Prepared SQL Query as a String...
    String sInsertQuery = "INSERT INTO first_table VALUES (?)";

    //Call method PreparedStatement
    PreparedStatement myPS = myConnection.prepareStatement(sInsertQuery);
    %>
    <br>
    <%
        //Assign each value to respective columns for Book's table.. (2-Create)
        out.println("Step 4: Perform insertion of record..!");
        String name = "Welcome to access MySQL database with JSP....!";
        myPS.setString(1, name);

        result = myPS.executeUpdate();

        if (result > 0) {
            %>
            <br>
            <%
                out.println("Step5: Close data connection...!");
                out.println(" ");
                out.println("Database connection is closed...!");
                out.print("<br>" + "The record : (" + name + ") is successfully created...!" + "<br>");
            }
            //Step 5: Close database connection...!
            myConnection.close();
        }
    %>
</body>
</html>
```

Output:

Lab 6 - Task 1 - Sample Insertion records into MySQL through JSP's page

Step 1: MySQL driver loaded...!

Step 2: Database is connected..!

Step 3: Prepared Statements created...!

Step 4: Perform insertion of record..!

Step5: Close data connection...! Database connection is closed...!

The record : (Welcome to access MySQL database with JSP....!) is successfully created...!

	name
▶	Welcome to access MySQL database with JSP....!
	Welcome to access MySQL database with JSP....!
	Welcome to access MySQL database with JSP....!
	Welcome to access MySQL database with JSP....!

Task 2:

Coding:

insertAuthor.jsp

```

6 <!--page contentType="text/html" pageEncoding="UTF-8"%-->
7 <!DOCTYPE html>
8 <html>
9 <head>
10 <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
11 <title>Semesta Kata</title>
12 </head>
13 <body>
14 <!--Task 6 - Task 2 - Perform creating and retrieving records via JSP page-->
15 <fieldset>
16 <legend>Author Registration</legend>
17 <form action="processAuthor.jsp" method="post">
18 <table>
19 <tr>
20 <td>
21 <label for="author">Author No</label>
22 </td>
23 <td>
24 <input type="text" id="author" name="author" placeholder="E.g. Uxxxxxx">
25 </td>
26 </tr>
27 <tr>
28 <td>
29 <label for="name">Name</label>
30 </td>
31 <td>
32 <input type="text" id="NAME" name="NAME" placeholder="Enter your name">
33 </td>
34 </tr>
35 <tr>
36 <td>
37 <label for="address">Address</label>
38 </td>
39 <td>
40 <input type="text" id="address" name="address" placeholder="Enter your address">
41 </td>
42 </tr>
43 <tr>
44 <td>
45 <label for="city">City</label>
46 </td>
47 <td>
48 <input type="text" id="city" name="city" placeholder="Enter your city">
49 </td>
50 </tr>
51 <tr>
52 <td>
53 <label for="state">State</label>
54 </td>
55 <td>
56 <input type="text" id="state" name="state" placeholder="Enter your state">
57 </td>
58 </tr>
59 <tr>
60 <td>
61 <label for="zip">Zip</label>
62 </td>
63 <td>
64 <input type="text" id="zip" name="zip" placeholder="Enter your zip">
65 </td>
66 </tr>
67 <tr>
68 <td>
69 <button type="submit" value="Submit">Submit</button>
70 <button type="reset" value="Reset">Cancel</button>
71 </td>
72 </tr>
73 </table>
74 </form>
75 </fieldset>
76 <footer><p>scoppy: 2024-Haiziq Aiman</p></footer>
77 </html>

```

Author.java

```

11 public class Author {
12     private String authno;
13     private String NAME;
14     private String address;
15     private String city;
16     private String state;
17     private String zip;
18
19     public String getAuthno() {
20         return authno;
21     }
22
23     public void setAuthno(String authno) {
24         this.authno = authno;
25     }
26
27     public String getName() {
28         return NAME;
29     }
30
31     public void setName(String NAME) {
32         this.NAME = NAME;
33     }
34
35     public String getAddress() {
36         return address;
37     }
38
39     public void setAddress(String address) {
40         this.address = address;
41     }
42
43     public String getCity() {
44         return city;
45     }
46
47     public void setCity(String city) {
48         this.city = city;
49     }
50
51     public String getState() {
52         return state;
53     }
54
55     public void setState(String state) {
56         this.state = state;
57     }
58
59     public String getZip() {
60         return zip;
61     }
62
63     public void setZip(String zip) {
64         this.zip = zip;
65     }
66
67
68
69

```

processAuthor.jsp

```
<!--page contentType="text/html" pageEncoding="UTF-8"%-->
<!--page language="java"%-->
<!--page import="java.sql.*"%-->
<!--@csrf token-->
</html>

<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>JSP Page</title>
</head>
<body>
<!--Lab 6 - Task 1 - Perform and retrieving records via JSP page-->
<jsp:useBean id="myAuthor" class="lab6.com.Author" scope="request"/>

<jsp:setProperty name="myAuthor" property="*"/>

<!--
int result;
Class.forName("com.mysql.cj.jdbc.Driver");

String myURL = "jdbc:mysql://localhost:3306/csm3023_lab6";
Connection myConnection = DriverManager.getConnection(myURL, "root", "admin");

String sqlInsertQuery = "INSERT INTO author(authno, NAME, address, city, state, zip) VALUES(?, ?, ?, ?, ?, ?)";

PreparedStatement myPS = myConnection.prepareStatement(sqlInsertQuery);

myPS.setString(1, myAuthor.getAuthno());
myPS.setString(2, myAuthor.getNAME());
myPS.setString(3, myAuthor.getAddress());
myPS.setString(4, myAuthor.getCity());
myPS.setString(5, myAuthor.getState());
myPS.setString(6, myAuthor.getZip());

result = myPS.executeUpdate();
if (result > 0) {
    out.println("Record successfully added into Author table...!");
    out.print("<p> + Record with author no " + myAuthor.getAuthno()
    + " successfully created..!" + "</p>");
    out.print("<p> + Details of record are: " + "</p>");
    out.print("<p>Name : " + myAuthor.getNAME() + "</p>");
    out.print("<p>Address : " + myAuthor.getAddress() + "</p>");
    out.print("<p>City : " + myAuthor.getCity() + "</p>");
    out.print("<p>State : " + myAuthor.getState() + "</p>");
    out.print("<p>Zip : " + myAuthor.getZip() + "</p>");
}

//Step5: close database connection...!
System.out.println("Step 5: Close database connection...!");
myConnection.close();
System.out.println(" ");
System.out.println("Database connection is closed..!");
-->
</body>
</html>
```

Output:

Lab 6 - Task 2 - Perform creating and retrieving records via JSP page

Author Registration

Author No

UK993902

Name

Muhaimin

Address

No 10, Jalan Jati

City

Kuala Nerus

State

Terengganu

Zip

21300

Submit

Cancel

©2024-Haziq Aiman

Lab 6 - Task 1 - Perform and retrieving records via JSP page

Record successfully added into Author table...!

Record with author no UK993902 successfully created..!

Details of record are;

Name : Muhaimin

Address : No 10, Jalan Jati

City : Kuala Nerus

State : Terengganu

Zip : 21300

	authno	NAME	address	city	state	zip
▶	UK239904	Raden Irdian	113 Lorong Lalap	Kuala Lumpur	Kuala Lumpur	48000
	UK993902	Muhaimin	No 10, Jalan Jati	Kuala Nerus	Terengganu	21300
★	NULL	NULL	NULL	NULL	NULL	NULL

Reflection

1. What have you learnt from this exercise?

I have learn how to using JSP to insert records and retrieve them from MySQL database.

2. Define step by step before you successfully perform the transaction in a database.

1.Load JDBC driver.

2.Establish the connection.

3.Create a PreparedStatement object.


4.Execute the query.

5.Close database connection.

Coding:


insertStudent.jsp

Student.java



processStudent.jsp

errorStudent.jsp



Output:

Student Registration

Student No	<input type="text" value="UK209306"/>
Name	<input type="text" value="Arthur Softlan"/>
Program	<input type="text" value="BSc. in Networking"/>
<input type="button" value="Submit"/> <input type="button" value="Cancel"/>	

Record successfully added into Student table...!

Record with student no UK209306 successfully created..!

Details of record are;

Student ID : UK209306

Name : Arthur Softlan

Program : BSc. in Networking

©2024-Ziqmunk

	studno	stuname	stuprogram
▶	UK12489	Ahmad Salam	BSc. with IM
	UK209306	Arthur Softlan	BSc. in Networking
	UK56789	Ahmad Azman	BSc. Soft. Eng.
	UK6789	Liew Cheng Huat	BSc. in Robotics

Reflection

1. What have you learnt from this exercise?

I have learnt how to use JSP Standard Action, scriptlets and regular expression to insert records and retrieve them from MySQL database.

2. Define step by step before you successfully perform the transaction in a database.

1. Load JDBC driver.
2. Establish the connection.
3. Create a PreparedStatement object.
4. Execute the query.
5. Close database connection.

Task 4:

Coding:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<%@page import="java.sql.*"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Hero Academy Student 2024/2025</title>
<style>
table{
border-collapse: collapse;
}
td, th{
border: 1px solid #999;
padding: 0.5rem;
text-align: left;
}
th{
background: gold;
}
</style>
</head>
<body>
<h1>Task 4: Retrieving record via JSP page</h1>

<%
out.print("<table>");
out.print("<thead>");
out.print("<tr>");
out.print("<th>" + "ISBNNo" + "</th>");
out.print("<th>" + "Author" + "</th>");
out.print("<th>" + "Title" + "</th>");
out.print("</tr>");
out.print("<tbody>");
out.print("<tbody>");
%>
<%
//Step 1: Load JDBC driver..
Class.forName("com.mysql.cj.jdbc.Driver");
System.out.println("Step 1: MySQL driver loaded...!");

//Step 2: Establishing database connection
String myURL = "jdbc:mysql://localhost:3306/csm3023_lab6";
Connection myConnection = DriverManager.getConnection(myURL, "root", "admin");
System.out.println("Step 2: Database is connected...!");

//Step 3: Create a PreparedStatement object...
Statement myStatement = myConnection.createStatement();

String myQuery = "SELECT * FROM student";
ResultSet myResultSet = myStatement.executeQuery(myQuery);

while(myResultSet.next()){
out.print("<tr>");
out.print("<td width='20%'>" + myResultSet.getString(1) + "</td>");
out.print("<td width='40%'>" + myResultSet.getString(2) + "</td>");
out.print("<td width='40%'>" + myResultSet.getString(3) + "</td>");
out.print("</tr>");
}

//Step5: close database connection..!
System.out.println("Step 5: Close database connection..!");
myConnection.close();
System.out.println(" ");
System.out.println("Database connection is closed..!");

out.print("</tbody>");
out.print("</table>");
%>
</body>
</html>
```

Output:

Task 4: Retrieving record via JSP page

ISBNNo	Author	Title
UK12489	Ahmad Salam	BSc. with IM
UK209306	Arthur Softlan	BSc. in Networking
UK56789	Ahmad Azman	BSc. Soft. Eng.
UK6789	Liew Cheng Huat	BSc. in Robotics

Reflection

1. What have you learnt from this exercise?

I have learned how to use Java Scriptlet to query a list of records.

2. Explain the differences when using Statement() and
PreparedStatement().

The Statement interface is used for executing static SQL statements while The PreparedStatement interface is precompiled and stored in an object.

Besides, Statement() cannot accept parameters at runtime while PreparedStatement() accepts input parameters at runtime (parameterized queries).

Statement() typically used for executing SQL queries that are run only once while
PreparedStatement() Ideal for executing the same SQL query multiple times with different parameter values.

Task 5:

Coding:

registerMarathon.jsp

```
<!--page contentType="text/html" pageEncoding="UTF-8"%-->
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Superhero Marathon 2025</title>
</head>
<body>
<h1>Superhero Marathon 2025</h1>
<fieldset>
<legend>Marathon Registration</legend>
<form action="processMarathon.jsp" method="post">
<table>
<tr>
<td>
<label for="icno">IC No</label>
</td>
<td>
<input type="text" id="icno" name="icno" placeholder="E.g.: 921110-10-2514">
</td>
</tr>
<tr>
<td>
<label for="name">Name</label>
</td>
<td>
<input type="text" id="name" name="name" placeholder="Enter your name">
</td>
</tr>
<tr>
<td>
<label for="category">Category</label>
</td>
<td>
<select id="category" name="category">
<option value="5 KM">5 KM</option>
<option value="7 KM">7 KM</option>
<option value="10 KM">10 KM</option>
</select>
</td>
</tr>
</table>
<tr>
<td>
<button type="submit" value="Submit">Submit</button>
<button type="reset" value="Reset">Cancel</button>
</td>
</tr>
</table>
</form>
</fieldset>
<footer>
<p>©copy; Superhero Marathon Asia 2025</p>
</footer>
</body>
</html>
```

Marathon.java

```
package lab6.com;

/**
 *
 * @author Lenovo
 */
public class Marathon {
    private String icno;
    private String name;
    private String category;

    public String getIcno() {
        return icno;
    }

    public void setIcno(String icno) {
        this.icno = icno;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getCategory() {
        return category;
    }

    public void setCategory(String category) {
        this.category = category;
    }
}
```

Database.java

```
public class Database {
    private static Connection myConnection = null;
    private static String myURL = "jdbc:mysql://localhost:3306/csm3023_lab6";
    private int result = 0;

    public static Connection getConnection() throws ClassNotFoundException {
        if (myConnection != null) {
            return myConnection;
        }
        else try {
            Class.forName("com.mysql.cj.jdbc.Driver");
            myConnection = DriverManager.getConnection(myURL, "root", "admin");
        }
        catch (SQLException e) {
            e.printStackTrace();
        }
        return myConnection;
    }

    public void closeConnection() throws ClassNotFoundException {
        try {
            myConnection.close();
        }
        catch (SQLException e) {
            e.printStackTrace();
        }
    }
}
```

MarathonDAO.java

```
import java.sql.Connection;
import java.sql.PreparedStatement;
import java.sql.SQLException;
import lab6.com.Database;

public class MarathonDAO {
    private Connection connection;
    private int result = 0;

    public MarathonDAO() throws ClassNotFoundException {
        connection = Database.getConnection();
    }

    public int addDetails(Marathon marathon) {
        try {
            String mySQL = "INSERT INTO marathon (icno, name, category) VALUES (?, ?, ?)";
            PreparedStatement preparedStatement = connection.prepareStatement(mySQL);

            System.out.println("IC no    = " + marathon.getIcno());
            System.out.println("Name      = " + marathon.getName());
            System.out.println("Category = " + marathon.getCategory());

            //Parameters
            preparedStatement.setString(1, marathon.getIcno());
            preparedStatement.setString(2, marathon.getName());
            preparedStatement.setString(3, marathon.getCategory());
            result = preparedStatement.executeUpdate();
        } catch (SQLException e) {
            e.printStackTrace();
        }
        return result;
    }
}
```

processMarathon.jsp

```
<%page contentType="text/html" pageEncoding="UTF-8"%>
<%page language="java"%>
<%page import="java.sql.*"%>
<%page import="lab6.com.Database"%>
<%page import="lab6.com.Marathon"%>
<%page import="lab6.com.MarathonDAO"%>
<DOCTYPE html>
<html>
    <head>
        <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
        <title>Superhero Marathon 2025</title>
    </head>
    <body>
        <jsp:useBean id="myMarathon" class="lab6.com.Marathon" scope="request"/>
        <jsp:setProperty name="myMarathon" property=""/>

        <%
            int result;
            //Step 1: create Database object...
            Database myDB = new Database();

            MarathonDAO object1 = new MarathonDAO();

            //Step 2: Add the records...
            result = object1.addDetails(myMarathon);

            //Step 3: Determine whether the transactions is success..
            if (result > 0) {
                System.out.println("\tRecord successfully added into Book's table...!");
                out.print("<p>    * Record with ID No. " + myMarathon.getIcno() +
                    " successfully created..!<br> *<br>");
                out.print("<p>    * Details of record are: " + "<br>");
                out.print("<p>IC NO      : " + myMarathon.getIcno() + "<br>");
                out.print("<p>Name      : " + myMarathon.getName() + "<br>");
                out.print("<p>Category   : " + myMarathon.getCategory() + "<br>");
            } else {
                out.print("<p>Sorry this is an error! maybe you already registered before?<br>");
            }

            //Step 4: Close database connection..!
            System.out.println("\tStep 4: Close database connection...!");
            myDB.closeConnection();
            System.out.println(" ");
            System.out.println("\tDatabase connection is closed...!");
        %>
    </body>
</html>
```

Output:

Superhero Marathon 2025

Marathon Registration

IC No

7201606-01-0376

Name

Wan Nur Saitama

Category

7 KM ▾

Submit

Cancel

©Superhero Marathon Asia 2025

Record with IC No 7201606-01-0376 successfully created..!

Details of record are:

Ic NO : 7201606-01-0376

Name : Wan Nur Saitama

Category : 7 KM

	icno	name	category
▶	021121-01-9738	sharon	7 KM
	031121-01-0865	abe	5 KM
	7201606-01-0376	Wan Nur Saitama	7 KM
	921102-11-9973	Mat Nor Acan	7 KM
•	HULL	HULL	HULL

Reflection

1. What have you learnt from this exercise?

I have learned how to use JavaBeans to perform SQL transaction using PreparedStatement().

2. Describe the benefits of using JavaBeans

JavaBeans allow components to be reused across different parts of a program.

JavaBeans are easy to configure and use.

They work across different platforms.

Coding:

```

<html>
  <head>
    <title>Department of Quality QMT</title>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
  </head>
  <body>
    <h1>Department of Quality QMT</h1>
    <fieldset>
      <legend>User Registration</legend>
      <form action="processUser.jsp">
        <div>
          <input type="text" id="username" name="username" placeholder="Enter a username">
        </div>
        <div>
          <input type="password" id="password" name="password" placeholder="Enter a password">
        </div>
        <div>
          <input type="text" id="firstname" name="firstname" placeholder="E.g. John">
        </div>
        <div>
          <input type="text" id="lastname" name="lastname" placeholder="E.g. ibn AbiShallah">
        </div>
        <div>
          <button type="submit" value="Submit">Submit</button>
          <button type="reset" value="Reset">Cancel</button>
        </div>
      </form>
    </fieldset>
    </body>
  </html>

```

```
<!page contentType="text/html" pageEncoding="UTF-8">
<?page language="java">
<?page import="java.sql.*">
<?page xmlns="http://jsp/1.0">
<%include file="
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Department of Quality DBMS/Title</title>
</head>
<body>
<?page session id="myUser" class="lab4.com.user" scope="request"/>
<?page outProperty name="myUser" property="*"/>

<%
int result;

//Step 1: Load JDBC driver...
Class.forName("com.mysql.cj.jdbc.Driver");
System.out.println("Step 1: MySQL driver loaded...");

//Step 2: Establish the connection
String myURL = "jdbc:mysql://localhost:3306/comBEE2_lab4";
Connection myConnection = DriverManager.getConnection(myURL, "root", "admin");
System.out.println("Step 2: Database is connected...");

//Step 3: Create a PreparedStatement object...
System.out.println("Step3: Prepared Statement created...");
String insertQuery = "INSERT INTO userprofile(username, password, firstname, lastname) VALUES(?, ?, ?, ?)";
System.out.println("SQL Query: " + insertQuery);

//Call method preparedStatement
PreparedStatement myPS = myConnection.prepareStatement(insertQuery);

//Assign each value in respective columns for Student's table. (C=Caste)
myPS.setString(1, myUser.getUserName());
myPS.setString(2, myUser.getPassword());
myPS.setString(3, myUser.getFirstName());
myPS.setString(4, myUser.getLastName());

result = myPS.executeUpdate();

if (result > 0)
    out.println("Account successfully added into User Table...");
    out.print("<p>" + "Record with Username : " + myUser.getUserName()
    + " successfully created..." + "</p>");
    out.print("<p>" + "Details of record are, " + "</p>");
    out.print("<p>Username : " + myUser.getUserName() + "</p>");
    out.print("<p>Password : " + myUser.getPassword() + "</p>");
    out.print("<p>Firstname : " + myUser.getFirstName() + "</p>");
    out.print("<p>Lastname : " + myUser.getLastName() + "</p>");
}

//Step4: close database connection...
System.out.println("Step 4: Close database connection...");
myConnection.close();
System.out.println(" ");
System.out.println("Database connection is closed...");

%>
</body>
```

login.jsp

```
<page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Department of Quality UMT</title>
</head>
<body>
<h1>Department of Quality UMT</h1>
<fieldset>
<legend>User Login</legend>
<form action="doLogin.jsp">
<table>
<tr>
<td>
<label for="username">Username</label>
</td>
<td>
<input type="text" id="username" name="username" placeholder="Enter a username">
</td>
</tr>
<tr>
<td>
<label for="password">Password</label>
</td>
<td>
<input type="password" id="password" name="password" placeholder="Enter a password">
</td>
</tr>
<tr>
<td>
<button type="submit" value="Submit">Submit</button>
<button type="reset" value="Reset">Cancel</button>
</td>
<td>
</td>
</tr>
</table>
</form>
</fieldset>
<div>
<div>
String errorMessage = request.getParameter("error");
if (errorMessage != null && !errorMessage.isEmpty()) {
    out.println("<p>msg="<code>color: red;</code> + errorMessage + "</p>");
}
</div>
</div>
<p>copy:Quality UMT - 2024</p>
</body>
</html>
```

doLogin.jsp

```

<%page contentType="text/html" pageEncoding="UTF-8"%>
<% page Import="java.sql.*", java.com.Bank" %>
<% page Import="java.io.*", java.util.*" %>
<%@OTYPE html%>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Department of Quality [MTC]/title>
</head>
<body>
<td>Department of Quality [MTC]/td>
<td>
// Retrieve username and password from the request
String username = request.getParameter("username");
String password = request.getParameter("password");

// Check if username and password are not null and not empty
if (username != null && !username.isEmpty() && password != null && !password.isEmpty()) {
// Establish database connection
Connection conn = null;
PreparedStatement pstmt = null;
ResultSet rs = null;
try {
Class.forName("com.mysql.cj.jdbc.Driver");
String url = "jdbc:mysql://localhost:3306/om321?useSSL=false&serverTimezone=UTC";
conn = DriverManager.getConnection(url, "root", "admin");

// Query to check if the username and password are valid
String query = "SELECT * FROM userprofile WHERE username = ? AND password = ?";
pstmt = conn.prepareStatement(query);
pstmt.setString(1, username);
pstmt.setString(2, password);
rs = pstmt.executeQuery();

if (rs.next()) {
// If user exists and credentials are valid, redirect to main.jsp
User user = new User();
user.setUserName(rs.getString("username"));
user.setFirstName(rs.getString("first_name"));
user.setLastName(rs.getString("last_name"));

// Set user object in session for later use
session.setAttribute("user", user);
response.sendRedirect("main.jsp");
} else {
// If invalid username or password, redirect back to login.jsp with error message
response.sendRedirect("login.jsp?error=InvalidUsernameAndPassword");
}
} catch (Exception e) {
e.printStackTrace();
} finally {
// Close resources
if (rs != null) rs.close();
if (pstmt != null) pstmt.close();
if (conn != null) conn.close();
}
} else {
// If username or password is empty, redirect back to login.jsp with error message
response.sendRedirect("login.jsp?error=UsernameAndPasswordAreRequired");
}
}
</body>
</html>

```

User.java

```
    */  
    public class User {  
        private String username;  
        private String password;  
        private String firstname;  
        private String lastname;  
  
        public String getUsername() {  
            return username;  
        }  
  
        public void setUsername(String username) {  
            this.username = username;  
        }  
  
        public String getPassword() {  
            return password;  
        }  
  
        public void setPassword(String password) {  
            this.password = password;  
        }  
  
        public String getFirstname() {  
            return firstname;  
        }  
  
        public void setFirstname(String firstname) {  
            this.firstname = firstname;  
        }  
  
        public String getLastname() {  
            return lastname;  
        }  
  
        public void setLastname(String lastname) {  
            this.lastname = lastname;  
        }  
  
    }
```

Output:

Department of Quality UMT

User Registration

Username

abetop

Password

Firstname

Zikri

Lastname

bin Ameer

Submit

Cancel

©Quality UMT - 2024

Record successfully added into User table...!

Record with Username abetop successfully created..!

Details of record are;

Username : abetop

Firstname : Zikri

Lastname : bin Ameer

	username	password	firstname	lastname
▶	abetop	@abetop123	Zikri	bin Ameer
	ziqmunk34	!abang123	Haziq Aiman	Bin Mustafa
*	NULL	NULL	NULL	NULL

Department of Quality UMT

User Login

Username

abetop

Password

Submit

Cancel

©Quality UMT - 2024

Welcome, Zikri bin Ameer

Your username is: abetop

[Logout](#)

Department of Quality UMT

User Login

Username

abangtop

Password

Submit

Cancel

©Quality UMT - 2024

Department of Quality UMT

User Login

Username

Enter a username

Password

Enter a password

Submit

Cancel

Invalid username or password

©Quality UMT - 2024