



ELEVATE YOUR BUSINESS WITH UNMATCHED EFFICIENCY

JCB 3DX

BACKHOE LOADER



High on Fuel Efficiency
Save more on fuel cost



High on performance
Matches all sites
requirement



Best in Class Quality
Reliable & durable
machine



4 Wheel Drive
All terrain capability



Spacious Cabin
More comfort



Standard 5 Year
Subscription



BRITISH ENGINEERING



Available Variants

3DX Plus

4WD, Engine Power 92hp,
6-in-1 Shovel,
Bucket - 0.26 cu.m



2DX

4WD, Engine Power 49hp,
GP Shovel,
Bucket - 0.18 cu.m



*T & C Apply.

SPECIFICATION: 3DX BACKHOE LOADER

ENGINE

JCB 448, 4 Cylinder, 56 kW (76 hp)

TRANSMISSION

JCB synchro shuttle transmission provides superb drive power in all conditions. It consists of a 4-speed, full synchromesh gearbox with integral torque convertor and electrically operated reversing power shuttle.

HYDRAULIC PUMP FLOW

108 LPM@2000 rpm

HYDRAULIC PRESSURE

3850 p.s.i.

BRAKES

JCB 'Q' brakes, hydraulically actuated, dual line, self adjusting (compensated), oil immersed multi-disc type on the rear axle.

STEERING

Front wheel full power hydrostatic system utilising the main hydraulic pump via a steering priority valve. In the event of engine failure, emergency steering is maintained.

ELECTRICAL

130 ampere-hour 12 V battery system with alternator and full road lighting

TYRES

Front: 12.5 x 18-12 PR (4WD)
Rear: 16.9 x 28-12 PR (4WD)

SHIPPING WEIGHT

7660 kg

WHEELBASE

2.24 m

STANDARD SHOVEL

1.1 cu.m GP Shovel (6-in-1 shovel as option)

STANDARD BUCKET CAPACITY

0.26 cu.m

DUMP HEIGHT

2.72 m

LOAD OVER HEIGHT

4.18 m

MAX. DIG DEPTH

4.77 m

MAX. WORKING HEIGHT

5.97 m

LOADER ARM BREAKOUT FORCE

4850 kgf

BUCKET TEAROUT FORCE

5700 kgf

All dimensions, weights and timings are variable within 1.5%,
JCB reserves the right to change specifications without prior notice.

EXPERIENCE THE BEST SERVICE



Extended
warranty
up to 3 year



Best-in-class
service



Easy parts
availability



Advanced
LiveLink

To know more, visit your nearest dealership

