

# Spectral Clustering for Axiom Selection

Zishi Wu

Department of Computer Science  
University of Miami

May 17, 2020

UNIVERSITY  
OF MIAMI



# Outline

- 1 Introduction
- 2 Related Work
- 3 Methodology



# Introduction

## Definitions

- What is Automated Theorem Proving (ATP)?
- *Logical formulae* are statements about a domain:
- Show that the *conjecture* is a *logical consequence* of the axioms (a.k.a premises).
- Applications:
  - Formal verification of software - Compilers (e.g. gcc, llvm)
  - Formal verification of hardware - CPU (e.g. 1994 Intel Pentium floating-point division bug)
  - Interactive proof assistants for mathematics (e.g. Isabelle, Mizar)

# Introduction

## Example

- Axiom 1: *All men are mortal.*
- Axiom 2: *Socrates is a man.*
- Conjecture: *Socrates is mortal.*



# Logical Consequence

## Logical Consequence

- Every model of the axioms is a model of the conjecture.
- A set of axioms has a *model* if there is an *interpretation* (assignment of boolean values) to the axioms such that the conjunction of the axioms evaluate to *True*.
- If we list all interpretations of  $N$  formulae on a truth table, we get  $2^N$  rows. This search space grows exponentially.
- The faster method is to show that the union of the axioms and the negation of the conjecture is *unsatisfiable*.  $Ax \cup \neg C = \emptyset$
- In other words, if no model of the axioms is a model of the negated conjecture, then all models of the axioms are models of the conjecture.

# Problem Statement

## Problem Statement

- A *large-theory* problem consists of a conjecture to be proven, and a large number of axioms to be considered.
- However, the solution set(s) usually consist of a few axioms.
- How do we select the necessary axioms? This is known as the problem of *premise selection*.



# Benchmark Data

## MPTP2078 Dataset

- Thousands of Problems for Theorem Provers (TPTP) [Sut17]
  - Standard set of test problems.
- Benchmark dataset of 2078 problems known as the Mizar Problems for Theorem Provers (MPTP2078) [AHK<sup>+</sup>14].
  - Encodes problems from the Mizar Mathematical Library (MML) of formalized mathematics into first-order logic form.
- There are two versions of each problem:
  - Bushy = smaller version (3 to 40 axioms, 1 to 15 needed)
  - Chainy = larger version (10 to 500 axioms, 2 to 119 needed)
- Premise selection performance compared to state-of-the-art Automated Theorem Provers:
  - E [Sch13]
  - Vampire [KV13]

# Graph Methods

## Minimal Proof Dependency

- Alama et al. [AHK<sup>+</sup>14]. constructed a knowledge base of minimal proof dependencies that a problem depends on and trained kernel-based machine learning methods on a feature matrix representation of that knowledge base.
- Minimal dependencies encoded as an adjacency matrix, where the  $(i, j)^{th}$  cell of the matrix has a value of 1 if the  $i^{th}$  formula of a problem is used in the proof of the  $j^{th}$  formula of a problem, and 0 otherwise.
- Formulate premise selection as a *ranking problem*:
  - Rank the axioms by how likely they are to prove a conjecture (e.g. shared minimal dependencies).
  - Choose a threshold value.
  - Select all axioms whose score is above that threshold.



# Related Work


## Extended Hutchinson Distance

- To construct an adjacency matrix, we require a measure of similarity or dissimilarity between each pair of nodes in a graph.
- Qinghua Liu [LXH17] proposed a dissimilarity metric between two terms  $\Delta_1$  and  $\Delta_2$ , that extends the Hutchinson distance [Hut97].
- Calculated by finding the Least Generalized Generalization (*lgg*) between two formulae. A term  $\Delta$  is the *lgg* of  $\Delta_1$  and  $\Delta_2$  iff
  - There are substitutions  $\theta_1$  and  $\theta_2$  such that  $\Delta\theta_1 = \Delta_1$  and  $\Delta\theta_2 = \Delta_2$ .
  - There exists no term  $\Delta'$  and substitutions  $\sigma$ ,  $\sigma_1$  and  $\sigma_2$  such that  $\Delta\sigma_1 = \Delta'$  and  $\Delta\sigma_2 = \Delta'$ .

# Related Work

## Least Generalized Generalization Example

- Note that the substitutions  $\theta_1$  and  $\theta_2$  are not limited to a single substitution rule. They can also consist of multiple substitution rules occurring one after the other.



- $P(a)$  could represent a predicate: **is\_man( Socrates )**
- $Q(b)$  could represent a predicate: **is\_mortal ( Man )**
- Here  $\Delta$  is the least generalized generalization of  $\Delta_1$  and  $\Delta_2$

# Related Work

## Extended Hutchinson Distance

- If there is no Least Generalized Generalization  $\Delta$  between two terms  $\Delta_1$  and  $\Delta_2$ , then their extended Hutchinson distance is  $\infty$ .  
Formally,  $\text{dissimilarity}(\Delta_1, \Delta_1) = \infty$  iff  $\text{lgg}(\Delta_1, \Delta_2) = \emptyset$ .
- If there exists a Least Generalized Generalization  $\Delta$  between two terms  $\Delta_1$  and  $\Delta_2$ , then the Extended Hutchinson Distance says:
  - More total substitutions required (from the  $\text{lgg}$  to both terms) equates to a higher dissimilarity score.
  - Fewer total substitutions required equates to a lower dissimilarity score.
- Note that this is a simplification of Qinghua's actual metric, which is more complicated.
- As expected, for any term  $\Delta_1$ ,  $\text{dissimilarity}(\Delta_1, \Delta_1) = 0$

# Graph Theory

## Spectral Clustering

- Von Luxburg [vL07] describes this technique to cluster vertices in an undirected graph according to some user-defined similarity metric.
- Adjacency matrix  $A$  consists of edge weights between pairs of vertices that represent their similarity.
- Degree matrix  $D$  is a diagonal matrix where the  $i^{th}$  element is the sum of the elements of the  $i^{th}$  column of  $A$ .
- Un-normalized Graph Laplacian matrix.
  - $L = D - A$
- Normalized Graph Laplacian matrix contains *features* of the graph
  - $L_{norm} = I - (D^{-1/2} L D^{-1/2})$

# Methodology

## Graph Representation

- Used Extended Hutchinson distance to get dissimilarity values of all pairs of vertices in a problem.
- Let  $\Phi_1$  and  $\Phi_2$  represent two formulae with dissimilarity of  $dsim(\phi_i, \phi_j)$ . We convert dissimilarity values into similarity values using the following formula:
  - $maxdsim(\mathcal{F}) = \max_{\phi_i, \phi_j \in \mathcal{F}} (dsim(\phi_i, \phi_j) \neq \infty)$
  - $sim(\Phi_1, \Phi_2, \mathcal{F}) = \max(0, maxdsim(\mathcal{F}) - dsim(\Phi_1, \Phi_2))$
- The logic problem becomes a fully-connected and undirected graph
  - Vertices  $V = \{\text{Axioms} \cup \text{Conjecture}\}$
  - Edges  $E =$  similarity values between vertices

# Example Graph

## Calculate Normalized Laplacian Matrix

- Adjacency, Degree, and Un-normalized Graph Laplacian

$$A = \begin{bmatrix} 0 & 3 & 0 \\ 3 & 0 & 1 \\ 0 & 1 & 0 \end{bmatrix} \quad D = \begin{bmatrix} 3 & 0 & 0 \\ 0 & 4 & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad L = \begin{bmatrix} 0 & 3 & 0 \\ 3 & 0 & 1 \\ 0 & 1 & 0 \end{bmatrix}$$

- Normalized Graph Laplacian

$$L_{norm} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} - \begin{bmatrix} \frac{1}{\sqrt{3}} & 0 & 0 \\ 0 & 1/2 & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 0 & 3 & 0 \\ 3 & 0 & 1 \\ 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} \frac{1}{\sqrt{3}} & 0 & 0 \\ 0 & 1/2 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

# Selection Method

## Spectral Clustering [vL07]

- Given graph  $G = (V, E)$
- Partition vertices in  $V$  into  $k$  clusters:  $C_1, C_2, \dots, C_k$
- Denote the cluster containing the conjecture as  $C_C$
- Problem may have more than one set of solutions
- Successful conjecture cluster only needs to contain one solution

# Spectral Clustering Algorithm

## A Tutorial on Spectral Clustering [vL07]

- 1 Construct a weight matrix  $W$  (i.e. adjacency matrix  $A$ )
- 2 Compute the normalized Laplacian matrix  $L_{norm}$  from  $W$
- 3 Compute the first  $k$  eigenvectors  $v_1, \dots, v_k$  of  $L_{norm}$  and construct a feature matrix  $U$  from those eigenvectors
- 4 For  $i = 1, \dots, n$ , let  $p_i$  be the feature vector for the  $i^{th}$  vertex, corresponding to the  $i^{th}$  row of  $U$
- 5 Cluster the vertices based on their feature vectors into  $k$  clusters:  $C_1, C_2, \dots, C_k$



# Spectral Clustering Algorithm

## K-Means Initialization Problem

- ⑤ Cluster the feature vectors into  $k$  clusters:  $C_1, C_2, \dots, C_k$ 
  - Each run of  $k$ -means chooses a different set of initial centroids for the  $k$  clusters
  - Results in different clusterings each run
  - We need a deterministic way of clustering that doesn't change over multiple runs of  $k$ -means



J. Alama, T. Heskes, D. Külwein, E. Tsivtsivadze, and J. Urban.  
Premise Selection for Mathematics by Corpus Analysis and Kernel  
Methods.

*Journal of Automated Reasoning*, 52(2):191–213, 2014.



F. R. K. Chung.

*Spectral Graph Theory*.

American Mathematical Society, 1997.



A. Hutchinson.

Metrics on Terms and Clauses.

In M. van Someren and G. Widmer, editors, *Proceedings of the 9th European Conference on Machine Learning*, number 1224 in Lecture Notes in Artificial Intelligence, pages 138–145. Springer-Verlag, 1997.



L. Kovacs and A. Voronkov.

First-Order Theorem Proving and Vampire.

In N. Sharygina and H. Veith, editors, *Proceedings of the 25th International Conference on Computer Aided Verification*, number 8044 in Lecture Notes in Artificial Intelligence, pages 1–35.  
Springer-Verlag, 2013.



Q. Liu, Y. Xu, and X. He.

New terms metric based on substitutions.

In *2017 12th International Conference on Intelligent Systems and Knowledge Engineering (ISKE)*, pages 1–6, 2017.



S. Schulz.

System Description: E 1.8.

In K. McMillan, A. Middeldorp, and A. Voronkov, editors, *Proceedings of the 19th International Conference on Logic for Programming, Artificial Intelligence, and Reasoning*, number 8312 in Lecture Notes in Computer Science, pages 477–483. Springer-Verlag, 2013.



G. Sutcliffe.

The TPTP Problem Library and Associated Infrastructure. From CNF to TH0, TPTP v6.4.0.

*Journal of Automated Reasoning*, 59(4):483–502, 2017.



Ulrike von Luxburg.

A tutorial on spectral clustering.

*Statistics and Computing*, 17(4):395–416, Dec 2007.