

CS 525 - ASD

Advanced Software Development

MS.CS Program
Department of Computer Science
Rene de Jong, MsC.



Maharishi University
OF MANAGEMENT

CS 525 - ASD

Advanced Software Development

© 2019 Maharishi University of Management

All course materials are copyright protected by international copyright laws and remain the property of the Maharishi University of Management. The materials are accessible only for the personal use of students enrolled in this course and only for the duration of the course. Any copying and distributing are not allowed and subject to legal action.



Maharishi University
OF MANAGEMENT

Lesson 9 Builder pattern



L1: ASD Introduction
L2: Strategy, Template method
L3: Observer pattern
L4: Composite pattern, iterator pattern
L5: Command pattern
L6: State pattern
L7: Chain Of Responsibility pattern

Midterm

L8: Proxy, Adapter, Mediator
L9: Factory, Builder, Decorator, Singleton
L10: Framework design
L11: Framework implementation
L12: Framework example: Spring framework
L13: Framework example: Spring framework

Final

Builder

- Builds a complex object using a step by step approach



Immutable class

- Once created, an immutable object can never be changed

```
public class Money {  
    private BigDecimal value;  
  
    public Money(BigDecimal value) {  
        this.value = value;  
    }  
  
    public Money add(Money money){  
        return new Money(value.add(money.getValue()));  
    }  
  
    public Money subtract(Money money){  
        return new Money(value.subtract(money.getValue()));  
    }  
  
    public BigDecimal getValue() {  
        return value;  
    }  
}
```

No setter methods

Mutation leads to the creation of new instances

Why immutable classes?

- Reasons to make a class immutable:
 - Less prone to errors
 - Easier to share
 - Thread safe
- Immutable classes in Java
 - `java.lang.String`
 - `java.io.File`
 - `java.util.Locale`
 - Almost all classes in `java.time`

Constructor with many parameters

Constructor is not expressive

```
public class Customer {  
    private String firstName;  
    private String lastname;  
    private String phone;  
    private String email;  
    private int age;  
    private int numberOfChildren;  
    private int shoesize;  
    private boolean isMarried;  
    private double yearlyIncome;  
    private double yearlyAmountSpendOnShoes;  

```

```
Customer customer = new Customer("Mary", "Jones", "0623416754",  
    "mjones@gmail.com", 34, 3, 8, true, 50000.0, 2000.0);
```

What do these parameters mean?

Easy to make mistakes

If you have optional parameters, you need many constructors

```
public Customer(String firstName, String lastname, String phone, String email, int age, int  
    numberOfChildren, int shoesize, boolean isMarried, double yearlyIncome, double  
    yearlyAmountSpendOnShoes) {  
    this.firstName = firstName;  
    this.lastname = lastname;  
    this.phone = phone;  
    this.email = email;  
    this.age = age;  
    this.numberOfChildren = numberOfChildren;  
    this.shoesize = shoesize;  
    this.isMarried = isMarried;  
    this.yearlyIncome = yearlyIncome;  
    this.yearlyAmountSpendOnShoes = yearlyAmountSpendOnShoes;  
}
```

Class can be immutable

Using setters

```
public class ApplicationUsingSetters {  
    public static void main(String[] args) {  
        Customer customer = new Customer();  
        customer.setFirstName("Mary");  
        customer.setLastname("Jones");  
        customer.setPhone("0623416754");  
        customer.setEmail("mjones@gmail.com");  
        customer.setAge(34);  
        customer.setNumberOfChildren(3);  
        customer.setShoesize(8);  
        customer.setMarried(true);  
        customer.setYearlyIncome(50000.0);  
        customer.setYearlyAmountSpendOnShoes(2000.0);  
        System.out.println(customer);  
    }  
}
```

Clear what the
parameters mean

Class is not
immutable

What if we want



- Expressive code
- Immutable class
- Solution: Builder

Builder example

```
public class Customer {  
    private String firstName;  
    private String lastname;  
    private String phone;  
    private String email;  
    private int age;  
    private int numberOfChildren;  
    private int shoesize;  
    private boolean isMarried;  
    private double yearlyIncome;  
    private double yearlyAmountSpendOnShoes;  
  
    public static class Builder {  
  
        private String firstName="";  
        private String lastname="";  
        private String phone="";  
        private String email="";  
        private int age = 0;  
        private int numberOfChildren = 0;  
        private int shoesize = 0;  
        private boolean isMarried = false;  
        private double yearlyIncome = 0.0;  
        private double yearlyAmountSpendOnShoes = 0.0;  
  
        public Builder withFirstName(String firstName) {  
            this.firstName = firstName;  
            return this;  
        }  
    }  
}
```

Builder inner class

'Setter' method on the builder

Return 'this' for method chaining

Builder example

```
public Builder withLastname(String lastname) {
    this.lastname = lastname;
    return this;
}
public Builder withPhone(String phone) {
    this.phone = phone;
    return this;
}
public Builder withEmail(String email) {
    this.email = email;
    return this;
}
public Builder withAge(int age) {
    this.age = age;
    return this;
}
public Builder withNumberOfChildren(int numberOfChildren) {
    this.numberOfChildren = numberOfChildren;
    return this;
}
public Builder withShoesize(int shoesize) {
    this.shoesize = shoesize;
    return this;
}
public Builder isMarried() {
    this.isMarried = true;
    return this;
}
```

Builder example

```
public Builder isNotMarried() {  
    this.isMarried = false;  
    return this;  
}  
public Builder withYearlyIncome(double yearlyIncome) {  
    this.yearlyIncome = yearlyIncome;  
    return this;  
}  
public Builder withYearlyAmountSpendOnShoes(double yearlyAmountSpendOnShoes) {  
    this.yearlyAmountSpendOnShoes = yearlyAmountSpendOnShoes;  
    return this;  
}  
  
public Customer build() {  
    return new Customer(this);  
}  
}
```

The build() method does the actual creation of the object

Builder example

```
private Customer(Builder builder) {  
    this.firstName = builder.firstName;  
    this.lastname = builder.lastname;  
    this.phone = builder.phone;  
    this.email = builder.email;  
    this.age = builder.age;  
    this.numberOfChildren = builder.numberOfChildren;  
    this.shoesize = builder.shoesize;  
    this.isMarried = builder.isMarried;  
    this.yearlyIncome = builder.yearlyIncome;  
    this.yearlyAmountSpendOnShoes = builder.yearlyAmountSpendOnShoes;  
}
```

The constructor has a Builder as argument

```
@Override  
public String toString() {  
    return "Customer [firstName=" + firstName + ", lastname=" + lastname + ", phone=" + phone + ",  
        email=" + email + ", age=" + age + ", numberOfChildren=" + numberOfChildren + ", shoesize=" +  
        shoesize + ", isMarried=" + isMarried + ", yearlyIncome=" + yearlyIncome + ",  
        yearlyAmountSpendOnShoes=" + yearlyAmountSpendOnShoes + "];"  
}
```

The client code

```
public class Application {  
  
    public static void main(String[] args) {  
        Customer customer1 = new Customer.Builder()  
            .withFirstName("Mary")  
            .withLastname("Jones")  
            .withEmail("mjones@gmail.com")  
            .withAge(34)  
            .isMarried()  
            .withNumberOfChildren(3)  
            .withPhone("0623416754")  
            .withShoesize(8)  
            .withYearlyIncome(50000.0)  
            .withYearlyAmountSpendOnShoes(2000.0)  
            .build();  
        System.out.println(customer1);  
  
        Customer customer2 = new Customer.Builder()  
            .withFirstName("Lucy")  
            .withLastname("Jhonson")  
            .isNotMarried()  
            .withPhone("0698345234")  
            .build();  
        System.out.println(customer2);  
    }  
}
```

Clear code

Customer is immutable

Builder used in Quartz

```
SchedulerFactory schedFact = new StdSchedulerFactory();
Scheduler sched = schedFact.getScheduler();
sched.start();
// define the job and tie it to our HelloJob class
JobDetail job = JobDetail("myJob", "group1", HelloJob.class);

// Trigger the job to run now, and then every 40 seconds
Trigger trigger = newTrigger("myTrigger", "group1", new Date(), null,
    SimpleTrigger.REPEAT_INDEFINITELY, 40)

// Tell quartz to schedule the job using our trigger
sched.scheduleJob(job, trigger);
```

Quartz 1.0

```
SchedulerFactory schedFact = new StdSchedulerFactory();
Scheduler sched = schedFact.getScheduler();
sched.start();
// define the job and tie it to our HelloJob class
JobDetail job = newJob(HelloJob.class)
    .withIdentity("myJob", "group1")
    .build();
// Trigger the job to run now, and then every 40 seconds
Trigger trigger = newTrigger()
    .withIdentity("myTrigger", "group1")
    .startNow()
    .withSchedule(simpleSchedule()
        .withIntervalInSeconds(40)
        .repeatForever())
    .build();
// Tell quartz to schedule the job using our trigger
sched.scheduleJob(job, trigger);
```

Quartz 2.0

Main point



- The builder pattern is a great help if you want to create objects with many different parameters.
- All the intelligence of Nature is available at the level of the Unified Field