

Predicting ski jumps using state-space model

Lars Thørväld
The Thørväld Group
Hekla, Iceland
larst@affiliation.org

Živa Hegler
Univerza v Ljubljani
Ljubljana, Slovenia

Neca Camlek
Univerza v Ljubljani
Ljubljana, Slovenia

Abstract

Ski jumping performance is shaped by both athlete technique and environmental conditions, with factors such as wind speed, wind direction, and ski orientation playing a critical role in determining jump trajectories. Accurate modeling of these trajectories is challenging due to the system's dynamic and time-dependent nature. In this work, we introduce a dataset of measured ski jumps and present a state-space modeling framework that captures the evolution of jumps under varying conditions. The model parameters are estimated using a ridge regression approach, enabling us to predict trajectories from initial states and wind sensor inputs. We evaluate the predictive performance of the model through leave-one-out cross-validation and analyze its stability, showing that the approach can generate realistic trajectories with reasonable accuracy. To complement the modeling results, we developed an interactive web application that allows users to explore both recorded and simulated jumps, adjust environmental factors, and visualize their effects through animations. Together, the dataset, modeling framework, and application offer a foundation for further research in ski jump analysis and provide an accessible tool for exploring the influence of external conditions on performance.

Keywords

datasets, SSM, ski jumping, simulations, least squares

1 Introduction

Ski jumping is a sport strongly influenced by both athletic technique and environmental conditions. Factors such as wind speed, wind direction, and different ski angles affect the trajectory and final distance of a jump, making accurate prediction a challenging problem. While statistical models and simulations have been applied in sports research for some time, many approaches simplify the problem and do not fully capture the dynamic evolution of the jump over time.

Recent advances in machine learning have introduced methods capable of modeling temporal systems with greater fidelity. In particular, state space models provide a mathematical framework for representing hidden internal states that evolve over time in response to external inputs. This makes them well-suited for modeling ski jumps, where environmental factors determine performance.

In this paper, we present a dataset of ski jumps together with a state space model trained to predict jump trajectories based on changing environmental conditions. The model is estimated using a least squares approach and demonstrates how inputs such as wind and ramp adjustments influence the resulting jump. Beyond

the modeling framework, we also developed an application that allows general users to interact with the data, run simulations, and visualize jump trajectories through animations.

The remainder of the paper is as follows. Section 2 presents the handling of received data. Next, the proposed methodology is described in Section 3. The project results are presented in Section 4. We discuss the results in Section 5 and conclude the paper in Section 6.

tazga oz ni neka ful razsirjena zadeva, zato se ta odstavek zdeje imenuje Data

2 Data

This section describes the data handling, focusing on state space models and our data processing.

2.1 State Space Model

State Space Models (SSMs) are a family of machine learning algorithms designed to capture and predict the behavior of dynamic systems by describing how their inner state changes over time. Instead of only looking at past inputs and outputs, SSMs explicitly model the underlying dynamics, making them well-suited for sequential data. In state space modeling, the objective is to identify the minimal set of system variables required to completely describe the system. These fundamental variables are referred to as the state variables. At any given time, the state of the system can be represented by a state vector, whose components correspond to the values of the respective state variables. SSMs are designed to predict both the manner in which inputs are reflected in the system's outputs and the evolution of a system's internal state over time and in response to specific inputs.

2.2 Data Processing

For our project we used 223 CSV files, each containing the data of one jump. Each contains 17 columns ('Position', 'Height above ground [m]', 'Time', 'X [m]', 'Y [m]', 'Z [m]', 'Opening Angle [°]', 'Stalling Angle Left [°]', 'Stalling Angle Right [°]', 'Roll Angle Left [°]', 'Roll Angle Right [°]', 'Yaw Angle Left [°]', 'Yaw Angle Right [°]', 'Speed hor. [km/h]', 'Speed vert. [km/h]', 'Speed resulting [km/h]', 'WindTime|WindName|WindSpeed|WindSpeedTangent|Wind...') and number of rows corresponding to the length of the jump. Data is recorded for every meter of air distance from the take-off point. of air distance from the take-off point.

The data required some preprocessing before it could be used for training the model. The column Time was written using a format: 0001-01-01T00:00:00.0000000+01:00. Here the 0001-01-01 means the date (January first in the year one), which is a place holder date, so we removed it. The +01:00 at the end indicates the time zone, which we also removed. The remaining part 00:00:00.0000000 indicates the time of the jump in hours, minutes, seconds and milliseconds. We converted this to a numerical value in seconds, which was then used as the time variable in the model. The column 'WindTime|WindName|WindSpeed|WindSpeedTangent|Wind...' contained multiple pieces of information separated by '|'. The

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

Information Society 2025, Ljubljana, Slovenia

© 2025 Copyright held by the owner/author(s).

wind was recorded on 12 sensors placed along the hill, each measuring one of the seven wind feature in the order represented in the column name. To keep all the data and not multiply the time stamps, we split this column into $12 \cdot 6 = 72$ columns, each representing one of the wind features for one of the sensors (sensor_feature).

Position - air distance from the take-off point in meters. Begins with a negative value, which represents the distance from the starting point to the take-off point. In ski jumping the starting point is adjusted according to the wind conditions, so this value is not constant.

Height above ground - height above the ground in meters.

Time - time of the jump in seconds from the start of the jump.

X, Y, Z - coordinates of the jumper in a 3D space in meters. The X axis is aligned with the hill direction, the Y axis is across the hill and the Z axis is vertical. The take-off point is at (0,0,0). AS SHOWN IN FIGURE.

Opening Angle - angle between the skis in degrees. IN THE PICTURE...

Stalling Angle Left, Stalling Angle Right - angle between the left/right ski and the horizontal plane in degrees.

Roll Angle Left, Roll Angle Right - angle between the left/right ski and the horizontal plane in degrees.

Yaw Angle Left, Yaw Angle Right - angle between the left/right ski and the horizontal plane in degrees.

Speed hor., Speed vert., Speed resulting - horizontal, vertical and resulting speed of the athlete in km/h.

And the wind features are as follows:

WindTime - time of the wind measurement in the same format as the Time column itself. Since the wind measurements are recorded less often, the wind values are applied to the most recent jump measurement and then just repeated until a new wind measurement is available. Since the wind is represented by a nonlinear function, it would be hard to capture it's movements with interpolation, so we decided to drop this column.

WindName - name of the sensor (Wi for $i = 1, \dots, 12$)

WindSpeed - resulting speed of the wind in km/h

WindSpeedTangent - speed of the wind tangent measured alongside the x axis (hill direction) in km/h

WindTurbulence - vertical speed of the wind turbulence in km/h

WindSpeedCleanTan - wind speed tangent with turbulence removed in km/h

WindSpeedCross - speed of the wind measurement alongside y axis across the hill in km/h

Durring the preprocessing we also removed some ski jumps that were incomplete or had corrupted data, so the final dataset contained around 200 ski jumps.

2.3 Additional Information

There are 12 wind sensors spread across on the ski jumping hill. To help with the analysis we separated the jumping section of the hill into 3 zones. The first zone contains wind sensos 1 to 4, the second zone contains sensors 5 to 8 and the third zone contains sensors 9 to 12.

3 Methodology

This section outlines our research methodology. We first present different variations of the SSM that we tested for the ski jump simulation, followed by describing our model and how it predicts the jumps. Finally, we present the description of our ski jump animation app.

3.1 Different variations as opposed to SSM

Some of the alternative approaches we considered for modeling ski jumps included classical physics-based models, but the data isn't sufficient to accurately capture all the forces acting on the jumper. We also tried a hybrid approach combining SSM and Physics-informed Neural Networks (PINNs), where the SSM would provide a baseline prediction, and the PINN would learn to correct any discrepancies, where it takes into account physical properties of the system, such as the mass of the pilot, wind properties and gravitational force. These parameters are included in the equations of motion, which are added to the overall loss function. So the model prefers solutions that are consistent with the laws of physics.. This turned out out to be less effective than a pure SSM approach. But the reason exceeds the this paper's purpose.

3.2 Ski jump prediction model

In order to fit our data to the SSM, we stored the data in for each file in three vectors. The main vector contains states or state variables of the system, which in our case are the X, Y and Z coordinates and velocitys of the jumper, and all the angles (opening, stalling, roll and yaw).

The observation vector contains the measured outputs of the system, which in our case are the X, Y and Z coordinates and height above ground. And the controls contain the external inputs to the system, which in our case are the wind measurements from all the sensors, that are averaged over each zone and feature (speed, tangent, cross and turbulence).

We then used the ridge regression to estimate the matrices A, B, C and D of the SSM, where we minimize the computed values from current and previous values and the next time stamp values. Thus the matrix A computes the next state from the current state, B computes the next state from the current control, C computes the next observation from the current state and D computes the next observation from the current control. We then use recursion to predict the next state from the prediction of the previous state and the current control, to get the full simulated jump. This allows us to predict the jump trajectory based on the environmental conditions and the starting state of the jumper.

3.3 Ski jump animation app

To make our results accessible beyond the research setting, we developed an interactive web application using Shiny for Python. The application serves as a front-end to the trained state space model and allows users to explore ski jump simulations under varying environmental conditions or just to observe different measured ski jumps. Through a set of input controls, users can adjust factors such as wind speed, wind directions, or different ski angles, and the application instantly updates the predicted jump trajectory.

The application presents the results as an animated visualization of the ski jump, showing the full trajectory and the final distance. In this way, the application functions both as an analytical tool, helping to test how different conditions affect performance,

and as an educational resource that makes the mechanics of ski jumping more easier to understand for a wider audience.

4 Main results

In this section, we present the results of our simulations. Firstly, we present a statistical comparison of all the models, followed by a precise analysis of our predictions.

kokr rezultati, kaj sva dosegli ig natančno opiševa kako sva preverjali kok dober je najin model in pač tudi poveva kok dober je najin model, mal še s tistimi napakami vrjetn pa tko

4.1 Models' comparison

In order to evaluate different models, we first had to define a metric for measuring the prediction error. Since the actual and simulated jumps are represented with X, Y, Z coordinates, but are measured at different time stamps, and can contain a different number of measurements, we had to find a way to compare them. We first tried to project the shorter trajectory on to the other one and compute the distance between the the original and the projection, but this method turned out to be computationally expensive. So we later decided to compute the distance between the actual and the simulated jump by interpolating both jumps. The new measurements contain the start and the end point and all the ones, where x reaches a natural value. We then compute the error as the norm of the difference between the two jumps. And after one of the jumps ends, we just add the distance from the end of the shorter jump to the end of the longer jump to the error. This way we penalize the model for not being able to predict the correct length of the jump.

Since we had a limited number of jumps, we used leave-one-out cross-validation to evaluate the models. For each jump, we trained the model on all the other jumps and then simulated the left out jump. We then computed the average error between the actual and the simulated jump for both the training and the test set.

In the process of developing our ski jump prediction model, we evaluated several variations to determine the most effective approach. We compared the performance of a pure State Space Model (SSM) against a hybrid model that combined SSM with Physics-informed Neural Networks (PINNs). The pure SSM demonstrated superior predictive accuracy, likely due to its ability to directly model the temporal dynamics of ski jumps without the added complexity of PINNs. (MAYBE ADD ACTUAL NUMBERS HERE) We also experimented with different configurations of the SSM, including using all available wind sensor data versus an averaged value of the zone. When we used all the sensors, the average error for each point (on training data is 1.67m and on test data is 1.89m), while when we averaged the sensors over the zones the error (on training data was 1.76m and on test data 1.82m). This suggests that averaging the wind data helps with the simulation.

4.2 Analysis of our model

Because the predictions of the model are made with matrix multiplications, they are very fast to compute, but also dependant on the stability of the matrices. To ensure the stability of the model, we computed the eigenvalues of the A matrix. And while most of the eigenvalues had an absolute value less than one, some were slightly above one. This indicates that the model is not fully stable, but should still produce reasonable results.

Since the wind is a very important factor in ski jumping, we also tried to capture the nonlinear movements of the wind by adding columns containing the square of the wind features. (ADD RESULTS IF ANY).

Since the simulation still requires quite a few inputs, we also made the simulation interactive, so the user can adjust the wind and see how it affects the jump. On the ski jumping app the user can use sliders to choose the wind speed, wind tangent, wind cross and wind turbulence for each of the three zones. This also means that the wind loosens the actual movement function. The rest of the inputs are set to the average values of all the jumps in the dataset.

5 Discussion

mal razglabljas o vsem, torej mal povežeš skupi kar sva do zdej povedali in predlagava kksne možne izboljšave mogoče torej najprej kok dober je najna stvar delala, kako sva bli omejeni (mogoče da nisva meli ful velik podatkov?) in kaj še lahko in bova izboljšali

This section examines the predictive performance of the trajectories, highlights the limitations of our current approach, and suggests directions for future improvements.

5.1 Limitations

The main limitation of our project is the relatively small number of ski jumps available for training the model. After preprocessing, the dataset contained only about 200 jumps, which may limit the SSM's ability to represent the full range of trajectory variations under different circumstances. As a result, the model may struggle to accurately predict jumps under novel or extreme conditions.

Additionally, the dataset lacks detailed information, or any information at all about individual jumpers, such as body weight, sex, or other physiological characteristics that are known to influence jump performance. Incorporating these variables could improve model accuracy and provide more personalized predictions.

Lastly, due to limited computing power, only one CPU with - of space was available, restricting the use of possible better models. To address these challenges, using cloud-based resources could help run larger models and improve the prediction of trajectories.

5.2 Future work and potential improvements

While the current approach shows promise, there are several avenues for future improvements. Some of which we are working on as of the time of writing this paper.

currently we are working on improving the sliders functions. Since the wind data determined by the user is static throughout the jump this adds a lot of generalization. In reality, wind conditions can change rapidly during a jump. So we would like to add additional controls to the app that would allow the user to define how the wind changes during the jump. They could choose whether the wind would be gaining or losing a certain feature (such as speed or turbulence) during the jump.

Expanding the dataset to include more jumps and additional contextual information about individual jumpers could enhance model accuracy. We could try to generate more data by using data augmentation techniques, such as adding noise to the wind measurements or slightly modifying the angles.

We could also try to find the the nonlinear movements of the wind and interpolating the wind measurements by their original time stamps to better capture the wind dynamics.

6 Conclusion

This paper presents a method for predicting ski jump trajectories based on environmental conditions. By incorporating external factors into the modeling framework and applying least squares estimation, we demonstrated that the model is capable of capturing the dynamics of ski jumps and producing realistic trajectory predictions. Furthermore, we developed an interactive application that makes the results accessible to a broader audience through simulations and animations of predicted jumps.

7 Acknowledgments

This work was supported by the Ski Association of Slovenia (SAS), whom we would like to thank for providing the ski jump data. The research was funded by (ADD WHEN YOU FIND OUT).

References

- [1] J. Doe and A. Novak. A Tiny Demo Entry. *Journal of Examples*, 2024.