

# Improving Viral Diagnostic Methods: A MATLAB Single Virion Counting System Utilizing Gold Nanoparticle Virus Aggregation and Plasmonic Nanobubble Detection

Bryan Hong, Jai Pal

## ISSUE


One of the largest issues plaguing the field of medicine is the lack of an accurate and efficient form of viral diagnosis. For example, our two most commonly utilized test diagnosis systems, the PCR and rapid test, sacrifice either accuracy or speed to achieve the other. Another issue currently present is the issue of viral quantification, the counting of virions within a nasal sample. These provide doctors with crucial information in treating infections; however, our current methods are under-developed, unstandardized, too slow, or too inaccurate.

### RSV Test Accuracy:

**PCR:** 94% accuracy, avg 2 hours

**Rapid Test:** 75% accuracy, avg 15 mins

**LAMP Test:** 91% accuracy, avg 50 mins



Demonstration of the Cycle Threshold Viral Quantification Mechanism. Figure created by Bryson Tiller.

## ENGINEERING GOALS

**I.** Design a virus detection mechanism that rapidly and accurately detects the Human Respiratory Syncytial Virus (RSV).

**II.** Create a virus quantification system that that determines the viral load using an individual virion counter.

**III.** Code an computer algorithm that takes in the virion count, age, and other factors as an input and outputs values such as the viral prognosis timeline and the severity of the infection in order to provide healthcare workers with a better interpretation of the virion count.

## MATERIALS

### CHEMICAL:

- 1) Deionized Water ( $\text{dH}_2\text{O}$ ), 195 mL, resistivity of  $18.0 \text{ M}\Omega \cdot \text{cm}$
- 2) Gold nanoparticle seeds.  $0.338 \text{ mL}$ ,  $2.23 \text{ nM}$
- 3) Tetra chloroauric (III) acid trihydrate ( $\text{HAuCl}_4 \cdot 3\text{H}_2\text{O}$ , 16961-25-4, 99.9%),  $1.997 \text{ mL}$ ,  $25 \text{ mM}$
- 4) Sodium Citrate tribasic dihydrate ( $\text{Na}_3\text{CA} \cdot 2\text{H}_2\text{O}$ , 6132-04-3,  $\geq 99\%$ ),  $1.997 \text{ mL}$ ,  $112.2 \text{ mM}$
- 5) 3,3'-Dithiobis (sulfosuccinimidyl propionate) (DTSSP, 21578),  $50 \text{ mg}$ ,  $5 \text{ mM}$
- 6) Borate Buffer,  $2 \text{ Mm}$

### BIOLOGICAL:


- 1) Palivizumab/Synagis
- 2) Purified Human Respiratory Syncytial Virus strain A2

### EQUIPMENT:

- 1) Amicon™ ultra centrifugal filter units
- 2) Centrifuge machine
- 3)  $250 \text{ mL}$  Erlenmeyer flask
- 4) Magnetic hot plate
- 5) Red HeNe  $633 \text{ nm}$  laser
- 6) Ekspla 28 ps,  $532 \text{ nm}$ , ultrafast pump laser
- 7)  $200 \mu\text{m}$  micro-capillary
- 8) MATLAB software for data collection
- 9) Synergy 2 BioTek plate reader
- 10) Malvern ZetaSizer Nano ZS DLS Machine
- 11) JEOL JEM-2010 Transmission electron microscope
- 12) Thorlabs photodetector for data collection
- 13) LeCroy WaveRunner oscilloscope for data collection
- 14) Syringe pump
- 15) Tkinter Python Interface Software
- 16)  $10 \text{K MWCO}$  Dialysis Cassette
- 17)  $20, 200, 500$ , and  $1000 \mu\text{L}$  pipette


## METHODOLOGY

**AuNP Synthesis-**  $15 \text{ nm}$  AuNPs were synthesized using the Plech Turkevich method. The deionized water, gold nanoparticle seeds, tetra chloroauric acid, and sodium citrate were mixed together in a  $250 \text{ mL}$  Erlenmeyer flask on a magnetic hot plate. Repeat this twice.



Unjugated 15nm AuNPs

**AuNP Virus Conjugation-** One batch of the  $15 \text{ nm}$  AuNPs were incubated in a  $2 \text{ Mm}$  borate buffer while the DTSSP crosslinkers were incubated with the Synagis antibodies for  $15 \text{ mins}$ . Eventually the DTSSP-Synagis were combined with the AuNPs in the borate buffer. Finally, sucrose-purified A2 RSV strains were incubated with the AuNPs for  $10 \text{ mins}$ , and then cleaned using the Amicon centrifugal units, creating RSV-conjugated AuNPs.



RSV-conjugated 15nm AuNPs

**Laser Detection Setup-** The  $28 \text{ ps}$ ,  $532 \text{ nm}$ , pulsating laser beam and the red HeNe laser beam were focused together through the center of the cross-section of the  $200 \mu\text{m}$  micro-capillary. A syringe pump pumps the AuNP solution at a rate of  $6 \mu\text{L}/\text{minute}$ . The laser beams were focused onto a photodetector and an oscilloscope.





Diagram of the oscilloscope


## METHODOLOGY

**Virion Counting Mechanism-** The picosecond laser will hit the AuNPs causing it to generate small **nanobubbles**. When the red HeNe laser hits the nanobubble, some of its energy will be **diffracted**, causing a decrease of laser energy. This decrease of energy is represented by the oscilloscope as a small dip in the laser energy. Furthermore, the size of the nanobubble also affects the amount of laser energy being diffracted. Unconjugated AuNPs will generate smaller nanobubbles, causing a smaller dip; while RSV-conjugated AuNPs will generate larger nanobubbles, causing it to diffract more laser energy and generate a larger dip.


**Threshold calculation-** One batch of the **unconjugated** AuNPs was pumped through the system. The **amplitude** and **area-under-the-curve (AUC)** was recorded for every nanobubble signal. Since the values for amplitude and AUC are normally distributed, the **threshold** was calculated to be  $\mu + 5\sigma$ . Finally, the batch of RSV-conjugated nanoparticles was pumped through, and the **amplitudes** and **AUC** were recorded for every single value. If either the values for amplitude **OR** AUC were greater than its respective threshold value, then an ON signal is counted, indicating 1 RSV virion. The virion count along with other values were inputted into a coding algorithm.



Laser diffraction by Gold nanoparticle





Oscilloscope dip generated by unconjugated vs conjugated AuNP



Threshold values



## RESULTS



**TRIAL 1:**  
0 PFU mL: **0 virions**  
TAMP: **225.65 mV**, Tauc: **137.13x10<sup>3</sup> mV·ns**  
10 PFU mL: **3 virions**  
100 PFU mL: **10 virions**  
10<sup>3</sup> PFU mL: **156 virions**  
10<sup>4</sup> PFU mL: **895 virions**  
10<sup>5</sup> PFU mL: **4.321x10<sup>4</sup> virions**  
5x10<sup>5</sup> PFU mL: **2.4787x10<sup>5</sup> virions**

**AVERAGE PERCENTAGE OF ON SIGNALS:**  
10 PFU mL: **0.452%**  
100 PFU mL: **0.530%**  
10<sup>3</sup> PFU mL: **0.712%**  
10<sup>4</sup> PFU mL: **2.792%**  
10<sup>5</sup> PFU mL: **97.621%**  
5x10<sup>5</sup> PFU mL: **98.172%**

## RESULTS



**SPEED OF DIAGNOSIS (mins):**  
**Nanobubble: 11.2**  
**PCR: 120**  
**Rapid: 15**  
**LAMP: 45**

**ACCURACY OF RESULTS (%):**  
**Nanobubble: 99**  
**PCR: 94**  
**Rapid: 80**  
**LAMP: 91**

## CONCLUSIONS

**I.** The results indicate that the **nanobubble** test reported an average speed of diagnosis that is around **4 minutes faster** than our current fastest means of diagnosis and reported an average sensitivity that is **5% higher** than our current most sensitivity means of diagnosis. Thus, concluding that our **engineering goal I** has been successfully accomplished.

**II.** Using Poisson Statistics to cross-validate the theoretical vs experimental results, we concluded that our virion counting mechanism had an accuracy rate of **97.8%**. This indicates that our **engineering goal II** has successfully been accomplished. However, we found that the  $\mu + 5\sigma$  threshold value created too many type II errors. **In future research**, we will work to minimize both type I and type II errors.

**III.** Our virion counting algorithm was compared to many clinical studies of individuals with virion counts. Since the outputs of our python coding algorithm were all qualitative data, statical analysis was not viable. We did conclude that our virion coding algorithm produced around an **88%** accuracy result, indicating that our **engineering goal III** was successful accomplished. However, more work to calibrate and incorporating other factors into our system is necessary for **future research**.

## IMPACTS

**I. Scientists-** Scientists would be able to use our technology to allow them to understand the spread of pandemics and viruses, potentially saving millions of lives as they are able to better prevent and diagnosis viruses.

**II- Healthcare Workers-** Healthcare workers could utilize our virion counting mechanism and our coding algorithm to personalize treatments for individual patients. For example, different amounts of viral load with different severities could be prescribed different kinds of medication and different types of monitoring. Notably, a baby with a high virion count could be prescribed to be monitored more carefully than a healthy adult with a low virion count.

**With pandemics jeopardizing the lives of billions across this planet, it's up to hands of scientists to develop technology that promises to save lives.**