Tutorial 5: Logical Database Design

Jin, Ziyang Kim, # 34893140 # 3 f4a0b

Kim, Joon Hyung # 35183128 11m8

February 2018

StudentInfo(S, N, M, A, C, T, I, L, G)

with the following FDs:

- $1. S \rightarrow N$
- 2. C -> T, I
- 3. I -> L
- $4. S, C, M \rightarrow G$
- 5. S, M -> A
- $6. A \rightarrow M$

1 Find all keys and prove that you have found them all.

Since S and C do not appear in any RHS of the FDs, S and C must be part of every key.

(S C)⁺ = S C N T I L \neq SI, so (S C) is not a key.

Guess (S C M) and (S C A) are keys.

 $(S C M)^+ = (S C M N T I L G A) = SI so (S C M)$ is a superkey.

 $(S C A)^+ = (S C A N T I L G M) = SI so (S C A)$ is a superkey.

Since (S C) is not a key, so (S C M) and (S C A) are minimal, so they are keys.

Consider the maximal set $X \subseteq (S \ N \ M \ A \ C \ T \ I \ L \ G)$ such that $(S \ C) \subset X$ and A, $M \notin X$. The maximal such X is $(S \ N \ C \ T \ I \ L \ G)$ $X^+ = (S \ N \ C \ T \ I \ L \ G)^+ = S \ N \ C \ T \ I \ L \ G \neq SI$ So any set other than $(S \ C \ M)$ and $(S \ C \ A)$ cannot be a key.

Therefore, (S C M) and (S C A) are the only keys for the relation SI.

2 Find a minimal cover for this set of FDs.

- Put the FDs in a Standard Form.
 S->N, C->T, C->I, I->L, SCM->G, SM->A, A->M.
- Minimize the Left Side of Each FD.
 Single attribute left sides are already minimized.
 SCM->G: S,C do not appear on LHS. M cannot be reduced from S,C.
 SM->A: S does not appear on LHS. M cannot be reduced from S.
 So the left sides are all minimized.
- Delete Redundant FDs.
 N, T, I, L, G, A, Monly appear once on RHS, so there is no redundant FD.

So the minimum cover for this set of FDs is:

- 1. S -> N
- $2. C \rightarrow T$
- 3. C -> I
- 4. I -> L
- $5. S, C, M \rightarrow G$
- $6. S, M \rightarrow A$
- $7. A \rightarrow M$

3 Obtain a lossless-join, BCNF decomposition of StudentInfo.

For FD (1): S->N, we decompose SI to S1 = (S N)

S2 = (S M A C T I L G)

For FD (3): I->L, we decompose S2 to

S3 = (I L)

S4 = (S M A C T I G)

For FD (2): C->T, I, we decompose S4 to

S5 = (C T I)

S6 = (S M A C G)

For FD (4): S,C,M->G, we decompose S6 to

S7 = (S C M G)

S8 = (S C M A)

```
For FD (6): A\rightarrow M, we decompose S8 to S9 = (A M) S10 = (S C A)
```

Note that FD (5) cannot be applied to any final decomposed relation, so the decomposition is done. FD (5): S,M->A is not preserved. So the final decomposition of StudentInfo is:

```
S1 = (S N)

S3 = (I L)

S5 = (C T I)

S7 = (S C M G)

S9 = (A M)

S10 = (S C A)
```

4 Obtain a lossless-join, dependency-preserving, 3NF decomposition of StudentInfo by making use of the BCNF decomposition in Question (c).

```
The BCNF decomposition we obtained from (c) does not preserve FD (5): S,M->A, so we add S11 = (S M A).

So the final 3NF decomposition is:
S1 = (S N)
S3 = (I L)
S5 = (C T I)
S7 = (S C M G)
S9 = (A M)
S10 = (S C A)
S11 = (S M A)
```

5 Obtain a lossless-join, dependency-preserving, 3NF decomposition of StudentInfo via synthesis by making use of your minimal cover in Question (b).

The minimum cover is S->N, C->T, C->I, I->L, SCM->G, SM->A, A-M. The relations obtained from a minimum cover set is:

```
R1 = (S N)
R2 = (C T)
R3 = (C I)
R4 = (I L)
R5 = (S C M G)
R6 = (S M A)
R7 = (A M)
```

6 Comment on the differences, if any, between your answers to Questions (d) and (e).