

Tutorial 3: Logical Database Design

Mapping ER Diagrams to the Relational Model

Jin, Ziyang
34893140
f4a0b

Kim, Joon Hyung
35183128
11m8

January 2018

1. 1:1

We choose to merge the relation to X side:

$X_R(\underline{K1}, A1, \mathbf{K2})$

K2 REFERENCES Y

$Y(\underline{K2}, A2)$

2. 1:M

$X(\underline{K1}, A1)$

$Y_R(\underline{K2}, A2, \mathbf{K1})$

K1 REFERENCES X

3. M:N(Binary Relationship)

$X(\underline{K1}, A1)$

$Y(\underline{K2}, A2)$

$R(\underline{\mathbf{K1}}, \underline{\mathbf{K2}}, A3)$

K1 REFERENCES X,

K2 REFERENCES Y

4. M:N(Ternary Relationship)

$X(\underline{K1}, A1)$

$Y(\underline{K2}, A2)$

Z(K3, A3)

R(K1, **K2**, **K3**, A4)
K1 REFERENCES X,
K2 REFERENCES Y,
K3 REFERENCES Z

5. 1:M Strong Entity with Total Participation

X(K1, A1)

Y R(K2, A2, **K1**)
K1 REFERENCES X, K1 cannot be null

6. 1:M Weak Entity with Total Participation (assume that A2 is the partial key)

X(K1, A1)

Y(A2, **K1**, A3)
K1 REFERENCES X, ON DELETE CASCADE

7. 1:1 and 1:M Unary Relationship

X(K1, A1, **RK1**)
RK1 REFERENCES X(K1)

8. M:N Unary Relationship

X(K1, A1)

R(R1K1, **R2K1**)
R1K1 REFERENCES X(K1),
R2K1 REFERENCES X(K1)

9. ISA 1

Assumption: not disjoint and not covering

X(K1, A1)

Y(K1, A2, A3)
K1 REFERENCES X

$Z(\underline{\mathbf{K1}}, A4, A5)$
 $\mathbf{K1}$ REFERENCES X

10. ISA 2 (the "d" means disjoint)
 Assumption: disjoint and covering

$Y(\underline{\mathbf{K1}}, A1, A2, A3)$

$Z(\underline{\mathbf{K1}}, A1, A4, A5)$