

Multi-source Transfer Learning for Signal Detection over a Fading Channel with Co-channel Interference

Ziyan Zheng*, Xinyi Tong*, Xinchun Yu*, Xiangxiang Xu^{†‡} and Shao-Lun Huang*[§]

* Tsinghua-Berkeley Shenzhen Institute, Tsinghua University, China


† Department of Electrical Engineering and Computer Science, Massachusetts Institute of Technology, USA

Presenter: Ziyan Zheng

1

Background

Background




◆ Signal detection task -- detect X from Y

Standard model-based approaches may be inapplicable if:

- Precise channel model is unavailable
- Optimal receiver is complicated or unknown

e.g.

Existence of co-channel interference



General ways to study co-channel interference / non-Gaussian noise

- Ignore
- Treat as Gaussian noise

Fig 1. A constellation of transmitted QPSK-modulated signals with QPSK-modulated interference

Background

◆ Deep Learning

Strength -- Feature extraction from complex-distributed data

Difficulty -- Lack of pilots for training in time-varying channels




Fig 2. A data stream with pilots

◆ Transfer Learning

In a detector for time-varying channel,
can historical data be used in training? -- Yes




Fig 3. A simple deep neural network

2

Model and Theory

Model

$$Y_t = H_t X_t + I_t + n_t$$

received signal discrete transmitted symbol

time-varying channel state matrix co-channel interference AWGN

◆ Notations and Assumptions

- $t \in \mathbb{Z}$: time period / packet index
- Each period t contains many symbols to transmit, the first several ones are pilots
- H_t, X_t, I_t, n_t are pairwise independent

◆ Goal

- Detect X_T from Y_T at the latest period $T \in \mathbb{Z}$

◆ Available training samples for the detector

- Source samples: $\left\{ \left(x_t^{(i)}, y_t^{(i)} \right) \right\}_{i=1}^{N_t}$ for $t = 1, 2, \dots, T - 1$
- Target samples: $\left\{ \left(x_T^{(i)}, y_T^{(i)} \right) \right\}_{i=1}^{N_T}$, note that $N_T \ll N_t (\forall t < T)$

MSTL Framework

◆ Intuition

What kind of sources would provide more useful knowledge to target task?




Fig 4. Intuition for transfer learning

- Source task 1: quite good
- Source task 2: less samples → Sample size is important
- Source task 3: not like target task → Similarity is important

MSTL Framework

First – Assume received symbols Y_t are discrete

- Define empirical distributions (learned model) as $\hat{P}_{X_t Y_t}(x, y) \triangleq \frac{1}{N_t} \sum_{i=1}^{N_t} \mathbb{1}\left\{x_t^{(i)} = x, y_t^{(i)} = y\right\}, 1 \leq t \leq T$
- Consider the linear combination of sources and target

$$Q_{X_T Y_T}^{(\mathbf{w})} \triangleq \sum_{t=1}^T w_t \hat{P}_{X_t Y_t}$$

with combining weights

$$\mathbf{w} \in \{(w_1, w_2, \dots, w_T) : \sum_{t=1}^T w_t = 1, w_t \geq 0\}$$

Characterize the knowledge transferred from each source to the target

- Testing loss

$$L_{\text{test}}^{(\mathbf{w})} \triangleq \mathbb{E} \left[\chi^2 \left(P_{X_T Y_T}, Q_{X_T Y_T}^{(\mathbf{w})} \right) \right]$$

the corresponding optimal weights

$$\mathbf{w}^* \triangleq \arg \min_{\mathbf{w}} L_{\text{test}}^{(\mathbf{w})}$$

Definition 1. For random variable X and Y , given a reference distribution R_{XY} for any distribution P_{XY} and Q_{XY} , the referenced χ^2 -distance between them is defined as

$$\chi_R^2(P_{XY}, Q_{XY}) \triangleq \sum_{x \in \mathcal{X}, y \in \mathcal{Y}} \frac{(P_{XY}(x, y) - Q_{XY}(x, y))^2}{R_{XY}(x, y)}. \quad (7)$$

In particular, $\chi_R^2(P_{XY}, Q_{XY})$ becomes Pearson χ^2 -distance denoted by $\chi^2(P_{XY}, Q_{XY})$ when $R_{XY} = P_{XY}$.

MSTL Framework

Proposition 1 ([15], Theorem 3). *The testing loss (5) for the target task is*

$$L_{test}^{(\mathbf{w})} = \chi^2 \left(P_{X_T Y_T}, \sum_{t=1}^T w_t P_{X_t Y_t} \right) + \sum_{t=1}^T \frac{w_t^2}{N_t} V_t, \quad (8)$$

where V_t is defined as

$$V_t \triangleq \sum_{x \in \mathcal{X}, y \in \mathcal{Y}} \frac{P_{X_t Y_t}(x, y)(1 - P_{X_t Y_t}(x, y))}{P_{X_T Y_T}(x, y)}. \quad (9)$$

Key factors to determine usefulness of historical data

- **Channel similarity** measured by $\chi^2 \left(P_{X_T Y_T}, \sum_{t=1}^T w_t P_{X_t Y_t} \right)$
- **Number of pilots and previous signals** for training, i.e. N_t for $t = 1, 2, \dots, T$
- **Complexity of the model** characterized by the domain needed to capture, i.e. $|\mathcal{X}| |\mathcal{Y}| - 1$ in V_T

MSTL Framework

When Y_t are continuous:

How the DNN models the distribution?

How to avoid the high dimensionality $|\mathcal{X}||\mathcal{Y}|$?

- Adopt discriminative model

$$\tilde{P}_{X_T|Y_T}^{(\mathbf{f}, \mathbf{g})}(x|y) \triangleq P_{X_T}(x)(1 + \mathbf{f}^T(x)\mathbf{g}(y))$$

- Weight $\hat{\mathbf{f}}_t$ is defined as

$$\hat{\mathbf{f}}_t \triangleq \arg \min_{\mathbf{f}} \chi_{R_{XY}}^2 \left(\hat{P}_{X_t Y_t}, P_{Y_t} \tilde{P}_{X_t|Y_t}^{(\mathbf{f}, \mathbf{g})} \right)$$

- The convex combination becomes

$$Q_{X_T|Y_T}^{(\mathbf{w})} \triangleq \sum_{t=0}^T w_t \tilde{P}_{X_T|Y_T}^{(\hat{\mathbf{f}}_t, \mathbf{g})} = \tilde{P}_{X_T|Y_T}^{(\hat{\mathbf{f}}, \mathbf{g})} \quad \text{with } \hat{\mathbf{f}} \triangleq \sum_{t=1}^T w_t \hat{\mathbf{f}}_t$$

- Testing loss

$$L_{\text{test}}^{(\mathbf{w})} \triangleq \mathbb{E} \left[\chi_{R_{XY}}^2 \left(P_{X_T Y_T}, P_{Y_T} Q_{X_T|Y_T}^{(\mathbf{w})} \right) \right]$$




Fig 5. A DNN for classification

Proposition 2 ([15], Theorem 4). *The testing loss (13) associated with the model (12) is*

$$\begin{aligned} L_{\text{test}}^{(\mathbf{w})} &= \chi_{R_{XY}}^2 \left(P_{Y_T} \tilde{P}_{X_T|Y_T}^{(\mathbf{f}_T, \mathbf{g})}, \sum_{t=1}^T w_t \tilde{P}_{X_T|Y_T}^{(\mathbf{f}_t, \mathbf{g})} \right) \\ &\quad + \sum_{t=1}^T \frac{w_t^2}{N_t} \tilde{V}_t + \chi_{R_{XY}}^2 \left(P_{X_T Y_T}, P_{Y_T} \tilde{P}_{X_T|Y_T}^{(\mathbf{f}_T, \mathbf{g})} \right), \end{aligned} \quad (15)$$

where $\mathbf{f}_t \triangleq \arg \min_{\mathbf{f}} \chi_{R_{XY}}^2 \left(P_{X_t Y_t}, P_{Y_t} \tilde{P}_{X_t|Y_t}^{(\mathbf{f}, \mathbf{g})} \right)$ and \tilde{V}_t is a constant independent of \mathbf{w} .

3

Algorithm

Algorithm for MSTL Detector

Algorithm 1 Algorithm for training the MSTL detector

Input:

Historical samples $\left\{ \left(x_t^{(i)} y_t^{(i)} \right) \right\}_{i=1}^{N_t}$ ($t = 1, 2, \dots, T - 1$)

Pilots $\left\{ \left(x_T^{(i)} y_T^{(i)} \right) \right\}_{i=1}^{N_T}$

Randomly initialize \mathbf{w}^* and DNN parameters

Output:

```

1: repeat
2:    $(\mathbf{f}^*, \mathbf{g}^*) \leftarrow \arg \min_{\mathbf{f}, \mathbf{g}} L^{(\mathbf{w}^*, \mathbf{f}, \mathbf{g})}$ 
3:    $\mathbf{w}^* \leftarrow \arg \min_{\mathbf{w}} L_{\text{test}}^{(\mathbf{w})}$ 
4: until  $\mathbf{w}^*$  converges
5:  $(\mathbf{f}^*, \mathbf{g}^*) \leftarrow \arg \min_{\mathbf{f}, \mathbf{g}} L^{(\mathbf{w}^*, \mathbf{f}, \mathbf{g})}$ 
6: return  $\mathbf{f}^*, \mathbf{g}^*$ ;

```



Determine \hat{x} by the MAP decision rule

$$\begin{aligned}\hat{x}(y) &= \arg \max_{x \in \mathcal{X}} \tilde{P}_{X_T|Y_T}^{(\mathbf{f}^*, \mathbf{g}^*)}(x|y) \\ &= \arg \max_{x \in \mathcal{X}} P_{Y_T}(y) \left(1 + \mathbf{f}^{*T}(x) \mathbf{g}^*(y) \right)\end{aligned}$$

Train neural networks

Solve a non-negative quadratic programming problem

- Loss function optimizing (\mathbf{f}, \mathbf{g})

$$L^{(\mathbf{w}, \mathbf{f}, \mathbf{g})} \triangleq \sum_{t=1}^T w_t \chi_{R_{XY}}^2 \left(\hat{P}_{X_t Y_t}, P_{Y_T} \tilde{P}_{X_T|Y_T}^{(\mathbf{f}, \mathbf{g})} \right)$$

- Loss function optimizing \mathbf{w}

$$\begin{aligned}L_{\text{test}}^{(\mathbf{w})} &= \chi_{R_{XY}}^2 \left(P_{Y_T} \tilde{P}_{X_T|Y_T}^{(\mathbf{f}_T, \mathbf{g})}, \sum_{t=1}^T w_t \tilde{P}_{X_T|Y_T}^{(\mathbf{f}_t, \mathbf{g})} \right) \\ &\quad + \sum_{t=1}^T \frac{w_t^2}{N_t} \tilde{V}_t + \chi_{R_{XY}}^2 \left(P_{X_T Y_T}, P_{Y_T} \tilde{P}_{X_T|Y_T}^{(\mathbf{f}_T, \mathbf{g})} \right)\end{aligned}$$

4

Simulation

Setting

$$Y_t = H_t X_t + I_t + n_t$$

◆ Time-varying flat Rayleigh fading channel with co-channel interference

- H_t -- Gauss-Markov process $H_t = aH_{t-1} + u_t$, $u_t \sim \mathcal{CN}(0, (1-a^2)\sigma_H^2)$
- X_t -- QPSK-modulated signals $X_t = K_t + jQ_t$, $(K_t, Q_t) \in \{(1,1), (-1,1), (-1,-1), (1,-1)\}$
- I_t -- QPSK-modulated interference $I_t \in \{q + jq, -q + jq, -q - jq, q - jq\}$ for some constant q
- n_t -- AWGN with variance σ_n^2

◆ Update process of the MSTL detector




Fig 6. The update process of the detector

Simulation

◆ Comparisons

- FCDNN-1 Conventional fully-connected DNN based on L_2 loss, using N_T pilots for training
- FCDNN-2 Using N_T pilots and $\sum_{t=T-9}^{T-1} N_t$ reserved samples for training
- LMMSE Estimate CSI by N_T pilots

◆ Implementation

- Measure of interference level

$$\text{SINR} \triangleq 10 \lg \frac{\sigma_H^2 |X_t|^2}{\sigma_n^2}$$

Set $q \propto \sigma_n$ for the consistency of interference and noise

- For each task time T , $N_t = 200$ for $t = T - 9, T - 8, \dots, T - 1$, discard samples before $t = T - 10$
- We vary: (i) Fading coefficient a
(ii) Number of pilots N_T
(iii) SINR

Simulation

◆ Results

- Largest gain occurs in the range $a \in [0.9875, 0.9975]$




Fig 7

- Low BER for high SINR




Fig 8

Simulation

◆ Results

- Outperforms other algorithms in a large range of pilots length




Fig 9

- Monotonous similarity of the sources




Fig 10

5

Conclusion

Main contributions

- We adopt a mathematical framework of MSL and develop a detection algorithm for time-varying channels. Our MSL-based detector involves pilots and much previous data in the training scheme to mitigate the effect of interference, without the direct estimation for CSI.
- Unlike most of the previous works that either ignored interference or treated interference as Gaussian noise, non-Gaussian-distributed co-channel interference is taken into consideration in the channel model.
- The proposed MSL detector is implemented in the signals stream over a simulated time-varying fading channel in the presence of co-channel interference, in which we show that our algorithm outperforms both the traditional method and conventional neural networks without the design of knowledge transfer in a variety of scenarios.

References

- [1] Z. Guo and P. Nilsson, "Algorithm and implementation of the k-best sphere decoding for mimo detection," *IEEE Journal on selected areas in communications*, vol. 24, no. 3, pp. 491–503, 2006.
- [2] S. Wu, L. Kuang, Z. Ni, J. Lu, D. Huang, and Q. Guo, "Low-complexity iterative detection for large-scale multiuser mimo-ofdm systems using approximate message passing," *IEEE Journal of Selected Topics in Signal Processing*, vol. 8, no. 5, pp. 902–915, 2014.
- [3] H. He, C.-K. Wen, S. Jin, and G. Y. Li, "Model-driven deep learning for mimo detection," *IEEE Transactions on Signal Processing*, vol. 68, pp. 1702–1715, 2020.
- [4] S. Park, H. Jang, O. Simeone, and J. Kang, "Learning to demodulate from few pilots via offline and online meta-learning," *IEEE Transactions on Signal Processing*, vol. 69, pp. 226–239, 2020.
- [5] O. Simeone, "A very brief introduction to machine learning with applications to communication systems," *IEEE Transactions on Cognitive Communications and Networking*, vol. 4, no. 4, pp. 648–664, 2018.
- [6] S. Bouchired, D. Roviras, and F. Castanié, "Equalisation of satellite mobile channels with neural network techniques," *Space Communications*, vol. 15, no. 4, pp. 209–220, 1998.
- [7] C. Liu, Y. Chen, and S.-H. Yang, "Signal detection with co-channel interference using deep learning," *Physical Communication*, vol. 47, p. 101343, 2021.
- [8] S. Catreux, P. F. Driessens, and L. J. Greenstein, "Attainable throughput of an interference-limited multiple-input multiple-output (mimo) cellular system," *IEEE transactions on communications*, vol. 49, no. 8, pp. 1307–1311, 2001.
- [9] V. S. Annapureddy and V. V. Veeravalli, "Gaussian interference networks: Sum capacity in the low-interference regime and new outer bounds on the capacity region," *IEEE Transactions on Information Theory*, vol. 55, no. 7, pp. 3032–3050, 2009.
- [10] A. Carleial, "A case where interference does not reduce capacity (corresp.)," *IEEE Transactions on Information Theory*, vol. 21, no. 5, pp. 569–570, 1975.
- [11] H. Ye, G. Y. Li, and B.-H. Juang, "Power of deep learning for channel estimation and signal detection in ofdm systems," *IEEE Wireless Communications Letters*, vol. 7, no. 1, pp. 114–117, 2017.
- [12] N. Farsad and A. Goldsmith, "Neural network detection of data sequences in communication systems," *IEEE Transactions on Signal Processing*, vol. 66, no. 21, pp. 5663–5678, 2018.
- [13] S. Thrun, L. K. Saul, and B. Schölkopf, *Advances in Neural Information Processing Systems 16: Proceedings of the 2003 Conference*, vol. 16. MIT press, 2004.
- [14] C. Tan, F. Sun, T. Kong, W. Zhang, C. Yang, and C. Liu, "A survey on deep transfer learning," in *International conference on artificial neural networks*, pp. 270–279, Springer, 2018.
- [15] X. Tong, X. Xu, S.-L. Huang, and L. Zheng, "A mathematical framework for quantifying transferability in multi-source transfer learning," *Advances in Neural Information Processing Systems*, vol. 34, 2021.
- [16] S. Rendle, "Factorization machines," in *2010 IEEE International conference on data mining*, pp. 995–1000, IEEE, 2010.
- [17] O. Levy and Y. Goldberg, "Neural word embedding as implicit matrix factorization," *Advances in neural information processing systems*, vol. 27, pp. 2177–2185, 2014.
- [18] M. Dong, L. Tong, and B. M. Sadler, "Optimal insertion of pilot symbols for transmissions over time-varying flat fading channels," *IEEE Transactions on Signal Processing*, vol. 52, no. 5, pp. 1403–1418, 2004.
- [19] G. A. Arredondo, W. H. Chriss, and E. H. Walker, "A multipath fading simulator for mobile radio," *IEEE Transactions on Vehicular Technology*, vol. 22, no. 4, pp. 241–244, 1973.
- [20] R. A. Iltis, "Joint estimation of pn code delay and multipath using the extended kalman filter," *IEEE Transactions on communications*, vol. 38, no. 10, pp. 1677–1685, 1990.
- [21] M. Stojanovic, J. G. Proakis, and J. A. Catipovic, "Analysis of the impact of channel estimation errors on the performance of a decision-feedback equalizer in fading multipath channels," *IEEE Transactions on Communications*, vol. 43, no. 2/3/4, pp. 877–886, 1995.
- [22] M. Medard, "The effect upon channel capacity in wireless communications of perfect and imperfect knowledge of the channel," *IEEE Transactions on Information theory*, vol. 46, no. 3, pp. 933–946, 2000.
- [23] D. Qiu, *Representation and transfer learning using information-theoretic approximations*. PhD thesis, Massachusetts Institute of Technology, 2020.
- [24] H. Kim, Y. Jiang, R. Rana, S. Kannan, S. Oh, and P. Viswanath, "Communication algorithms via deep learning," *arXiv preprint arXiv:1805.09317*, 2018.
- [25] S. Verdu *et al.*, *Multiuser detection*. Cambridge university press, 1998.

Thanks !