


Bipartite Grid Partitioning of a Random Geometric Graph

Zizhen Chen and David W. Matula

Southern Methodist University


{zizhenc, matula}@smu.edu

DCOSS 2017, Ottawa, Canada




Outline


- Introduction
 - Background
 - Question (Purpose)
- Modeling
 - Goal
 - Topologies
 - Cell Method
- Procedure Overview
- Backbone Grid Partitioning Algorithms
 - Smallest-last Coloring
 - Relay Coloring
- Determine Backbone Grid
- Bi-regular Backbone Grid Feature
- Benchmark Data Sets
- Visualization and 3D Exploration
- Conclusions, Questions and Future Works
- References



Background


- Wireless Sensor Networks (WSN)
 - Autonomous
 - Low power
 - Inexpensive
 - Large amount
 - Growing Field
 - Outer Space Field [7]






Question

- Can we partition wireless sensors over a region into backbone grids such that:
 - The partition generates small number of grids
 - Each backbone set covers most of the region




Edges: 5038
Max degree: 41
Min degree: 5
Avg. degree: 25.19




Examples


- Manually constructed backbone grid deployments of multiple coverage [2] [3]:




(a) Hexagon
6-Coverage



(b) Cartesian
4-Coverage




(c) Bi-regular 3,4
-Coverage ()




Modeling

- Random Geometric Graph (RGG)
 - A random undirected graph generated on a bounded region by:
 - Deploying n nodes (vertices) at random uniformly and independently
 - Connecting two vertices () iff their distance .
 - For different surfaces and sensor densities, we prefer to specify the parameters and “expected average degree” of the RGG, letting be determined by these specifications.
- Reasons [1]
 - Scalability
 - Feasibility
 - Large amount deployment




Goal

- Partition an RGG into bipartite subgraphs (backbone grids) such that:
 - The partition generates a reasonably small number of bipartite backbone grids
 - The set of bipartite backbone grids comprises a significant majority of the total number of vertices.
 - Each bipartite backbone grid is similarly structured and covers most of the region with at least triple coverage





One Bipartite Backbone Grid Example and its Coverage

Vertices: 61
Edges: 68
Avg. degree: 2.27






Covers almost all region






Topologies

- Unit Square, Unit Disk, Unit Sphere and other 3D topology Explorations (All algorithms are topology based only)
- Justification
 - Average degree of vertices in different locations.






Example of a Large RGG: $G(20000, 0.08)$


Edges: 3759504
Max degree: 467
Min degree: 96
Avg. degree: 375.95

Observations:


Expected Avg. Degree

Degree of vertex on convex hull
implies






Cell Method Yields Edges in O(m)




Observations:


Number pairs checked per vertex:




Cell method: G(20000, 0.08)




Next




Cell method: G(20000, 0.08)




Next




Cell method: G(20000, 0.08)




Next




Cell method: G(20000, 0.08)




Next



Cell method: G(20000, 0.08)




End



Procedure Overview (all linear time)

- Generate an RGG of n vertices, m edges using cell method.
- Determine primary independent sets using smallest-last coloring algorithm [4].
- Determine relay independent sets adaptively paired with primaries using relay coloring algorithm.
- Determine backbone grid in each paired bipartite subgraph.



Smallest-last Coloring Algorithm

- A sequential coloring algorithm based on vertices in smallest-last ordering.
- Smallest-last ordering has been Proved
 - Efficient (Linear Time) [4]
 - Better than other sequential algorithms [5]

Algorithm 1 Smallest-last Coloring

Input: Graph $G(V, E)$

Output: Vertex Ordering S


$S \leftarrow \emptyset$

while $V \setminus S \neq \emptyset$ **do**


append to S the vertex with smallest degree
in the subgraph induced by V in S

end while


Greedy-Color $G \setminus S$ in inverse order of S




Smallest-last Ordering: G(20000,0.08)




Next




Smallest-last ordering: G(20000,0.08)




Next




Smallest-last Ordering: G(20000,0.08)




Next




Smallest-last Ordering: G(20000,0.08)




Next 




Smallest-last Ordering: G(20000,0.08)





Next




Smallest-last Ordering: G(20000,0.08)




Next 




Smallest-last Ordering: G(20000,0.08)




End




Plot: Avg. Degree and Degree when Deleted






Observations


- Expected deletion degree (Geometry)
- Average “degree when deleted”
- Justification
 - Successive deletion removes all m edges in n steps and each time delete amount on average.
- Claim
 - Degree when deleted plot should be flat.




SL-coloring: $G(20,000,0.08)$




Next




SL-coloring: $G(20,000,0.08)$




Next




SL-coloring: $G(20,000,0.08)$




Next




SL-coloring: $G(20,000,0.08)$




Next




SL-coloring: $G(20,000,0.08)$




Next



SL-coloring: $G(20,000,0.08)$






End




Observations

- Upper bound of number of colors should be Max min-degree and the lower bound should be around .






One Independent Set Example



Vertices with same color value forms an independent set.


Combine any two independent sets will get an bipartite sub-graph.




Bipartite Subgraph Pairing problem


**“Distort”
problem**


However, pairing arbitrary independent sets may generate many small components rather than one 'giant' component







Plot: Color set sizes






Plot: Color set sizes







Adaptive (Relay) Coloring Algorithm



(a) Relay Degree Lists



(b) Maximum One-color Adjacencies



Relay Coloring Algorithm

Algorithm 2 Relay Coloring

Input: Graph $G(V, E)$ and relay lists $L[i](2 \leq i \leq 5)$

Output: Relay colors allocated to vertices in V_r (relay candidates set)

for $i = 5$ to 2 **do**

while $\text{!}L[i].\text{isEmpty}()$ **do**

 Try to assign a relay color paired with its primary neighbor color

if the relay color is already assigned to one of its relay neighbour vertices **then**

 continue


else

 assign this relay color


end if


end while

end for




Plot: Color Set Sizes






One Bipartite Subgraph Example




Combining the primary color set and the paired relay color set will generate one bipartite subgraph.




Determine Backbone Grid

- Giant Component Subgraph: Delete minor components (BFS or DFS)
- Two-core Subgraph: Delete vertices of degree 0 and degree 1 (Termed “Tails”) (Based on smallest-last ordering)
- Block Subgraph: Delete minor blocks (BFS)



Determine Backbone Grid




Cyan: Minor blocks

Green: Minor components

Pink: Tails


Observations:

For a dense enough graph, it usually generates giant component directly with few or no minor blocks.




Bi-regular Feature(visual triangulation)


- Adding Gabriel rule to independent sets



(a) Primary
Set




(b) Relay Set



Benchmark Data Sets

Table I: Unit Square Test Benchmarks


N	8000	16000	32000	64000	128000
r	0.057	0.040	0.028	0.020	0.014
$\overline{d(G)}$	76.52	77.99	78.99	79.62	79.97
Backbones	17	18	18	18	18
Surplus	10.16%	8.01%	8.51%	8.45%	8.51%
$\overline{N(B)}$	422.76	817.67	1626.50	3255.28	6505.89
$\overline{Avg(d(B))}$	2.67	2.64	2.66	2.67	2.69
$\overline{Avg(F(B))}$	8.07	8.49	8.32	8.30	8.08
$\overline{Avg(F(2\text{-core}))}$	6.80	6.84	6.77	6.76	6.72
$\overline{D(B)}$	99.58%	99.12%	99.05%	99.48%	99.37%



Benchmark Data Sets

Table II: Unit Disk Test Benchmarks


N	8000	16000	32000	64000	128000
r	0.101	0.071	0.050	0.036	0.025
$\overline{d(G)}$	77.30	78.86	79.31	79.85	80.17
Backbones	17	18	18	18	18
Surplus	10.29%	8.74%	8.49%	8.12%	8.65%
$\overline{N(B)}$	422.18	811.22	1626.83	3266.94	6496.00
$\overline{Avg(d(B))}$	2.67	2.65	2.66	2.68	2.69
$\overline{Avg(F(B))}$	8.12	8.37	8.34	8.18	8.09
$\overline{Avg(F(2\text{-core}))}$	6.73	6.80	6.75	6.73	6.72
$\overline{D(B)}$	99.78%	99.07%	99.36%	99.67%	99.44%



Benchmark Data Sets


Table III: Unit Sphere Test Benchmarks

N	8000	16000	32000	64000	128000
r	0.201	0.142	0.100	0.071	0.050
$\overline{d(G)}$	81.00	80.91	80.99	80.95	80.98
Backbones	18	18	18	18	18
Surplus	8.66%	8.26%	8.26%	8.37%	8.34%
$\overline{N(B)}$	406.67	815.44	1630.94	3258.06	6517.94
$\overline{Avg(d(B))}$	2.72	2.72	2.71	2.72	2.72
$\overline{Avg(F(B))}$	7.67	7.78	7.78	7.83	7.83
$\overline{Avg(F(2\text{-core}))}$	6.63	6.60	6.64	6.63	6.64
$\overline{D(B)}$	99.86%	99.91%	99.82%	99.86%	99.85%




Conclusions, Questions and Future works

- Advantages
 - Topology only (Avoid geographical variations) and support unlimited topologies.
 - All procedures are efficient (linear time)
 - Algorithms not relying on locations of sensors
- Question: Practical or not?
 - Practical:
 - Great! Where else can I publish my work?
 - Impractical:
 - It's a measurement of constructing dominating backbones in WSN's
 - As an academic research work of Graph Theory, this kind of partitioning exists in RGG.
- Future works: Some empirical observations need theoretical proof.




Visualization and 3D Exploration

Show Time...



Reference

- [1] Kenniche, Hichem, and Vlady Ravelomananana. "Random geometric graphs as model of wireless sensor networks." Computer and Automation Engineering (ICCAE), 2010 The 2nd International Conference on. Vol. 4. IEEE, 2010.
- [2] S. Kumar, T. H. Lai, and J. Balogh, "On k-coverage in a mostly sleeping sensor network," in Proceedings of the 10th annual international conference on Mobile computing and networking. ACM, 2004, pp. 144–158.
- [3] P.-J. Wan and C.-W. Yi, "Coverage by randomly deployed wireless sensor networks," IEEE/ACM Transactions on Networking (TON), vol. 14, no. SI, pp. 2658–2669, 2006
- [4] D. W. Matula and L. L. Beck, "Smallest-last ordering and clustering and graph coloring algorithms," Journal of the ACM (JACM), vol. 30, no. 3, pp. 417–427, 1983.
- [5] D. Mahjoub and D. W. Matula, "Employing (1- ϵ) dominating set partitions as backbones in wireless sensor networks," in Proceedings of the Meeting on Algorithm Engineering & Experiments. Society for Industrial and Applied Mathematics, 2010, pp. 98–112.
- [6] K. R. Gabriel and R. R. Sokal, "A new statistical approach to geographic variation analysis," Systematic Biology, vol. 18, no. 3, pp. 259–278, 1969.
- [7] E. Del Re, R. Pucci, and L. S. Ronga, "Ieee802. 15.4 wireless sensor network in mars exploration scenario," in Satellite and Space Communications, 2009. IWSSC 2009. International Workshop on. IEEE, 2009, pp. 284–288.



•••

Thank you!
Merci!

zizhenc@smu.edu