

钛虎轻量化关节模组

详细参数表

*单编关节模组为CAN通信，双编关节模组兼容CAN和Ethercat通信

产品系列		关节型号 (模组外径红标)	减速比	启停峰值扭矩 (N.m)	平均负载转矩容许最大值 (N.m) (机器人场景)	2000rpm/ (减速比) 时额定转矩 (N.m) (工业场景)	输出端峰值转速 (RPM)	额定转速 (RPM) (1/2额定扭矩)	电机功率 (W)	供电电压 (V)	最大持续电流 (A)	额定电流 (A)	编码器 分辨率 (bit)	背隙 (arcsec)	扭矩常数 (N.m/A)	通孔 (mm)	长度 无刹车/带刹车 (mm)	重量 无刹车/带刹车(kg)	惯量 无刹车/带刹车(g * cm ²)
PRO系列		CRA-RI30-40-PRO-2-XXX	51/101	3.3/4.8	2.3/3.3	1.8/2.4	118/59	90/45	36	24-48	2	1	16	40/40	0.024	6	60±0.5/78.6±0.5	0.19/0.27	27.4/45.1
		CRA-RI30-40-PRO-2-XXX-2E-EC	51/101	3.3/4.8	2.3/3.3	1.8/2.4	118/59	90/45	36	24-48	2	1	16/18	40/40	0.024	6	60.5±0.5/79±0.5	0.23/0.27	23.73/28.15
		CRA-RI40-52-PRO-2-XXX	51/101	8.3/11	5.5/8.9	3.5/5	118/59	80/40	90	24-48	3	2	16	40/30	0.05	12	62±0.5/82±0.5	0.32/0.42	73/116.2
		CRA-RI40-52-PRO-2-XXX-2E-EC	51/101	8.3/11	5.5/8.9	3.5/5	118/59	80/40	90	24-48	3	2	16/18	40/30	0.05	12	64.5±0.5/85.5±0.5	0.37/0.46	85.14/94.52
		CRA-RI50-70-PRO-2-XXX	51/81/101	23/29/34	8.6/13.5/13.5	6.6/9.6/9.6	97/61/49	75/46/37	150	24-48	5	3.6	16	20/20/10	0.089	12	63±0.5/81.5±0.5	0.66/0.78	158.8/228.8
		CRA-RI50-70-PRO-2-XXX-2E-EC	51/81/101	23/29/34	8.6/13.5/13.5	6.6/9.6/9.6	97/61/49	75/46/37	150	24-48	5	3.6	16/18	20/20/10	0.089	12	66.5±0.5/85±0.5	0.68/0.81	170.47/216.37
		CRA-RI60-80-PRO-2-XXX	51/81/101/121	42/53/66/66	32/33/49/49	19.8/27.5/30/30	82/51/41/32	68/43/34/24	300	24-48	6.7	5	16	20/20/10/10	0.096	18	72.5±0.5/91.5±0.5	1.03/1.2	394.8/492
		CRA-RI60-80-PRO-2-XXX-2E-EC	51/81/101/121	42/53/66/66	32/33/49/49	19.8/27.5/30/30	82/51/41/32	68/43/34/24	300	24-48	6.7	5	16/18	20/20/10/10	0.096	18	72.5±0.5/93.8±0.5	1.04/1.24	479.96/571.15
		CRA-RI70-90-PRO-2-XXX	51/81/101/121	69/91/102/108	42/58/61/61	32/42/50/50	77/48/40/30	61/38/30/25	500	24-48	8.4	6.1	16	20/20/10/10	0.118	18	73.5±0.5/92±0.5	1.27/1.5	596.4/746.7
		CRA-RI70-90-PRO-2-XXX-2E-EC	51/81/101/121	69/91/102/108	42/58/61/61	32/42/50/50	77/48/40/30	61/38/30/25	500	24-48	8.4	6.1	16/18	20/20/10/10	0.118	18	73.5±0.5/94±0.5	1.3/1.5	622.79/783.02
		CRA-RI80-110-PRO-2-XXX	51/81/101/121/161	121/169/194/207/217	68.5/107/133/133/133	48/78/84/84/84	65/43/36/30/22	54/35/27/23/17	750	24-48	10.4	9	16	20/20/10/10/10	0.143	27	85.5±0.5/105.5±0.5	2.06/2.26	1477.6/1761.1
		CRA-RI80-110-PRO-2-XXX-2E-EC	51/81/101/121/161	121/169/194/207/217	68.5/107/133/133/133	48/78/84/84/84	65/43/36/30/22	54/35/27/23/17	750	24-48	10.4	9	16/18	20/20/10/10/10	0.143	27	85.5±0.5/107±0.5	2.05/2.24	1532.07/1612.04
		CRA-RI100-142-PRO-2-XXX	51/81/101/121/161	267/376/411/436/459	133/206/267/267/267	94/146/169/169/169	55/37/29/24/18	44/29/22/18/12	1000	24-48	16.9	15.8	16	20/20/10/10/10	0.175	32	100.5±0.5/121.5±0.5	3.96/4.38	3910.2/4744.7
		CRA-RI100-142-PRO-2-XXX-2E-EC	51/81/101/121/161	267/376/411/436/459	133/206/267/267/267	94/146/169/169/169	55/37/29/24/18	44/29/22/18/12	1000	24-48	16.9	15.8	16/18	20/20/10/10/10	0.175	32	103.5±0.5/126.5±0.5	3.97/4.46	5935.35/7854.45
		CRA-RI110-170-PRO-2-XXX	51/81/101/121/161	497/641/702/762/800	242/351/460/557/557	169/255/328/363/363	33/21/16/14/10	22/15/12/10/7	1500	24-48	30.2	14.1	16	20/20/10/10/10	0.293	40	121.7±0.5/147.7±0.5	6.84/7.52	8333.3/10709.2
		CRA-RI110-170-PRO-2-XXX-2E-EC	51/81/101/121/161	497/641/702/762/800	242/351/460/557/557	169/255/328/363/363	33/21/16/14/10	22/15/12/10/7	1500	24-48	30.2	14.1	16/18	20/20/10/10/10	0.293	40	124.5±0.5/156.5±0.5	6.87/7.61	9689.83/12630.38
PRO-S系列		CRA-RI50-60-PRO-2-XXX	51/81/101	23/29/34	8.6/13.5/13.5	6.6/9.6/9.6	97/61/49	75/46/37	150	24-48	5	3.6	16	20/20/10	0.089	12	63±0.5/81.5±0.5	0.45/0.58	158.8/228.8
		CRA-RI50-60-PRO-2-XXX-2E-EC	51/81/101	23/29/34	8.6/13.5/13.5	6.6/9.6/9.6	97/61/49	75/46/37	150	24-48	5	3.6	16/18	20/20/10	0.089	12	66.5±0.5/85.5±0.5	0.47/0.6	170.46/216.37
		CRA-RI60-70-PRO-2-XXX	51/81/101/121	42/53/66/66	32/33/49/49	19.8/27.5/30/30	82/51/41/32	68/43/34/24	300	24-48	6.7	5	16	20/20/10/10	0.096	18	72.5±0.5/93±0.5	0.73/0.88	394.8/492
		CRA-RI60-70-PRO-2-XXX-2E-EC	51/81/101/121	42/53/66/66	32/33/49/49	19.8/27.5/30/30	82/51/41/32	68/43/34/24	300	24-48	6.7	5	16/18	20/20/10/10	0.096	18	74±0.5/94±0.5	0.76/0.88	452.3/542.87
		CRA-RI70-80-PRO-2-XXX	51/81/101/121	69/91/102/108	42/58/61/61	32/42/50/50	77/48/40/30	61/38/30/25	500	24-48	8.4	6.1	16	20/20/10/10	0.118	18	73±0.5/91.5±0.5	0.9/1.11	596.4/746.7
		CRA-RI70-80-PRO-2-XXX-2E-EC	51/81/101/121	69/91/102/108	42/58/61/61	32/42/50/50	77/48/40/30	61/38/30/25	500	24-48	8.4	6.1	16/18	20/20/10/10	0.118	18	73±0.5/93.5±0.5	0.99/1.19	624.19/784.5
		CRA-RI80-97-PRO-2-XXX	51/81/101/121/161	121/169/194/207/217	68.5/107/133/133/133	48/78/84/84/84	65/43/36/30/22	54/35/27/23/17	750	24-48	11.1	9.6	16	20/20/10/10/10	0.143	27	85.5±0.5/105.5±0.5	1.5/1.63	1477.6/1761.1
		CRA-RI80-97-PRO-2-XXX-2E-EC	51/81/101/121/161	121/169/194/207/217	68.5/107/133/133/133	48/78/84/84/84	65/43/36/30/22	54/35/27/23/17	750	24-48	11.1	9.6	16/18	20/20/10/10/10	0.143	27	85.5±0.5/107±0.5	1.62/1.75	1532.07/1700.15
		CRA-RI100-120-PRO-2-XXX	51/81/101/121/161	267/376/411/436/459	133/206/267/267/267	94/146/169/169/169	55/37/29/24/18	44/29/22/18/12	1000	24-48	20.2	15.8	16	20/20/10/10/10	0.175	32	100.5±0.5/121.5±0.5	2.52/3.21	3910.2/4744.7
		CRA-RI100-120-PRO-2-XXX-2E-EC	51/81/101/121/161	267/376/411/436/459	133/206/267/267/267	94/146/169/169/169	55/37/29/24/18	44/29/22/18/12	1000	24-48	20.2	15.8	16/18	20/20/10/10/10	0.175	32	103.5±0.5/126.5±0.5	2.51/3.33	5962.63/7017.1

*数据仅供参考