



Family 1: Decoder-backend				Change decoder algorithm; hold prior and deadline fixed
	Decoder algorithm	Prior distribution	Deadline budget (μs)	Examples
C_0	Corr. matching	SI1000	No deadline	CM $\rightarrow$ Tesseract PM $\rightarrow$ CM PM $\rightarrow$ Tesseract
	$\neq$	=	=	
C_1	Tesseract	SI1000	No deadline	

Family 2: Decoder-prior				Sweep prior distribution; hold decoder and deadline fixed
	Decoder algorithm	Prior distribution	Deadline budget (μs)	
C_0	Tesseract	dem_simple	No deadline	5,724 prior variants across 3 families 19.08M paired shots
	=	$\neq$	=	
C_1	Tesseract	dem_corr / iso / sh	No deadline	

Family 3: Runtime-deadline				Apply measured service-time budget; hold decoder and prior fixed
	Decoder algorithm	Prior distribution	Deadline budget (μs)	
C_0	Corr. matching	SI1000	∞ (no limit)	4 $\mu s \rightarrow$ 93.6% miss 5 $\mu s \rightarrow$ partial miss 7 $\mu s \rightarrow \approx 0\%$ miss
	=	=	$\neq$	
C_1	Corr. matching	SI1000	$D \in \{4,5,6,7,8\} \mu s$	