GeomBase 模块提纲

```
import math
epsilon = 1e-7
epsilonSquare = epsilon*epsilon

class Point3D:
    def __init__(self, x = 0.0, y = 0.0, z = 0.0, w = 1.0):
    def __str__(self):
    def clone(self):
    def pointTo(self, other):
    def translate(self, vec):
    def translated(self, vec):
    def multiplied(self, m):
    def distance(self, other):
    def distanceSquare(self, other):
    def middle(self, other):
    def isCoincide(self, other):
    def isIdentical(self, other):
    def __add__(self, vec):    # +
    def __sub__(self, other):    # -
    def __mul__(self, m):    # *

class Vector3D:
    def __init__(self, dx = 0.0, dy = 0.0, dz = 0.0, dw = 0.0):
    def __str__(self):
    def clone(self):
    def reverse(self):
    def reversed(self):
    def dotProduct(self, other):
    def crossProduct(self, other):
    def amplify(self, f):
    def amplified(self, f):
    def length(self):
    def lengthSquare(self):
    def normalize(self):
    def normalized(self):
    def isZeroVector(self):
    def multiplied(self, m):
    def isParallel(self, other):
    def getAngle(self, vec):    # 0 ~PI
    def getAngle2D(self):    # 0 ~ 2PI, On XY Plane
    def getOrthoVector2D(self):    # On XY Plane
    def __add__(self, other):
    def __sub__(self, other):
    def __mul__(self, m):

class Matrix3D:
    def __init__(self):
    def __str__(self):
    def makeIdentical(self):
    def mutiplied(self, other):
    def getDeterminant(self):
    def getReverseMatrix(self):
    @staticmethod
    def createTranslateMatrix(dx, dy, dz):
    @staticmethod
    def createScaleMatrix(sx, sy, sz):
    @staticmethod
    def createRotateMatrix(axis, angle):
    @staticmethod
    def createMirrorMatrix(point, normal):
        pass
    def __mul__(self, other):
    def __add__(self, other):
    def __sub__(self, other):
```