Polyline 模块提纲

```
from GeomBase import *

class Polyline:
    def __init__(self):    self.points = []
    def __str__(self):
    def clone(self):
    def count(self):    返回多边形顶点数
    def addPoint(self, pt):    添加一个Point3D点
    def addTuple(self, tuple):    添加一个形如(x,y,z)的 tuple 点
    def raddPoint(self, pt):    反向插入一个点，即在0位插入点
    def removePoint(self, index):
    def point(self, index):
    def startPoint(self):    返回多段线起点
    def endPoint(self):    返回多段线终点
    def isClosed(self):    返回多段线是否闭合，True or False
    def reverse(self):    对多段线的方向取反
    def getArea(self):    夺取多边形的面积
    def makeCCW(self):    强制将多边形调整成CCW，逆时针
    def makeCW(self):    强制将多边形调整成CW，顺时针
    def isCCW(self):    多边形是否是逆时针，True or False
    def translate(self, vec):
    def translated(self, vec):
    def appendSegment(self, seg):    拼接一条线段到多边形起点或终点，如果拼接成功，返回True，否则返回False
    def multiply(self, m):
    def multiplied(self, m):


def writePolyline(path, polyline: Polyline):
    f = None
    try:
        f = open(path, 'w')
        f.write('%s\n' % polyline.count())
        for pt in polyline.points:
            txt = "%s, %s, %s\n" % (pt.x, pt.y, pt.z)
            f.write(txt)
    except Exception as ex:
        print(ex)
    finally:
        if f:
            f.close()

def readPolyline(path):
    f = None
    try:
        f = open(path, 'r')
        poly = Polyline()
        number = int(f.readline())
        for i in range(number):
            txt = f.readline()
            txts = txt.split(',')
            x, y, z = float(txts[0]), float(txts[1]), float(txts[2])
            poly.addPoint(Point3D(x, y, z))
        return poly
    except Exception as ex:
        print(ex)
    finally:
        if f:
            f.close()
```