

Comment	Description	Designator	Footprint	Quantity
0.1uF	Capacitor	C1, C2, C3	CB1	3
1K	Resistor	R2, R9, R14, R15, R19, R23	AXIAL0.3	6
1N4148	Diode	D5, D6	Diode0.3	2
1ohm/0.5W	Resistor	R3, R10	AXIAL0.4	2
1ohm/1W	Resistor	R21	AXIAL0.5	1
1uF	Capacitor	C4, C6, C9, C10	C2	4
10K	Resistor	R1, R4, R6, R7, R8, R12, R16, R17, R20, R22, R24, R25	AXIAL0.3	12
20k	Resistor	VR1	VR3296-1	1
47K	Resistor	R5, R11, R18	AXIAL0.3	3
470uF/16V	Capacitor	C5	CD6	1
8050	Transisotr	Q1, Q2	TO92A	2
AD	Connector	J2	SIP6	1
Header 4	Header, 4-Pin	P1, P2	HDR1X4	2
IOH	Connector	J4	SIP8	1
IOL	Connector	J3	SIP8	1
LED_1	LED	D1, D2, D3, D4	LED5	4
LM35DZ	Precision Centigrade Temperature Sensor, 3-pin TO-92	U2	TO92	1
LM324AN	Quad Low-Power Operational Amplifier	U1	646-06	1
POWER	Connector	J1	SIP6	1
RELAY5V	Relay	RLY1, RLY2	HK4100F	2
TEST TP	测试环	TP3, TP4	HDR2.54-Y-LI-1P	2
USB	双联USB插座	JK2	USB*2-1	1
USB	TYPE-C-2P	USB1	TYPE-C-2P	1
按键	Button	S1	SW_PB-四	1
自锁开关	Switch	SW1	双刀双掷自锁开关	1