Weston LaFon - Wellsite Geologist

303-594-1732

1712 Sherman Avenue Canon City, CO 81212 wslafon@gmail.com Meridian Energy Inc.

1475 Ward Cir. Franktown, CO 80116 303-594-0515

Well Prognosis

Meridian Energy Inc., Dawes #1 (15-193-21149)

Discovery Drilling Inc

SE NW NW SE section 34, T. 8S, R. 35W Thomas County, Kansas (2175' FSL, 2250' FEL)

GL 3319' KB 3327'

Sample Catching:

Wash, clean, hang in 10 sack bundles in clean, dry place.

Begin Samples @ 3800'

DO NOT DRY. Clean out hopper real good before each collection.

10' samples from 3800 to TD

In the event drilling ceases for any reason and circulation is being maintained continue

to catch samples in 20 minute intervals for up to an hour.

In the event drilling ceases for any length of time notify geologist and catch circulated

samples.

Strap pipe: At first test, last bit trip and/or at TD

Drilling time: Drillers keep 1' drilling time from 2700' to 2900' and from 3800' to TD

Mud: Do not mix mud before clearing with mud engineer. Have mud in shape for possible DST at ~3900'

(Topeka).

Logging: DIL, Microlog, CNL/FDC

Testing: As directed by wellsite geologist

Geologist call depths: 1) When preparing to drill out from surface casing - (303) 594-1732

2) At Anhydrite/ Stone Corral (~2800')

3) At 3800'

Stop Depth: 4100' - Call me again if I'm not on location

Morning Reports: Please email to me at wslafon@gmail.com; maxwell@meridianenergy.us; neallafon@gmail.com

Testing Company: Diamond **Loggers:** Midwest Wireline 785-623-1246

Mud: Mud Co - Reid Atkins - 785-694-3741

Thank You

Formation Tops (estimated)	<u>MD</u>	<u>subsea</u>	#1-35 FS Frahm (3308' KB)
Stone Corral	2819	+508	2797 (+511)
Topeka	3912	-585	3896 (-588)
Heebner	4106	-779	4090 (-782)
Lansing A	4152	-825	4136 (-828)
Base of KC	4426	-1099	4410 (-1102)
Altamont B	4481	-1154	4465 (-1157)
Pawnee	4543	-1216	4527 (-1219)
Ft Scott	4601	-1274	4585 (-1277)
Cherokee	4636	-1309	4620 (-1312)
Mississippian	4766	-1439	4750 (-1442)
TD	4850		, ,