A Reproducible Study of Client-Side Request Signing on Two Social Platforms: Virtualization versus Obfuscation

Sreenandhu Nair
Independent security research
https://github.com/zkp6c4vr89-coder/tiktok-xhs-signing-analysis

***Abstract*—Large web platforms attach cryptographic-looking signatures to API requests to tell real browsers from automated clients. We study the client-side signing code of two of them, TikTok (the `webmssdk` script that emits `X-Bogus` and `X-Gnarly`) and Xiaohongshu / RedNote (the `x-s` header), as a reproducibility exercise. We independently replicate a prior community analysis of TikTok's bytecode virtual machine against a current bundle, and apply the same toolkit to Xiaohongshu. Our contribution is understanding and reusable tooling, not a means of access: no working signer is released. We find that the two platforms make opposite architectural choices. TikTok virtualizes its signer into a bespoke register machine (we recover 365 opcodes and 351 functions and disassemble 89.7% of a 98,961-byte bytecode image), whereas Xiaohongshu ships string-array- and control-flow-obfuscated JavaScript over two encrypted data blobs. We also document that TikTok *replaced* its VM between the version a 2025 analysis examined (core 1.12.2) and the one we captured (1.16.6): stack machine to register machine, 77 to 365 opcodes. In both cases a runtime environment-integrity check, not the obfuscation, was the barrier to end-to-end extraction; we stopped at that boundary by design. Every number in this paper traces to a script, trace, or data file in the public repository.**

I. Introduction

Modern social platforms protect their web APIs by having the browser compute a signature over each request and send it in custom headers. A request without a valid signature is rejected, so the signing code is a high-value target for both scrapers and defenders. The code ships to every visitor, so it is heavily obfuscated.

This paper treats two such systems as objects of a *reproducibility* study. Part A independently replicates a 2025 community reverse-engineering of TikTok's `webmssdk` [9] against a bundle we captured ourselves. Part B applies the resulting toolkit to Xiaohongshu's `x-s` signature. Part C compares them. The guiding constraint is that the contribution is *understanding plus reusable analysis tooling*, never a usable signer: we publish algorithm descriptions, diagrams, test vectors, and pass/fail results, and we keep raw bundles and any validation-only reimplementation out of the public repository.

Contributions.

- An independent, reproducible replication of the TikTok `webmssdk` VM analysis against a current bundle, with a reusable bytecode decoder, opcode-table builder, and disassembler (Section V).
- A finding that TikTok *replaced* its protection VM between versions (stack to register machine, 77 to 365 opcodes, 272 to 351 functions), making a prior static analysis obsolete (Sections V, VII).
- The first (to our knowledge) write-up of the current Xiaohongshu `x-s` signer's structure: a `javascript-obfuscator` payload over two encrypted data blobs, with the input/output contract and a reusable evaluating deobfuscation pass (Section VI).
- A comparative taxonomy of the two defensive strategies, and the observation that in both cases a runtime integrity check, not the code obfuscation, was the true analysis barrier (Section VII).
- A fully reproducible pipeline (`make reproduce`) and an explicit ethical boundary: we decline to defeat the integrity checks because that crosses into building a signer (Section III).

II. Background and Related Work

JavaScript obfuscation and deobfuscation. Obfuscation hides a program's intent while preserving behaviour; Collberg *et al.* [1] give the classic taxonomy (layout, data, and control transformations, judged by potency, resilience, stealth, and cost). On the web specifically, Skolka *et al.* [2] measured obfuscation in the wild and found that most obfuscated scripts resemble the output of a single tool and that such code is disproportionately used for fingerprinting—both borne out by our Xiaohongshu case.

Virtualization-based obfuscation. The strongest technique we encounter translates logic into bytecode for a custom interpreter. Rolles [3] framed these obfuscators as interpreters that can be attacked by writing a disassembler for their bytecode; Sharif *et al.* [4] automated reverse-engineering of such emulators dynamically; Yadegari *et al.* [5] gave a semantics-based, obfuscation-agnostic deobfuscator. Our TikTok work is a hand-built instance of Rolles's recipe applied to a JavaScript VM.

Fingerprinting and bot detection. Signing is one half of bot detection; the other is binding the signature to hard-to-forge device state. Eckersley [6] showed browser configurations are widely unique; Nikiforakis *et al.* [7] dissected commercial fingerprinting providers; Laperdrix *et al.* [8] survey

the area. The environment reads we record (Section VII) are exactly the surface these works describe.

Prior work on these platforms. The TikTok analysis we replicate is a community repository [9]; the author describes it as a rapid effort and invites correction. Xiaohongshu's `x-s` has been discussed in blog posts and the open-source *xhshow* project; we treat those as leads to verify, not ground truth, and we did not consult *xhshow*'s source during our own analysis.

III. Ethics and Scope

This is defensive and educational research with no affiliation to either company. We observe four rules. (1) *No signer is released.* The public repository contains descriptions, diagrams, test vectors, and pass/fail results; any reimplementation built to validate understanding stays in a git-ignored directory and is never published. (2) *We work offline.* The live sites were touched only to capture public static bundles, logged out, at human pace, with a generic user agent and no cookies; no automated or bulk requests were sent to any API. When a CDN returned HTTP 403 without a site referer, we declined to spoof headers to retrieve the file. (3) *No personal data.* All harness inputs are synthetic; no real accounts, cookies, or device identifiers appear anywhere. (4) *No full bundles.* We publish only SHA-256 hashes, URLs, capture dates, and the short excerpts needed to make a point; the copyrighted bundles stay git-ignored.

A consequence worth stating plainly: both signers abort when run outside a real browser because of a runtime *environment-integrity check*. Defeating that check is the step that would turn our understanding into a working signer, so *we deliberately stop there*. This is a scope boundary, not a failed attempt; it is why Section VI reports no valid `x-s` test vectors.

IV. Methodology

All analysis runs offline against pinned bundles. Each analysed file is recorded in `data/bundles.csv` with platform, filename, URL, SHA-256, and capture date, and `make verify-samples` checks every local sample against its hash. The offline pipeline (`make reproduce`) runs deobfuscation, disassembly, tracing, and figure generation from the pinned inputs.

The toolkit is written to be reused across both platforms. *Deobfuscation* (`tools/deobf/`) uses Babel to parse each bundle into an AST and apply passes: a classic string-array pass that resolves `ARR[n]` and decoder-call indirections to literals, and an evaluating pass that handles the `javascript-obfuscator` preset by running the array/rotation/decoder prelude in a sandboxed `node:vm` context and rewriting decoder calls with their decoded values. *Virtual-machine analysis* (`tools/vm/`) comprises a bytecode loader, an opcode-table builder that extracts the handler array and classifies each handler's operand encoding on the AST, a linear and recursive-descent disassembler, and a string-pool decoder. *Tracing* (`tools/harness/`) runs the signer in a `node:vm` context whose global is a logging-Proxy browser shim.

The shim is the same for both platforms. Every property read on `window`, `navigator`, `document`, `screen`, and their descendants is recorded through nested `Proxy` objects, producing the fingerprint surface. All values are fixed synthetic stubs, and `Date` and `Math.random` are made deterministic, so a trace is reproducible and contains no personal data. We inject two hooks into the bundle source before running it: one on the VM's string decoder (to log every decoded string with its key) and one on the dispatch site (to count executed opcodes). Every quantitative claim below is produced by one of these tools and is regenerable with `make reproduce`.

V. Case Study 1: TikTok

Bundle. The reference analysis [9] pinned no hash; it pasted deobfuscated source, from which we recovered the version it examined: `webmssdk` core **1.12.2**. A logged-out load of `tiktok.com` referenced one signer URL, from which we captured `webmssdk` core **1.16.6** (asset `1.0.0.417`; SHA-256 `6625c4fd...`). The four-minor-version gap is the study's first finding.

Strings. The reference removed a JavaScript-level string array with a Babel `MemberExpression` pass. In 1.16.6 that layer is *gone*: no rotating string array, zero `parseInt` checksums, no 40-element string-literal arrays. The strings moved into the VM bytecode, decoded at runtime by a base64-plus-repeating-XOR routine. Our reusable string-array pass therefore has no target here—a concrete instance of version drift changing the obfuscation surface.

The VM. 1.16.6 is a *register* machine, not the reference's stack machine (Fig. 1). The interpreter function `S(start,this,args,ctx,_,L)` builds a frame `u` with a register file `u.o` (slots 0–6 preloaded with `null`, `undefined`, `true`, `false`, a return sentinel, the arguments, and the call context), a program counter `u.I` into the decompressed bytecode, a try/handler stack `u.A`, and a boundary `u.L` above which registers are boxed closure cells. The dispatch loop is

```
while (u.I < g.length && C(u,4) === w) {
  f = (g[u.I++]<<8) | g[u.I++]; // 16-bit opcode
  d[f](u); // handler
}
return C(u,4); // write reg 4 = return
```

Each handler reads its operands with three readers (`O` for 1 byte, `p` for 2 bytes, `m` for 3 bytes) and accesses registers through getters/setters (`C`/`L` get, `Q`/`I` set). A function returns by writing register 4, which ends the loop. Table I summarises these elements.

Bytecode is delivered as base64 then raw DEFLATE, the decompression the reference had hard-coded around, yielding a 98,961-byte image. We implement the loader (`tools/vm/decode.js`), extract the handler table (**365** opcodes; Fig. 2), classify each handler's operand encoding on the AST, and build a recursive-descent disassembler. Function entries come from 206 constant `S(...)` offsets plus operand-driven children; following them reaches **351** functions, **245** of which return cleanly, covering **89.7%** of the image (Fig. 3). The entry function disassembles as, e.g.:




Fig. 1. TikTok `webmssdk` 1.16.6 register-VM architecture: a 16-bit opcode is fetched from the DEFLATE-decompressed bytecode and dispatched through a 365-entry handler table that reads operands and mutates the register file; writing register 4 returns.

TABLE I
1.16.6 VM STATE AND PRIMITIVES (RECOVERED IN `TOOLS/VM/`).

Element	Role
`u.o[]`	register file (0–6 preloaded)
`u.I`	program counter (byte offset)
`u.A`	try/exception handler stack
`u.L`	boxed-register boundary
`O/p/m`	1/2/3-byte operand readers
`C,L / Q,I`	register get / set
write `u.o[4]`	function return
`l(n,t)`	string decode: base64 then XOR key t

```
 0 op218 store [0, 14, 8]
 7 op175 make-function [52,46,9,10,24,54]
23 op148 make-function [9,56,14,868,11]
36 op353 call [1,1,10,1,4,7,11]
```

Many opcodes are specialised: 99 are *terminal* (each inlines a whole function body and ends with a write to register 4), which is why 365 exceeds the reference's 77—the compiler emitted one handler per operation shape rather than a fixed instruction set. The count 365 is exact (the handler-array length); the category breakdown in Fig. 2 is a heuristic labelling of handler bodies and is not load-bearing for any count.

Tracing. Under the harness, the bootstrap executes 8,884 VM dispatches across 89 opcodes before it halts on environment APIs we do not emulate; the decoder hook recovers correct plaintext, confirming the string model. We recover the token names from the base64/XOR pool by keeping only exact matches (an exact "`X-Bogus`" decode cannot be coincidental): `X-Bogus` at pool index 686, `X-Gnarly` at 688, `msToken` at 685. Scanning the disassembly for instructions that load those indices maps each token to its producing functions—`X-Bogus` at `fn@70647` and neighbours, `X-Gnarly` at `fn@73223`, all assembled at `fn@61636`. This is our analog of the reference's `vm103`/`vm249` result; the offsets differ because the VM differs. The numeric constant pool names the primitives: an LCG increment, the golden-ratio constant `0x9E3779B9`, SHA-256 round constants, FNV offsets, and the `strData` envelope magic `538969122`; a bundled MD5 (`JS_MD5_NO_NODE_JS`) appears in the fingerprint surface. We did not produce a signature headless, so the exact composition is stated as referenced, not byte-confirmed.

Worked example: from bytecode bytes to `X-Bogus`. To make the pipeline concrete, we trace one instruction end to end. In `fn@61636` (the header-assembly function), byte offset 62,053 holds




Fig. 2. Opcode categories recovered from the TikTok `webmssdk` 1.16.6 handler table (365 opcodes), generated by `make_figures.py` from `data/tiktok_opcodes_1.16.6.json`.




Fig. 3. Recursive-descent disassembly outcome and linear byte coverage for the 1.16.6 bytecode image.

```
01 20 02 ae 00 05 00 07 00 1b
```

The dispatcher reads the first two bytes as the opcode `0x0120 = 288` (an array-build handler) and then four 2-byte operands: `0x02ae = 686`, 5, 7, 27. Operand 686 is a string-pool index. Pool entry `A[686]` is the base64 string `"PVgnJSUPHg=="`; decoding it (base64, then XOR with the pooled key `A[5] = "eueJBzmo"`) yields exactly `"X-Bogus"`. So this instruction, in this function, places the `X-Bogus` header name into an array under construction—which is how we attribute the token to `fn@61636` without executing it. The same chain recovers `X-Gnarly` (`A[688]`) and `msToken` (`A[685]`). Every step here is reproduced by `tools/vm/disasm.js` and `tools/vm/strings.js`.

Table II is the claim-by-claim replication (full detail in `analysis/tiktok/REPLICATION.md`). Of 12 claims, 5 reproduce directly, 5 reproduce in a different form attributable to the version change, 1 is a technique with no target in 1.16.6, and 1 (exact end-to-end composition) is unverified. No claim contradicted the reference outright; the divergences are all explained by the VM replacement.

VI. CASE STUDY 2: XIAOHONGSHU

Contract. `xiaohongshu.com` redirects to the `rednote.com` rebrand, whose login page still serves the public PC-web bundles. The signer lives in `vendor-dynamic` (SHA-256 `25e31f6b...`). An axios interceptor establishes the contract: `l = window.sign(url, body)` returns a header object merged into the request, carrying `x-s`, `x-t`, and `x-s-common`; `_webmsxyw` is the newer signer global. Inputs

TABLE II
TIKTOK CLAIM-BY-CLAIM REPLICATION. R = REPRODUCED; R* = REPRODUCED IN A DIFFERENT FORM (VERSION DRIFT); T = TECHNIQUE ONLY; U = UNVERIFIED.

Reference claim	Verdict
A bytecode VM protects the signer	R
VM is a *stack* machine with a `switch`	R* (register, handler table)
77 opcodes	R* (365)
272 VM functions	R* (351 found)
JS-level string array (Babel-removable)	T (absent in 1.16.6)
Varint bytecode parser, no decompression	R* (base64+DEFLATE)
Per-function disassembly	R
Custom runtime string decoder	R (base64+XOR)
`vm103`/`vm249`=X-Bogus/X-Gnarly	R* (`fn@70647`/`fn@73223`)
MD5 in the pipeline	R (MD5 lib flag)
Mixing with `0x9E3779B9`	R (pool constant)
Exact X-Bogus byte composition	U

are the request URL (URI plus serialized query), the body, the `a1` cookie (with `webId`/`gid`), and a timestamp (Fig. 4).

Form and deobfuscation. The signer is embedded as a 288,347-character string that the bundle `eval`s. It begins `var _0x5ae8=[...]`—a `javascript-obfuscator` string array of 1045 entries, with a decoder (`_0xc8b2`), an alias (`_0xe762c0`), and a rotation IIFE that reorders the array under a `parseInt` checksum:

```
var _0x5ae8=['doeZk','vSuEv',...]; // pool
var _0xc8b2=function(i,k){... // decoder
  ...return _0x5ae8[i-0x0]...};
var _0xe762c0=_0xc8b2; // alias
(function(a,b){while(!![]){... // rotation
  a['push'](a['shift']());...}}(_0x5ae8,0x1a2));
glb[_0xe762c0(0x73)]=function(a,b,c){...} // signer
```

We built an evaluating string-array pass (`tools/deobf/passes/string-array-eval.js`) that detects the decoder structurally, resolves its aliases transitively (40 here, including per-function local aliases), evaluates the array/rotation/decoder prelude in a sandbox, and rewrites literal-argument calls. It resolves 297 of them; e.g. `glb[_0xe762c0(0x73)]` becomes `glb["_AUuXfEG27Xa3x"]`. Three layers remain: computed-index decoder calls, control-flow flattening (`while(true){switch}` dispatchers), and two encrypted hex data blobs (`__$c`, `__bc`) that the signer interprets—so the signer is partly data-driven, not pure inline JavaScript. This is still far more readable than TikTok's VM: roughly 90% is ordinary JS after the pass, versus 0% before the VM is rebuilt.

Algorithm (partial) and vectors. Under the harness the payload loads and defines the signer `glb["_AUuXfEG27Xa3x"](url,body,ctx)`, but it aborts with an environment-integrity error after reading `document.documentElement.getAttribute`. A reachable helper builds a to-be-signed string of the form `url + 1013904243`—the same LCG constant seen in TikTok. Primitive evidence is partial: base64 (`atob`) is confirmed; MD5 is referenced but its magic constants are not plaintext (they live in the encrypted blobs), so MD5 use is *referenced, not byte-confirmed*; the older public claim of RC4 and a custom Base64/Base58 alphabet is *not independently confirmed* on this 2026 bundle. Because the signer aborts, **we produced no valid `x-s` test vectors**; `data/test_vectors/xhs.json` records the inputs, the integrity-check blocker, and a clearly-labelled non-signature partial output. The pass rate is therefore N/A by design (Section III).

TABLE III
OBFUSCATION TECHNIQUE TAXONOMY. "CONF." = CONFIRMED BY OUR TOOLING; "REF." = REFERENCED IN CODE/CONSTANTS BUT NOT BYTE-CONFIRMED.

	TikTok 1.16.6	Xiaohongshu 2026
Core strategy	bytecode VM (conf.)	string array + CFG (conf.)
Dispatch	365-opcode reg. VM	`while/switch` flattening
String hiding	base64+XOR pool (conf.)	array decoder+aliases (conf.)
Code/data packing	base64+DEFLATE (conf.)	encrypted blobs (conf.)
Hash primitives	MD5/SHA-256 (ref.)	MD5 (ref.), base64 (conf.)
Randomness	LCG, `0x9E3779B9` (conf.)	LCG const (conf.)
Anti-tamper	env init gate (conf.)	integrity check (conf.)

VII. COMPARATIVE ANALYSIS

Table III is the technique taxonomy. The headline is a choice of *where to put the cost*. TikTok virtualizes: nothing is readable until the interpreter is rebuilt, but then coverage is broad. Xiaohongshu obfuscates ordinary JavaScript: most is readable after a string pass, but a small encrypted core resists. Both bind URL, body, a persistent identifier, and a millisecond timestamp into the signature, and both share a Numerical-Recipes LCG increment (`1013904223`/`1013904243`).

Version drift. For TikTok this is quantified: between core 1.12.2 and 1.16.6 the VM was replaced wholesale (stack → register, 77 → 365 opcodes, 272 → 351 functions, JS string array → in-VM pool, hard-coded bytes → base64+DEFLATE). For Xiaohongshu we pinned a single bundle and make no cadence claim; we note only the rebrand and a modern obfuscator toolchain.

Analysis difficulty. We did not log wall-clock hours, so we report relative effort by tooling built: TikTok required five new tools (decoder, table builder, disassembler, pool decoder, harness) and was ∼0% readable without them; Xiaohongshu required three and was ∼90% readable after the string pass. TikTok has a higher up-front cost but broad payoff; Xiaohongshu is faster to first insight but its crypto core is gated.

Lessons for defenders. First, virtualization and obfuscation are a cost-shape choice, not a security level; both were analysable to the level needed to describe the pipeline. Second, and most important, *the real barrier was the runtime environment-integrity check, not the code hiding*: binding signatures to hard-to-forge environment state stopped end-to-end extraction more cheaply than heavy static obfuscation. Third, well-known constants (LCG increments, `0x9E3779B9`, SHA-256 and MD5 tables) leak the primitive inventory before any deobfuscation. Fourth, version drift was the strongest defence we measured: TikTok's wholesale VM swap would break any static signer.




Fig. 4. The two signing pipelines at the level our evidence supports. Primitives shown for TikTok are named by its constant pool (referenced, not all byte-confirmed); the Xiaohongshu crypto core is partly inside encrypted data blobs we did not fully reverse.

VIII. Discussion and Limitations

Our results are bounded in ways we state explicitly. We produced no signature for either platform, so token-to-function maps come from static operand analysis, not from observing a live signature, and exact byte-level composition is unverified. Primitive claims marked "referenced" (notably MD5 on both platforms, and RC4/custom-alphabet on Xiaohongshu) are named in code or constants but not confirmed by reproducing an output. Fingerprint surfaces are the bootstrap-phase subset each signer reads before aborting, not the complete set. The TikTok disassembler does not yet follow the 33 in-function jump opcodes, so 106 of 351 functions desync and coverage is 89.7%, not 100%. Opcode categories are heuristic labels. For Xiaohongshu the encrypted `__$c`/`__bc` blobs and control-flow flattening are not fully stripped. Finally, the 1.12.2 bundle the reference used is no longer served, so our cross-version comparison for TikTok relies partly on its pasted source. Several of these gaps (jump-aware disassembly, CFG unflattening) are tractable future work; others (defeating the integrity checks) are deliberately out of scope.

IX. Conclusion

Two platforms, the same goal, opposite strategies: TikTok virtualizes its request signer into a 365-opcode register machine that it rotates aggressively across versions, while Xiaohongshu obfuscates ordinary JavaScript over an encrypted data core. We replicated the TikTok analysis against a current bundle, showed its VM had been replaced since the prior study, and produced a reusable offline toolkit that applies to both. In both cases the decisive defence was a runtime environment-integrity check rather than the obfuscation itself—a boundary we chose not to cross, which is precisely why no signer accompanies this paper.

Appendix A
Pinned Bundles

All in `data/bundles.csv`, captured 2026-11-12/13, logged out, with SHA-256 pinned and checked by `make verify-samples`:

- TikTok `webmssdk.1.0.0.417.js` (core 1.16.6), `6625c4fd...a814c8`.
- Xiaohongshu `vendor-dynamic.bb0b0051.js` (signer), `25e31f6b...`.
- Xiaohongshu `index`, `vendor`, `bundler-runtime` (siblings).

Appendix B
Opcode Encoding (representative)

Each row of `data/tiktok_opcodes_1.16.6.json` gives an opcode's operand-read sequence (hence its byte length), whether it writes the return register, and a heuristic category. Table IV shows representative rows.

TABLE IV
Representative opcodes (of 365). Reads: `O`=1B, `P`=2B, `M`=3B.

op	category	reads	operand B	terminal
0	construct	–	0	yes
1	bitwise	–	0	yes
2	make-function	`ppm`	7	no
3	call	`pppppp`	12	no
41	compare	`ppmp`	9	no
65	arith	`pppppp`	12	no
218	store	`Opp`	5	no
347	construct	`ppOppp`	11	no

Appendix C
Fingerprint Surfaces

Both are the subset read before each signer aborts (Section VIII).

TikTok (`data/tiktok_fingerprint_surface.json`):

- `navigator`, `navigator.connection`
- `document.readyState`, `document.addEventListener`
- the Slardar telemetry registry
- a bundled MD5 flag (`JS_MD5_NO_NODE_JS`)

Xiaohongshu (`data/xhs_fingerprint_surface.json`):

- `document.cookie`
- `document.documentElement.getAttribute`
- `document.addEventListener`

Appendix D
Pass and Tool Catalogue

`tools/deobf/`: string-array pass and evaluating string-array pass (6 unit tests). `tools/vm/`: `decode.js`, `build_opcode_table.js`, `disasm.js`, `strings.js`, `pipeline.js` (3 tests). `tools/harness/`: `env.js` logging shim, `run_tiktok.js`, `run_xhs.js`. Token map in `data/tiktok_token_map_1.16.6.json`; vectors status in `data/test_vectors/xhs.json`.

APPENDIX E
FULL OPCODE TABLE

All 365 opcodes of the 1.16.6 VM, auto-generated from `data/tiktok_opcodes_1.16.6.json` by `paper/figures/make_opcode_table.py`. Columns per entry: opcode (`op`), heuristic category (`cat`: con/bit/mkf/cal/arr/sto/cmp/ari/lod/oth/ctl), and operand-read string (`rd`: `O`=1B, `p`=2B, `m`=3B; `--`=none).

op	cat	rd	op	cat	rd	op	cat	rd	op	cat	rd
0	con	–	1	bit	–	2	mkf	ppm	3	cal	pppppp
4	arr	ppppp	5	sto	ppppp	6	bit	ppppp	7	cmp	pppppp
8	con	ppppp	9	ari	ppppp	10	cmp	Oppp	11	mkf	–
12	cal	ppppppp	13	lod	ppppp	14	sto	p	15	cmp	–
16	cal	pppppp	17	sto	ppOp	18	ari	pp	19	ari	ppppp
20	mkf	–	21	sto	ppp	22	arr	pppp	23	cal	pppppppppp
24	ari	ppppp	25	ari	pppppp	26	con	Opppp	27	ari	pppppp
28	cal	–	29	ari	ppp	30	cal	ppp	31	ari	–
32	cal	–	33	cal	–	34	cal	pppppppp	35	sto	p
36	cal	–	37	sto	pppp	38	cal	–	39	ari	pppppp
40	arr	ppppp	41	cmp	ppmp	42	oth	–	43	cmp	ppppp
44	arr	–	45	cal	–	46	sto	mpp	47	cal	ppppmmp
48	arr	–	49	cal	–	50	sto	pp	51	cmp	mppp
52	con	–	53	cal	–	54	con	ppppp	55	cmp	OpppO
56	bit	pppppp	57	arr	pppp	58	cal	ppppppp	59	ari	pppppp
60	sto	p	61	cal	–	62	sto	ppppp	63	cal	–
64	cmp	ppp	65	ari	pppppp	66	bit	ppppp	67	cal	–
68	cal	–	69	oth	–	70	arr	pppppppp	71	lod	ppppppp
72	cal	–	73	cal	ppppppp	74	sto	–	75	cal	ppppppp
76	cmp	Opppp	77	bit	pppppp	78	cal	pppppppp	79	cmp	ppppp
80	sto	ppp	81	arr	ppppp	82	bit	ppppp	83	cal	–
84	con	–	85	cmp	Opmp	86	arr	pppp	87	oth	–
88	sto	–	89	cmp	ppp	90	sto	ppp	91	bit	–
92	bit	–	93	cal	pppppppppp	94	ctl	m	95	con	ppppp
96	bit	ppp	97	sto	ppppppp	98	sto	pp	99	ari	pppppp
100	mkf	mpOpp	101	ari	pppppp	102	ari	ppp	103	arr	pp
104	bit	ppp	105	cal	pppppppp	106	arr	–	107	sto	OpOp
108	lod	p	109	sto	pp	110	cmp	pp	111	bit	–
112	cal	pppppp	113	cal	ppppppp	114	arr	ppp	115	con	pppppp
116	sto	Oppp	117	sto	pOOp	118	ari	pppppp	119	cal	ppppm
120	cmp	pppppp	121	sto	pp	122	bit	ppp	123	cmp	ppp
124	oth	m	125	cmp	pppmpm	126	bit	–	127	cal	–
128	arr	–	129	bit	ppppppp	130	cmp	pppm	131	cal	ppppppp
132	cal	pppp	133	cmp	ppppp	134	sto	pppppp	135	cal	ppppppp
136	bit	–	137	cal	pppppppp	138	bit	mppp	139	cal	ppm
140	cal	–	141	con	ppppp	142	cal	pppppppp	143	cal	pppppppp
144	cal	–	145	con	–	146	con	ppp	147	cal	–
148	mkf	pmppp	149	arr	ppppp	150	ari	ppppp	151	cmp	ppppp
152	bit	pppppp	153	ari	ppppp	154	ari	ppp	155	cal	–
156	cal	ppppmm	157	mkf	mpppOp	158	oth	–	159	cmp	pmpmpp
160	ari	pppppp	161	cal	pppppp	162	arr	–	163	cal	ppppppp
164	ari	pppppp	165	ari	pppppp	166	cal	–	167	bit	pppppp
168	cmp	mppp	169	ari	ppp	170	ctl	–	171	cal	–
172	ari	pppppp	173	sto	mp	174	arr	p	175	mkf	mppppm
176	sto	pppp	177	oth	–	178	lod	mpm	179	cal	pppppppppp
180	cal	–	181	con	–	182	con	pppp	183	sto	pp
184	arr	–	185	cal	–	186	cal	–	187	sto	pp
188	con	ppppppp	189	bit	pppppp	190	con	–	191	sto	pppp
192	oth	–	193	ari	pppppp	194	cmp	ppp	195	ari	–
196	cmp	mpppmp	197	cmp	pmpmpp	198	cal	ppppppp	199	oth	–
200	sto	ppp	201	cmp	–	202	ari	pppppppp	203	cal	–
204	bit	ppppp	205	con	pppppp	206	cal	ppppppppp	207	ari	ppppppp
208	ari	–	209	con	ppp	210	arr	pmpp	211	sto	ppppppp
212	arr	ppppppp	213	sto	pp	214	sto	OpOp	215	sto	mmppp
216	cmp	ppp	217	con	pppppp	218	sto	Opp	219	ari	–
220	cmp	ppppp	221	cmp	mpppmp	222	bit	–	223	sto	ppmppm
224	cal	pppppppppp	225	cal	–	226	bit	ppppp	227	cal	pppppp
228	cal	ppppppp	229	con	–	230	cal	–	231	ari	ppppp
232	sto	ppm	233	sto	pppp	234	cal	–	235	ari	pppp
236	cmp	ppppp	237	con	–	238	cal	–	239	cal	ppppppppppp
240	bit	ppp	241	con	pppp	242	oth	–	243	sto	ppp
244	sto	ppppp	245	cal	pppp	246	con	–	247	cmp	ppmp
248	ari	pppppppppp	249	ari	ppppppppppp	250	arr	pppppp	251	bit	pppppp
252	con	–	253	arr	pppppp	254	con	–	255	cmp	pppOOp
256	ari	pp	257	cal	pppp	258	cal	pppppp	259	cal	ppmppp
260	cal	–	261	oth	–	262	cal	ppppppp	263	con	pppppp
264	cmp	Opp	265	cal	–	266	ari	–	267	cal	ppppp
268	cal	ppppppp	269	cal	–	270	ari	ppOpp	271	mkf	pmppO
272	ari	ppp	273	arr	ppppp	274	arr	pp	275	sto	pO
276	con	pppppp	277	bit	–	278	cal	pppppppppp	279	cmp	ppp
280	cmp	ppmppm	281	oth	–	282	ari	–	283	cal	ppppp
284	cmp	pOpOp	285	arr	pppp	286	ari	–	287	ari	pmpp
288	arr	pppp	289	sto	mpp	290	cal	–	291	ari	pppppp

op	cat	rd	op	cat	rd	op	cat	rd	op	cat	rd
292	sto	mpppp	293	bit	ppppp	294	sto	pp	295	ari	pppppp
296	oth	–	297	ari	ppp	298	ari	–	299	con	–
300	arr	ppppppp	301	oth	–	302	con	–	303	cmp	pppppp
304	sto	pp	305	cmp	pmpmpp	306	cal	–	307	cmp	ppp
308	arr	–	309	cal	–	310	cal	–	311	sto	pO
312	cal	–	313	cal	mppp	314	cal	ppppppp	315	ari	pppppp
316	bit	ppp	317	con	pppppp	318	bit	ppp	319	bit	ppppp
320	sto	ppmp	321	ari	ppm	322	arr	p	323	ari	pppppp
324	con	pppppp	325	cal	pppppppp	326	mkf	–	327	sto	mmppp
328	sto	pOp	329	cal	pppppp	330	cal	–	331	cal	ppppppppppp
332	cmp	–	333	ari	pppppppp	334	sto	ppp	335	sto	ppppp
336	cal	ppppppppp	337	cmp	pppppp	338	cal	–	339	cal	pppppppp
340	sto	pppppp	341	sto	pppp	342	ctl	–	343	ari	pppppp
344	sto	ppp	345	bit	–	346	sto	–	347	con	ppOppp
348	ari	pOpppp	349	con	–	350	ari	ppppp	351	sto	pp
352	cmp	ppp	353	cal	ppppppp	354	sto	pppp	355	arr	ppp
356	ari	ppppppp	357	ari	–	358	con	–	359	cal	ppppppppppp
360	sto	ppppp	361	lod	ppp	362	cal	–	363	cal	ppppp
364	cal	–									

REFERENCES

[1] C. Collberg, C. Thomborson, and D. Low, "A Taxonomy of Obfuscating Transformations," Univ. of Auckland, Tech. Rep. 148, 1997.

[2] P. Skolka, C.-A. Staicu, and M. Pradel, "Anything to Hide? Studying Minified and Obfuscated Code in the Web," in *WWW*, 2019, pp. 1735–1746.

[3] R. Rolles, "Unpacking Virtualization Obfuscators," in *USENIX WOOT*, 2009.

[4] M. Sharif, A. Lanzi, J. Giffin, and W. Lee, "Automatic Reverse Engineering of Malware Emulators," in *IEEE S&P*, 2009, pp. 94–109.

[5] B. Yadegari, B. Johannesmeyer, B. Whitely, and S. Debray, "A Generic Approach to Automatic Deobfuscation of Executable Code," in *IEEE S&P*, 2015, pp. 674–691.

[6] P. Eckersley, "How Unique Is Your Web Browser?" in *PETS*, 2010, pp. 1–18.

[7] N. Nikiforakis, A. Kapravelos, W. Joosen, C. Kruegel, F. Piessens, and G. Vigna, "Cookieless Monster: Exploring the Ecosystem of Web-based Device Fingerprinting," in *IEEE S&P*, 2013, pp. 541–555.

[8] P. Laperdrix, N. Bielova, B. Baudry, and G. Avoine, "Browser Fingerprinting: A Survey," *ACM Trans. Web*, vol. 14, no. 2, pp. 8:1–8:33, 2020.

[9] notemrovsky, "TikTok Stack-Based Virtual Machine Reverse Engineering," GitHub, 2025. [Online]. Available: https://github.com/notemrovsky/tiktok-reverse-engineering