

The Last Challenge Attack:

Exploiting a Vulnerable Implementation of the
Fiat-Shamir Transform in a KZG-based SNARK

Oana Ciobotaru, Maxim Peter, Vesselin Velichkov

OpenZeppelin

ZKProof 6
Berlin, May 22-24, 2024

The Last Challenge Attack: Historical Context

Background of the Finding

- Finding discovered as part of a Linea PLONK verifier audit.
- Initial theoretical concern regarding the underlying Fiat-Shamir (FS) transform implementation.
- The finding was proven exploitable in practice, making it a critical vulnerability.
- Promptly communicated and fixed.

<https://github.com/Consensys/gnark/security/advisories/GHSA-7p92-x423-vwj6>

The Last Challenge Attack: Historical Context

Background of the Finding

- Finding discovered as part of a Linea PLONK verifier audit.
- Initial theoretical concern regarding the underlying Fiat-Shamir (FS) transform implementation.
- The finding was proven exploitable in practice, making it a critical vulnerability.
- Promptly communicated and fixed.

<https://github.com/Consensys/gnark/security/advisories/GHSA-7p92-x423-vwj6>

Extension

The attack may affect any SNARK implementation which uses KZG as the polynomial commitment scheme.

Can you solve this system?

Linear system of 2 equations with 2 unknowns*

$$\begin{cases} F + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n = A \\ W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n = B \end{cases}$$

with W_1, W_2 the unknowns, the rest are known values.

* An attacker would need to solve the above system in the context of elliptic curve points in the first source group w.r.t a pairing. The scalars are elements of the corresponding scalar field.

Solution

A solution (W_1, W_2) exists if and only if $u \neq 0$ and $z_1 \neq z_2$.

Can you solve this system?

Linear system of 2 equations with 2 unknowns*

$$\begin{cases} F + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n = A \\ W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n = B \end{cases}$$

with W_1, W_2 the unknowns, the rest are known values.

* An attacker would need to solve the above system in the context of elliptic curve points in the first source group w.r.t a pairing. The scalars are elements of the corresponding scalar field.

Solution

A solution (W_1, W_2) exists if and only if $u \neq 0$ and $z_1 \neq z_2$.

You have just learned about the core of the Last Challenge Attack!

The Last Challenge Attack (LCA) in a Nutshell

Main Idea

- **Overview:** Targets incorrect implementations of the Fiat-Shamir (FS) transform for KZG-based SNARK verifiers*.
- **Concrete setting:** The last FS challenge u is computed incorrectly as independent of certain components of the argument** π .
- **Outcome:** Enables a malicious SNARK prover to compute an argument π' for a false statement, while π' is accepted with high probability as valid by the affected SNARK verifier.


* In fact, LCA may apply to any batched KZG-based protocol in which the FS transform has not been implemented correctly with respect to the KZG proof batching challenge.

** For the purposes of this talk, “argument” and “proof” are used interchangeably.


- ① Setting: Scaling Ethereum
- ② The Fiat-Shamir Transform
- ③ The KZG Multipoint Evaluation Scheme
- ④ The Last Challenge Attack
- ⑤ Implications
- ⑥ Conclusions

Setting: Scaling Ethereum

- L2 ZK-Rollups execute transactions off-chain.
- (SNARK) prover \mathcal{P} provides a succinct ZK argument π on L1.
- π testifies that transactions were executed correctly.
- (SNARK) verifier \mathcal{V} verifies on L1 the correctness of π .
- The state of L2 on L1 (and the state of L1) are updated accordingly.



Interactive vs. Non-interactive Arguments



The Fiat-Shamir (FS) Transform

- By default, computing π is an interactive process between the prover \mathcal{P} and the verifier \mathcal{V} .
- The FS transform turns that into a non-interactive process via an idealised random oracle model (ROM).
- In practice, the non-interactive prover and non-interactive verifier independently compute the same unpredictable challenges as the hash of the computation transcript up to that point.

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

gen(d)

Choose $\mathbf{x} \in \mathbb{F}$. Output $\mathbf{srs} = (g_1, \mathbf{x} \cdot g_1, \dots, \mathbf{x}^{d-1} \cdot g_1, g_2, \mathbf{x} \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

gen(d)

Choose $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

com(f, srs)

Output $cm = f(x) \cdot g_1$.

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

$gen(d)$

Choose $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

$com(f, srs)$

Output $cm = f(x) \cdot g_1$.

$open(\{cm_j\}_{j=1}^t, z, \{s_j\}_{j=1}^t)$

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

$gen(d)$

Choose $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

$com(f, srs)$

Output $cm = f(x) \cdot g_1$.

$open(\{cm_j\}_{j=1}^t, z, \{s_j\}_{j=1}^t)$

- 1 Round 1: V_{KZG} sends uniformly random $\gamma \in \mathbb{F}$ to P_{KZG} .

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

$gen(d)$

Choose $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

$com(f, srs)$

Output $cm = f(x) \cdot g_1$.

$open(\{cm_j\}_{j=1}^t, z, \{s_j\}_{j=1}^t)$

- 1 Round 1: V_{KZG} sends uniformly random $\gamma \in \mathbb{F}$ to P_{KZG} .
- 2 Round 2: P_{KZG} computes poly $h(X) = \sum_{j=1}^t \gamma^{j-1} \cdot \frac{f_j(x) - f_j(z)}{X - z}$.

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

$gen(d)$

Choose $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

$com(f, srs)$

Output $cm = f(x) \cdot g_1$.

$open(\{cm_j\}_{j=1}^t, z, \{s_j\}_{j=1}^t)$

- ① Round 1: V_{KZG} sends uniformly random $\gamma \in \mathbb{F}$ to P_{KZG} .
- ② Round 2: P_{KZG} computes poly $h(X) = \sum_{j=1}^t \gamma^{j-1} \cdot \frac{f_j(x) - f_j(z)}{X - z}$.

Using the srs , P_{KZG} computes and sends to V_{KZG} the KZG proof $\pi_{KZG} = W$, where $W = h(x) \cdot g_1$.

Reminder: The KZG Polynomial Commitment Scheme

It assumes parties P_{KZG} (sender/prover) and V_{KZG} (recipient/verifier).

It requires a pairing friendly elliptic curve and, hence, an associated secure pairing e , a scalar field \mathbb{F} , two pairing source groups $\mathbb{G}_1, \mathbb{G}_2$ (among others).

$gen(d)$

Choose $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2) \in \mathbb{G}_1^d \times \mathbb{G}_2^2$.

$com(f, srs)$

Output $cm = f(x) \cdot g_1$.

$open(\{cm_j\}_{j=1}^t, z, \{s_j\}_{j=1}^t)$

- ① Round 1: V_{KZG} sends uniformly random $\gamma \in \mathbb{F}$ to P_{KZG} .
- ② Round 2: P_{KZG} computes poly $h(X) = \sum_{j=1}^t \gamma^{j-1} \cdot \frac{f_j(x) - f_j(z)}{X - z}$.

Using the srs , P_{KZG} computes and sends to V_{KZG} the

KZG proof $\pi_{KZG} = W$, where $W = h(x) \cdot g_1$.

- ③ Round 3: V_{KZG} computes $F = \sum_{j=1}^t \gamma^{j-1} \cdot cm_j - (\sum_{j=1}^t \gamma^{j-1} \cdot s_j) \cdot g_1$.

V_{KZG} outputs **acc** if and only if $e(F + z \cdot W, g_2) = e(W, x \cdot g_2)$.

The KZG Multipoint Evaluation Scheme (KZG MES)

Let $n \geq 2$; assume parties P_{KZG} and V_{KZG} and proceed as follows:

gen(d)

Choose (secret) random $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2)$.

com(f, srs)

Output $cm = f(x) \cdot g_1$.

The KZG Multipoint Evaluation Scheme (KZG MES)

Let $n \geq 2$; assume parties P_{KZG} and V_{KZG} and proceed as follows:

gen(d)

Choose (secret) random $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2)$.

com(f, srs)

Output $\mathbf{cm} = f(x) \cdot g_1$.

open($((\{\mathbf{cm}_{i,j}\}_{j \in [t]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t]})_{i \in [n]})$)

The KZG Multipoint Evaluation Scheme (KZG MES)

Let $n \geq 2$; assume parties P_{KZG} and V_{KZG} and proceed as follows:

gen(d)

Choose (secret) random $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2)$.

com(f, srs)

Output $\mathbf{cm} = f(x) \cdot g_1$.

open($((\{\mathbf{cm}_{i,j}\}_{j \in [t]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t]})_{i \in [n]})$

- 1 Round 1: V_{KZG} sends uniformly random $\{\gamma_i\}_{i \in [n]} \in \mathbb{F}^n$ to P_{KZG} .

The KZG Multipoint Evaluation Scheme (KZG MES)

Let $n \geq 2$; assume parties P_{KZG} and V_{KZG} and proceed as follows:

gen(d)

Choose (secret) random $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2)$.

com(f, srs)

Output $cm = f(x) \cdot g_1$.

open($(\{cm_{i,j}\}_{j \in [t_i]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [n]}$)

- 1 Round 1: V_{KZG} sends uniformly random $\{\gamma_i\}_{i \in [n]} \in \mathbb{F}^n$ to P_{KZG} .
- 2 Round 2: P_{KZG} computes polys $\{h_i(X) = \sum_{j=1}^{t_i} \gamma_i \cdot \frac{f_{i,j}(x) - f_{i,j}(z_i)}{X - z_i}\}_{i \in [n]}$.

The KZG Multipoint Evaluation Scheme (KZG MES)

Let $n \geq 2$; assume parties P_{KZG} and V_{KZG} and proceed as follows:

gen(d)

Choose (secret) random $x \in \mathbb{F}$. Output $srs = (g_1, x \cdot g_1, \dots, x^{d-1} \cdot g_1, g_2, x \cdot g_2)$.

com(f, srs)

Output $cm = f(x) \cdot g_1$.

open($(\{cm_{i,j}\}_{j \in [t_i]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [n]}$)

- 1 Round 1: V_{KZG} sends uniformly random $\{\gamma_i\}_{i \in [n]} \in \mathbb{F}^n$ to P_{KZG} .
- 2 Round 2: P_{KZG} computes polys $\{h_i(X) = \sum_{j=1}^{t_i} \gamma_i \cdot \frac{f_{i,j}(x) - f_{i,j}(z_i)}{X - z_i}\}_{i \in [n]}$.

Using the srs , P_{KZG} computes and sends to V_{KZG} the

KZG MES proof $\pi_{KZG} = (W_i)_{i=1}^n$, where $W_i = h_i(x) \cdot g_1$.

The KZG Multipoint Evaluation Scheme (cont.)

$\text{open}((\{\mathbf{cm}_{i,j}\}_{j \in [t_i]})_{i \in [a]}, \{z_i\}_{i \in [a]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [a]})$

8 Round 3:

The KZG Multipoint Evaluation Scheme (cont.)

$\text{open}((\{cm_{i,j}\}_{j \in [t_i]})_{i \in [a]}, \{z_i\}_{i \in [a]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [a]})$

8 *Round 3:*

V_{KZG} chooses random $u \in \mathbb{F}$.

The KZG Multipoint Evaluation Scheme (cont.)

$\text{open}((\{\mathbf{cm}_{i,j}\}_{j \in [t_i]})_{i \in [n]}, \{s_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [n]})$

8 Round 3:

V_{KZG} chooses random $u \in \mathbb{F}$.

V_{KZG} computes $\{F_i\}_{i \in [n]}$, $F_i = \sum_{j=1}^{t_i} \gamma_i \cdot \mathbf{cm}_{i,j} - (\sum_{j=1}^{t_i} \gamma_i \cdot s_{i,j}) \cdot g_1$

The KZG Multipoint Evaluation Scheme (cont.)

$open((\{\mathbf{cm}_{i,j}\}_{j \in [t_i]})_{i \in [a]}, \{z_i\}_{i \in [a]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [a]})$

8 Round 3:

V_{KZG} chooses random $u \in \mathbb{F}$.

V_{KZG} computes $\{F_i\}_{i \in [n]}$, $F_i = \sum_{j=1}^{t_i} \gamma_i \cdot \mathbf{cm}_{i,j} - (\sum_{j=1}^{t_i} \gamma_i \cdot s_{i,j}) \cdot g_1$

V_{KZG} outputs **acc** if and only if the following holds:

$$\begin{aligned} e(F_1 + \dots + u^{n-1} \cdot F_n + z_1 \cdot W_1 + \dots + u^{n-1} \cdot z_n \cdot W_n, g_2) = \\ = e(W_1 + \dots + u^{n-1} \cdot W_n, x \cdot g_2). \end{aligned}$$

The KZG Multipoint Evaluation Scheme (cont.)

$open((\{\mathbf{cm}_{i,j}\}_{j \in [t_i]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [n]})$

8 Round 3:

V_{KZG} chooses random $u \in \mathbb{F}$.

V_{KZG} computes $\{F_i\}_{i \in [n]}$, $F_i = \sum_{j=1}^{t_i} \gamma_i \cdot \mathbf{cm}_{i,j} - (\sum_{j=1}^{t_i} \gamma_i \cdot s_{i,j}) \cdot g_1$

V_{KZG} outputs **acc** if and only if the following holds:

$$\begin{aligned} e(F_1 + \dots + u^{n-1} \cdot F_n + z_1 \cdot W_1 + \dots + u^{n-1} \cdot z_n \cdot W_n, g_2) = \\ = e(W_1 + \dots + u^{n-1} \cdot W_n, x \cdot g_2). \end{aligned}$$

Quick Note (We Come Back To It Later!)

Last challenge u defined in Round 3 is only computed and used by V_{KZG} .

The KZG Multipoint Evaluation Scheme (cont.)

$\text{open}((\{\mathbf{cm}_{i,j}\}_{j \in [t_i]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [n]})$

⑧ *Round 3:*

V_{KZG} chooses random $u \in \mathbb{F}$.

V_{KZG} computes $\{F_i\}_{i \in [n]}$, $F_i = \sum_{j=1}^{t_i} \gamma_i \cdot \mathbf{cm}_{i,j} - (\sum_{j=1}^{t_i} \gamma_i \cdot s_{i,j}) \cdot g_1$

V_{KZG} outputs **acc** if and only if the following holds:

$$\begin{aligned} e(F_1 + \dots + u^{n-1} \cdot F_n + z_1 \cdot W_1 + \dots + u^{n-1} \cdot z_n \cdot W_n, g_2) = \\ = e(W_1 + \dots + u^{n-1} \cdot W_n, x \cdot g_2). \end{aligned}$$

Quick Note (We Come Back To It Later!)

Last challenge u defined in *Round 3* is only computed and used by V_{KZG} .

Lemma: Security of KZG MES in the AGM

KZG MES has *completeness and knowledge-soundness in the algebraic group model under the Q-DLOG assumption*.

(See proof of Lemma 6 from [ePrint 2024/398](#) for full details.)

Properties of the Non-interactive Version of KZG MES

Let P_{KZGN} , V_{KZGN} be the non-interactive version of KZG MES prover, verifier.

The non-interactive version of KZG MES:

- is obtained by applying the FS transform;
- can be proven secure in the ROM.

Non-interactive Version of KZG MES and Variants

Properties of the Non-interactive Version of KZG MES

Let P_{KZGN} , V_{KZGN} be the non-interactive version of KZG MES prover, verifier.

The non-interactive version of KZG MES:

- is obtained by applying the FS transform;
- can be proven secure in the ROM.

Reminder 1: All challenges are computed by both P_{KZGN} , V_{KZGN} as the hash of the entire communication transcript up to that point in the protocol.

Non-interactive Version of KZG MES and Variants

Properties of the Non-interactive Version of KZG MES

Let P_{KZGN} , V_{KZGN} be the non-interactive version of KZG MES prover, verifier.

The non-interactive version of KZG MES:

- is obtained by applying the FS transform;
- can be proven secure in the ROM.

Reminder 1: All challenges are computed by both P_{KZGN} , V_{KZGN} as the hash of the entire communication transcript up to that point in the protocol.

Reminder 2: Last challenge u is actually only computed and used by V_{KZGN} !

Non-interactive Version of KZG MES and Variants

Properties of the Non-interactive Version of KZG MES

Let P_{KZGN} , V_{KZGN} be the non-interactive version of KZG MES prover, verifier.

The non-interactive version of KZG MES:

- is obtained by applying the FS transform;
- can be proven secure in the ROM.

Reminder 1: All challenges are computed by both P_{KZGN} , V_{KZGN} as the hash of the entire communication transcript up to that point in the protocol.

Reminder 2: Last challenge u is actually only computed and used by V_{KZGN} !

Assume reducing computational costs is important, including unnecessary hashing!

Non-interactive Version of KZG MES and Variants

Properties of the Non-interactive Version of KZG MES

Let P_{KZGN} , V_{KZGN} be the non-interactive version of KZG MES prover, verifier.

The non-interactive version of KZG MES:

- is obtained by applying the FS transform;
- can be proven secure in the ROM.

Reminder 1: All challenges are computed by both P_{KZGN} , V_{KZGN} as the hash of the entire communication transcript up to that point in the protocol.

Reminder 2: Last challenge u is actually only computed and used by V_{KZGN} !

Assume reducing computational costs is important, including unnecessary hashing!

Dilemma

Does non-interactive KZG MES still remain secure (i.e., *knowledge-sound*) if the non-interactive verifier (i.e., a variation on V_{KZGN}) computes u as the hash of only a part of the full transcript (e.g., excluding some π_{KZG} components)?

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing \mathbf{u} as the hash of the full transcript excluding the first two components of π_{KZG} .

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.
- Using the inputs to the KZG pairing check, P'_{KZGN} produces $A, B \in \mathbb{G}_1$ such that $e(A, g_2) = e(B, x \cdot g_2)$.

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.
- Using the inputs to the KZG pairing check, P'_{KZGN} produces $A, B \in \mathbb{G}_1$ such that $e(A, g_2) = e(B, x \cdot g_2)$.

- P'_{KZGN} sets green-font variables to domain-respecting arbitrary values:

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.
- Using the inputs to the KZG pairing check, P'_{KZGN} produces $A, B \in \mathbb{G}_1$ such that $e(A, g_2) = e(B, x \cdot g_2)$.

2 P'_{KZGN} sets green-font variables to domain-respecting arbitrary values:

- $(\{cm_{i,j}\}_{j \in [t_i]})_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]})_{i \in [n]} \rightarrow$ inputs to **open!**

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.
- Using the inputs to the KZG pairing check, P'_{KZGN} produces $A, B \in \mathbb{G}_1$ such that $e(A, g_2) = e(B, x \cdot g_2)$.

2 P'_{KZGN} sets green-font variables to domain-respecting arbitrary values:

- $(\{cm_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}) \rightarrow$ inputs to **open!**
- $\pi'_{KZG} = (W_1, W_2, W_3, \dots, W_n) \rightarrow n \geq 2!$

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.
- Using the inputs to the KZG pairing check, P'_{KZGN} produces $A, B \in \mathbb{G}_1$ such that $e(A, g_2) = e(B, x \cdot g_2)$.

2 P'_{KZGN} sets green-font variables to domain-respecting arbitrary values:

- $(\{cm_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}) \rightarrow$ inputs to **open!**
- $\pi'_{KZG} = (w_1, w_2, w_3, \dots, w_n) \rightarrow n \geq 2!$

P'_{KZGN} aims to create π'_{KZG} for a false statement!

The Last Challenge Attack

Let P'_{KZGN} be a malicious non-interactive prover as per below.

Let V'_{KZGN} be the variation on V_{KZGN} verifier computing u as the hash of the full transcript excluding the first two components of π_{KZG} .

Steps 1–3

1 Bootstrapping:

- P'_{KZGN} simulates single instance single evaluation point KZG for arbitrary $f(X) \in \mathbb{F}[X]$ evaluated at arbitrary $z \in \mathbb{F}$.
- Using the inputs to the KZG pairing check, P'_{KZGN} produces $A, B \in \mathbb{G}_1$ such that $e(A, g_2) = e(B, x \cdot g_2)$.

2 P'_{KZGN} sets green-font variables to domain-respecting arbitrary values:

- $(\{cm_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}, \{z_i\}_{i \in [n]}, (\{s_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}) \rightarrow$ inputs to **open!**
- $\pi'_{KZG} = (W_1, W_2, W_3, \dots, W_n) \rightarrow n \geq 2!$

P'_{KZGN} aims to create π'_{KZG} for a false statement!

- 3 Using $(\{cm_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}$ and $(\{s_{i,j}\}_{j \in [t_i]} \}_{i \in [n]}$, P'_{KZGN} deterministically computes $F_1, \dots, F_n \in \mathbb{G}_1$ following *Round 3* of KZG MES.

The Last Challenge Attack (cont.)

Steps 4–6

The Last Challenge Attack (cont.)

Steps 4–6

- ④ V'_{KZGN} computes \mathbf{u} as the hash of the full transcript excluding $\mathbf{W}_1, \mathbf{W}_2$.
This is deviation from the FS transform!

The Last Challenge Attack (cont.)

Steps 4–6

- ④ V'_{KZGN} computes u as the hash of the full transcript excluding W_1, W_2 .
This is deviation from the FS transform!

P'_{KZGN} exploits that by solving the following system where W_1, W_2 are the only unknowns:

$$\begin{cases} F + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n = A \\ W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n = B \end{cases}$$

and the rest are constants as follows (see also Steps 1–3):

$$\begin{aligned} & e(\underbrace{F_1 + \dots + u^{n-1} \cdot F_n}_{F} + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n, g_2) \stackrel{?}{=} \\ & \underbrace{\hspace{15em}}_A \\ & \stackrel{?}{=} e(\underbrace{W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n}_B, x \cdot g_2). \end{aligned}$$

The Last Challenge Attack (cont.)

Steps 4–6

- ④ V'_{KZGN} computes u as the hash of the full transcript excluding W_1, W_2 .
This is deviation from the FS transform!

P'_{KZGN} exploits that by solving the following system where W_1, W_2 are the only unknowns:

$$\begin{cases} F + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n = A \\ W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n = B \end{cases}$$

and the rest are constants as follows (see also Steps 1–3):

$$\begin{aligned} & e(\underbrace{F_1 + \dots + u^{n-1} \cdot F_n}_{F} + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n, g_2) \stackrel{?}{=} \\ & \underbrace{\hspace{15em}}_A \\ & \stackrel{?}{=} e(\underbrace{W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n}_B, x \cdot g_2). \end{aligned}$$

- ⑤ P'_{KZGN} fills in the corresponding slots of π'_{KZG} with the values W_1, W_2 .

The Last Challenge Attack (cont.)

Steps 4–6

- 4 V'_{KZGN} computes u as the hash of the full transcript excluding W_1, W_2 .
This is deviation from the FS transform!

P'_{KZGN} exploits that by solving the following system where W_1, W_2 are the only unknowns:

$$\begin{cases} F + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n = A \\ W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n = B \end{cases}$$


and the rest are constants as follows (see also Steps 1–3):

$$\begin{aligned} & e(\underbrace{F_1 + \dots + u^{n-1} \cdot F_n}_{F} + z_1 \cdot W_1 + u \cdot z_2 \cdot W_2 + \dots + u^{n-1} \cdot z_n \cdot W_n, g_2) \stackrel{?}{=} \\ & \underbrace{\hspace{15em}}_A \\ & \stackrel{?}{=} e(\underbrace{W_1 + u \cdot W_2 + \dots + u^{n-1} \cdot W_n}_B, x \cdot g_2). \end{aligned}$$

- 5 P'_{KZGN} fills in the corresponding slots of π'_{KZG} with the values W_1, W_2 .
- 6 V'_{KZGN} accepts proof π'_{KZG} as valid with probability 1.


Implications

Let \mathcal{P}' be a malicious SNARK prover with a P'_{KZGN} subcomponent. \mathcal{P}' can set itself as the owner of all the assets by changing the Merkle root (part of the **PI**) and steal all user funds.



Implications

Let \mathcal{P}' be a malicious SNARK prover with a P'_{KZGN} subcomponent. \mathcal{P}' can set itself as the owner of all the assets by changing the Merkle root (part of the **PI**) and steal all user funds.



- Introduced LCA, a new type of attack on specific incorrect implementations of the FS transform for KZG-based SNARKs.
- LCA exploits the fact that the last challenge defined by the FS transform is incorrectly computed as independent from some of the SNARK proof components.
- LCA is related but different from the weak FS transform attacks occurring when public input or public are parameters not fully incorporated into the transcript.

Takeaways

- FS challenges must depend on the entire transcript up to that point of the computation.
- Follow the protocol!

Challenges can be challenging, so mind your Fiat-Shamir-s!

Thank you!

ePrint 2024/398