DATI ELETTRICI E PRESTAZIONI

ELECTRICAL DATA AND PERFORMANCES

n _n rpm	Motore <i>Motor</i>	P _n kW	V _n	I _n	F _n Hz	M _n Nm	n ₁	n ₂ rpm	n ₃ rpm	M _{max} Nm	J Kgm²	W kg
TPIII	AJAr180S	30,4		72,2	112	580	тріп	трін	тріп	1100	0,391	370
	AJAr180M	41,9	1	99,6		800				1500	0,536	460
	AJAr180L	49,7	400	118	25	950	600	800	4300	1800	0,619	520
	AJAr180P	55,0		131		1050	000 000	000	(3800)	2000	0,690	560
	AJAr180X	62,9		149		1200				2250	0,790	640
	AJAr225M	61,8		143		1180				2240	0,960	800
	AJAr225L	73,3	400	170	05	1400	000	000	3400	2660	1,120	880
500	AJAr225P	86,4		200	25	1650	600 800	800	(2800)	3100	1,250	1000
	AJAr225X	102		237		1950				3700	1,470	1180
	AJAr280S	85,9		208		1640				3100	1,370	1300
	AJAr280M	104		251	25	1980			3700	1,650	1450	
	AJAr280MX	115	400	279		2200	600	800	3000	4100	1,820	1580
	AJAr280L	127	400	307	23	2420	000	000	(2800)	4500	1,970	1650
	AJAr280P	138		335		2640				5000	2,140	1800
	AJAr280PX	150		363		2865				5400	2,340	1950
	AJAr180S	35,2	1	82,8		580			1100	0,391	370	
	AJAr180M	48,6		114		800			4300	1500	0,536	460
	AJAr180L	57,7	400	136	29	950	700	900	(3800)	1800	0,619	520
	AJAr180P	63,8		150		1050				2000	0,690	560
1	AJAr180X	72,9		171		1200				2250	0,790	640 800
	AJAr225M	71,7	400	164 195		1180 1400		900	3400 (2800)	2240 2660	0,960 1,120	880
580	AJAr225L AJAr225P	85,0 100		230	29	1650	700			3100	1,120	1000
	AJAr225X	118		271		1950				3700	1,470	1180
	AJAr280S	100		238		1640				3100	1,370	1300
	AJAr280M	120	1	288		1980			3000 (2800)	3700	1,650	1450
	AJAr280MX	134	400	320	00	2200	700 900	000		4100	1,820	1580
	AJAr280L	147		352	29	2420		900		4500	1,970	1650
	AJAr280P	160		384		2640				5000	2,140	1800
	AJAr280PX	174		417		2865			5400	2,340	1950	
	AJAr180S	39,5	400	89,5	33	580	800 1000		0 4300 (3800)	1100	0,391	370
	AJAr180M	54,5		123		800		1000		1500	0,536	460
	AJAr180L	64,7		147		950				1800	0,619	520
	AJAr180P	71,5 81,7		162 185		1050 1200				2000 2250	0,690 0,790	560 640
	AJAr180X				33			1000	3400 (2800)			
	AJAr225M AJAr225L	80,3 95,3		180 213		1180 1400				2240 2660	0,960 1,120	800 880
650	AJAr225P	112	400	251		1650	800			3100	1,250	1000
	AJAr225X	132		297		1950			(2000)	3700	1,470	1180
	AJAr280S	112		264		1640	800 1000	1000	3000 (2800)	3100	1,370	1300
	AJAr280M	135	1	319	- 33	1980				3700	1,650	1450
	AJAr280MX	150	400	354		2200				4100	1,820	1580
	AJAr280L	165	400	290		2420				4500	1,970	1650
	AJAr280P	180		425		2640				5000	2,140	1800
	AJAr280PX	195		462		2865				5400	2,340	1950
1000	AJAr180S	58,3	400	129		557	1200 150			1100	0,391	370
	AJAr180M	80,4		178		768		1500	4300 (3800)	1500	0,536	460
	AJAr180L AJAr180P	95,5 106		211 234	50	912 1008	1200			1800 2000	0,619 0,690	520 560
	AJAr180X	121		267		1152				2250	0,890	640
	AJAr225M	119	400	259	50	1133	1200 15	1500	3400 (2800)	2240	0,960	800
	AJAr225L	141		308		1344				2660	1,120	880
	AJAr225P	166		363		1584				3100	1,250	1000
	AJAr225X	196		428		1872				3700	1,470	1180
	AJAr280S	165		386		1574				3100	1,370	1300
	AJAr280M	199	400	466	50	1901	1200 1500	1500	3000 (2800)	3700	1,650	1450
	AJAr280MX	221		517		2112				4100	1,820	1580
	AJAr280L	243		569		2323				4500	1,970	1650
	AJAr280P	265		621		2534				5000	2,140	1800
	AJAr280PX	289		674		2760			5400	2,340	1950	


Attenzione:

I dati elettrici e le prestazioni sono indicativi e sono soggetti a variazioni e/o modifiche senza preavviso.

Attention:

Electrical data and performances are indicative and can be changed without notice.





Size	В	B1	D	E	F	GA	LR	L1	W	Z
180S	400	430	60 ^{m6}	-		64	1005		174	
180M	520	550	65 ^{m6}			69	1125		294	_
180L	590	620		140	18		1195	200 2)	364	M 20
180P	640	670					1245		414	
180X	710	740					1295		484	_

Note:

IM1001 (B3) Standard


IM2001 (B35) Su richiesta – Option available on request Pressacavi non forniti - Cable glands not included in the supply

Attenzione:

Le dimensioni sono indicative e sono soggette a variazioni e/o modifiche senza preavviso.

Attention:

Dimension are indicative and can be changed without notice.



Size	В	D	E	F	GA	L	w	Z
225M	675	75 ^{m6}	140	20	79.5	1355	390	
225L	725	(85 ^{m6}) ²⁾	(170) ²⁾	(22) ²⁾	(90) ²⁾	1405	440	M20
225P	803	– 85 ^{m6}	170	22	90 —	1515	518	WIZU
225X	923	– oo	170	22	90 —	1635	638	-


Note:

IM1001 (B3) Standard

IM2001 (B35) Su richiesta – Option available on request Pressacavi non forniti - Cable glands not included in the supply

Le dimensioni sono indicative e sono soggette a variazioni e/o modifiche senza preavviso.

Dimension are indicative and can be changed without notice.



Size	В	L	w
280S	560	1490	510
280M	640	1570	590
280MX	700	1630	650
280L	750	1680	700
280P	810	1740	760
280PX	870	1800	820

Note:

IM1001 (B3) Standard

IM2001 (B35) Su richiesta – Option available on request Pressacavi non forniti - Cable glands not included in the supply

Attenzione:

Le dimensioni sono indicative e sono soggette a variazioni e/o modifiche senza preavviso.

Attention:

Dimension are indicative and can be changed without notice.