A transformation sequence from word `beginWord` to word `endWord` using a dictionary `wordList` is a sequence of words `beginWord -> s1 -> s2 -> ... -> sk` such that:

- Every adjacent pair of words differs by a single letter.
- Every `si` for `1 <= i <= k` is in `wordList`. Note that `beginWord` does not need to be in `wordList`.
- `sk == endWord`

Given two words, `beginWord` and `endWord`, and a dictionary `wordList`, return all the shortest transformation sequences from `beginWord` to `endWord`, or an empty list if no such sequence exists. Each sequence should be returned as a list of the words `[beginWord, s1, s2, ..., sk]`.

**Example 1:**

```
Input: beginWord = "hit", endWord = "cog", wordList = ["hot","dot","dog","lot","log","cog"]
Output: [["hit","hot","dot","dog","cog"],["hit","hot","lot","log","cog"]]
Explanation: There are 2 shortest transformation sequences:
"hit" -> "hot" -> "dot" -> "dog" -> "cog"
"hit" -> "hot" -> "lot" -> "log" -> "cog"
```

**Example 2:**

```
Input: beginWord = "hit", endWord = "cog", wordList = ["hot","dot","dog","lot","log"]
Output: []
Explanation: The endWord "cog" is not in wordList, therefore there is no valid transformation sequence.
```

**Constraints:**

- `1 <= beginWord.length <= 5`
- `endWord.length == beginWord.length`
- `1 <= wordList.length <= 500`
- `wordList[i].length == beginWord.length`
- `beginWord`, `endWord`, and `wordList[i]` consist of lowercase English letters.
- `beginWord != endWord`
- All the words in `wordList` are unique.

Accepted 1,000,000 Submissions 3,000,000 Attempting 100%

**Related Topics:**

Array String Backtracking Breadth-First Search

Similar Questions:

Word Ladder (Hard) Minimum Genetic Mutation (Medium)

**Hint 1:**

Start from `beginWord` and search for `endWord` using BFS.

**Hint 2:**

Do you need to check if every two words differ by a single letter efficiently? Is there a way to achieve this faster than trying all pairs?

**Hint 3:**

Can you use two sets to make the BFS bidirectional?

**Hint 4:**

Once you find the `endWord`, backtrack using BFS to find all the shortest transformation sequences.

Sponsored by Algolia

Algolia powers search for your apps and websites. Build a great search experience with our suite of APIs and developer tools.

Sponsored by Cloudinary

Cloudinary is the image and video API for websites and apps. Upload, store, manage, manipulate and deliver images and videos at scale.

Sponsored by Scout APM

Scout APM: Application performance monitoring that's actually useful. Try it free for 14 days.

## Solution

### Approach 1: Bidirectional BFS + Backtracking

**Intuition**

Finding all shortest transformation sequences is a two-phase problem. First, we need to find the shortest distance from `beginWord` to `endWord`. Second, we need to reconstruct all paths that achieve this distance.

Bidirectional BFS is an optimization that searches from both ends simultaneously. Instead of exploring all words reachable in `d` steps from the start, we explore words reachable in `d/2` steps from each end. This can dramatically reduce the search space.

**Algorithm**

1. **Preprocessing**: Add `beginWord` to the word list if it's not already there. Create a set for O(1) lookup.

2. **Bidirectional BFS**: Use two sets, `beginSet` and `endSet`, to track the current frontiers. Always expand the smaller set to minimize work.

3. **Finding neighbors**: For each word, try changing each character to every letter from 'a' to 'z'. If the resulting word is in the dictionary, it's a neighbor.

4. **Tracking parents**: When we find a word in the opposite frontier, we've found a shortest path. Record the parent relationship to reconstruct paths later.

5. **Backtracking**: Once we've found the shortest distance, use DFS to reconstruct all paths by following parent pointers.

**Implementation**

```
class Solution {
    public List<List<String>> findLadders(String beginWord, String endWord, List<String> wordList) {
        Set<String> dict = new HashSet<>(wordList);
        if (!dict.contains(endWord)) return new ArrayList<>();
        dict.add(beginWord);

        // Bidirectional BFS to find shortest distance
        Set<String> beginSet = new HashSet<>();
        Set<String> endSet = new HashSet<>();
        beginSet.add(beginWord);
        endSet.add(endWord);

        // Map: word -> list of parents (words that can reach it in shortest path)
        Map<String, List<String>> parents = new HashMap<>();
        boolean forward = true;
        boolean found = false;

        while (!beginSet.isEmpty() && !endSet.isEmpty() && !found) {
            // Always expand the smaller set
            if (beginSet.size() > endSet.size()) {
                Set<String> temp = beginSet;
                beginSet = endSet;
                endSet = temp;
                forward = !forward;
            }

            Set<String> nextSet = new HashSet<>();
            for (String word : beginSet) {
                char[] chars = word.toCharArray();
                for (int i = 0; i < chars.length; i++) {
                    char original = chars[i];
                    for (char c = 'a'; c <= 'z'; c++) {
                        chars[i] = c;
                        String next = new String(chars);
                        if (endSet.contains(next)) {
                            found = true;
                            addParent(parents, forward ? next : word, forward ? word : next);
                        } else if (dict.contains(next) && !beginSet.contains(next)) {
                            nextSet.add(next);
                            addParent(parents, forward ? next : word, forward ? word : next);
                        }
                    }
                    chars[i] = original;
                }
            }
            beginSet = nextSet;
        }

        // Backtrack to build all paths
        List<List<String>> result = new ArrayList<>();
        if (found) {
            backtrack(result, new ArrayList<>(), endWord, parents, beginWord);
        }
        return result;
    }

    private void addParent(Map<String, List<String>> parents, String child, String parent) {
        parents.computeIfAbsent(child, k -> new ArrayList<>()).add(parent);
    }

    private void backtrack(List<List<String>> result, List<String> path, String word,
                           Map<String, List<String>> parents, String beginWord) {
        path.add(word);
        if (word.equals(beginWord)) {
            List<String> reversed = new ArrayList<>(path);
            Collections.reverse(reversed);
            result.add(reversed);
        } else {
            for (String parent : parents.getOrDefault(word, new ArrayList<>())) {
                backtrack(result, path, parent, parents, beginWord);
            }
        }
        path.remove(path.size() - 1);
    }
}
```

**Complexity Analysis**

Let $N$ be the number of words in the dictionary, $L$ be the length of each word, and $A$ be the size of the alphabet (26).

- Time complexity: $O(N \cdot L \cdot A + P)$ where $P$ is the total number of shortest paths. In the worst case, $P$ can be exponential.
- Space complexity: $O(N \cdot L + P)$ for storing the dictionary and all paths.

### Approach 2: BFS + DFS with Layer Tracking

**Intuition**

Instead of bidirectional search, we can use standard BFS while tracking which layer each word is discovered in. Once we reach `endWord`, we know the shortest distance. Then we can use DFS to find all paths that follow this distance.

**Algorithm**

1. **BFS phase**: Explore level by level. Record the parents of each word (all words that can reach it in the shortest distance).

2. **Stop condition**: Stop BFS when we reach `endWord` or exhaust all reachable words.

3. **DFS phase**: Starting from `endWord`, follow parent pointers back to `beginWord` to collect all shortest paths.

**Implementation**

```
class Solution {
    public List<List<String>> findLadders(String beginWord, String endWord, List<String> wordList) {
        Set<String> dict = new HashSet<>(wordList);
        if (!dict.contains(endWord)) return new ArrayList<>();

        // BFS to build parent map
        Map<String, List<String>> parents = new HashMap<>();
        Set<String> current = new HashSet<>();
        current.add(beginWord);
        boolean found = false;

        while (!current.isEmpty() && !found) {
            dict.removeAll(current);
            Set<String> next = new HashSet<>();
            for (String word : current) {
                char[] chars = word.toCharArray();
                for (int i = 0; i < chars.length; i++) {
                    char original = chars[i];
                    for (char c = 'a'; c <= 'z'; c++) {
                        chars[i] = c;
                        String newWord = new String(chars);
                        if (newWord.equals(endWord)) {
                            found = true;
                            parents.computeIfAbsent(newWord, k -> new ArrayList<>()).add(word);
                        } else if (dict.contains(newWord)) {
                            next.add(newWord);
                            parents.computeIfAbsent(newWord, k -> new ArrayList<>()).add(word);
                        }
                    }
                    chars[i] = original;
                }
            }
            current = next;
        }

        // DFS to collect all paths
        List<List<String>> result = new ArrayList<>();
        if (found) {
            dfs(result, new ArrayList<>(), endWord, parents, beginWord);
        }
        return result;
    }

    private void dfs(List<List<String>> result, List<String> path, String word,
                     Map<String, List<String>> parents, String beginWord) {
        path.add(word);
        if (word.equals(beginWord)) {
            List<String> reversed = new ArrayList<>(path);
            Collections.reverse(reversed);
            result.add(reversed);
        } else {
            for (String parent : parents.getOrDefault(word, new ArrayList<>())) {
                dfs(result, path, parent, parents, beginWord);
            }
        }
        path.remove(path.size() - 1);
    }
}
```

**Complexity Analysis**

Let $N$ be the number of words in the dictionary, $L$ be the length of each word, and $A$ be the size of the alphabet (26).

- Time complexity: $O(N \cdot L \cdot A + P)$ where $P$ is the total number of shortest paths.
- Space complexity: $O(N \cdot L + P)$ for storing the dictionary and all paths.

### Approach 3: Optimized Bidirectional BFS

**Intuition**

This approach combines bidirectional BFS with an optimization: we only add words to the parent map when they're discovered in the direction that matches the current BFS direction. This avoids duplicate entries and makes path reconstruction cleaner.

**Algorithm**

1. **Bidirectional BFS**: Use two sets and always expand the smaller one.

2. **Direction-aware parent tracking**: When adding parents, ensure we're recording the correct relationship based on which direction we're searching.

3. **Path reconstruction**: Use DFS with the parent map to collect all paths.

**Implementation**

```
class Solution {
    public List<List<String>> findLadders(String beginWord, String endWord, List<String> wordList) {
        Set<String> dict = new HashSet<>(wordList);
        if (!dict.contains(endWord)) return new ArrayList<>();
        dict.add(beginWord);

        Set<String> beginSet = new HashSet<>();
        Set<String> endSet = new HashSet<>();
        beginSet.add(beginWord);
        endSet.add(endWord);

        Map<String, List<String>> parents = new HashMap<>();
        boolean forward = true;
        boolean found = false;

        while (!beginSet.isEmpty() && !endSet.isEmpty() && !found) {
            if (beginSet.size() > endSet.size()) {
                Set<String> temp = beginSet;
                beginSet = endSet;
                endSet = temp;
                forward = !forward;
            }

            Set<String> nextSet = new HashSet<>();
            for (String word : beginSet) {
                char[] chars = word.toCharArray();
                for (int i = 0; i < chars.length; i++) {
                    char original = chars[i];
                    for (char c = 'a'; c <= 'z'; c++) {
                        chars[i] = c;
                        String next = new String(chars);
                        if (endSet.contains(next)) {
                            found = true;
                            String child = forward ? next : word;
                            String parent = forward ? word : next;
                            parents.computeIfAbsent(child, k -> new ArrayList<>()).add(parent);
                        } else if (dict.contains(next) && !beginSet.contains(next)) {
                            nextSet.add(next);
                            String child = forward ? next : word;
                            String parent = forward ? word : next;
                            parents.computeIfAbsent(child, k -> new ArrayList<>()).add(parent);
                        }
                    }
                    chars[i] = original;
                }
            }
            beginSet = nextSet;
        }

        List<List<String>> result = new ArrayList<>();
        if (found) {
            dfs(result, new ArrayList<>(), endWord, parents, beginWord);
        }
        return result;
    }

    private void dfs(List<List<String>> result, List<String> path, String word,
                     Map<String, List<String>> parents, String beginWord) {
        path.add(word);
        if (word.equals(beginWord)) {
            List<String> reversed = new ArrayList<>(path);
            Collections.reverse(reversed);
            result.add(reversed);
        } else {
            for (String parent : parents.getOrDefault(word, new ArrayList<>())) {
                dfs(result, path, parent, parents, beginWord);
            }
        }
        path.remove(path.size() - 1);
    }
}
```

**Complexity Analysis**

Let $N$ be the number of words in the dictionary, $L$ be the length of each word, and $A$ be the size of the alphabet (26).

- Time complexity: $O(N \cdot L \cdot A + P)$ where $P$ is the total number of shortest paths.
- Space complexity: $O(N \cdot L + P)$ for storing the dictionary and all paths.

Sponsored by Algolia

Algolia powers search for your apps and websites. Build a great search experience with our suite of APIs and developer tools.

Sponsored by Cloudinary

Cloudinary is the image and video API for websites and apps. Upload, store, manage, manipulate and deliver images and videos at scale.

Sponsored by Scout APM

Scout APM: Application performance monitoring that's actually useful. Try it free for 14 days.

## Comments

Sign in to comment

**Sort By:** Newest Best Most Votes

**Type comment here... (Markdown is supported)**

Preview

**Post**

**Ashish Kumar Singh** 2 years ago

Can someone please explain why this code is giving TLE?

```
class Solution {
    public List<List<String>> findLadders(String beginWord, String endWord, List<String> wordList) {
        List<List<String>> ans = new ArrayList<>();
        Set<String> set = new HashSet<>(wordList);
        if(!set.contains(endWord)) return ans;
        Queue<List<String>> q = new LinkedList<>();
        List<String> start = new ArrayList<>();
        start.add(beginWord);
        q.add(start);
        int level = 0;
        while(!q.isEmpty()){
            List<String> curr = q.poll();
            if(curr.size() > level){
                level = curr.size();
                set.removeAll(curr);
            }
            String last = curr.get(curr.size()-1);
            if(last.equals(endWord)){
                if(ans.size() == 0 || ans.get(0).size() == curr.size()){
                    ans.add(curr);
                }
            }
            for(int i=0;i<last.length();i++){
                for(char ch='a';ch<='z';ch++){
                    char[] arr = last.toCharArray();
                    arr[i] = ch;
                    String word = new String(arr);
                    if(set.contains(word)){
                        List<String> temp = new ArrayList<>(curr);
                        temp.add(word);
                        q.add(temp);
                    }
                }
            }
        }
        return ans;
    }
}
```

Reply