

# Администрирование сетевых подсистем

Базовая защита от атак типа «brute force» (Лабораторная работа №16)

---

Заур Мустафаев

12 декабря 2025

Российский университет дружбы народов, Москва, Россия

## Цели и задачи работы

---

Получение практических навыков настройки и использования Fail2ban для защиты серверных служб от атак типа «brute force».

## Установка и запуск Fail2ban

---

```
Running scriptlet: fail2ban-1.1.0-6.el10_0.noarch 3/3

Installed:
  fail2ban-1.1.0-6.el10_0.noarch          fail2ban-firewalld-1.1.0-6.el10_0.noarch
  fail2ban-selinux-1.1.0-6.el10_0.noarch  fail2ban-sendmail-1.1.0-6.el10_0.noarch
  fail2ban-server-1.1.0-6.el10_0.noarch

Complete!
[root@server.zmustafaev.net zmustafaev]#
[root@server.zmustafaev.net zmustafaev]# systemctl start fail2ban
[root@server.zmustafaev.net zmustafaev]# systemctl enable fail2ban.service
Created symlink '/etc/systemd/system/multi-user.target.wants/fail2ban.service' → '/usr/lib/systemd/system/fail2ban.service'.
[root@server.zmustafaev.net zmustafaev]# █
```

Рис. 1: Установка и запуск Fail2ban

```
[zmustafaev@server.zmustafaev.net ~]$ sudo tail -f /var/log/fail2ban.log
[sudo] password for zmustafaev:
2025-12-12 14:48:07,879 fail2ban.server      [10680]: INFO      -----
-----
2025-12-12 14:48:07,879 fail2ban.server      [10680]: INFO      Starting Fail2ban v1.1.0
2025-12-12 14:48:07,879 fail2ban.observer    [10680]: INFO      Observer start...
2025-12-12 14:48:07,882 fail2ban.database    [10680]: INFO      Connected to fail2ban persistent database
'/var/lib/fail2ban/fail2ban.sqlite3'
2025-12-12 14:48:07,883 fail2ban.database    [10680]: WARNING   New database created. Version '4'
```

Рис. 2: Запуск fail2ban и автозагрузка

## Базовая настройка Fail2ban

---

```
customisation.local  [----] 14 L:[ 1+12 13/ 1  
[DEFAULT]  
bantime = 3600  
  
[sshd]  
port = ssh,2022  
enabled = true  
  
[sshd-ddos]  
filter = sshd  
enabled = true  
  
[selinux-ssh]  
enabled = true
```

# Настройка параметров SSH

```
2025-12-12 14:51:20,893 fail2ban.jail [11344]: INFO Creating new jail 'sshd'
2025-12-12 14:51:20,895 fail2ban.jail [11344]: INFO Jail 'sshd' uses systemd {}
2025-12-12 14:51:20,895 fail2ban.jail [11344]: INFO Initiated 'systemd' backend
2025-12-12 14:51:20,896 fail2ban.filter [11344]: INFO maxLines: 1
2025-12-12 14:51:20,901 fail2ban.filtersystemd [11344]: INFO [sshd] Added journal match for: '_SYSTEMD_
UNIT=sshd.service + _COMM=sshd + _COMM=sshd-session'
2025-12-12 14:51:20,901 fail2ban.filter [11344]: INFO maxRetry: 5
2025-12-12 14:51:20,901 fail2ban.filter [11344]: INFO findtime: 600
2025-12-12 14:51:20,901 fail2ban.actions [11344]: INFO banTime: 3600
2025-12-12 14:51:20,901 fail2ban.filter [11344]: INFO encoding: UTF-8
2025-12-12 14:51:20,901 fail2ban.jail [11344]: INFO Creating new jail 'selinux-ssh'
2025-12-12 14:51:20,903 fail2ban.jail [11344]: INFO Jail 'selinux-ssh' uses pyinotify {}
2025-12-12 14:51:20,904 fail2ban.jail [11344]: INFO Initiated 'pyinotify' backend
2025-12-12 14:51:20,905 fail2ban.datedetector [11344]: INFO date pattern '': 'Epoch'
2025-12-12 14:51:20,905 fail2ban.filter [11344]: INFO maxRetry: 5
2025-12-12 14:51:20,905 fail2ban.filter [11344]: INFO findtime: 600
2025-12-12 14:51:20,905 fail2ban.actions [11344]: INFO banTime: 3600
2025-12-12 14:51:20,905 fail2ban.filter [11344]: INFO encoding: UTF-8
2025-12-12 14:51:20,905 fail2ban.filter [11344]: INFO Added logfile: '/var/log/audit/audit.log'
(pos = 0, hash = 2bac1d1460b4ddb65dad9af08e925a24fbelecb)
2025-12-12 14:51:20,906 fail2ban.jail [11344]: INFO Creating new jail 'sshd-ddos'
2025-12-12 14:51:20,906 fail2ban.jail [11344]: INFO Jail 'sshd-ddos' uses pyinotify {}
2025-12-12 14:51:20,906 fail2ban.jail [11344]: INFO Initiated 'pyinotify' backend
2025-12-12 14:51:20,907 fail2ban.filter [11344]: INFO maxLines: 1
2025-12-12 14:51:20,907 fail2ban.filter [11344]: INFO maxRetry: 5
2025-12-12 14:51:20,907 fail2ban.filter [11344]: INFO findtime: 600
2025-12-12 14:51:20,907 fail2ban.actions [11344]: INFO banTime: 3600
2025-12-12 14:51:20,907 fail2ban.filter [11344]: INFO encoding: UTF-8
2025-12-12 14:51:20,907 fail2ban.jail [11344]: INFO Jail 'sshd' started
2025-12-12 14:51:20,908 fail2ban.jail [11344]: INFO Jail 'selinux-ssh' started
2025-12-12 14:51:20,909 fail2ban.jail [11344]: INFO Jail 'sshd-ddos' started
2025-12-12 14:51:20,911 fail2ban.filtersystemd [11344]: INFO [sshd] Jail is in operation now (process n
ew journal entries)
```

Рис. 4: Настройка SSH-защиты

customisation.local [----] 14 L:[ 11+29 40/ 40] \*(4

[selinux-ssh]  
enabled = true

[apache-auth]  
enabled = true

[apache-badbots]  
enabled = true

[apache-noscript]  
enabled = true

[apache-overflows]  
enabled = true

[apache-nohome]  
enabled = true

[apache-botsearch]  
enabled = true

[apache-fakegooglebot]  
enabled = true

[apache-modsecurity]  
enabled = true

[apache-shellshock]  
enabled = true

## Включение HTTP-защиты

```
(pos = 0, hash = 66eb785d2d04563df04eacb022af427599573363)
2025-12-12 14:56:21,903 fail2ban.filter [12058]: INFO Added logfile: '/var/log/httpd/ssl_error_log'
og' (pos = 0, hash = 207f373360c71fa65be6d05e5267fcfa3aaa4d8b)
2025-12-12 14:56:21,903 fail2ban.filter [12058]: INFO Added logfile: '/var/log/httpd/www.zmustaf
aev.net-error_log' (pos = 0, hash = ed421f0035abcca6a40a8dd472467db53dc7f581)
2025-12-12 14:56:21,903 fail2ban.jail [12058]: INFO Creating new jail 'apache-shellshock'
2025-12-12 14:56:21,903 fail2ban.jail [12058]: INFO Jail 'apache-shellshock' uses pyinotify {}
2025-12-12 14:56:21,904 fail2ban.jail [12058]: INFO Initiated 'pyinotify' backend
2025-12-12 14:56:21,905 fail2ban.filter [12058]: INFO maxRetry: 1
2025-12-12 14:56:21,905 fail2ban.filter [12058]: INFO findtime: 600
2025-12-12 14:56:21,905 fail2ban.actions [12058]: INFO banTime: 3600
2025-12-12 14:56:21,905 fail2ban.filter [12058]: INFO encoding: UTF-8
2025-12-12 14:56:21,905 fail2ban.filter [12058]: INFO Added logfile: '/var/log/httpd/server.zmus
tafaev.net-error_log' (pos = 0, hash = )
2025-12-12 14:56:21,905 fail2ban.filter [12058]: INFO Added logfile: '/var/log/httpd/error_log'
(pos = 0, hash = 66eb785d2d04563df04eacb022af427599573363)
2025-12-12 14:56:21,905 fail2ban.filter [12058]: INFO Added logfile: '/var/log/httpd/ssl_error_log'
og' (pos = 0, hash = 207f373360c71fa65be6d05e5267fcfa3aaa4d8b)
2025-12-12 14:56:21,906 fail2ban.filter [12058]: INFO Added logfile: '/var/log/httpd/www.zmustaf
aev.net-error_log' (pos = 0, hash = ed421f0035abcca6a40a8dd472467db53dc7f581)
2025-12-12 14:56:21,906 fail2ban.jail [12058]: INFO Creating new jail 'sshd-ddos'
2025-12-12 14:56:21,906 fail2ban.jail [12058]: INFO Jail 'sshd-ddos' uses pyinotify {}
2025-12-12 14:56:21,907 fail2ban.jail [12058]: INFO Initiated 'pyinotify' backend
2025-12-12 14:56:21,907 fail2ban.filter [12058]: INFO maxLines: 1
2025-12-12 14:56:21,908 fail2ban.filter [12058]: INFO maxRetry: 5
2025-12-12 14:56:21,908 fail2ban.filter [12058]: INFO findtime: 600
2025-12-12 14:56:21,908 fail2ban.actions [12058]: INFO banTime: 3600
2025-12-12 14:56:21,908 fail2ban.filter [12058]: INFO encoding: UTF-8
2025-12-12 14:56:21,908 fail2ban.jail [12058]: INFO Jail 'sshd' started
2025-12-12 14:56:21,908 fail2ban.filtersystemd [12058]: INFO [sshd] Jail is in operation now (process n
ew journal entries)
2025-12-12 14:56:21,910 fail2ban.jail [12058]: INFO Jail 'selinux-ssh' started
2025-12-12 14:56:21,910 fail2ban.jail [12058]: INFO Jail 'apache-auth' started
```

Рис. 6: HTTP-защита Apache

```
enabled = true
```

```
[postfix]
```

```
enabled = true
```

```
[postfix-rbl]
```

```
enabled = true
```

```
[dovecot]
```

```
enabled = true
```

```
[postfix-sasl]
```

```
enabled = true
```

1 Help

2 Save

3 Mark

4 Replac

## Проверка работы Fail2ban

---

```
[root@server.zmustafaev.net zmustafaev]#  
[root@server.zmustafaev.net zmustafaev]# fail2ban-client status  
Status  
|- Number of jail:      16  
  '- Jail list:  apache-auth, apache-badbots, apache-botsearch, apache-fakegooglebot, apache-modsecurity, ap  
    ache-nohome, apache-noscript, apache-overflows, apache-shellshock, dovecot, postfix, postfix-rbl, postfix-s  
    asl, selinux-ssh, sshd, sshd-ddos  
[root@server.zmustafaev.net zmustafaev]# fail2ban-client status sshd  
Status for the jail: sshd  
|- Filter  
|  |- Currently failed: 0  
|  |- Total failed:     0  
|  '- Journal matches:  _SYSTEMD_UNIT=sshd.service + _COMM=sshd + _COMM=sshd-session  
'- Actions  
  |- Currently banned: 0  
  |- Total banned:     0  
  '- Banned IP list:  
[root@server.zmustafaev.net zmustafaev]# fail2ban-client set sshd maxretry 2  
2  
[root@server.zmustafaev.net zmustafaev]#
```

Рис. 9: Статус jail sshd

```
2025-12-12 14:58:14,618 fail2ban.jail [12362]: INFO Jail 'postfix-sasl' started
2025-12-12 14:58:14,618 fail2ban.jail [12362]: INFO Jail 'sshd-ddos' started
2025-12-12 15:00:35,943 fail2ban.filter [12362]: INFO maxRetry: 2
2025-12-12 15:01:55,175 fail2ban.filter [12362]: INFO [sshd] Found 192.168.1.30 - 2025-12-12 15:
01:54
2025-12-12 15:01:58,660 fail2ban.filter [12362]: INFO [sshd] Found 192.168.1.30 - 2025-12-12 15:
01:58
2025-12-12 15:01:58,746 fail2ban.actions [12362]: NOTICE [sshd] Ban 192.168.1.30
2025-12-12 15:02:02,375 fail2ban.filter [12362]: INFO [sshd] Found 192.168.1.30 - 2025-12-12 15:
02:02
```

Рис. 10: Блокировка IP-адреса

## Разблокировка IP-адреса

```
[root@server.zmustafaev.net zmustafaev]#  
[root@server.zmustafaev.net zmustafaev]# fail2ban-client status sshd  
Status for the jail: sshd  
|- Filter  
| |- Currently failed: 1  
| |- Total failed: 3  
| `-- Journal matches: _SYSTEMD_UNIT=sshd.service + _COMM=sshd + _COMM=sshd-session  
`-- Actions  
    |- Currently banned: 1  
    |- Total banned: 1  
    `-- Banned IP list: 192.168.1.30  
[root@server.zmustafaev.net zmustafaev]# fail2ban-client set sshd unbanip 192.168.1.30  
1  
[root@server.zmustafaev.net zmustafaev]# fail2ban-client status sshd  
Status for the jail: sshd  
|- Filter  
| |- Currently failed: 1  
| |- Total failed: 3  
| `-- Journal matches: _SYSTEMD_UNIT=sshd.service + _COMM=sshd + _COMM=sshd-session  
`-- Actions  
    |- Currently banned: 0  
    |- Total banned: 1  
    `-- Banned IP list:  
[root@server.zmustafaev.net zmustafaev]#
```

Рис. 11: Разблокировка IP-адреса

## Игнорирование доверенного IP

zmustafaev@server:/home/zmustafaev – mcedit /etc/fail2ban

```
customisation.local [----] 35 L:[ 1+ 3 4/ 54] *(61
[DEFAULT]
bantime = 3600

ignoreip = 127.0.0.1/8 192.168.1.30

[sshd]
port = ssh,2022
enabled = true

[sshd-ddos]
filter = sshd
enabled = true

[selinux-ssh]
enabled = true

[apache-auth]
enabled = true

[apache-badbots]
enabled = true
```

## Выводы по проделанной работе

---

В ходе лабораторной работы была настроена система защиты сервера с использованием Fail2ban. Реализована защита SSH, веб-служб и почтовых сервисов, выполнена проверка механизмов блокировки и разблокировки IP-адресов, а также подготовлена автоматизация конфигурации для повторного развёртывания.