

Word 2010 DepositMO plugin - API reference and source guide

0.1.20

Generated by Doxygen 1.7.1

Tue Nov 29 2011 16:57:43

Contents

1	Namespace Index	1
1.1	Package List	1
2	Class Index	3
2.1	Class List	3
3	Namespace Documentation	5
3.1	Package uk	5
3.2	Package uk.ac	5
3.3	Package uk.ac.soton	5
3.4	Package uk.ac.soton.ses	5
3.5	Package uk.ac.soton.ses.Word2010DepositMOAddIn	6
3.5.1	Detailed Description	7
3.6	Package uk.ac.soton.ses.Word2010DepositMOAddIn.Properties	7
4	Class Documentation	9
4.1	uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox Class Reference	9
4.1.1	Detailed Description	10
4.1.2	Constructor & Destructor Documentation	10
4.1.2.1	AboutBox	10
4.1.3	Member Function Documentation	10
4.1.3.1	Dispose	10
4.1.3.2	InitializeComponent	11
4.1.3.3	okButton_Click	14
4.1.4	Member Data Documentation	14
4.1.4.1	components	14
4.1.4.2	labelCompanyName	14
4.1.4.3	labelCopyright	14
4.1.4.4	labelProductName	14

4.1.4.5	labelVersion	14
4.1.4.6	logoPictureBox	15
4.1.4.7	okButton	15
4.1.4.8	tableLayoutPanel	15
4.1.4.9	textBoxDescription	15
4.1.5	Property Documentation	15
4.1.5.1	AssemblyCompany	15
4.1.5.2	AssemblyCopyright	15
4.1.5.3	AssemblyDescription	16
4.1.5.4	AssemblyProduct	16
4.1.5.5	AssemblyTitle	16
4.1.5.6	AssemblyVersion	16
4.2	uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositaryControl Class Reference	16
4.2.1	Detailed Description	19
4.2.2	Constructor & Destructor Documentation	19
4.2.2.1	DepositMORepositaryControl	19
4.2.3	Member Function Documentation	19
4.2.3.1	_SubmitDocument	19
4.2.3.2	addRepository	23
4.2.3.3	addToGroupButton_Click	23
4.2.3.4	DepositMORepositaryControl_Load	24
4.2.3.5	Dispose	24
4.2.3.6	DumpListingToLog	25
4.2.3.7	DumpListingToLog	25
4.2.3.8	InitializeComponent	26
4.2.3.9	logException	31
4.2.3.10	logMessage	31
4.2.3.11	removeFromGroupButton_Click	32
4.2.3.12	SubmitDocument	32
4.2.3.13	SubmitDocument	33
4.2.3.14	submitToAll	34
4.2.3.15	submitToAllButton_Click	34
4.2.3.16	submitToThisRepositoryButton_Click	34
4.2.3.17	updateEprintButton_Click	35
4.2.3.18	WarningBox	35
4.2.4	Member Data Documentation	36

4.2.4.1	addToGroupButton	36
4.2.4.2	components	36
4.2.4.3	documentLocationLabel	36
4.2.4.4	documentLocationTextBox	36
4.2.4.5	groupRepositoryGroupBox	36
4.2.4.6	lockobj	37
4.2.4.7	messagesGroupBox	37
4.2.4.8	passwordLabel	37
4.2.4.9	passwordTextBox	37
4.2.4.10	removeFromGroupButton	37
4.2.4.11	repositoryCollectionTabControl	37
4.2.4.12	repositoryControlGroupBox	38
4.2.4.13	repositoryLocationLabel	38
4.2.4.14	repositoryLocationTextBox	38
4.2.4.15	submissionLogTextBox	38
4.2.4.16	submitToAllButton	38
4.2.4.17	submitToThisRepositoryButton	38
4.2.4.18	updateEprintButton	39
4.2.4.19	usernameLabel	39
4.2.4.20	usernameTextBox	39
4.2.5	Property Documentation	39
4.2.5.1	endpoint	39
4.2.5.2	password	39
4.2.5.3	username	39
4.3	uk.ac.soton.ses.Word2010DepositMOAddIn.Globals Class Reference	40
4.3.1	Detailed Description	40
4.3.2	Constructor & Destructor Documentation	40
4.3.2.1	Globals	40
4.3.3	Member Data Documentation	40
4.3.3.1	_factory	41
4.3.3.2	_ThisRibbonCollection	41
4.3.3.3	_Word2010DepositMOAddIn	41
4.3.4	Property Documentation	41
4.3.4.1	Factory	41
4.3.4.2	Ribbons	41
4.3.4.3	Word2010DepositMOAddIn	41

4.4	uk.ac.soton.ses.HtmlScraper Class Reference	42
4.4.1	Detailed Description	42
4.4.2	Member Function Documentation	42
4.4.2.1	GetAttributeContent	42
4.4.2.2	GetAttributeContent	43
4.4.2.3	GetMetaContent	46
4.4.2.4	GetMetaContent	46
4.5	uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm Class Reference	47
4.5.1	Detailed Description	48
4.5.2	Constructor & Destructor Documentation	48
4.5.2.1	LogViewerForm	48
4.5.3	Member Function Documentation	48
4.5.3.1	closeButton_Click	48
4.5.3.2	copyButton_Click	49
4.5.3.3	Dispose	49
4.5.3.4	InitializeComponent	49
4.5.4	Member Data Documentation	50
4.5.4.1	closeButton	51
4.5.4.2	components	51
4.5.4.3	copyButton	51
4.5.4.4	logTextBox	51
4.6	uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm Class Reference	51
4.6.1	Detailed Description	52
4.6.2	Constructor & Destructor Documentation	52
4.6.2.1	QuickSubmitForm	52
4.6.3	Member Function Documentation	53
4.6.3.1	cancelButton_Click	53
4.6.3.2	Dispose	53
4.6.3.3	InitializeComponent	54
4.6.3.4	submitButton_Click	56
4.6.4	Member Data Documentation	57
4.6.4.1	cancelButton	57
4.6.4.2	components	57
4.6.4.3	passwordLabel	57
4.6.4.4	passwordTextBox	57
4.6.4.5	repositoryLocationLabel	57

4.6.4.6	repositoryLocationTextBox	58
4.6.4.7	submitButton	58
4.6.4.8	usernameLabel	58
4.6.4.9	usernameTextBox	58
4.7	uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl Class Reference	58
4.7.1	Detailed Description	59
4.7.2	Constructor & Destructor Documentation	60
4.7.2.1	RepositoryGroupUserControl	60
4.7.3	Member Function Documentation	60
4.7.3.1	Dispose	60
4.7.3.2	InitializeComponent	60
4.7.4	Member Data Documentation	62
4.7.4.1	components	62
4.7.4.2	identLabel	62
4.7.4.3	passwordLabel	63
4.7.4.4	passwordTextBox	63
4.7.4.5	repositoryLocationLabel	63
4.7.4.6	repositoryLocationTextBox	63
4.7.4.7	usernameLabel	63
4.7.4.8	usernameTextBox	63
4.7.5	Property Documentation	63
4.7.5.1	endpoint	64
4.7.5.2	id	64
4.7.5.3	password	64
4.7.5.4	username	64
4.8	uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources Class Reference	65
4.8.1	Detailed Description	65
4.8.2	Constructor & Destructor Documentation	65
4.8.2.1	Resources	65
4.8.3	Member Data Documentation	65
4.8.3.1	resourceCulture	66
4.8.3.2	resourceMan	66
4.8.4	Property Documentation	66
4.8.4.1	Culture	66
4.8.4.2	DocumentImage	66
4.8.4.3	ResourceManager	66

4.9	uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Settings Class Reference	67
4.9.1	Detailed Description	67
4.9.2	Member Data Documentation	67
4.9.2.1	defaultInstance	67
4.9.3	Property Documentation	67
4.9.3.1	Default	67
4.10	uk.ac.soton.ses.SwordAtomReader Class Reference	67
4.10.1	Detailed Description	69
4.10.2	Constructor & Destructor Documentation	69
4.10.2.1	SwordAtomReader	69
4.10.3	Member Function Documentation	70
4.10.3.1	GetMultipleNodes	70
4.10.3.2	GetSingleNode	70
4.10.3.3	GetXPathText	70
4.10.3.4	GetXPathTextArray	71
4.10.3.5	GetXPathValue	71
4.10.4	Member Data Documentation	71
4.10.4.1	atomXml	71
4.10.4.2	xnm	72
4.10.5	Property Documentation	72
4.10.5.1	AtomContentSrc	72
4.10.5.2	AtomContentType	72
4.10.5.3	AtomGenerator	72
4.10.5.4	AtomGeneratorUri	72
4.10.5.5	AtomGeneratorVersion	72
4.10.5.6	AtomId	72
4.10.5.7	AtomPublished	73
4.10.5.8	AtomSummary	73
4.10.5.9	AtomTitle	73
4.10.5.10	AtomUpdated	73
4.10.5.11	AtomXml	73
4.10.5.12	ContentsHref	73
4.10.5.13	EditHref	74
4.10.5.14	EditMediaHref	74
4.10.5.15	SwordNoop	74
4.10.5.16	SwordPackaging	74

4.10.5.17	SwordTreatment	74
4.11	uk.ac.soton.ses.SwordClientHandler Class Reference	74
4.11.1	Detailed Description	78
4.11.2	Constructor & Destructor Documentation	78
4.11.2.1	SwordClientHandler	78
4.11.2.2	SwordClientHandler	78
4.11.3	Member Function Documentation	79
4.11.3.1	CreateContainer	79
4.11.3.2	CreateContainer	79
4.11.3.3	Delete	80
4.11.3.4	DepositDocxToContents	80
4.11.3.5	DepositEprintsXml	81
4.11.3.6	DepositEprintsXml	82
4.11.3.7	DepositXml	82
4.11.3.8	DepositXml	83
4.11.3.9	DepositZipToEprint	83
4.11.3.10	DepositZipToEprint	84
4.11.3.11	GetBasicAuthAtomWebRequest	84
4.11.3.12	GetBasicAuthAtomWebRequest	85
4.11.3.13	GetEprintInfo	85
4.11.3.14	GetResponseLocation	86
4.11.3.15	GetXmlResponse	86
4.11.3.16	ListRecords	87
4.11.3.17	ListRecords	88
4.11.3.18	PostDocxToContainer	89
4.11.3.19	PostDocxToContainer	90
4.11.3.20	PostDocxToContainer	90
4.11.3.21	PostDocxToRepository	91
4.11.3.22	PostDocxToRepository	91
4.11.3.23	PutToDocument	92
4.11.3.24	PutToDocument	93
4.11.3.25	ResolveInbox	94
4.11.3.26	WriteFileToRequest	94
4.11.4	Member Data Documentation	95
4.11.4.1	_endpoint	95
4.11.4.2	_password	95

4.11.4.3	_resolveInbox	95
4.11.4.4	_username	95
4.11.4.5	BUFFER_SIZE	96
4.11.4.6	DOCX_CONTENTTYPE	96
4.11.4.7	EP2_PACKAGING	96
4.11.4.8	EXTRACT_MEDIA	96
4.11.4.9	LIST_RECORD_PATH	96
4.11.5	Property Documentation	96
4.11.5.1	Endpoint	97
4.11.5.2	Password	97
4.11.5.3	Username	97
4.12	uk.ac.soton.ses.SwordClientHandlerTests Class Reference	97
4.12.1	Detailed Description	98
4.12.2	Constructor & Destructor Documentation	98
4.12.2.1	SwordClientHandlerTests	98
4.12.3	Member Function Documentation	98
4.12.3.1	Run	98
4.12.3.2	TestAtomReader	100
4.12.3.3	TestCreateContainer	100
4.12.3.4	TestDelete	101
4.12.3.5	TestDepositEprintsXml	101
4.12.3.6	TestDepositZipToEprint	101
4.12.3.7	TestGetInfo	102
4.12.3.8	TestList	102
4.12.3.9	TestPutOnly	103
4.12.3.10	TestPutToDocument	103
4.12.3.11	TestResolveInbox	104
4.12.4	Member Data Documentation	104
4.12.4.1	consoleWriter	104
4.12.4.2	EPRINT_TO_DELETE	104
4.12.4.3	response	104
4.12.4.4	sword2Endpoint	104
4.12.4.5	sword2Password	105
4.12.4.6	sword2User	105
4.12.4.7	xws	105
4.13	uk.ac.soton.ses.SwordListAuthor Class Reference	105

4.13.1 Detailed Description	106
4.13.2 Constructor & Destructor Documentation	106
4.13.2.1 SwordListAuthor	106
4.13.3 Member Data Documentation	106
4.13.3.1 name	106
4.13.4 Property Documentation	106
4.13.4.1 Name	106
4.14 uk.ac.soton.ses.SwordListEntry Class Reference	107
4.14.1 Detailed Description	107
4.14.2 Constructor & Destructor Documentation	108
4.14.2.1 SwordListEntry	108
4.14.3 Member Function Documentation	108
4.14.3.1 AddAuthor	108
4.14.4 Member Data Documentation	108
4.14.4.1 authors	108
4.14.4.2 href	109
4.14.4.3 id	109
4.14.4.4 summary	109
4.14.4.5 title	109
4.14.4.6 updated	109
4.14.5 Property Documentation	109
4.14.5.1 Authors	109
4.14.5.2 Href	109
4.14.5.3 Id	109
4.14.5.4 Summary	110
4.14.5.5 Title	110
4.14.5.6 Updated	110
4.15 uk.ac.soton.ses.SwordListReader Class Reference	110
4.15.1 Detailed Description	111
4.15.2 Constructor & Destructor Documentation	111
4.15.2.1 SwordListReader	111
4.15.3 Member Function Documentation	112
4.15.3.1 GetEntryById	112
4.15.3.2 ParseEntries	112
4.15.4 Member Data Documentation	113
4.15.4.1 entries	113

4.15.4.2	swordListXml	113
4.15.4.3	title	113
4.15.4.4	updated	113
4.15.4.5	xnm	113
4.15.5	Property Documentation	114
4.15.5.1	Entries	114
4.16	uk.ac.soton.ses.Word2010DepositMOAddIn.ThisRibbonCollection Class Reference	114
4.16.1	Detailed Description	114
4.16.2	Constructor & Destructor Documentation	114
4.16.2.1	ThisRibbonCollection	114
4.16.3	Property Documentation	115
4.16.3.1	Word2010DepositMORibbon	115
4.17	uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn Class Reference	115
4.17.1	Detailed Description	118
4.17.2	Constructor & Destructor Documentation	118
4.17.2.1	Word2010DepositMOAddIn	118
4.17.3	Member Function Documentation	118
4.17.3.1	AddMessageToLogStack	118
4.17.3.2	AddRepositoryControl	119
4.17.3.3	Application_DocumentOpen	120
4.17.3.4	BeginInitialization	120
4.17.3.5	BindToData	120
4.17.3.6	DecrementSubmissionThreadCount	120
4.17.3.7	EndInitialization	121
4.17.3.8	FinishInitialization	121
4.17.3.9	GetActiveDocumentProperties	121
4.17.3.10	GetActiveSubmissionString	122
4.17.3.11	GetAllLogMessages	122
4.17.3.12	IncrementSubmissionThreadCount	122
4.17.3.13	Initialize	123
4.17.3.14	InitializeCachedData	123
4.17.3.15	InitializeComponents	123
4.17.3.16	InitializeControls	123
4.17.3.17	InitializeData	124
4.17.3.18	InitializeDataBindings	124
4.17.3.19	InternalStartup	124

4.17.3.20	IsCached	125
4.17.3.21	LogMessage	125
4.17.3.22	LogMessage	125
4.17.3.23	MakeAllInvisible	126
4.17.3.24	MakeAllVisible	126
4.17.3.25	NeedsFill	127
4.17.3.26	OnShutdown	127
4.17.3.27	SetSingleLineTextBox	127
4.17.3.28	SetTextCallback	128
4.17.3.29	StartCaching	128
4.17.3.30	StopCaching	129
4.17.3.31	ThisAddIn_Shutdown	129
4.17.3.32	ThisAddIn_Startup	129
4.17.4	Member Data Documentation	130
4.17.4.1	Application	130
4.17.4.2	CustomTaskPanels	130
4.17.4.3	defaultEndpoint	130
4.17.4.4	defaultPassword	130
4.17.4.5	defaultUsername	131
4.17.4.6	lockobj	131
4.17.4.7	log	131
4.17.4.8	MAX_LOG_LINES	131
4.17.4.9	missing	131
4.17.4.10	PURGE_NUMBER_OF_LOG_LINES	131
4.17.4.11	repositoryControls	132
4.17.4.12	submissionThreadCounter	132
4.17.4.13	VstoSmartTags	132
4.17.5	Property Documentation	132
4.17.5.1	DefaultEndpoint	132
4.17.5.2	DefaultPassword	133
4.17.5.3	DefaultUsername	133
4.17.5.4	SubmissionThreadCount	133
4.18	uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon Class	
	Reference	133
4.18.1	Detailed Description	135
4.18.2	Constructor & Destructor Documentation	135
4.18.2.1	Word2010DepositMORibbon	135

4.18.3	Member Function Documentation	135
4.18.3.1	aboutRibbonButton_Click	135
4.18.3.2	Dispose	136
4.18.3.3	InitializeComponent	136
4.18.3.4	quickSubmissionRibbonGroup_DialogLauncherClick	139
4.18.3.5	quickSubmitButton_Click	139
4.18.3.6	Word2010DepositMOMainGroup_DialogLauncherClick	139
4.18.3.7	Word2010DepositMOREpositoryButton_Click	140
4.18.3.8	Word2010DepositMOREpositoryHideButton_Click	140
4.18.3.9	Word2010DepositMORibbon_Load	141
4.18.4	Member Data Documentation	141
4.18.4.1	aboutRibbonButton	141
4.18.4.2	aboutRibbonGroup	141
4.18.4.3	components	141
4.18.4.4	endpointEditBox	142
4.18.4.5	quickPassword	142
4.18.4.6	quickSubmissionRibbonGroup	142
4.18.4.7	quickSubmitButton	142
4.18.4.8	quickUsername	142
4.18.4.9	tab1	142
4.18.4.10	Word2010DepositMOMainGroup	143
4.18.4.11	Word2010DepositMOREpositoryButton	143
4.18.4.12	Word2010DepositMOREpositoryHideButton	143
4.18.4.13	Word2010DepositMORibbonTab	143

Chapter 1

Namespace Index

1.1 Package List

Here are the packages with brief descriptions (if available):

uk	5
uk.ac	5
uk.ac.soton	5
uk.ac.soton.ses	5
uk.ac.soton.ses.Word2010DepositMOAddIn (Namespace for Microsoft Word 2010 De- positMO add-in)	6
uk.ac.soton.ses.Word2010DepositMOAddIn.Properties	7

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox (About Box for Word 2010 DepositMO add-in)	9
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl (Custom Windows Forms user control for Microsoft Word 2010 DepositMO add-in) . . .	16
uk.ac.soton.ses.Word2010DepositMOAddIn.Globals	40
uk.ac.soton.ses.HtmlScraper (Limited basic HTML parsing routines)	42
uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm (Internal log viewer for Microsoft Word 2010 DepositMO add-in)	47
uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm (Quick submission form for the Microsoft Word 2010 DepositMO add-in)	51
uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl (Custom Windows Forms user control for repository groups in Microsoft Word 2010 DepositMO add-in)	58
uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources (A strongly-typed resource class, for looking up localized strings, etc)	65
uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Settings	67
uk.ac.soton.ses.SwordAtomReader (SWORD 2 Atom XML reader)	67
uk.ac.soton.ses.SwordClientHandler (SWORD 2 client implementation for .NET)	74
uk.ac.soton.ses.SwordClientHandlerTests (A series of basic tests for the .NET API) . . .	97
uk.ac.soton.ses.SwordListAuthor (SWORD author)	105
uk.ac.soton.ses.SwordListEntry (SWORD entry for the collection list)	107
uk.ac.soton.ses.SwordListReader (SWORD list reader)	110
uk.ac.soton.ses.Word2010DepositMOAddIn.ThisRibbonCollection	114
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn (Entry point for the Microsoft Word 2010 DepositMO add-in)	115
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon (Ribbon interface for Microsoft Word 2010 DepositMO add-in)	133

Chapter 3

Namespace Documentation

3.1 Package uk

Packages

- package [ac](#)

3.2 Package uk.ac

Packages

- package [soton](#)

3.3 Package uk.ac.soton

Packages

- package [ses](#)

3.4 Package uk.ac.soton.ses

Packages

- package [Word2010DepositMOAddIn](#)
Namespace for Microsoft Word 2010 DepositMO add-in.

Classes

- class [HtmlScraper](#)
Limited basic HTML parsing routines.

- class [SwordAtomReader](#)
SWORD 2 Atom XML reader.
- class [SwordClientHandler](#)
SWORD 2 client implementation for .NET.
- class [SwordClientHandlerTests](#)
A series of basic tests for the .NET API.
- class [SwordListAuthor](#)
SWORD author.
- class [SwordListEntry](#)
SWORD entry for the collection list.
- class [SwordListReader](#)
SWORD list reader.

3.5 Package [uk.ac.soton.ses.Word2010DepositMOAddIn](#)

Namespace for Microsoft Word 2010 DepositMO add-in.

Packages

- package [Properties](#)

Classes

- class [AboutBox](#)
About Box for Word 2010 DepositMO add-in.
- class [DepositMOREpositoryControl](#)
Custom Windows Forms user control for Microsoft Word 2010 DepositMO add-in.
- class [LogViewerForm](#)
Internal log viewer for Microsoft Word 2010 DepositMO add-in.
- class [QuickSubmitForm](#)
Quick submission form for the Microsoft Word 2010 DepositMO add-in.
- class [RepositoryGroupUserControl](#)
Custom Windows Forms user control for repository groups in Microsoft Word 2010 DepositMO add-in.
- class [Word2010DepositMOAddIn](#)
Entry point for the Microsoft Word 2010 DepositMO add-in.

- class [Globals](#)
- class [ThisRibbonCollection](#)
- class [Word2010DepositMORibbon](#)

Ribbon interface for Microsoft Word 2010 DepositMO add-in.

3.5.1 Detailed Description

Namespace for Microsoft Word 2010 DepositMO add-in.

3.6 Package uk.ac.soton.ses.Word2010DepositMOAddIn.Properties

Classes

- class [Resources](#)
A strongly-typed resource class, for looking up localized strings, etc.
- class [Settings](#)

Chapter 4

Class Documentation

4.1 uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox Class Reference

About Box for Word 2010 DepositMO add-in.

Public Member Functions

- [AboutBox](#) ()

Protected Member Functions

- override void [Dispose](#) (bool disposing)
Clean up any resources being used.

Properties

- string [AssemblyTitle](#) [get]
- string [AssemblyVersion](#) [get]
- string [AssemblyDescription](#) [get]
- string [AssemblyProduct](#) [get]
- string [AssemblyCopyright](#) [get]
- string [AssemblyCompany](#) [get]

Private Member Functions

- void [okButton_Click](#) (object sender, EventArgs e)
- void [InitializeComponent](#) ()

Required method for Designer support - do not modify the contents of this method with the code editor.

Private Attributes

- System.ComponentModel.IContainer [components](#) = null
Required designer variable.
- System.Windows.Forms.TableLayoutPanel [tableLayoutPanel](#)
- System.Windows.Forms.PictureBox [logoPictureBox](#)
- System.Windows.Forms.Label [labelProductName](#)
- System.Windows.Forms.Label [labelVersion](#)
- System.Windows.Forms.Label [labelCopyright](#)
- System.Windows.Forms.Label [labelCompanyName](#)
- System.Windows.Forms.TextBox [textBoxDescription](#)
- System.Windows.Forms.Button [okButton](#)

4.1.1 Detailed Description

About Box for Word 2010 DepositMO add-in.

Definition at line 30 of file AboutBox.cs.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 `uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AboutBox ()`

Definition at line 32 of file AboutBox.cs.

```
{
    InitializeComponent();
    this.Text = String.Format("About {0}", AssemblyTitle);
    this.labelProductName.Text = AssemblyProduct;
    this.labelVersion.Text = String.Format("Version {0}",
AssemblyVersion);
    this.labelCopyright.Text = AssemblyCopyright;
    this.labelCompanyName.Text = AssemblyCompany;
    this.textBoxDescription.Text = AssemblyDescription;
}
```

4.1.3 Member Function Documentation

4.1.3.1 `override void uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.Dispose (bool disposing) [protected]`

Clean up any resources being used.

Definition at line 29 of file AboutBox.Designer.cs.

```
{
    if (disposing && (components != null))
    {
        components.Dispose();
    }
    base.Dispose(disposing);
}
```


4.1.3.2 void uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.InitializeComponent () [private]

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 44 of file AboutBox.Designer.cs.

```
{
    System.ComponentModel.ComponentResourceManager resources = new System
.ComponentModel.ComponentResourceManager(typeof(AboutBox));
    this.tableLayoutPanel = new System.Windows.Forms.TableLayoutPanel();
    this.logoPictureBox = new System.Windows.Forms.PictureBox();
    this.labelProductName = new System.Windows.Forms.Label();
    this.labelVersion = new System.Windows.Forms.Label();
    this.labelCopyright = new System.Windows.Forms.Label();
    this.labelCompanyName = new System.Windows.Forms.Label();
    this.textBoxDescription = new System.Windows.Forms.TextBox();
    this.okButton = new System.Windows.Forms.Button();
    this.tableLayoutPanel.SuspendLayout();
    ((System.ComponentModel.ISupportInitialize)(this.logoPictureBox)).BeginInit();
    this.SuspendLayout();
    //
    // tableLayoutPanel
    //
    this.tableLayoutPanel.ColumnCount = 2;
    this.tableLayoutPanel.ColumnStyles.Add(new System.Windows.Forms.Column
nStyle(System.Windows.Forms.SizeType.Percent, 33F));
    this.tableLayoutPanel.ColumnStyles.Add(new System.Windows.Forms.Column
nStyle(System.Windows.Forms.SizeType.Percent, 67F));
    this.tableLayoutPanel.Controls.Add(this.logoPictureBox, 0, 0);
    this.tableLayoutPanel.Controls.Add(this.labelProductName, 1, 0);
    this.tableLayoutPanel.Controls.Add(this.labelVersion, 1, 1);
    this.tableLayoutPanel.Controls.Add(this.labelCopyright, 1, 2);
    this.tableLayoutPanel.Controls.Add(this.labelCompanyName, 1, 3);
    this.tableLayoutPanel.Controls.Add(this.textBoxDescription, 1, 4);
    this.tableLayoutPanel.Controls.Add(this.okButton, 1, 5);
    this.tableLayoutPanel.Dock = System.Windows.Forms.DockStyle.Fill;
    this.tableLayoutPanel.Location = new System.Drawing.Point(9, 9);
    this.tableLayoutPanel.Name = "tableLayoutPanel";
    this.tableLayoutPanel.RowCount = 6;
    this.tableLayoutPanel.RowStyles.Add(new System.Windows.Forms.RowStyle
(System.Windows.Forms.SizeType.Percent, 10F));
    this.tableLayoutPanel.RowStyles.Add(new System.Windows.Forms.RowStyle
(System.Windows.Forms.SizeType.Percent, 10F));
    this.tableLayoutPanel.RowStyles.Add(new System.Windows.Forms.RowStyle
(System.Windows.Forms.SizeType.Percent, 10F));
    this.tableLayoutPanel.RowStyles.Add(new System.Windows.Forms.RowStyle
(System.Windows.Forms.SizeType.Percent, 10F));
    this.tableLayoutPanel.RowStyles.Add(new System.Windows.Forms.RowStyle
(System.Windows.Forms.SizeType.Percent, 10F));
    this.tableLayoutPanel.RowStyles.Add(new System.Windows.Forms.RowStyle
(System.Windows.Forms.SizeType.Percent, 50F));
    this.tableLayoutPanel.Size = new System.Drawing.Size(417, 265);
    this.tableLayoutPanel.TabIndex = 0;
    //
    // logoPictureBox
    //
    this.logoPictureBox.Dock = System.Windows.Forms.DockStyle.Fill;
    this.logoPictureBox.Image = ((System.Drawing.Image)(resources.GetObject
ct("logoPictureBox.Image")));
    this.logoPictureBox.Location = new System.Drawing.Point(3, 3);
    this.logoPictureBox.Name = "logoPictureBox";
    this.tableLayoutPanel.SetRowSpan(this.logoPictureBox, 6);
    this.logoPictureBox.Size = new System.Drawing.Size(131, 259);
}
```

```

        this.logoPictureBox.SizeMode = System.Windows.Forms.PictureBoxSizeMode.
e.StretchImage;
        this.logoPictureBox.TabIndex = 12;
        this.logoPictureBox.TabStop = false;
        //
        // labelProductName
        //
        this.labelProductName.Dock = System.Windows.Forms.DockStyle.Fill;
        this.labelProductName.Location = new System.Drawing.Point(143, 0);
        this.labelProductName.Margin = new System.Windows.Forms.Padding(6, 0,
3, 0);
        this.labelProductName.MaximumSize = new System.Drawing.Size(0, 17);
        this.labelProductName.Name = "labelProductName";
        this.labelProductName.Size = new System.Drawing.Size(271, 17);
        this.labelProductName.TabIndex = 19;
        this.labelProductName.Text = "Product Name";
        this.labelProductName.TextAlign = System.Drawing.ContentAlignment.Mid
dleLeft;
        //
        // labelVersion
        //
        this.labelVersion.Dock = System.Windows.Forms.DockStyle.Fill;
        this.labelVersion.Location = new System.Drawing.Point(143, 26);
        this.labelVersion.Margin = new System.Windows.Forms.Padding(6, 0, 3,
0);
        this.labelVersion.MaximumSize = new System.Drawing.Size(0, 17);
        this.labelVersion.Name = "labelVersion";
        this.labelVersion.Size = new System.Drawing.Size(271, 17);
        this.labelVersion.TabIndex = 0;
        this.labelVersion.Text = "Version";
        this.labelVersion.TextAlign = System.Drawing.ContentAlignment.MiddleL
eft;
        //
        // labelCopyright
        //
        this.labelCopyright.Dock = System.Windows.Forms.DockStyle.Fill;
        this.labelCopyright.Location = new System.Drawing.Point(143, 52);
        this.labelCopyright.Margin = new System.Windows.Forms.Padding(6, 0, 3
, 0);
        this.labelCopyright.MaximumSize = new System.Drawing.Size(0, 17);
        this.labelCopyright.Name = "labelCopyright";
        this.labelCopyright.Size = new System.Drawing.Size(271, 17);
        this.labelCopyright.TabIndex = 21;
        this.labelCopyright.Text = "Copyright";
        this.labelCopyright.TextAlign = System.Drawing.ContentAlignment.Middl
eLeft;
        //
        // labelCompanyName
        //
        this.labelCompanyName.Dock = System.Windows.Forms.DockStyle.Fill;
        this.labelCompanyName.Location = new System.Drawing.Point(143, 78);
        this.labelCompanyName.Margin = new System.Windows.Forms.Padding(6, 0,
3, 0);
        this.labelCompanyName.MaximumSize = new System.Drawing.Size(0, 17);
        this.labelCompanyName.Name = "labelCompanyName";
        this.labelCompanyName.Size = new System.Drawing.Size(271, 17);
        this.labelCompanyName.TabIndex = 22;
        this.labelCompanyName.Text = "Company Name";
        this.labelCompanyName.TextAlign = System.Drawing.ContentAlignment.Mid
dleLeft;
        //
        // textBoxDescription
        //
        this.textBoxDescription.Dock = System.Windows.Forms.DockStyle.Fill;
        this.textBoxDescription.Location = new System.Drawing.Point(143, 107)
;
        this.textBoxDescription.Margin = new System.Windows.Forms.Padding(6,

```

```

3, 3, 3);
    this.textBoxDescription.Multiline = true;
    this.textBoxDescription.Name = "textBoxDescription";
    this.textBoxDescription.ReadOnly = true;
    this.textBoxDescription.ScrollBars = System.Windows.Forms.ScrollBars.
Both;
    this.textBoxDescription.Size = new System.Drawing.Size(271, 126);
    this.textBoxDescription.TabIndex = 23;
    this.textBoxDescription.TabStop = false;
    this.textBoxDescription.Text = "Description";
    //
    // okButton
    //
    this.okButton.Anchor = ((System.Windows.Forms.AnchorStyles)((System.W
indows.Forms.AnchorStyles.Bottom | System.Windows.Forms.AnchorStyles.Right)));
    this.okButton.DialogResult = System.Windows.Forms.DialogResult.Cancel
;
    this.okButton.Location = new System.Drawing.Point(339, 239);
    this.okButton.Name = "okButton";
    this.okButton.Size = new System.Drawing.Size(75, 23);
    this.okButton.TabIndex = 24;
    this.okButton.Text = "&OK";
    this.okButton.Click += new System.EventHandler(this.okButton_Click);
    //
    // AboutBox
    //
    this.AcceptButton = this.okButton;
    this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
    this.AutoScaleMode = System.Windows.Forms.AutoScaleMode.Font;
    this.ClientSize = new System.Drawing.Size(435, 283);
    this.Controls.Add(this.tableLayoutPanel);
    this.FormBorderStyle = System.Windows.Forms.FormBorderStyle.FixedDial
og;
    this.MaximizeBox = false;
    this.MinimizeBox = false;
    this.Name = "AboutBox";
    this.Padding = new System.Windows.Forms.Padding(9);
    this.ShowIcon = false;
    this.ShowInTaskbar = false;
    this.StartPosition = System.Windows.Forms.FormStartPosition.CenterPar
ent;
    this.Text = "AboutBox";
    this.tableLayoutPanel.ResumeLayout(false);
    this.tableLayoutPanel.PerformLayout();
    ((System.ComponentModel.ISupportInitialize)(this.logoPictureBox)).End
Init();
    this.ResumeLayout(false);
}

```

4.1.3.3 void uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.okButton_Click (object sender, EventArgs e) [private]

Definition at line 123 of file AboutBox.cs.

```

{
    this.Close();
    this.Dispose();
}

```

4.1.4 Member Data Documentation

4.1.4.1 System.ComponentModel.IContainer
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.components
= null [private]

Required designer variable.

Definition at line 24 of file AboutBox.Designer.cs.

4.1.4.2 System.Windows.Forms.Label
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.labelCompanyName
[private]

Definition at line 199 of file AboutBox.Designer.cs.

4.1.4.3 System.Windows.Forms.Label
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.labelCopyright [private]

Definition at line 198 of file AboutBox.Designer.cs.

4.1.4.4 System.Windows.Forms.Label
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.labelProductName
[private]

Definition at line 196 of file AboutBox.Designer.cs.

4.1.4.5 System.Windows.Forms.Label
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.labelVersion
[private]

Definition at line 197 of file AboutBox.Designer.cs.

4.1.4.6 System.Windows.Forms.PictureBox
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.logoPictureBox [private]

Definition at line 195 of file AboutBox.Designer.cs.

4.1.4.7 System.Windows.Forms.Button
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.okButton
[private]

Definition at line 201 of file AboutBox.Designer.cs.

4.1.4.8 System.Windows.Forms.TableLayoutPanelPanel
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.tableLayoutPanel
[private]

Definition at line 194 of file AboutBox.Designer.cs.

4.1.4.9 **System.Windows.Forms.TextBox**
uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.textBoxDescription
[private]

Definition at line 200 of file AboutBox.Designer.cs.

4.1.5 Property Documentation

4.1.5.1 **string uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AssemblyCompany**
[get]

Definition at line 110 of file AboutBox.cs.

4.1.5.2 **string uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AssemblyCopyright**
[get]

Definition at line 97 of file AboutBox.cs.

4.1.5.3 **string uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AssemblyDescription**
[get]

Definition at line 71 of file AboutBox.cs.

4.1.5.4 **string uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AssemblyProduct**
[get]

Definition at line 84 of file AboutBox.cs.

4.1.5.5 **string uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AssemblyTitle** **[get]**

Definition at line 46 of file AboutBox.cs.

4.1.5.6 **string uk.ac.soton.ses.Word2010DepositMOAddIn.AboutBox.AssemblyVersion**
[get]

Definition at line 63 of file AboutBox.cs.

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/AboutBox.cs
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/AboutBox.Designer.cs

4.2 uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl Class Reference

Custom Windows Forms user control for Microsoft Word 2010 DepositMO add-in.

Public Member Functions

- [DepositMORepositryControl](#) ()
Constructor.

Protected Member Functions

- override void [Dispose](#) (bool disposing)
Clean up any resources being used.

Properties

- internal string [username](#) [get]
The username for the repository at the endpoint.
- internal string [password](#) [get]
The password for the repository.
- internal string [endpoint](#) [get]
The repository's endpoint.

Private Member Functions

- void [DepositMORepositryControl_Load](#) (object sender, EventArgs e)
OnLoad handler; adds tooltips.
- void [submitToThisRepositoryButton_Click](#) (object sender, EventArgs e)
Event handler for clicking the submit to this repository button.
- void [SubmitDocument](#) (bool updateExisting)
Submits the document to the endpoint.
- void [logMessage](#) (string message)
Logs the supplied message to the submission log text box and the global log message stack.
- internal void [SubmitDocument](#) (bool updateExisting, string username, string password, string endpoint)
Fires the document submission on a separate thread to avoid locking Word's UI whilst the deposition is being negotiated.
- bool [_SubmitDocument](#) (bool updateExisting, string username, string password, string endpoint)
Submits the document to the target endpoint, or updates the document at the target endpoint using the supplied credentials.
- void [logException](#) (Exception ex)

*Logs the exception
ex
to the global log.*

- void [DumpListingToLog](#) ()
Dumps the user's repository contents to the log.
- void [DumpListingToLog](#) (string username, string password, string endpoint)
Dumps the user's repository contents to the log.
- void [updateEprintButton_Click](#) (object sender, EventArgs e)
Event handler for the update ePrint button.
- void [WarningBox](#) (string message)
*Displays a warning dialogue box with the message
message*
- void [addRepository](#) (string username, string password, string endpoint)
Adds a repository to the group.
- void [addToGroupButton_Click](#) (object sender, EventArgs e)
Event handler when the add to group button has been clicked.
- void [removeFromGroupButton_Click](#) (object sender, EventArgs e)
Removes the currently selected tab page from the tab control.
- void [submitToAllButton_Click](#) (object sender, EventArgs e)
Click event handler for submit to all repositories.
- void [submitToAll](#) ()
Iterates across all the tab pages, takes the repository/username/password triples from there and attempts to submit the document to each repository.
- void [InitializeComponent](#) ()
Required method for Designer support - do not modify the contents of this method with the code editor.

Private Attributes

- System.ComponentModel.IContainer [components](#) = null
Required designer variable.
- System.Windows.Forms.GroupBox [repositoryControlGroupBox](#)
- System.Windows.Forms.TextBox [repositoryLocationTextBox](#)
- System.Windows.Forms.Label [repositoryLocationLabel](#)
- System.Windows.Forms.Button [submitToThisRepositoryButton](#)
- System.Windows.Forms.TextBox [passwordTextBox](#)
- System.Windows.Forms.Label [passwordLabel](#)
- System.Windows.Forms.TextBox [usernameTextBox](#)
- System.Windows.Forms.Label [usernameLabel](#)
- System.Windows.Forms.Button [updateEprintButton](#)

- System.Windows.Forms.Button [addToGroupButton](#)
- System.Windows.Forms.GroupBox [groupRepositoryGroupBox](#)
- System.Windows.Forms.Button [removeFromGroupButton](#)
- System.Windows.Forms.TabControl [repositoryCollectionTabControl](#)
- System.Windows.Forms.Button [submitToAllButton](#)
- System.Windows.Forms.TextBox [submissionLogTextBox](#)
- System.Windows.Forms.TextBox [documentLocationTextBox](#)
- System.Windows.Forms.Label [documentLocationLabel](#)
- System.Windows.Forms.GroupBox [messagesGroupBox](#)

Static Private Attributes

- static readonly object [lockobj](#) = new object()
Lock object for threading.

4.2.1 Detailed Description

Custom Windows Forms user control for Microsoft Word 2010 DepositMO add-in.

Definition at line 31 of file DepositMORepositoryControl.cs.

4.2.2 Constructor & Destructor Documentation

4.2.2.1 `uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.DepositMORepositoryControl()`

Constructor.

Sets the default endpoint, username and password

Definition at line 56 of file DepositMORepositoryControl.cs.

```
{
    InitializeComponent();
    this.repositoryLocationTextBox.Text = Globals.Word2010DepositMOAddIn.
DefaultEndpoint;
    this.usernameTextBox.Text = Globals.Word2010DepositMOAddIn.DefaultUse
rname;
    this.passwordTextBox.Text = Globals.Word2010DepositMOAddIn.DefaultPas
sword;
}
```

4.2.3 Member Function Documentation

4.2.3.1 `bool uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl._SubmitDocument(bool updateExisting, string username, string password, string endpoint) [private]`

Submits the document to the target endpoint, or updates the document at the target endpoint using the supplied credentials.

Parameters

updateExisting `true`
to update an existing document, else
`false`

username The username of the user at the repository

password The password of the user at the repository

endpoint The endpoint of the repository

Returns

Definition at line 143 of file DepositMORepositoryControl.cs.

References `uk.ac.soton.ses.SwordClientHandler.PostDocxToRepository()`, and
`uk.ac.soton.ses.SwordClientHandler.PutToDocument()`.

```
{
    // we might not technically have come in on a new thread but to keep
things consistent we'll
    // increment the counter here, and decrement it at every handled exit
point of the method
    Globals.Word2010DepositMOAddIn.IncrementSubmissionThreadCount();

    #region Pre-submission checks
    // pre-submission checks
    if (String.IsNullOrEmpty(endpoint))
    {
        this.WarningBox("Attempting to submit document to empty endpoint;
cowardly refusing to continue");
        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadCount();
        return false;
    }
    #endregion

    // grab a reference to the active document outside the lock so if som
eone
    // changes the active document whilst another thread is active it wil
l
    // be the correct document
    Document d = Globals.Word2010DepositMOAddIn.Application.ActiveDocumen
t;

    // ensure the user has saved their document before continuing (see
// read-lock comments below)
    try
    {
        d.Save();
    }
    catch
    {
        // for some reason the standard flow control of Word means that
// if the user cancels the save dialogue, an exception will be th
rown
        // --- this is contrary to standard Windows Forms behaviour

        this.WarningBox("Didn't save the document this time; deposition a
borted");
        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadCount();
        return false;
    }
}
```

```

// this could be spun off on a separate (singleton-type) thread
// to avoid UI glitches if the remote isn't responding quickly
lock (lockobj)
{
    SwordClientHandler sch = null;
    string originalDocumentName = null;
    string tempFileName = null;
    bool updateResult = false;

    // get the full path and filename of the document and remember th
is
    originalDocumentName = d.FullName;

    // save the file to the temporary path
    tempFileName += Path.GetTempPath() + d.Name;

    try
    {
        // we need to 'save as' under a different filename as Word ha
s an exclusive
        // read-lock on the current document; 'Type.Missing' through
the call until
        // we can set the 'add to recent files' flag to false
        d.SaveAs2(tempFileName, Type.Missing, Type.Missing, Type.Miss
ing, false);

        // we then need to 'save as' the original filename to restore
the control
        // to the user
        d.SaveAs2(originalDocumentName);
    }
    catch (COMException cex)
    {
        this.logMessage("A problem occurred with " + cex.Source + " w
hilst trying to save the document");
        this.logException(cex);
        this.logMessage("Couldn't submit document " + originalDocumen
tName + " this time as " + cex.Source + " will not allow it");

        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadCount
();
        return false;
    }

    // initialise the SWORD handler
    this.logMessage("Connecting to repository at " + endpoint);
    sch = new SwordClientHandler(username, password, endpoint);

    // use the PUT parts of SWORD if we're updating
    if (updateExisting)
    {
        // 'endpoint' in this context should now be the location of t
he document
        #region Update existing document
        try { updateResult = sch.PutToDocument(tempFileName,
endpoint); }
        catch (Exception ex)
        {
            this.logMessage("Could not update document at " +
endpoint);
            this.logException(ex);
        }
        finally { File.Delete(tempFileName); }

        if (updateResult)
        {
            this.logMessage("Successfully updated document at " +

```

```

        endpoint);
        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadC
ount();
        return true;
    }
    else
    {
        this.logMessage("Couldn't update document at " +
        endpoint);
        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadC
ount();
        return false;
    }
    #endregion
}
else
{
    #region Create new document
    // create new document
    string documentUri = null;

    try { documentUri = sch.PostDocxToRepository(tempFileName); }

    catch (Exception ex)
    {
        this.logMessage("Could not deposit document to " +
        endpoint);
        this.logException(ex);
    }
    finally { File.Delete(tempFileName); }
    #endregion

    // check for null response. Behaviour at this point is undefi
ned
    if (documentUri == null)
    {
        this.logMessage("Couldn't understand response from server
        at endpoint " + endpoint + "; please check deposition manually");
        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadC
ount();
        return false;
    }

    #region Response handling on new deposition
    // attempt to parse the response
    if (!String.IsNullOrEmpty(documentUri))
    {
        this.logMessage("Document deposited at " + documentUri);
        Globals.Word2010DepositMOAddIn.SetSingleLineTextBox(docum
entUri, this.documentLocationTextBox);
    }
    else
    {
        this.logMessage("Warning: response from endpoint " +
        endpoint + " did not contain a reference to the submitted document");
        Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadC
ount();
        return false;
    }
    Globals.Word2010DepositMOAddIn.DecrementSubmissionThreadCount
();
    return true;
    #endregion
}
}
}

```

4.2.3.2 void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.addRepository
 (*string username*, *string password*, *string endpoint*) [**private**]

Adds a repository to the group.

Parameters

username The username of the user at the repository

password The password of the user at the repository

endpoint The endpoint of the repository

Definition at line 362 of file DepositMORepositoryControl.cs.

References uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.endpoint,
 uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.id,
 uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.password, and
 uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.username.

```
{
    // get a unique number for this session so we can grab a handle back
    to it later
    int high_id = 0;
    foreach (TabPage t in this.repositoryCollectionTabControl.TabPages)
    {
        int tabvalue = int.Parse(t.Text);
        if (tabvalue > high_id)
        {
            high_id = tabvalue;
        }
    }
    int id = high_id + 1;
    string idstring = id.ToString();

    // create a new repository control
    RepositoryGroupUserControl rguc = new RepositoryGroupUserControl();
    rguc.Name = idstring;
    rguc.id = id;
    rguc.username = username;
    rguc.password = password;
    rguc.endpoint = endpoint;

    // create a new tab page with the ID...
    TabPage tp = new TabPage(idstring);

    // ... add the repository control to the page ...
    tp.Controls.Add(rguc);

    // ... and add it to the tab control
    this.repositoryCollectionTabControl.TabPages.Add(tp);
    this.logMessage("Added repository " + rguc.endpoint + " to collection
with ID " + idstring);
}
```

4.2.3.3 void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.addToGroupButton_
Click (object sender, EventArgs e) [private**]**

Event handler when the add to group button has been clicked.

Parameters

sender Event sender
e Event arguments

Definition at line 401 of file DepositMORepositoryControl.cs.

```
{
    this.addRepository(this.username, this.password, this.endpoint);
}
```

4.2.3.4 void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.DepositMORepositoryControl.Load (object *sender*, EventArgs *e*) [private]

OnLoad handler; adds tooltips.

Parameters

sender Event sender
e Event parameters

Definition at line 69 of file DepositMORepositoryControl.cs.

```
{
    new ToolTip().SetToolTip(this.addToGroupButton, "Add these repository details to the group to submit documents en masse");
    new ToolTip().SetToolTip(this.documentLocationTextBox, "The location of the document");
    new ToolTip().SetToolTip(this.passwordTextBox, "The password of the user at the repository");
    new ToolTip().SetToolTip(this.usernameTextBox, "The username of the user at the repository");
    new ToolTip().SetToolTip(this.removeFromGroupButton, "Removes the selected repository's details from the group");
    new ToolTip().SetToolTip(this.repositoryLocationTextBox, "The location (endpoint) of the repository");
    new ToolTip().SetToolTip(this.submitToAllButton, "Submits the current document to all endpoints in the group, using the credentials specific to each repository");
    new ToolTip().SetToolTip(this.submissionLogTextBox, "Information about the submissions (successes, failures, counts and so on)");
    new ToolTip().SetToolTip(this.submitToThisRepositoryButton, "Submits the current document to the specified endpoint");
    new ToolTip().SetToolTip(this.updateEprintButton, "Updates the document at the specified endpoint");
}
```

4.2.3.5 override void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.Dispose (bool *disposing*) [protected]

Clean up any resources being used.

Parameters

disposing true if managed resources should be disposed; otherwise, false.

Definition at line 30 of file DepositMORepositoryControl.Designer.cs.

```
{
    if (disposing && (components != null))
    {
        components.Dispose();
    }
    base.Dispose(disposing);
}
```

4.2.3.6 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.DumpListingToLog () [private]

Dumps the user's repository contents to the log.

Definition at line 303 of file DepositMORepositoryControl.cs.

```
{
    this.DumpListingToLog(this.username, this.password, this.endpoint);
}
```

4.2.3.7 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.DumpListingToLog (string username, string password, string endpoint) [private]

Dumps the user's repository contents to the log.

Parameters

username Repository username

password Repository password

endpoint Repository endpoint

Definition at line 314 of file DepositMORepositoryControl.cs.

References uk.ac.soton.ses.SwordClientHandler.ListRecords(), uk.ac.soton.ses.SwordListEntry.Title, and uk.ac.soton.ses.SwordListEntry.Updated.

```
{
    SwordClientHandler sch = new SwordClientHandler(username, password,
endpoint);
    XmlDocument recordsXml = sch.ListRecords(true);
    if (recordsXml != null)
    {
        SwordListReader slr = new SwordListReader(recordsXml);
        foreach (SwordListEntry sle in slr.Entries)
        {
            this.logMessage(sle.Title + " [ " + sle.Updated.ToLocalTime()
.ToLongDateString() + " ]");
        }
    }
}
```

4.2.3.8 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.InitializeComponent () [private]

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 45 of file DepositMORepositoryControl.Designer.cs.

```
{
    this.repositoryControlGroupBox = new System.Windows.Forms.GroupBox();

    this.documentLocationTextBox = new System.Windows.Forms.TextBox();
    this.documentLocationLabel = new System.Windows.Forms.Label();
    this.addToGroupButton = new System.Windows.Forms.Button();
    this.updateEprintButton = new System.Windows.Forms.Button();
    this.passwordTextBox = new System.Windows.Forms.TextBox();
    this.passwordLabel = new System.Windows.Forms.Label();
    this.usernameTextBox = new System.Windows.Forms.TextBox();
    this.usernameLabel = new System.Windows.Forms.Label();
    this.repositoryLocationTextBox = new System.Windows.Forms.TextBox();
    this.repositoryLocationLabel = new System.Windows.Forms.Label();
    this.submitToThisRepositoryButton = new System.Windows.Forms.Button();

;
    this.groupRepositoryGroupBox = new System.Windows.Forms.GroupBox();
    this.submitToAllButton = new System.Windows.Forms.Button();
    this.removeFromGroupButton = new System.Windows.Forms.Button();
    this.repositoryCollectionTabControl = new System.Windows.Forms.TabControl();
    this.submissionLogTextBox = new System.Windows.Forms.TextBox();
    this.messagesGroupBox = new System.Windows.Forms.GroupBox();
    this.repositoryControlGroupBox.SuspendLayout();
    this.groupRepositoryGroupBox.SuspendLayout();
    this.messagesGroupBox.SuspendLayout();
    this.SuspendLayout();
    //
    // repositoryControlGroupBox
    //
    this.repositoryControlGroupBox.Anchor = ((System.Windows.Forms.AnchorStyles)((System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyles.Bottom | System.Windows.Forms.AnchorStyles.Left | System.Windows.Forms.AnchorStyles.Right)));
    this.repositoryControlGroupBox.Controls.Add(this.documentLocationTextBox);
    this.repositoryControlGroupBox.Controls.Add(this.documentLocationLabel);
    this.repositoryControlGroupBox.Controls.Add(this.addToGroupButton);
    this.repositoryControlGroupBox.Controls.Add(this.updateEprintButton);

    this.repositoryControlGroupBox.Controls.Add(this.passwordTextBox);
    this.repositoryControlGroupBox.Controls.Add(this.passwordLabel);
    this.repositoryControlGroupBox.Controls.Add(this.usernameTextBox);
    this.repositoryControlGroupBox.Controls.Add(this.usernameLabel);
    this.repositoryControlGroupBox.Controls.Add(this.repositoryLocationTextBox);
    this.repositoryControlGroupBox.Controls.Add(this.repositoryLocationLabel);
    this.repositoryControlGroupBox.Controls.Add(this.submitToThisRepositoryButton);
    this.repositoryControlGroupBox.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte) 0));
    this.repositoryControlGroupBox.Location = new System.Drawing.Point(4, 4);
    this.repositoryControlGroupBox.Name = "repositoryControlGroupBox";
    this.repositoryControlGroupBox.Size = new System.Drawing.Size(200, 22
```

```

3);
    this.repositoryControlGroupBox.TabIndex = 0;
    this.repositoryControlGroupBox.TabStop = false;
    this.repositoryControlGroupBox.Text = "Repository Control";
    //
    // documentLocationTextBox
    //
    this.documentLocationTextBox.Anchor = ((System.Windows.Forms.AnchorStyles) (((System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyles.Left)
        | System.Windows.Forms.AnchorStyles.Right))));
    this.documentLocationTextBox.Font = new System.Drawing.Font("Tahoma",
        8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)
        0));
    this.documentLocationTextBox.Location = new System.Drawing.Point(7, 1
33);
    this.documentLocationTextBox.Name = "documentLocationTextBox";
    this.documentLocationTextBox.Size = new System.Drawing.Size(187, 21);

    this.documentLocationTextBox.TabIndex = 10;
    //
    // documentLocationLabel
    //
    this.documentLocationLabel.AutoSize = true;
    this.documentLocationLabel.Font = new System.Drawing.Font("Tahoma", 8
.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)
    0));
    this.documentLocationLabel.Location = new System.Drawing.Point(7, 117
);
    this.documentLocationLabel.Name = "documentLocationLabel";
    this.documentLocationLabel.Size = new System.Drawing.Size(95, 13);
    this.documentLocationLabel.TabIndex = 9;
    this.documentLocationLabel.Text = "Document location";
    //
    // addToGroupButton
    //
    this.addToGroupButton.Font = new System.Drawing.Font("Tahoma", 8.25F,
        System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte) 0)
    );
    this.addToGroupButton.Location = new System.Drawing.Point(94, 159);
    this.addToGroupButton.Name = "addToGroupButton";
    this.addToGroupButton.Size = new System.Drawing.Size(82, 52);
    this.addToGroupButton.TabIndex = 8;
    this.addToGroupButton.Text = "Add to repository collection";
    this.addToGroupButton.UseVisualStyleBackColor = true;
    this.addToGroupButton.Click += new System.EventHandler(this.
addToGroupButton_Click);
    //
    // updateEprintButton
    //
    this.updateEprintButton.Font = new System.Drawing.Font("Tahoma", 8.25
F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte) 0
));
    this.updateEprintButton.Location = new System.Drawing.Point(7, 188);
    this.updateEprintButton.Name = "updateEprintButton";
    this.updateEprintButton.Size = new System.Drawing.Size(76, 23);
    this.updateEprintButton.TabIndex = 7;
    this.updateEprintButton.Text = "Update";
    this.updateEprintButton.UseVisualStyleBackColor = true;
    this.updateEprintButton.Click += new System.EventHandler(this.
updateEprintButton_Click);
    //
    // passwordTextBox
    //
    this.passwordTextBox.Anchor = ((System.Windows.Forms.AnchorStyles) (((
        System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyles.Left)
        | System.Windows.Forms.AnchorStyles.Right))));

```



```
        this.passwordTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F,
System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0)))
;
        this.passwordTextBox.Location = new System.Drawing.Point(69, 89);
        this.passwordTextBox.Name = "passwordTextBox";
        this.passwordTextBox.PasswordChar = '*';
        this.passwordTextBox.Size = new System.Drawing.Size(125, 21);
        this.passwordTextBox.TabIndex = 6;
        //
        // passwordLabel
        //
        this.passwordLabel.AutoSize = true;
        this.passwordLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, Sy
stem.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0)));
        this.passwordLabel.Location = new System.Drawing.Point(9, 92);
        this.passwordLabel.Name = "passwordLabel";
        this.passwordLabel.Size = new System.Drawing.Size(53, 13);
        this.passwordLabel.TabIndex = 5;
        this.passwordLabel.Text = "Password";
        //
        // usernameTextBox
        //
        this.usernameTextBox.Anchor = ((System.Windows.Forms.AnchorStyles)(((
System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyles.Left
| System.Windows.Forms.AnchorStyles.Right))););
        this.usernameTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F,
System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0)))
;
        this.usernameTextBox.Location = new System.Drawing.Point(69, 63);
        this.usernameTextBox.Name = "usernameTextBox";
        this.usernameTextBox.Size = new System.Drawing.Size(125, 21);
        this.usernameTextBox.TabIndex = 4;
        //
        // usernameLabel
        //
        this.usernameLabel.AutoSize = true;
        this.usernameLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, Sy
stem.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0)));
        this.usernameLabel.Location = new System.Drawing.Point(8, 66);
        this.usernameLabel.Name = "usernameLabel";
        this.usernameLabel.Size = new System.Drawing.Size(55, 13);
        this.usernameLabel.TabIndex = 3;
        this.usernameLabel.Text = "Username";
        //
        // repositoryLocationTextBox
        //
        this.repositoryLocationTextBox.Anchor = ((System.Windows.Forms.Anchor
Styles)(((System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyl
es.Left
| System.Windows.Forms.AnchorStyles.Right))););
        this.repositoryLocationTextBox.Font = new System.Drawing.Font("Tahoma
", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((
byte)0)));
        this.repositoryLocationTextBox.Location = new System.Drawing.Point(7,
37);
        this.repositoryLocationTextBox.Name = "repositoryLocationTextBox";
        this.repositoryLocationTextBox.Size = new System.Drawing.Size(187, 21
);
        this.repositoryLocationTextBox.TabIndex = 2;
        //
        // repositoryLocationLabel
        //
        this.repositoryLocationLabel.AutoSize = true;
        this.repositoryLocationLabel.Font = new System.Drawing.Font("Tahoma",
8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((by
te)0)));
        this.repositoryLocationLabel.Location = new System.Drawing.Point(7, 2
```

```

0);
    this.repositoryLocationLabel.Name = "repositoryLocationLabel";
    this.repositoryLocationLabel.Size = new System.Drawing.Size(99, 13);
    this.repositoryLocationLabel.TabIndex = 1;
    this.repositoryLocationLabel.Text = "Repository location";
    //
    // submitToThisRepositoryButton
    //
    this.submitToThisRepositoryButton.Font = new System.Drawing.Font("Tah
oma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point,
    ((byte)0));
    this.submitToThisRepositoryButton.Location = new System.Drawing.Point
(7, 159);
    this.submitToThisRepositoryButton.Name = "submitToThisRepositoryButto
n";
    this.submitToThisRepositoryButton.Size = new System.Drawing.Size(76,
23);
    this.submitToThisRepositoryButton.TabIndex = 0;
    this.submitToThisRepositoryButton.Tag = "";
    this.submitToThisRepositoryButton.Text = "Submit";
    this.submitToThisRepositoryButton.UseVisualStyleBackColor = true;
    this.submitToThisRepositoryButton.Click += new System.EventHandler(th
is.submitToThisRepositoryButton_Click);
    //
    // groupRepositoryGroupBox
    //
    this.groupRepositoryGroupBox.Anchor = ((System.Windows.Forms.AnchorSt
yles)((System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AncorStyl
es.Left)
        | System.Windows.Forms.AnchorStyles.Right)));
    this.groupRepositoryGroupBox.Controls.Add(this.submitToAllButton);
    this.groupRepositoryGroupBox.Controls.Add(this.removeFromGroupButton)
;
    this.groupRepositoryGroupBox.Controls.Add(this.
repositoryCollectionTabControl);
    this.groupRepositoryGroupBox.Font = new System.Drawing.Font("Tahoma",
    8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((by
te)0));
    this.groupRepositoryGroupBox.Location = new System.Drawing.Point(4, 2
34);
    this.groupRepositoryGroupBox.Name = "groupRepositoryGroupBox";
    this.groupRepositoryGroupBox.Size = new System.Drawing.Size(200, 206)
;
    this.groupRepositoryGroupBox.TabIndex = 1;
    this.groupRepositoryGroupBox.TabStop = false;
    this.groupRepositoryGroupBox.Text = "Repository Collection";
    //
    // submitToAllButton
    //
    this.submitToAllButton.Font = new System.Drawing.Font("Tahoma", 8.25F
, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0)
));
    this.submitToAllButton.Location = new System.Drawing.Point(7, 177);
    this.submitToAllButton.Name = "submitToAllButton";
    this.submitToAllButton.Size = new System.Drawing.Size(89, 23);
    this.submitToAllButton.TabIndex = 10;
    this.submitToAllButton.Text = "Submit to all";
    this.submitToAllButton.UseVisualStyleBackColor = true;
    this.submitToAllButton.Click += new System.EventHandler(this.
submitToAllButton_Click);
    //
    // removeFromGroupButton
    //
    this.removeFromGroupButton.Font = new System.Drawing.Font("Tahoma", 8
.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte
)0));
    this.removeFromGroupButton.Location = new System.Drawing.Point(102, 1

```

```
77);
    this.removeFromGroupButton.Name = "removeFromGroupButton";
    this.removeFromGroupButton.Size = new System.Drawing.Size(91, 23);
    this.removeFromGroupButton.TabIndex = 9;
    this.removeFromGroupButton.Text = "Remove";
    this.removeFromGroupButton.UseVisualStyleBackColor = true;
    this.removeFromGroupButton.Click += new System.EventHandler(this.
removeFromGroupButton_Click);
    //
    // repositoryCollectionTabControl
    //
    this.repositoryCollectionTabControl.Anchor = ((System.Windows.Forms.A
nchorStyles)((System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.Ancho
rStyles.Left)
        | System.Windows.Forms.AnchorStyles.Right)));
    this.repositoryCollectionTabControl.Font = new System.Drawing.Font("T
ahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Poin
t, (byte)(0));
    this.repositoryCollectionTabControl.Location = new System.Drawing.Poi
nt(7, 20);
    this.repositoryCollectionTabControl.Name = "repositoryCollectionTabCo
ntrol";
    this.repositoryCollectionTabControl.SelectedIndex = 0;
    this.repositoryCollectionTabControl.Size = new System.Drawing.Size(18
7, 151);
    this.repositoryCollectionTabControl.TabIndex = 0;
    //
    // submissionLogTextBox
    //
    this.submissionLogTextBox.BorderStyle = System.Windows.Forms.BorderSt
yle.None;
    this.submissionLogTextBox.Dock = System.Windows.Forms.DockStyle.Fill;

    this.submissionLogTextBox.Font = new System.Drawing.Font("Tahoma", 8.
25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, (byte)
(0));
    this.submissionLogTextBox.Location = new System.Drawing.Point(3, 17);

    this.submissionLogTextBox.Multiline = true;
    this.submissionLogTextBox.Name = "submissionLogTextBox";
    this.submissionLogTextBox.ReadOnly = true;
    this.submissionLogTextBox.ScrollBars = System.Windows.Forms.ScrollBar
s.Vertical;
    this.submissionLogTextBox.Size = new System.Drawing.Size(194, 80);
    this.submissionLogTextBox.TabIndex = 2;
    //
    // messagesGroupBox
    //
    this.messagesGroupBox.Anchor = ((System.Windows.Forms.AnchorStyles)((
System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyles.Left)
        | System.Windows.Forms.AnchorStyles.Right)));
    this.messagesGroupBox.Controls.Add(this.submissionLogTextBox);
    this.messagesGroupBox.Font = new System.Drawing.Font("Tahoma", 8.25F,
System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, (byte)(0)
);
    this.messagesGroupBox.Location = new System.Drawing.Point(4, 446);
    this.messagesGroupBox.Name = "messagesGroupBox";
    this.messagesGroupBox.Size = new System.Drawing.Size(200, 100);
    this.messagesGroupBox.TabIndex = 3;
    this.messagesGroupBox.TabStop = false;
    this.messagesGroupBox.Text = "Messages";
    //
    // DepositMORepositaryControl
    //
    this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
    this.AutoScaleMode = System.Windows.Forms.AutoScaleModeMode.Font;
    this.Controls.Add(this.messagesGroupBox);
```

```

        this.Controls.Add(this.groupRepositoryGroupBox);
        this.Controls.Add(this.repositoryControlGroupBox);
        this.Name = "DepositMORepositoryControl";
        this.Size = new System.Drawing.Size(207, 559);
        this.Load += new System.EventHandler(this.
DepositMORepositoryControl_Load);
        this.repositoryControlGroupBox.ResumeLayout(false);
        this.repositoryControlGroupBox.PerformLayout();
        this.groupRepositoryGroupBox.ResumeLayout(false);
        this.messagesGroupBox.ResumeLayout(false);
        this.messagesGroupBox.PerformLayout();
        this.ResumeLayout(false);
    }

```

4.2.3.9 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.logException (Exception *ex*) [private]

Logs the exception

ex

to the global log.

Parameters

ex Exception to log

Definition at line 294 of file DepositMORepositoryControl.cs.

```

{
    this.logMessage("Full error was: " + ex.ToString());
    this.logMessage("Please contact your administrator or report this if
you believe it to be a bug");
}

```

4.2.3.10 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.logMessage (string *message*) [private]

Logs the supplied message to the submission log text box and the global log message stack.

Parameters

message The message to log

Definition at line 113 of file DepositMORepositoryControl.cs.

```

{
    Globals.Word2010DepositMOAddIn.LogMessage(message, this.
submissionLogTextBox);
}

```

4.2.3.11 void**uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.removeFromGroupButton_Click (object *sender*, EventArgs *e*) [private]**

Removes the currently selected tab page from the tab control.

Note that at the moment we don't do anything with the repository control underneath (GC?)

Parameters

sender Event sender

e Event arguments

Definition at line 412 of file DepositMORepositoryControl.cs.

```
{
    if (this.repositoryCollectionTabControl.SelectedTab != null)
    {
        this.repositoryCollectionTabControl.TabPages.Remove(this.
repositoryCollectionTabControl.SelectedTab);
    }
}
```

4.2.3.12 void**uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.SubmitDocument (bool *updateExisting*) [private]**

Submits the document to the endpoint.

If

updateExisting

is true, then the endpoint will be taken to be that in the document location text area, otherwise the general repository endpoint will be used

Parameters

updateExisting

Definition at line 99 of file DepositMORepositoryControl.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.submitButton_Click().

```
{
    string documentEndpoint = this.endpoint;
    if (updateExisting)
    {
        documentEndpoint = this.documentLocationTextBox.Text;
    }
    this.SubmitDocument(updateExisting, this.username, this.password, documentEndpoint); //this.endpoint);
}
```

4.2.3.13 internal void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.SubmitDocument (bool *updateExisting*, string *username*, string *password*, string *endpoint*) [private]

Fires the document submission on a separate thread to avoid locking Word's UI whilst the deposition is being negotiated.

The thread is issued via a delegate to provide the underlying submission method (

`_SubmitDocument`

) with multiple parameters

Parameters

updateExisting true
if the endpoint represents an existing document, else
false
for a new submission
username The username for the repository at
endpoint
password The password associated with
username
endpoint The endpoint against which submission should occur

Definition at line 128 of file DepositMOREpositoryControl.cs.

```
{
    Thread submitThread = new Thread(() => this._SubmitDocument(updateExi
sting, username, password, endpoint));
    submitThread.Start();
}
```

4.2.3.14 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.submitToAll () [private]

Iterates across all the tab pages, takes the repository/username/password triples from there and attempts to submit the document to each repository.

Definition at line 434 of file DepositMOREpositoryControl.cs.

References uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.endpoint,
uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.password, and
uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.username.

```
{
    int submissionCount = 0;
    foreach (TabPage tabPage in this.repositoryCollectionTabControl.TabPa
ges)
    {
        RepositoryGroupUserControl rguc = (RepositoryGroupUserControl)tab
Page.Controls[0];
```

```
        this.SubmitDocument(false, rguc.username, rguc.password, rguc.end
point);
        submissionCount++;
    }
    this.LogMessage("Submitted document to " + submissionCount.ToString()
+ " repositories");
}
```

4.2.3.15 void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.submitToAllButton_Click (object sender, EventArgs e) [private]

Click event handler for submit to all repositories.

Parameters

sender

e

Definition at line 425 of file DepositMORepositoryControl.cs.

```
{
    this.submitToAll();
}
```

4.2.3.16 void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.submitToThisRepositoryButton_Click (object sender, EventArgs e) [private]

Event handler for clicking the submit to this repository button.

Parameters

sender Event sender

e Event arguments

Definition at line 88 of file DepositMORepositoryControl.cs.

```
{
    this.SubmitDocument(false);
}
```

4.2.3.17 void

uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.updateEPrintButton_Click (object sender, EventArgs e) [private]

Event handler for the update ePrint button.

Parameters

sender Event sender

e Event arguments

Definition at line 333 of file DepositMORepositoryControl.cs.

```
{
    if (this.documentLocationTextBox.Text == String.Empty || this.documen
tLocationTextBox.Text == "")
    {
        //this.logMessage("No document location provided; refusing to upd
ate");
        this.WarningBox("No document location has been provided against w
hich to update. Perhaps you meant to submit rather than update?");
    }
    else
    {
        this.SubmitDocument(true);
    }
}
```

4.2.3.18 void uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.WarningBox (string message) [private]

Displays a warning dialogue box with the message

message

Parameters

message The message to display

Definition at line 350 of file DepositMORepositoryControl.cs.

```
{
    MessageBox.Show(message, "DepositMO", MessageBoxButtons.OK, MessageBo
xIcon.Warning);
    this.logMessage(message);
}
```

4.2.4 Member Data Documentation

4.2.4.1 System.Windows.Forms.Button uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.addToGroupButton [private]

Definition at line 312 of file DepositMORepositoryControl.Designer.cs.

4.2.4.2 System.ComponentModel.IContainer uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.components = null [private]

Required designer variable.

Definition at line 24 of file DepositMORepositoryControl.Designer.cs.

4.2.4.3 System.Windows.Forms.Label
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.documentLocationLabel
[private]

Definition at line 319 of file DepositMORepositoryControl.Designer.cs.

4.2.4.4 System.Windows.Forms.TextBox
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.documentLocationTextBox
[private]

Definition at line 318 of file DepositMORepositoryControl.Designer.cs.

4.2.4.5 System.Windows.Forms.GroupBox
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.groupRepositoryGroupBox
[private]

Definition at line 313 of file DepositMORepositoryControl.Designer.cs.

4.2.4.6 readonly object
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.lockobj
= new object() [static, private]

Lock object for threading.

Definition at line 51 of file DepositMORepositoryControl.cs.

4.2.4.7 System.Windows.Forms.GroupBox
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.messagesGroupBox
[private]

Definition at line 320 of file DepositMORepositoryControl.Designer.cs.

4.2.4.8 System.Windows.Forms.Label
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.passwordLabel
[private]

Definition at line 308 of file DepositMORepositoryControl.Designer.cs.

4.2.4.9 System.Windows.Forms.TextBox
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.passwordTextBox
[private]

Definition at line 307 of file DepositMORepositoryControl.Designer.cs.

4.2.4.10 System.Windows.Forms.Button
uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.removeFromGroupButton
[private]

Definition at line 314 of file DepositMORepositoryControl.Designer.cs.

4.2.4.11 `System.Windows.Forms.TabControl`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.repositoryCollectionTabControl`
`[private]`

Definition at line 315 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.12 `System.Windows.Forms.GroupBox`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.repositoryControlGroupBox`
`[private]`

Definition at line 303 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.13 `System.Windows.Forms.Label`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.repositoryLocationLabel`
`[private]`

Definition at line 305 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.14 `System.Windows.Forms.TextBox`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.repositoryLocationTextBox`
`[private]`

Definition at line 304 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.15 `System.Windows.Forms.TextBox`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.submissionLogTextBox`
`[private]`

Definition at line 317 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.16 `System.Windows.Forms.Button`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.submitToAllButton`
`[private]`

Definition at line 316 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.17 `System.Windows.Forms.Button`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.submitToThisRepositoryButton`
`[private]`

Definition at line 306 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.18 `System.Windows.Forms.Button`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.updateEprintButton`
`[private]`

Definition at line 311 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.19 `System.Windows.Forms.Label`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.usernameLabel`
`[private]`

Definition at line 310 of file `DepositMORepositoryControl.Designer.cs`.

4.2.4.20 `System.Windows.Forms.TextBox`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.usernameTextBox`
`[private]`

Definition at line 309 of file `DepositMORepositoryControl.Designer.cs`.

4.2.5 Property Documentation

4.2.5.1 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.endpoint`
`[get, private]`

The repository's endpoint.

Definition at line 46 of file `DepositMORepositoryControl.cs`.

4.2.5.2 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.password`
`[get, private]`

The password for the repository.

Definition at line 41 of file `DepositMORepositoryControl.cs`.

4.2.5.3 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.username`
`[get, private]`

The username for the repository at the endpoint.

Definition at line 36 of file `DepositMORepositoryControl.cs`.

The documentation for this class was generated from the following files:

- `Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/DepositMORepositoryControl.cs`
- `Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/DepositMORepositoryControl.Designer.cs`

4.3 uk.ac.soton.ses.Word2010DepositMOAddIn.Globals Class Reference

Properties

- static internal [Word2010DepositMOAddIn Word2010DepositMOAddIn](#) `[get, set]`

- static internal `global::Microsoft.Office.Tools.Word.ApplicationFactory` [Factory](#) [get, set]
- static internal [ThisRibbonCollection](#) `Ribbons` [get]

Private Member Functions

- [Globals](#) ()

Static Private Attributes

- static [Word2010DepositMOAddIn](#) `_Word2010DepositMOAddIn`
- static `global::Microsoft.Office.Tools.Word.ApplicationFactory` [_factory](#)
- static [ThisRibbonCollection](#) `_ThisRibbonCollection`

4.3.1 Detailed Description

Definition at line 177 of file `Word2010DepositMOAddIn.Designer.cs`.

4.3.2 Constructor & Destructor Documentation

4.3.2.1 `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals.Globals ()` [private]

Definition at line 180 of file `Word2010DepositMOAddIn.Designer.cs`.

```

    {
    }

```

4.3.3 Member Data Documentation

4.3.3.1 `global::Microsoft.Office.Tools.Word.ApplicationFactory` `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals._factory` [static, private]

Definition at line 185 of file `Word2010DepositMOAddIn.Designer.cs`.

4.3.3.2 `ThisRibbonCollection` `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals._ThisRibbonCollection` [static, private]

Definition at line 187 of file `Word2010DepositMOAddIn.Designer.cs`.

4.3.3.3 `Word2010DepositMOAddIn` `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals._Word2010DepositMOAddIn` [static, private]

Definition at line 183 of file `Word2010DepositMOAddIn.Designer.cs`.

4.3.4 Property Documentation

4.3.4.1 `internal global::Microsoft.Office.Tools.Word.ApplicationFactory` `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals.Factory` [`static`, `get`, `set`, `private`]

Definition at line 204 of file Word2010DepositMOAddIn.Designer.cs.

4.3.4.2 `internal ThisRibbonCollection` `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals.Ribbons` [`static`, `get`, `private`]

Definition at line 218 of file Word2010DepositMOAddIn.Designer.cs.

4.3.4.3 `internal Word2010DepositMOAddIn` `uk.ac.soton.ses.Word2010DepositMOAddIn.Globals.Word2010DepositMOAddIn` [`static`, `get`, `set`, `private`]

Definition at line 190 of file Word2010DepositMOAddIn.Designer.cs.

The documentation for this class was generated from the following file:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMOAddIn.Designer.cs

4.4 uk.ac.soton.ses.HtmlScraper Class Reference

Limited basic HTML parsing routines.

Static Public Member Functions

- static string [GetMetaContent](#) (string address, string name)
Returns the content metatag value for the supplied parameter name and web address.
- static string [GetMetaContent](#) (string address, string name, string target)
Returns the value of the named attribute from a metatag if this exists.
- static string [GetAttributeContent](#) (string address, string type, string namelabel, string name, string target)
Returns the value of the named attribute from the supplied address.
- static string [GetAttributeContent](#) (HttpRequest request, string type, string namelabel, string name, string target)
Gathers values from an HTML file's attribute where another named attribute matches another value.

4.4.1 Detailed Description

Limited basic HTML parsing routines.

Definition at line 30 of file HtmlScraper.cs.

4.4.2 Member Function Documentation

4.4.2.1 static string uk.ac.soton.ses.HtmlScraper.GetAttributeContent (string address, string type, string namelabel, string name, string target) [static]

Returns the value of the named attribute from the supplied address.

For example, given:

link rel="foo" href="bar"

Parameters

address Web address containing HTML to be parsed

type Type of tag, e.g. link

namelabel Label of the name, e.g. rel

name Name, e.g. foo

target Target label, e.g. href

Returns

Target value, e.g. bar

Definition at line 66 of file HtmlScraper.cs.

```
{
    return GetAttributeContent((HttpRequest)HttpRequest.Create(addr
ess), type, namelabel, name, target);
}
```

4.4.2.2 static string uk.ac.soton.ses.HtmlScraper.GetAttributeContent (HttpRequest request, string type, string namelabel, string name, string target) [static]

Gathers values from an HTML file's attribute where another named attribute matches another value.

For example, given:

link rel="foo" href="bar"

as HTML content from <http://www.example.com>, one can retrieve the value 'bar' by calling:

GetAttributeContent((HttpRequest)HttpRequest.Create("http://www.example.com"), "link", "rel", "foo", "href").

Note that this method hasn't been exhaustively tested but appears to work fairly well even for relatively broken HTML 4 documents (as well as nice, strict XHTML ones). Additionally, as the whole HTML document is loaded into RAM whilst parsing (in order to ditch and close the request/responses early) a truly massive HTML document could* cause a

OutOfMemoryException

.

All exceptions are caught, outputted to any debug listener, and rethrown

It is not optimised and could contain bugs, so please use with caution!

Parameters

request The HTTP web request from which to gather an HTML response

type The type of tag (e.g. "meta" or "link")

namelabel The label of the tag to match

name The value of the labelled tag to match

target The label of the target tag

Returns

The value of the target tag

Definition at line 95 of file HtmlScraper.cs.

```

    {
        string contentvalue = null;
        string responsestring = null;

        // return early if the input is bad
        if (type == null || namelabel == null || name == null || target == null || request == null)
        {
            return null;
        }

        string targettagtype = type.ToLower();
        string targetnamelabel = namelabel.ToLower();

        try
        {
            // first, get the page code into a string for parsing
            using (HttpWebResponse resp = (HttpWebResponse)request.GetResponse())
            {
                using (TextReader tr = new StreamReader(resp.GetResponseStream()))
                {
                    responsestring = tr.ReadToEnd();
                }
            }

            // request doesn't close and response should be already closed

            for (int l = 0; l < responsestring.Length - targettagtype.Length; l++)
            {
                // do we have an opening tag?
                if (responsestring[l].Equals('<'))
                {
                    // gather the substring to see if this tag is a meta
                    string substring = responsestring.Substring(l, targettagtype.Length + 1);
                    if (substring.ToLower().Equals("<" + targettagtype))
                    {
                        // find end
                        int endpoint = -1;
                        for (int e = l; e < responsestring.Length; e++)
                        {
                            if (responsestring[e].Equals('>'))
                            {
                                endpoint = e;
                                break;
                            }
                        }
                    }
                }
            }
        }
    }

```

```

    }

    // we successfully found the end of the meta line(s)
    if (endpoint > -1)
    {
        // isolate this meta line
        string metaline = responsestring.Substring(1, end

point - 1 + 1);

        // find the 'name' part
        int nameIndex = metaline.ToLower().IndexOf(" " +

targetnamelabel);

        if (nameIndex > -1)
        {
            int startchar = -1;
            int endchar = -1;
            for (int i = nameIndex; i < metaline.Length;

i++)

                {
                    if (metaline[i] == '"' || metaline[i] ==

'\')

                        {
                            if (startchar == -1)
                            {
                                startchar = i;
                            }
                            else
                            {
                                endchar = i;
                            }
                        }

                            if (startchar > -1 && endchar > -1)
                            {
                                break;
                            }
                        }

                    // this should be the name of the meta tag
                    string namevalue = metaline.Substring(startch

ar + 1, endchar - (startchar + 1));
                    Debug.WriteLine(String.Format("Found tag type

{0} with name {1}", targetnamelabel, namevalue));

                    // is it the one we want?
                    if (namevalue.ToLower().Equals(name.ToLower())

))

                        {
                            Debug.WriteLine(String.Format("Correct li

ne found: {0}", metaline));

                            int contentstart = -1;
                            int contentend = -1;
                            int contentindex = -1;

                            // ok, now look for the attribute we want

                            the value for inside this meta

                            contentindex = metaline.IndexOf(" " + tar

get);

                            if (contentindex > -1)
                            {
                                for (int i = contentindex; i < metali

ne.Length; i++)

                                    {
                                        if (metaline[i] == '"' || metalin

e[i] == '\')

                                            {

```


Generated on Tue Nov 29 2011 16:57:43 for Word 2010 DepositMO plugin - API reference and source guide by Doxygen

```
{  
    return GetMetaContent (address, name, "content");  
}
```

4.4.2.4 static string uk.ac.soton.ses.HtmlScraper.GetMetaContent (string address, string name, string target) [static]

Returns the value of the named attribute from a metatag if this exists.

Parameters

address Web address containing HTML to be parsed

name Name of the content parameter (e.g. foo if name="foo")

target Name of the target attribute (e.g. value if value="bar")

Returns

Value of the target attribute (e.g. bar if value="bar")

Definition at line 50 of file HtmlScraper.cs.

```
{  
    return GetAttributeContent ((HttpWebRequest) HttpWebRequest.Create (address), "meta", "name", name, target);  
}
```

The documentation for this class was generated from the following file:

- Q:/Projects/SwordHandler/SwordHandler/HtmlScraper.cs

4.5 uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm Class Reference

Internal log viewer for Microsoft Word 2010 DepositMO add-in.

Public Member Functions

- [LogViewerForm \(\)](#)
Windows form for viewing the log.

Protected Member Functions

- override void [Dispose](#) (bool disposing)
Clean up any resources being used.

Private Member Functions

- void `closeButton_Click` (object sender, EventArgs e)
Event triggered by clicking the log viewer's close button.
- void `copyButton_Click` (object sender, EventArgs e)
Copies the contents of the log text box to the clipboard.
- void `InitializeComponent` ()
Required method for Designer support - do not modify the contents of this method with the code editor.

Private Attributes

- System.ComponentModel.IContainer `components` = null
Required designer variable.
- System.Windows.Forms.Button `closeButton`
- System.Windows.Forms.TextBox `logTextBox`
- System.Windows.Forms.Button `copyButton`

4.5.1 Detailed Description

Internal log viewer for Microsoft Word 2010 DepositMO add-in.

Definition at line 25 of file LogViewerForm.cs.

4.5.2 Constructor & Destructor Documentation

4.5.2.1 uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.LogViewerForm ()

Windows form for viewing the log.

Definition at line 30 of file LogViewerForm.cs.

```
{
    InitializeComponent();
    // set the contents of the text box to be the singleton's log message
    stack
    this.logTextBox.Lines = Globals.Word2010DepositMOAddIn.GetAllLogMessa
ges();
}
```

4.5.3 Member Function Documentation

4.5.3.1 void uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.closeButton_Click (object sender, EventArgs e) [private]

Event triggered by clicking the log viewer's close button.

Parameters

sender Event sender

e Event arguments

Definition at line 42 of file LogViewerForm.cs.

```
{
    this.Close();
    this.Dispose();
}
```

4.5.3.2 void uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.copyButton_Click (object *sender*, EventArgs *e*) [private]

Copies the contents of the log text box to the clipboard.

Parameters

sender

e

Definition at line 53 of file LogViewerForm.cs.

```
{
    Clipboard.SetText (this.logTextBox.Text);
}
```

4.5.3.3 override void uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.Dispose (bool *disposing*) [protected]

Clean up any resources being used.

Parameters

disposing true if managed resources should be disposed; otherwise, false.

Definition at line 30 of file LogViewerForm.Designer.cs.

```
{
    if (disposing && (components != null))
    {
        components.Dispose();
    }
    base.Dispose(disposing);
}
```

4.5.3.4 void

uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.InitializeComponent (
) [private]

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 45 of file LogViewerForm.Designer.cs.

```
{
    this.closeButton = new System.Windows.Forms.Button();
    this.logTextBox = new System.Windows.Forms.TextBox();
    this.copyButton = new System.Windows.Forms.Button();
    this.SuspendLayout();
    //
    // closeButton
    //
    this.closeButton.Anchor = ((System.Windows.Forms.AnchorStyles)((System
m.Windows.Forms.AnchorStyles.Bottom | System.Windows.Forms.AnchorStyles.Right)));

    this.closeButton.Font = new System.Drawing.Font("Tahoma", 8.25F);
    this.closeButton.Location = new System.Drawing.Point(364, 264);
    this.closeButton.Name = "closeButton";
    this.closeButton.Size = new System.Drawing.Size(75, 23);
    this.closeButton.TabIndex = 0;
    this.closeButton.Text = "Close";
    this.closeButton.UseVisualStyleBackColor = true;
    this.closeButton.Click += new System.EventHandler(this.
closeButton_Click);
    //
    // logTextBox
    //
    this.logTextBox.Anchor = ((System.Windows.Forms.AnchorStyles)((System
em.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStyles.Bottom
    | System.Windows.Forms.AnchorStyles.Left)
    | System.Windows.Forms.AnchorStyles.Right)));
    this.logTextBox.BorderStyle = System.Windows.Forms.BorderStyle.None;
    this.logTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F);
    this.logTextBox.Location = new System.Drawing.Point(12, 12);
    this.logTextBox.Multiline = true;
    this.logTextBox.Name = "logTextBox";
    this.logTextBox.ReadOnly = true;
    this.logTextBox.ScrollBars = System.Windows.Forms.ScrollBars.Vertical
;

    this.logTextBox.Size = new System.Drawing.Size(427, 246);
    this.logTextBox.TabIndex = 1;
    //
    // copyButton
    //
    this.copyButton.Anchor = ((System.Windows.Forms.AnchorStyles)((System
.Windows.Forms.AnchorStyles.Bottom | System.Windows.Forms.AnchorStyles.Left)));
    this.copyButton.Font = new System.Drawing.Font("Tahoma", 8.25F);
    this.copyButton.Location = new System.Drawing.Point(12, 265);
    this.copyButton.Name = "copyButton";
    this.copyButton.Size = new System.Drawing.Size(75, 23);
    this.copyButton.TabIndex = 2;
    this.copyButton.Text = "Copy";
    this.copyButton.UseVisualStyleBackColor = true;
    this.copyButton.Click += new System.EventHandler(this.
copyButton_Click);
    //
    // LogViewerForm
    //
    this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
    this.AutoScaleMode = System.Windows.Forms.AutoScaleMode.Font;
    this.ClientSize = new System.Drawing.Size(451, 299);
```

```
        this.Controls.Add(this.copyButton);  
        this.Controls.Add(this.logTextBox);  
        this.Controls.Add(this.closeButton);  
        this.Name = "LogViewerForm";  
        this.Text = "DepositMO message stack";  
        this.ResumeLayout(false);  
        this.PerformLayout();  
    }  
}
```

4.5.4 Member Data Documentation

4.5.4.1 System.Windows.Forms.Button

uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.closeButton
[private]

Definition at line 108 of file LogViewerForm.Designer.cs.

4.5.4.2 System.ComponentModel.IContainer

uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.components = null
[private]

Required designer variable.

Definition at line 24 of file LogViewerForm.Designer.cs.

4.5.4.3 System.Windows.Forms.Button

uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.copyButton
[private]

Definition at line 110 of file LogViewerForm.Designer.cs.

4.5.4.4 System.Windows.Forms.TextBox

uk.ac.soton.ses.Word2010DepositMOAddIn.LogViewerForm.logTextBox
[private]

Definition at line 109 of file LogViewerForm.Designer.cs.

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/LogViewerForm.cs
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/LogViewerForm.Designer.cs

4.6 uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm Class Reference

Quick submission form for the Microsoft Word 2010 DepositMO add-in.

Public Member Functions

- [QuickSubmitForm](#) ()

Constructor for quick submission Windows form.

Protected Member Functions

- override void [Dispose](#) (bool disposing)

Clean up any resources being used.

Private Member Functions

- void [cancelButton_Click](#) (object sender, EventArgs e)
- void [submitButton_Click](#) (object sender, EventArgs e)
- void [InitializeComponent](#) ()

Required method for Designer support - do not modify the contents of this method with the code editor.

Private Attributes

- System.ComponentModel.IContainer [components](#) = null

Required designer variable.

- System.Windows.Forms.Button [cancelButton](#)
- System.Windows.Forms.TextBox [passwordTextBox](#)
- System.Windows.Forms.Label [passwordLabel](#)
- System.Windows.Forms.TextBox [usernameTextBox](#)
- System.Windows.Forms.Label [usernameLabel](#)
- System.Windows.Forms.TextBox [repositoryLocationTextBox](#)
- System.Windows.Forms.Label [repositoryLocationLabel](#)
- System.Windows.Forms.Button [submitButton](#)

4.6.1 Detailed Description

Quick submission form for the Microsoft Word 2010 DepositMO add-in.

Definition at line 32 of file QuickSubmitForm.cs.

4.6.2 Constructor & Destructor Documentation

4.6.2.1 uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.QuickSubmitForm ()

Constructor for quick submission Windows form.

Definition at line 37 of file QuickSubmitForm.cs.

```

{
    InitializeComponent();
    this.repositoryLocationTextBox.Text = Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().endpointEditBox.Text;

    if (!String.IsNullOrEmpty(Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().quickUsername))
    {
        this.usernameTextBox.Text = Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().quickUsername;
    }

    if (!String.IsNullOrEmpty(Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().quickPassword))
    {
        this.passwordTextBox.Text = Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().quickPassword;
    }
}

```

4.6.3 Member Function Documentation

4.6.3.1 void uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.cancelButton_Click (object sender, EventArgs e) [private]

Definition at line 53 of file QuickSubmitForm.cs.

```

{
    this.Close();
    this.Dispose();
}

```

4.6.3.2 override void uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.Dispose (bool disposing) [protected]

Clean up any resources being used.

Parameters

disposing true if managed resources should be disposed; otherwise, false.

Definition at line 29 of file QuickSubmitForm.Designer.cs.

```

{
    if (disposing && (components != null))
    {
        components.Dispose();
    }
    base.Dispose(disposing);
}

```


4.6.3.3 void

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.InitializeComponent
 () [private]

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 44 of file QuickSubmitForm.Designer.cs.

```
{
    this.cancelButton = new System.Windows.Forms.Button();
    this.passwordTextBox = new System.Windows.Forms.TextBox();
    this.passwordLabel = new System.Windows.Forms.Label();
    this.usernameTextBox = new System.Windows.Forms.TextBox();
    this.usernameLabel = new System.Windows.Forms.Label();
    this.repositoryLocationTextBox = new System.Windows.Forms.TextBox();
    this.repositoryLocationLabel = new System.Windows.Forms.Label();
    this.submitButton = new System.Windows.Forms.Button();
    this.SuspendLayout();
    //
    // cancelButton
    //
    this.cancelButton.Location = new System.Drawing.Point(402, 55);
    this.cancelButton.Name = "cancelButton";
    this.cancelButton.Size = new System.Drawing.Size(75, 23);
    this.cancelButton.TabIndex = 0;
    this.cancelButton.Text = "Cancel";
    this.cancelButton.UseVisualStyleBackColor = true;
    this.cancelButton.Click += new System.EventHandler(this.
cancelButton_Click);
    //
    // passwordTextBox
    //
    this.passwordTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F,
System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
;
    this.passwordTextBox.Location = new System.Drawing.Point(125, 62);
    this.passwordTextBox.Name = "passwordTextBox";
    this.passwordTextBox.PasswordChar = '*';
    this.passwordTextBox.Size = new System.Drawing.Size(100, 21);
    this.passwordTextBox.TabIndex = 12;
    //
    // passwordLabel
    //
    this.passwordLabel.AutoSize = true;
    this.passwordLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, Sy
stem.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
    this.passwordLabel.Location = new System.Drawing.Point(65, 65);
    this.passwordLabel.Name = "passwordLabel";
    this.passwordLabel.Size = new System.Drawing.Size(53, 13);
    this.passwordLabel.TabIndex = 11;
    this.passwordLabel.Text = "Password";
    //
    // usernameTextBox
    //
    this.usernameTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F,
System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
;
    this.usernameTextBox.Location = new System.Drawing.Point(125, 36);
    this.usernameTextBox.Name = "usernameTextBox";
    this.usernameTextBox.Size = new System.Drawing.Size(100, 21);
    this.usernameTextBox.TabIndex = 10;
    //
    // usernameLabel
    //
    this.usernameLabel.AutoSize = true;
```

```

        this.usernameLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte) 0));
        this.usernameLabel.Location = new System.Drawing.Point(64, 39);
        this.usernameLabel.Name = "usernameLabel";
        this.usernameLabel.Size = new System.Drawing.Size(55, 13);
        this.usernameLabel.TabIndex = 9;
        this.usernameLabel.Text = "Username";
        //
        // repositoryLocationTextBox
        //
        this.repositoryLocationTextBox.Anchor = ((System.Windows.Forms.AnchorStyles)((System.Windows.Forms.AnchorStyles.Top | System.Windows.Forms.AnchorStylesLeft | System.Windows.Forms.AnchorStyles.Right)));
        this.repositoryLocationTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte) 0));
        this.repositoryLocationTextBox.Location = new System.Drawing.Point(125, 9);
        this.repositoryLocationTextBox.Name = "repositoryLocationTextBox";
        this.repositoryLocationTextBox.Size = new System.Drawing.Size(354, 21);
    };
    this.repositoryLocationTextBox.TabIndex = 8;
    //
    // repositoryLocationLabel
    //
    this.repositoryLocationLabel.AutoSize = true;
    this.repositoryLocationLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte) 0));
    this.repositoryLocationLabel.Location = new System.Drawing.Point(20, 12);
    this.repositoryLocationLabel.Name = "repositoryLocationLabel";
    this.repositoryLocationLabel.Size = new System.Drawing.Size(99, 13);
    this.repositoryLocationLabel.TabIndex = 7;
    this.repositoryLocationLabel.Text = "Repository location";
    //
    // submitButton
    //
    this.submitButton.Location = new System.Drawing.Point(321, 55);
    this.submitButton.Name = "submitButton";
    this.submitButton.Size = new System.Drawing.Size(75, 23);
    this.submitButton.TabIndex = 13;
    this.submitButton.Text = "Submit";
    this.submitButton.UseVisualStyleBackColor = true;
    this.submitButton.Click += new System.EventHandler(this.submitButton_Click);
    //
    // QuickSubmitForm
    //
    this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
    this.AutoScaleMode = System.Windows.Forms.AutoScaleMode.Font;
    this.ClientSize = new System.Drawing.Size(491, 95);
    this.Controls.Add(this.submitButton);
    this.Controls.Add(this.passwordTextBox);
    this.Controls.Add(this.passwordLabel);
    this.Controls.Add(this.usernameTextBox);
    this.Controls.Add(this.usernameLabel);
    this.Controls.Add(this.repositoryLocationTextBox);
    this.Controls.Add(this.repositoryLocationLabel);
    this.Controls.Add(this.cancelButton);
    this.Name = "QuickSubmitForm";
    this.Text = "DepositMO quick submission";
    this.ResumeLayout(false);
    this.PerformLayout();

}

```

4.6.3.4 void uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.submitButton_Click (object sender, EventArgs e) [private]

Definition at line 59 of file QuickSubmitForm.cs.

References uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.SubmitDocument().

```
{
    CustomTaskPaneCollection ctps = Globals.Word2010DepositMOAddIn.Custom
TaskPanes;
    if (ctps.Count == 0)
    {
        // abort
        this.Close();
        this.Dispose();
        return;
    }

    CustomTaskPane currentTaskPane = null;

    foreach (CustomTaskPane ctp in ctps)
    {
        if (ctp.Window == Globals.Word2010DepositMOAddIn.Application.ActiveWindow)
        {
            currentTaskPane = ctp;
        }
    }

    if (currentTaskPane == null)
    {
        // abort
        MessageBox.Show("Could not get the correct task pane");
        this.Close();
        this.Dispose();
        return;
    }

    if(currentTaskPane.Control is DepositMOREpositoryControl)
    {
        DepositMOREpositoryControl dmrControl = (DepositMOREpositoryControl)currentTaskPane.Control;
        dmrControl.SubmitDocument(false, this.usernameTextBox.Text, this.passwordTextBox.Text, this.repositoryLocationTextBox.Text);
    }
    else
    {
        MessageBox.Show("Couldn't get control over the repository panel")
    }
;

    // update the internal fields on the ribbon if applicable

    if (!String.IsNullOrEmpty(this.usernameTextBox.Text))
    {
        Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().quickUsername = this.usernameTextBox.Text;
    }

    if (!String.IsNullOrEmpty(this.passwordTextBox.Text))
    {
        Globals.Ribbons.GetRibbon<Word2010DepositMORibbon>().quickPassword = this.passwordTextBox.Text;
    }

    this.Close();
}
```

```
        this.Dispose();  
    }
```

4.6.4 Member Data Documentation

4.6.4.1 System.Windows.Forms.Button

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.cancelButton
[private]

Definition at line 155 of file QuickSubmitForm.Designer.cs.

4.6.4.2 System.ComponentModel.IContainer

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.components = null
[private]

Required designer variable.

Definition at line 23 of file QuickSubmitForm.Designer.cs.

4.6.4.3 System.Windows.Forms.Label

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.passwordLabel
[private]

Definition at line 157 of file QuickSubmitForm.Designer.cs.

4.6.4.4 System.Windows.Forms.TextBox

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.passwordTextBox
[private]

Definition at line 156 of file QuickSubmitForm.Designer.cs.

4.6.4.5 System.Windows.Forms.Label

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.repositoryLocationLabel
[private]

Definition at line 161 of file QuickSubmitForm.Designer.cs.

4.6.4.6 System.Windows.Forms.TextBox

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.repositoryLocationTextBox
[private]

Definition at line 160 of file QuickSubmitForm.Designer.cs.

4.6.4.7 System.Windows.Forms.Button

uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.submitButton
[private]

Definition at line 162 of file QuickSubmitForm.Designer.cs.

4.6.4.8 **System.Windows.Forms.Label**
uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.usernameLabel
[private]

Definition at line 159 of file QuickSubmitForm.Designer.cs.

4.6.4.9 **System.Windows.Forms.TextBox**
uk.ac.soton.ses.Word2010DepositMOAddIn.QuickSubmitForm.usernameTextBox
[private]

Definition at line 158 of file QuickSubmitForm.Designer.cs.

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/QuickSubmitForm.cs
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/QuickSubmitForm.Designer.cs

4.7 uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl Class Reference

Custom Windows Forms user control for repository groups in Microsoft Word 2010 DepositMO add-in.

Public Member Functions

- [RepositoryGroupUserControl](#) ()
Default constructor.

Protected Member Functions

- override void [Dispose](#) (bool disposing)
Clean up any resources being used.

Properties

- string [endpoint](#) [get, set]
Endpoint.
- string [username](#) [get, set]
Username.
- string [password](#) [get, set]
Password.
- int [id](#) [get, set]
Control ID.

Private Member Functions

- void [InitializeComponent](#) ()

Required method for Designer support - do not modify the contents of this method with the code editor.

Private Attributes

- System.ComponentModel.IContainer [components](#) = null

Required designer variable.

- System.Windows.Forms.TextBox [passwordTextBox](#)
- System.Windows.Forms.Label [passwordLabel](#)
- System.Windows.Forms.TextBox [usernameTextBox](#)
- System.Windows.Forms.Label [usernameLabel](#)
- System.Windows.Forms.TextBox [repositoryLocationTextBox](#)
- System.Windows.Forms.Label [repositoryLocationLabel](#)
- System.Windows.Forms.Label [identLabel](#)

4.7.1 Detailed Description

Custom Windows Forms user control for repository groups in Microsoft Word 2010 DepositMO add-in.

Definition at line 31 of file RepositoryGroupUserControl.cs.

4.7.2 Constructor & Destructor Documentation

4.7.2.1 [uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.RepositoryGroupUserControl](#) ()

Default constructor.

Sets endpoint, username and password

Definition at line 56 of file RepositoryGroupUserControl.cs.

```
{
    InitializeComponent();
    this.endpoint = Globals.Word2010DepositMOAddIn.DefaultEndpoint;
    this.username = Globals.Word2010DepositMOAddIn.DefaultUsername;
    this.password = Globals.Word2010DepositMOAddIn.DefaultPassword;
}
```

4.7.3 Member Function Documentation

4.7.3.1 **override void** [uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.Dispose](#) (**bool disposing**) [**protected**]

Clean up any resources being used.

Parameters

disposing true if managed resources should be disposed; otherwise, false.

Definition at line 30 of file RepositoryGroupUserControl.Designer.cs.

```
{
    if (disposing && (components != null))
    {
        components.Dispose();
    }
    base.Dispose(disposing);
}
```

4.7.3.2 void

**uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.InitializeComponent
() [private]**

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 45 of file RepositoryGroupUserControl.Designer.cs.

```
{
    this.passwordTextBox = new System.Windows.Forms.TextBox();
    this.passwordLabel = new System.Windows.Forms.Label();
    this.usernameTextBox = new System.Windows.Forms.TextBox();
    this.usernameLabel = new System.Windows.Forms.Label();
    this.repositoryLocationTextBox = new System.Windows.Forms.TextBox();
    this.repositoryLocationLabel = new System.Windows.Forms.Label();
    this.identLabel = new System.Windows.Forms.Label();
    this.SuspendLayout();
    //
    // passwordTextBox
    //
    this.passwordTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
    ;
    this.passwordTextBox.Location = new System.Drawing.Point(66, 75);
    this.passwordTextBox.Name = "passwordTextBox";
    this.passwordTextBox.PasswordChar = '*';
    this.passwordTextBox.Size = new System.Drawing.Size(92, 21);
    this.passwordTextBox.TabIndex = 12;
    //
    // passwordLabel
    //
    this.passwordLabel.AutoSize = true;
    this.passwordLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
    this.passwordLabel.Location = new System.Drawing.Point(6, 78);
    this.passwordLabel.Name = "passwordLabel";
    this.passwordLabel.Size = new System.Drawing.Size(53, 13);
    this.passwordLabel.TabIndex = 11;
    this.passwordLabel.Text = "Password";
    //
    // usernameTextBox
    //
    this.usernameTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
    ;
    this.usernameTextBox.Location = new System.Drawing.Point(66, 49);
    this.usernameTextBox.Name = "usernameTextBox";
```

```

        this.usernameTextBox.Size = new System.Drawing.Size(92, 21);
        this.usernameTextBox.TabIndex = 10;
        //
        // usernameLabel
        //
        this.usernameLabel.AutoSize = true;
        this.usernameLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
        this.usernameLabel.Location = new System.Drawing.Point(5, 52);
        this.usernameLabel.Name = "usernameLabel";
        this.usernameLabel.Size = new System.Drawing.Size(55, 13);
        this.usernameLabel.TabIndex = 9;
        this.usernameLabel.Text = "Username";
        //
        // repositoryLocationTextBox
        //
        this.repositoryLocationTextBox.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
        this.repositoryLocationTextBox.Location = new System.Drawing.Point(4, 23);
        this.repositoryLocationTextBox.Name = "repositoryLocationTextBox";
        this.repositoryLocationTextBox.Size = new System.Drawing.Size(179, 21);
    );
    this.repositoryLocationTextBox.TabIndex = 8;
    //
    // repositoryLocationLabel
    //
    this.repositoryLocationLabel.AutoSize = true;
    this.repositoryLocationLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
    this.repositoryLocationLabel.Location = new System.Drawing.Point(4, 6);
    );
    this.repositoryLocationLabel.Name = "repositoryLocationLabel";
    this.repositoryLocationLabel.Size = new System.Drawing.Size(99, 13);
    this.repositoryLocationLabel.TabIndex = 7;
    this.repositoryLocationLabel.Text = "Repository location";
    //
    // identLabel
    //
    this.identLabel.AutoSize = true;
    this.identLabel.Font = new System.Drawing.Font("Tahoma", 8.25F, System.Drawing.FontStyle.Regular, System.Drawing.GraphicsUnit.Point, ((byte)0));
    this.identLabel.Location = new System.Drawing.Point(98, 6);
    this.identLabel.Name = "identLabel";
    this.identLabel.Size = new System.Drawing.Size(13, 13);
    this.identLabel.TabIndex = 13;
    this.identLabel.Text = "0";
    this.identLabel.Visible = false;
    //
    // RepositoryGroupUserControl
    //
    this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
    this.AutoScaleMode = System.Windows.Forms.AutoScaleMode.Font;
    this.Controls.Add(this.identLabel);
    this.Controls.Add(this.passwordTextBox);
    this.Controls.Add(this.passwordLabel);
    this.Controls.Add(this.usernameTextBox);
    this.Controls.Add(this.usernameLabel);
    this.Controls.Add(this.repositoryLocationTextBox);
    this.Controls.Add(this.repositoryLocationLabel);
    this.Name = "RepositoryGroupUserControl";
    this.Size = new System.Drawing.Size(186, 196);
    this.ResumeLayout(false);
    this.PerformLayout();

```



```
}
```

4.7.4 Member Data Documentation

4.7.4.1 `System.ComponentModel.IContainer`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.components`
`= null [private]`

Required designer variable.

Definition at line 24 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.2 `System.Windows.Forms.Label`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.identLabel`
`[private]`

Definition at line 148 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.3 `System.Windows.Forms.Label`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.passwordLabel`
`[private]`

Definition at line 143 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.4 `System.Windows.Forms.TextBox`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.passwordTextBox`
`[private]`

Definition at line 142 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.5 `System.Windows.Forms.Label`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.repositoryLocationLabel`
`[private]`

Definition at line 147 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.6 `System.Windows.Forms.TextBox`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.repositoryLocationTextBox`
`[private]`

Definition at line 146 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.7 `System.Windows.Forms.Label`
`uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.usernameLabel`
`[private]`

Definition at line 145 of file RepositoryGroupUserControl.Designer.cs.

4.7.4.8 **System.Windows.Forms.TextBox**

uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.usernameTextBox
[private]

Definition at line 144 of file RepositoryGroupUserControl.Designer.cs.

4.7.5 **Property Documentation**

4.7.5.1 **string**

uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.endpoint
[get, set]

Endpoint.

Definition at line 36 of file RepositoryGroupUserControl.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.addRepository(),
and uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.submitToAll().

4.7.5.2 int uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.id
[get, set]

Control ID.

Definition at line 51 of file RepositoryGroupUserControl.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.addRepository().

4.7.5.3 **string**

uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.password
[get, set]

Password.

Definition at line 46 of file RepositoryGroupUserControl.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.addRepository(),
and uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.submitToAll().

4.7.5.4 **string**

uk.ac.soton.ses.Word2010DepositMOAddIn.RepositoryGroupUserControl.username
[get, set]

Username.

Definition at line 41 of file RepositoryGroupUserControl.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.addRepository(),
and uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl.submitToAll().

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/RepositoryGroupUserControl.cs
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/RepositoryGroupUserControl.Designer.cs

4.8 uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources Class Reference

A strongly-typed resource class, for looking up localized strings, etc.

Properties

- static internal global::System.Resources.ResourceManager [ResourceManager](#) [get]
Returns the cached ResourceManager instance used by this class.
- static internal global::System.Globalization.CultureInfo [Culture](#) [get, set]
Overrides the current thread's CurrentUICulture property for all resource lookups using this strongly typed resource class.
- static internal System.Drawing.Bitmap [DocumentImage](#) [get]

Private Member Functions

- internal [Resources](#) ()

Static Private Attributes

- static global::System.Resources.ResourceManager [resourceMan](#)
- static global::System.Globalization.CultureInfo [resourceCulture](#)

4.8.1 Detailed Description

A strongly-typed resource class, for looking up localized strings, etc.

Definition at line 25 of file Resources.Designer.cs.

4.8.2 Constructor & Destructor Documentation

4.8.2.1 internal uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.Resources () [private]

Definition at line 32 of file Resources.Designer.cs.

```

    {
    }

```

4.8.3 Member Data Documentation

4.8.3.1 global::System.Globalization.CultureInfo uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.resourceCulture [static, private]

Definition at line 29 of file Resources.Designer.cs.

4.8.3.2 `global::System.Resources.ResourceManager`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.resourceMan`
`[static, private]`

Definition at line 27 of file Resources.Designer.cs.

4.8.4 Property Documentation

4.8.4.1 `internal global::System.Globalization.CultureInfo`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.Culture`
`[static, get, set, private]`

Overrides the current thread's `CurrentUICulture` property for all resource lookups using this strongly typed resource class.

Definition at line 54 of file Resources.Designer.cs.

4.8.4.2 `internal System.Drawing.Bitmap`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.DocumentImage`
`[static, get, private]`

Definition at line 63 of file Resources.Designer.cs.

4.8.4.3 `internal global::System.Resources.ResourceManager`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.ResourceManager`
`[static, get, private]`

Returns the cached `ResourceManager` instance used by this class.

Definition at line 39 of file Resources.Designer.cs.

The documentation for this class was generated from the following file:

- `Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Properties/Resources.Designer.cs`

4.9 uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Settings Class Reference

Properties

- static [Settings Default](#) `[get]`

Static Private Attributes

- static [Settings defaultInstance](#) = (([Settings](#))(global::System.Configuration.ApplicationSettingsBase.SynchronizeSettings()))

4.9.1 Detailed Description

Definition at line 16 of file Settings.Designer.cs.

4.9.2 Member Data Documentation

4.9.2.1 Settings

```
uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Settings.defaultInstance  
= ((Settings)(global::System.Configuration.ApplicationSettingsBase.Synchronized(new  
Settings())))) [static, private]
```

Definition at line 18 of file Settings.Designer.cs.

4.9.3 Property Documentation

4.9.3.1 Settings uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Settings.Default [static, get]

Definition at line 20 of file Settings.Designer.cs.

The documentation for this class was generated from the following file:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Properties/Settings.Designer.cs

4.10 uk.ac.soton.ses.SwordAtomReader Class Reference

SWORD 2 Atom XML reader.

Public Member Functions

- [SwordAtomReader](#) (XmlDocument [atomXml](#))
Creates a new SWORD Atom reader from the supplied XML document.

Properties

- XmlDocument [AtomXml](#) [get, set]
Gets or sets the Atom response on this instance.
- string [EditMediaHref](#) [get]
Edit media href.
- string [EditHref](#) [get]
Edit href.
- string [ContentsHref](#) [get]
Contents href.

- string [AtomId](#) [get]
Atom ID.
- string [AtomTitle](#) [get]
Atom title.
- string [AtomGenerator](#) [get]
Atom generator.
- string [AtomGeneratorUri](#) [get]
Atom generator URL.
- string [AtomGeneratorVersion](#) [get]
Atom generator version.
- string [AtomSummary](#) [get]
Atom summary.
- string [AtomContentType](#) [get]
Atom content type.
- string [AtomContentSrc](#) [get]
Atom content source.
- string [SwordTreatment](#) [get]
SWORD treatment.
- string [SwordPackaging](#) [get]
SWORD packaging.
- string [SwordNoop](#) [get]
SWORD noop.
- DateTime [AtomUpdated](#) [get]
Atom updated.
- DateTime [AtomPublished](#) [get]
Atom published.

Private Member Functions

- string [GetXPathValue](#) (string XPathQuery)
- string [GetXPathText](#) (string XPathQuery)
- string[] [GetXPathTextArray](#) (string XPathQuery)
- XmlNode [GetSingleNode](#) (string XPathQuery)
- XmlNodeList [GetMultipleNodes](#) (string XPathQuery)

Private Attributes

- XmlDocument [atomXml](#) = null
The Atom XML document.
- XmlNamespaceManager [xnm](#) = null
XML namespace manager for Atom XML document.

4.10.1 Detailed Description

SWORD 2 Atom XML reader.

Definition at line 28 of file SwordAtomReader.cs.

4.10.2 Constructor & Destructor Documentation

4.10.2.1 uk.ac.soton.ses.SwordAtomReader.SwordAtomReader (XmlDocument *atomXml*)

Creates a new SWORD Atom reader from the supplied XML document.

Parameters

atomXml Atom XML

Definition at line 44 of file SwordAtomReader.cs.

```
{
    this.atomXml = atomXml;
    if (this.atomXml != null)
    {
        this.xnm = new XmlNamespaceManager(this.atomXml.NameTable);
        this.xnm.AddNamespace("atom", "http://www.w3.org/2005/Atom");
        this.xnm.AddNamespace("sword", "http://purl.org/net/sword/");
    }
}
```

4.10.3 Member Function Documentation

4.10.3.1 XmlNodeList uk.ac.soton.ses.SwordAtomReader.GetMultipleNodes (string *xPathQuery*) [private]

Definition at line 99 of file SwordAtomReader.cs.

```
{
    if (this.atomXml == null)
    {
        return null;
    }
    return this.atomXml.SelectNodes(xpathQuery, this.xnm);
}
```

4.10.3.2 XmlNode uk.ac.soton.ses.SwordAtomReader.GetSingleNode (string *xPathQuery*) [private]

Definition at line 90 of file SwordAtomReader.cs.

```
{
    if (this.atomXml == null)
    {
        return null;
    }
    return this.atomXml.SelectSingleNode(xPathQuery, this.xnm);
}
```

4.10.3.3 string uk.ac.soton.ses.SwordAtomReader.GetXPathText (string *xPathQuery*) [private]

Definition at line 65 of file SwordAtomReader.cs.

```
{
    XmlNode singleNode = this.GetSingleNode(xPathQuery);
    if (singleNode == null)
    {
        return null;
    }
    return singleNode.InnerText;
}
```

4.10.3.4 string [] uk.ac.soton.ses.SwordAtomReader.GetXPathTextArray (string *xPathQuery*) [private]

Definition at line 75 of file SwordAtomReader.cs.

```
{
    XmlNodeList multipleNodes = this.GetMultipleNodes(xPathQuery);
    if (multipleNodes == null)
    {
        return null;
    }
    string[] nodetexts = new string[multipleNodes.Count];
    for (int i = 0; i < multipleNodes.Count; i++)
    {
        nodetexts[i] = multipleNodes[i].InnerText;
    }
    return nodetexts;
}
```

4.10.3.5 string uk.ac.soton.ses.SwordAtomReader.GetXPathValue (string *xPathQuery*) [private]

Definition at line 55 of file SwordAtomReader.cs.

```
{
    XmlNode singleNode = this.GetSingleNode(xPathQuery);
    if (singleNode == null)
```



```
    {  
        return null;  
    }  
    return singleNode.Value;  
}
```

4.10.4 Member Data Documentation

4.10.4.1 XmlDocument uk.ac.soton.ses.SwordAtomReader.atomXml = null [private]

The Atom XML document.

Definition at line 33 of file SwordAtomReader.cs.

4.10.4.2 XmlNamespaceManager uk.ac.soton.ses.SwordAtomReader.xnm = null [private]

XML namespace manager for Atom XML document.

Definition at line 38 of file SwordAtomReader.cs.

4.10.5 Property Documentation

4.10.5.1 string uk.ac.soton.ses.SwordAtomReader.AtomContentSrc [get]

Atom content source.

Definition at line 187 of file SwordAtomReader.cs.

4.10.5.2 string uk.ac.soton.ses.SwordAtomReader.AtomContentType [get]

Atom content type.

Definition at line 182 of file SwordAtomReader.cs.

4.10.5.3 string uk.ac.soton.ses.SwordAtomReader.AtomGenerator [get]

Atom generator.

Definition at line 162 of file SwordAtomReader.cs.

4.10.5.4 string uk.ac.soton.ses.SwordAtomReader.AtomGeneratorUri [get]

Atom generator URI.

Definition at line 167 of file SwordAtomReader.cs.

4.10.5.5 string uk.ac.soton.ses.SwordAtomReader.AtomGeneratorVersion [get]

Atom generator version.

Definition at line 172 of file SwordAtomReader.cs.

4.10.5.6 string uk.ac.soton.ses.SwordAtomReader.AtomId [get]

Atom ID.

Definition at line 152 of file SwordAtomReader.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestAtomReader(),
uk.ac.soton.ses.SwordClientHandlerTests.TestDepositEprintsXml(), and
uk.ac.soton.ses.SwordClientHandlerTests.TestDepositZipToEprint().

4.10.5.7 DateTime uk.ac.soton.ses.SwordAtomReader.AtomPublished [get]

Atom published.

Definition at line 212 of file SwordAtomReader.cs.

4.10.5.8 string uk.ac.soton.ses.SwordAtomReader.AtomSummary [get]

Atom summary.

Definition at line 177 of file SwordAtomReader.cs.

4.10.5.9 string uk.ac.soton.ses.SwordAtomReader.AtomTitle [get]

Atom title.

Definition at line 157 of file SwordAtomReader.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestGetInfo().

4.10.5.10 DateTime uk.ac.soton.ses.SwordAtomReader.AtomUpdated [get]

Atom updated.

Definition at line 207 of file SwordAtomReader.cs.

4.10.5.11 XmlDocument uk.ac.soton.ses.SwordAtomReader.AtomXml [get, set]

Gets or sets the Atom response on this instance.

Definition at line 112 of file SwordAtomReader.cs.

4.10.5.12 string uk.ac.soton.ses.SwordAtomReader.ContentsHref [get]

Contents href.

Definition at line 147 of file SwordAtomReader.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestGetInfo().

4.10.5.13 string uk.ac.soton.ses.SwordAtomReader.EditHref [get]

Edit href.

Definition at line 142 of file SwordAtomReader.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestAtomReader().

4.10.5.14 string uk.ac.soton.ses.SwordAtomReader.EditMediaHref [get]

Edit media href.

Definition at line 124 of file SwordAtomReader.cs.

Referenced by uk.ac.soton.ses.SwordClientHandler.PostDocxToContainer(), and uk.ac.soton.ses.SwordClientHandlerTests.TestAtomReader().

4.10.5.15 string uk.ac.soton.ses.SwordAtomReader.SwordNoop [get]

SWORD noop.

Definition at line 202 of file SwordAtomReader.cs.

4.10.5.16 string uk.ac.soton.ses.SwordAtomReader.SwordPackaging [get]

SWORD packaging.

Definition at line 197 of file SwordAtomReader.cs.

4.10.5.17 string uk.ac.soton.ses.SwordAtomReader.SwordTreatment [get]

SWORD treatment.

Definition at line 192 of file SwordAtomReader.cs.

The documentation for this class was generated from the following file:

- Q:/Projects/SwordHandler/SwordHandler/SwordAtomReader.cs

4.11 uk.ac.soton.ses.SwordClientHandler Class Reference

SWORD 2 client implementation for .NET.

Public Member Functions

- [SwordClientHandler](#) (string username, string password, string endpoint)
Creates a new SWORD 2 handler instance.
- [SwordClientHandler](#) (string username, string password, string endpoint, bool resolveInbox)
Creates a new SWORD 2 handler instance.
- string [PostDocxToContainer](#) (string docxFilename)
Deposits the .docx from the supplied filename to the initialised endpoint with the default content type.

- string [PostDocxToContainer](#) (string docxFilename, string contentType)
Deposits the .docx from the supplied filename to the initialised endpoint with the supplied content type.
- string [DepositDocxToContents](#) (string docxFilename, string contentType, string containerUri)
Deposits the .docx from the supplied filename to the supplied endpoint with the supplied content type.
- string [PostDocxToRepository](#) (string docxFilename, string contentType, string endpoint)
Creates a container on the repository and posts the supplied docx file to that container.
- string [PostDocxToRepository](#) (string docxFilename)
Creates a container on the repository and posts the supplied docx file to that container, using the default docx content type and the initialised endpoint on the instance.
- string [PostDocxToContainer](#) (string docxFilename, string contentType, string containerUri)
Posts the supplied docx file to the supplied container.
- string [CreateContainer](#) ()
Creates an empty container on the initialised repository.
- string [CreateContainer](#) (string endpoint)
Creates an empty container on the repository at the supplied endpoint.
- string [GetResponseLocation](#) (HttpRequest wr)
Gets the location of the response from the provided
`HttpRequest`
- XmlDocument [GetEprintInfo](#) (string uri)
Gets information about the ePrint at the provided URI.
- bool [PutToDocument](#) (string documentFileName, string endpoint)
Performs a PUT to the supplied endpoint with the supplied document filename using
`DOCX_CONTENTTYPE`
`.`
- bool [PutToDocument](#) (string documentFileName, string endpoint, string contentType)
Performs a PUT to the supplied endpoint with the supplied document filename using the supplied content type.
- XmlDocument [DepositZipToEprint](#) (string zipFileName)
Deposits the zip file in the supplied filename to the initialised endpoint with a gzip content type (to be formally standardised at the server side).
- XmlDocument [DepositZipToEprint](#) (string zipFileName, string contentType)
Deposits the zip file in the supplied filename to the initialised endpoint with the supplied content type.
- XmlDocument [DepositEprintsXml](#) (XmlDocument xmlDocument)
Deposits the EP2 XML document to the initialised endpoint with X-Packaging type
`EP2_PACKAGING`
- XmlDocument [DepositEprintsXml](#) (string xmlFileName)

Deposits the EP2 XML document in the supplied filename to the initialised endpoint with X-Packaging type
 EP2_PACKAGING

- XmlDocument [DepositXml](#) (string xmlFileName, string xPackaging)
Deposits the XML document in the supplied filename to the initialised endpoint with the supplied X-Packaging type.
- XmlDocument [DepositXml](#) (XmlDocument xmlDocument, string xPackaging)
Deposits the XML document to the initialised endpoint with the supplied X-Packaging type.
- XmlDocument [Delete](#) (string swordUrl)
Deletes the document at the target address
 swordUrl
 .
- XmlDocument [ListRecords](#) (bool stripEndpoint)
List all records at the endpoint.
- XmlDocument [ListRecords](#) ()
List all records at the endpoint, by calling endpoint/id/records (
 LIST_RECORD_PATH
).

Properties

- string [Username](#) [set]
Sets the username associated with the repository.
- string [Password](#) [set]
Sets the password associated with the repository.
- string [Endpoint](#) [set]
Sets the endpoint associated with the repository.

Private Member Functions

- internal void [ResolveInbox](#) ()
Resolves the inbox based on the currently-supplied endpoint.
- HttpRequest [GetBasicAuthAtomWebRequest](#) (string targetUri)
Creates a web request instance to the target URI, adding in basic authorisation from the username and password on the instance, and setting the
 accept
header of the request to be
 application/atom+xml
- HttpRequest [GetBasicAuthAtomWebRequest](#) (Uri targetUri)
Creates a web request instance to the target URI, adding in basic authorisation from the username and password on the instance, and setting the

accept
header of the request to be
application/atom+xml

- void [WriteFileToRequest](#) (string filename, HttpRequest wr)

*Writes the file in
filename
to the web request
wr
.*

- XmlDocument [GetXmlResponse](#) (HttpRequest wr)

Gets an XML document as the response from a web request.

Private Attributes

- internal bool [_resolveInbox](#) = false

TODO: Whether the inbox URL should be resolved from the HTML of the supplied endpoint.

- string [_username](#)

The repository username.

- string [_password](#)

The repository password.

- string [_endpoint](#)

The main repository endpoint.

Static Private Attributes

- static int [BUFFER_SIZE](#) = 16 * 1024

Buffer size for uploads in bytes.

- static string [EP2_PACKAGING](#) = "http://eprints.org/ep2/data/2.0"

EP2 packaging header value.

- static string [DOCX_CONTENTTYPE](#) = "application/vnd.openxmlformats-officedocument.wordprocessingml.document"

.docx content type

- static string [LIST_RECORD_PATH](#) = "/id/records"

The path for listing records.

- static string [EXTRACT_MEDIA](#) = "true"

Should media be extracted by default, or ignored? Note that this is going into a header so it should be a string rather than a Boolean.

4.11.1 Detailed Description

SWORD 2 client implementation for .NET. Library functions for communicating with a SWORD 2 compliant server

Definition at line 35 of file SwordClientHandler.cs.

4.11.2 Constructor & Destructor Documentation

4.11.2.1 uk.ac.soton.ses.SwordClientHandler.SwordClientHandler (string *username*, string *password*, string *endpoint*)

Creates a new SWORD 2 handler instance.

Parameters

username The repository username
password The repository password
endpoint The main repository endpoint

Definition at line 124 of file SwordClientHandler.cs.

```
{
    this._username = username;
    this._password = password;
    this._endpoint = endpoint;
}
```

4.11.2.2 uk.ac.soton.ses.SwordClientHandler.SwordClientHandler (string *username*, string *password*, string *endpoint*, bool *resolveInbox*)

Creates a new SWORD 2 handler instance.

Parameters

username The repository username
password The repository password
endpoint The main repository endpoint
resolveInbox Whether to attempt to resolve the 'inbox' from the supplied endpoint

Definition at line 138 of file SwordClientHandler.cs.

```
{
    this._username = username;
    this._password = password;
    this._endpoint = endpoint;
    this._resolveInbox = resolveInbox;
    this.ResolveInbox();
}
```

4.11.3 Member Function Documentation

4.11.3.1 `string uk.ac.soton.ses.SwordClientHandler.CreateContainer ()`

Creates an empty container on the initialised repository.

Returns

The address of the new empty container

Definition at line 381 of file `SwordClientHandler.cs`.

Referenced by `uk.ac.soton.ses.SwordClientHandlerTests.TestCreateContainer()`.

```
{
    return this.CreateContainer(this._endpoint);
}
```

4.11.3.2 `string uk.ac.soton.ses.SwordClientHandler.CreateContainer (string endpoint)`

Creates an empty container on the repository at the supplied endpoint.

Parameters

endpoint The endpoint at which to create the new empty container

Returns

The address of the new empty container

Definition at line 391 of file `SwordClientHandler.cs`.

```
{
    HttpRequest wr = this.GetBasicAuthAtomWebRequest(endpoint);
    wr.Method = "POST";
    wr.ContentType = "application/atom+xml";
    wr.Headers.Add("In-Progress", "true");
    string emptyAtom = @"<?xml version=""1.0"" encoding=""utf-8"" ?>
    <entry xmlns=""http://www.w3.org/2005/Atom"" />";
    wr.ContentLength = (long)emptyAtom.Length;

    // TODO: not the most elegant way to write this 'empty' Atom request
    // but functional
    using (Stream requestStream = wr.GetRequestStream())
    {
        foreach (byte b in emptyAtom)
        {
            requestStream.WriteByte(b);
        }
    }

    return this.GetResponseLocation(wr);
}
```


4.11.3.3 XmlDocument uk.ac.soton.ses.SwordClientHandler.Delete (string *swordUrl*)

Deletes the document at the target address

swordUrl

.

Parameters

swordUrl The target address at which the document resides

Returns

Atom response

Definition at line 613 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestDelete().

```
{
    HttpWebRequest wr = this.GetBasicAuthAtomWebRequest(swordUrl);
    wr.Method = "DELETE";
    return this.GetXmlResponse(wr);
}
```

4.11.3.4 string uk.ac.soton.ses.SwordClientHandler.DepositDocxToContents (string *docxFilename*, string *contentType*, string *contentUri*)

Deposits the .docx from the supplied filename to the supplied endpoint with the supplied content type.

Parameters

docxFilename The filename of the .docx to deposit

contentType The content type to use for the deposition

contentUri The endpoint against which the deposition should occur

Returns

Atom response

Definition at line 299 of file SwordClientHandler.cs.

```
{
    FileInfo fi = new FileInfo(docxFilename);
    HttpWebRequest wr = this.GetBasicAuthAtomWebRequest(contentUri);

    wr.Method = "POST";
    wr.Headers.Add("Content-Disposition", "form-data; name=\"" + fi.Name
+ "\"; filename=\"" + fi.Name + "\"");
    wr.ContentType = contentType;
    wr.ContentLength = fi.Length;
    // should the default be to extract media, or ignore it?
    wr.Headers.Add("X-Extract-Media", EXTRACT_MEDIA);
    wr.Headers.Add("X-Override-Metadata", "true");
}
```

```
//wr.Headers.Add("Metadata-Relevant", "true");  
wr.Headers.Add("In-Progress", "true");  
this.WriteFileToRequest(docxFilename, wr);  
  
return this.GetResponseLocation(wr); //this.GetXmlResponse(wr);  
}
```

4.11.3.5 **XmlDocument uk.ac.soton.ses.SwordClientHandler.DepositEprintsXml (XmlDocument xmlDoc)**

Deposits the EP2 XML document to the initialised endpoint with X-Packaging type

EP2_PACKAGING

Parameters

xmlDoc The EP2 XML document to deposit

Returns

Atom response

Definition at line 545 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestDepositEprintsXml().

```
{  
    return this.DepositXml(xmlDoc, EP2_PACKAGING);  
}
```

4.11.3.6 **XmlDocument uk.ac.soton.ses.SwordClientHandler.DepositEprintsXml (string xmlFileName)**

Deposits the EP2 XML document in the supplied filename to the initialised endpoint with X-Packaging type

EP2_PACKAGING

Parameters

xmlFileName The filename of the EP2 XML document to deposit

Returns

Atom response

Definition at line 556 of file SwordClientHandler.cs.

```
{  
    return this.DepositXml(xmlFileName, EP2_PACKAGING);  
}
```

4.11.3.7 XmlDocument uk.ac.soton.ses.SwordClientHandler.DepositXml (XmlDocument *xmlDocument*, string *xPackaging*)

Deposits the XML document to the initialised endpoint with the supplied X-Packaging type.

Parameters

xmlDocument The XML document to deposit

xPackaging The X-Packaging type

Returns

Atom response

Definition at line 582 of file SwordClientHandler.cs.

```
{
    HttpWebRequest wr = this.GetBasicAuthAtomWebRequest(this._endpoint);

    wr.Method = "POST";
    wr.Headers.Add("X-Packaging", xPackaging);
    wr.ContentType = "text/xml";

    // note that we can't wrap the Stream here with a using as there
    // is a possibility that Dispose will get called more than once
    // and this will generate an ObjectDisposedException. Instead,
    // we'll not assign the request stream to anything and just
    // pass it through directly

    XmlWriterSettings xws = new XmlWriterSettings();
    xws.CloseOutput = true;

    using (XmlWriter xw = XmlWriter.Create(wr.GetRequestStream(), xws))
    {
        xmlDocument.WriteTo(xw);

        // ensure that the XML writer is flushed as this does *not* happen
        // automatically
        xw.Flush();
    }
    return this.GetXmlResponse(wr);
}
```

4.11.3.8 XmlDocument uk.ac.soton.ses.SwordClientHandler.DepositXml (string *xmlFileName*, string *xPackaging*)

Deposits the XML document in the supplied filename to the initialised endpoint with the supplied X-Packaging type.

Parameters

xmlFileName The filename of the XML document to deposit

xPackaging The X-Packaging type

Returns

Atom response

Definition at line 568 of file SwordClientHandler.cs.

```
{
    XmlDocument xmlDocument = new XmlDocument();
    xmlDocument.Load(xmlFileName);
    return this.DepositXml(xmlDocument, xPackaging);
}
```

4.11.3.9 **XmlDocument uk.ac.soton.ses.SwordClientHandler.DepositZipToEprint (string zipFileName, string contentType)**

Deposits the zip file in the supplied filename to the initialised endpoint with the supplied content type.

Parameters

zipFileName The zip filename

contentType The content type

Returns

Atom response

Definition at line 525 of file SwordClientHandler.cs.

```
{
    FileInfo fi = new FileInfo(zipFileName);
    HttpRequest wr = this.GetBasicAuthAtomWebRequest(this._endpoint);
    wr.Method = "POST";
    wr.Headers.Add("Content-Disposition", "form-data; name=\"" + fi.Name
+ "\"; filename=\"" + fi.Name + "\"");
    wr.ContentType = contentType;
    wr.ContentLength = fi.Length;
    wr.Headers.Add("X-Extract-Archive", "true");
    this.WriteFileToRequest(zipFileName, wr);

    return this.GetXmlResponse(wr);
}
```

4.11.3.10 **XmlDocument uk.ac.soton.ses.SwordClientHandler.DepositZipToEprint (string zipFileName)**

Deposits the zip file in the supplied filename to the initialised endpoint with a gzip content type (to be formally standardised at the server side).

Parameters

zipFileName The zip filename

Returns

Atom response

Definition at line 513 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestDepositZipToEprint().

```
{  
    return this.DepositZipToEprint(zipFileName, "application/g-zip");  
}
```

4.11.3.11 **HttpRequest**

**uk.ac.soton.ses.SwordClientHandler.GetBasicAuthAtomWebRequest (string
targetUri) [private]**

Creates a web request instance to the target URI, adding in basic authorisation from the username and password on the instance, and setting the

accept

header of the request to be

application/atom+xml

Parameters

targetUri The URI to which the request should be made

Returns

Web request

Definition at line 173 of file SwordClientHandler.cs.

```
{  
    return this.GetBasicAuthAtomWebRequest(new Uri(targetUri));  
}
```

4.11.3.12 **HttpRequest**

**uk.ac.soton.ses.SwordClientHandler.GetBasicAuthAtomWebRequest (Uri
targetUri) [private]**

Creates a web request instance to the target URI, adding in basic authorisation from the username and password on the instance, and setting the

accept

header of the request to be

application/atom+xml

Parameters

targetUri The URI to which the request should be made

Returns

Web request

Definition at line 185 of file SwordClientHandler.cs.

```

    {
        HttpWebRequest request = (HttpWebRequest)WebRequest.Create(targetUri)
    ;
        CredentialCache cc = new CredentialCache();
        cc.Add(targetUri, "Basic", new NetworkCredential(this._username, this
._password, "Authenticate"));
        //cc.Add(new Uri(targetUri), "Basic", new NetworkCredential(this._use
rname, this._password));
        request.Credentials = cc;
        request.Headers.Add(HttpRequestHeader.Authorization, "Basic " + Conve
rt.ToBase64String(new ASCIIEncoding().GetBytes(this._username + ':' + this.
_password)));
        request.Accept = "application/atom+xml";
        return request;
    }

```

4.11.3.13 XmlDocument uk.ac.soton.ses.SwordClientHandler.GetEprintInfo (string *uri*)

Gets information about the ePrint at the provided URI.

Parameters

uri ePrint URI

Returns

Atom XML document

Definition at line 434 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestGetInfo().

```

    {
        HttpWebRequest wr = this.GetBasicAuthAtomWebRequest(uri);
        wr.Method = "GET";
        return this.GetXmlResponse(wr);
    }

```

4.11.3.14 string uk.ac.soton.ses.SwordClientHandler.GetResponseLocation (HttpWebRequest *wr*)

Gets the location of the response from the provided

HttpWebRequest

Parameters

wr The web request to query

Returns

Location string

Definition at line 419 of file SwordClientHandler.cs.

```

{
    string location = null;
    using (HttpWebResponse resp = (HttpWebResponse)wr.GetResponse())
    {
        location = resp.Headers[HttpResponseHeader.Location].ToString();
    }
    return location;
}

```

4.11.3.15 XmlDocument uk.ac.soton.ses.SwordClientHandler.GetXmlResponse (HttpRequest wr) [private]

Gets an XML document as the response from a web request.

The response will be

null

if it is invalid, either because it is not well-formed XML (e.g. HTML 4.0) or there was no acceptable response available from the server (e.g. 404)

Parameters

wr The web request from which the response should be requested

Returns

The XML document response

Definition at line 232 of file SwordClientHandler.cs.

```

{
    XmlDocument xmlResponse = null;

    try
    {
        using (WebResponse res = wr.GetResponse())
        {
            using (Stream resStream = res.GetResponseStream())
            {
                // when this method was implemented, the SWORD 2 server w
as still returning HTML:
                // if (((HttpWebResponse)res).StatusCode == HttpStatusCode
e.OK)
                // {
                //     return null;
                // }
                // - so try/catch this in case it changes

                try
                {
                    xmlResponse = new XmlDocument();
                    xmlResponse.Load(resStream);
                }
                catch (XmlException xex)
                {
                    Debug.WriteLine(xex);
                    // xmlResponse = null; // depends how we want to hand
le this
                }
            }
        }
    }
}

```

```

        }
    }
    catch (WebException wex)
    {
        // likely a 404, write the exception if we're in debug mode, and
fall through
        // to return the null response
        Debug.WriteLine(wex);
    }
    return xmlResponse;
}

```

4.11.3.16 XmlDocument uk.ac.soton.ses.SwordClientHandler.ListRecords ()

List all records at the endpoint, by calling endpoint/id/records (

LIST_RECORD_PATH

).

Returns

List of records in XML format, else

null

Exceptions

WebException Typically thrown at a timeout on the endpoint

Definition at line 695 of file SwordClientHandler.cs.

```

{
    return this.ListRecords(false);
}

```

4.11.3.17 XmlDocument uk.ac.soton.ses.SwordClientHandler.ListRecords (bool stripEndpoint)

List all records at the endpoint.

Parameters

stripEndpoint true

if the endpoint should be stripped down and the default of /id/records (

LIST_RECORD_PATH

) used, else

false

if the literal endpoint, suffixed with /id/records (

LIST_RECORD_PATH

) value should be used

Returns

List of records in XML format, else

null

Exceptions

WebException Typically thrown at a timeout on the endpoint

Definition at line 629 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositoryControl.DumpListingToLog(), and uk.ac.soton.ses.SwordClientHandlerTests.TestList().

```

    {
        string target = this._endpoint;

        HttpRequest initialWr = null;
        HttpRequest realWr = null;
        HttpResponse wresp = null;
        XmlDocument xmlDocument = null;

        if (stripEndpoint)
        {
            target = new Uri(this._endpoint).GetLeftPart(UriPartial.Authority
);
        }
        string records = target + LIST_RECORD_PATH;

        Debug.WriteLine("Requesting records from " + records);
        initialWr = this.GetBasicAuthAtomWebRequest(records);
        initialWr.Method = "GET";

        try
        {
            wresp = initialWr.GetResponse();
        }
        catch (WebException wex)
        {
            // if we've timed out, rethrow the exception
            if (wex.Status == WebExceptionStatus.Timeout)
            {
                throw wex;
            }

            // being forced to handle exceptions as part of normal program co
ntrol

            // is not pleasant (303 in this case)
            Debug.WriteLine(wex.Response.ResponseUri);
            Uri realUri = wex.Response.ResponseUri;
            realWr = this.GetBasicAuthAtomWebRequest(realUri);
            realWr.Method = "GET";
            wresp = realWr.GetResponse();
        }

        using (Stream resStream = wresp.GetResponseStream())
        {
            try
            {
                xmlDocument = new XmlDocument();
                xmlDocument.Load(resStream);
            }
            catch (XmlException xex)
            {
                Debug.WriteLine(xex);
            }
        }
    }

```

```

        }
    }

    if (wresp != null)
    {
        wresp.Close();
    }

    return xmlDocument;
}

```

4.11.3.18 string uk.ac.soton.ses.SwordClientHandler.PostDocxToContainer (string *docxFilename*, string *contentType*, string *containerUri*)

Posts the supplied docx file to the supplied container.

Parameters

docxFilename The filename of the docx to post

contentType The content type of the docx

containerUri The URI of the container

Returns

Definition at line 362 of file SwordClientHandler.cs.

References uk.ac.soton.ses.SwordAtomReader.EditMediaHref.

```

{
    XmlDocument response = this.GetEprintInfo(containerUri);
    if (response == null) return null;

    SwordAtomReader sar = new SwordAtomReader(response);
    if (sar == null) return null;

    string editMediaHref = sar.EditMediaHref;
    Debug.WriteLine("Edit media href is {0}", editMediaHref);
    if (String.IsNullOrEmpty(editMediaHref)) return null;

    return this.DepositDocxToContents(docxFilename, contentType, editMediaHref);
}

```

4.11.3.19 string uk.ac.soton.ses.SwordClientHandler.PostDocxToContainer (string *docxFilename*)

Deposits the .docx from the supplied filename to the initialised endpoint with the default content type.

Parameters

docxFilename The filename of the .docx to deposit

Returns

Atom response

Definition at line 276 of file SwordClientHandler.cs.

```
{
    return this.PostDocxToContainer(docxFilename, DOCX_CONTENTTYPE);
}
```

4.11.3.20 string uk.ac.soton.ses.SwordClientHandler.PostDocxToContainer (string docxFilename, string contentType)

Deposits the .docx from the supplied filename to the initialised endpoint with the supplied content type.

Parameters

docxFilename The filename of the .docx to deposit
contentType The content type to use for the deposition

Returns

Atom response

Definition at line 287 of file SwordClientHandler.cs.

```
{
    return this.PostDocxToContainer(docxFilename, contentType, this._endpoint);
}
```

4.11.3.21 string uk.ac.soton.ses.SwordClientHandler.PostDocxToRepository (string docxFilename, string contentType, string endpoint)

Creates a container on the repository and posts the supplied docx file to that container.

Parameters

docxFilename The filename of the docx to post
contentType The content type of the docx
endpoint The endpoint against which the posting should occur

Returns

Definition at line 326 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl._SubmitDocument(), and uk.ac.soton.ses.SwordClientHandlerTests.TestPutToDocument().

```
{
    string container = this.CreateContainer(endpoint);
    if (String.IsNullOrEmpty(container))
    {
        return null;
    }

    return this.PostDocxToContainer(docxFilename, contentType);
}
```

4.11.3.22 **string uk.ac.soton.ses.SwordClientHandler.PostDocxToRepository (string *docxFilename*)**

Creates a container on the repository and posts the supplied docx file to that container, using the default docx content type and the initialised endpoint on the instance.

Parameters

docxFilename The filename of the docx to post

Returns

Definition at line 344 of file SwordClientHandler.cs.

```
{
    string container = this.CreateContainer(this._endpoint);
    if (String.IsNullOrEmpty(container))
    {
        return null;
    }

    return this.PostDocxToContainer(docxFilename, DOCX_CONTENTTYPE, container);
}
```

4.11.3.23 **bool uk.ac.soton.ses.SwordClientHandler.PutToDocument (string *documentFileName*, string *endpoint*)**

Performs a PUT to the supplied endpoint with the supplied document filename using

DOCX_CONTENTTYPE

.

This will update an existing entry on the SWORD target

Parameters

documentFileName The filename of the document to use for the update

endpoint The endpoint against which the update should occur

Returns

Atom response

Definition at line 448 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMOREpositoryControl._-SubmitDocument(), uk.ac.soton.ses.SwordClientHandlerTests.TestPutOnly(), and uk.ac.soton.ses.SwordClientHandlerTests.TestPutToDocument().

```
{
    return this.PutToDocument(documentFileName, endpoint,
        DOCX_CONTENTTYPE);
}
```

4.11.3.24 `bool uk.ac.soton.ses.SwordClientHandler.PutToDocument (string documentFileName, string endpoint, string contentType)`

Performs a PUT to the supplied endpoint with the supplied document filename using the supplied content type.

This will update an existing entry on the SWORD target

Parameters

documentFileName The filename of the document to use for the update

endpoint The endpoint against which the update should occur

contentType The content type to use for the update

Returns

Atom response

Definition at line 461 of file SwordClientHandler.cs.

```
{
    HttpRequest wr = this.GetBasicAuthAtomWebRequest(endpoint);
    FileInfo fi = new FileInfo(documentFileName);
    wr.Method = "PUT";
    wr.Headers.Add("Content-Disposition", "form-data; name=\"" + fi.Name
+ "\"; filename=\"" + fi.Name + "\"");
    wr.ContentType = contentType;
    wr.ContentLength = fi.Length;
    wr.Headers.Add("X-Extract-Media", "true");
    wr.Headers.Add("X-Override-Metadata", "true");
    //wr.Headers.Add("Metadata-Relevant", "true");
    wr.Headers.Add("In-Progress", "true");
    this.WriteFileToRequest(documentFileName, wr);
    HttpResponseMessage response = null;
    try
    {
        response = (HttpResponseMessage)wr.GetResponse();
    }
    catch (WebException ex)
    {
        Debug.WriteLine(ex);
        if (ex.Response != null && ex.Response.Headers != null)
        {
            foreach (HttpHeader h in ex.Response.Headers)
            {
                Debug.WriteLine("Header: " + h.ToString());
            }
        }
    }

    if (response == null) { return false; }

    bool responseOk = false;
    if (response.StatusCode == HttpStatusCode.OK)
    {
        responseOk = true;
    }

    if (response != null)
    {
        response.Close();
    }
}
```

```
        return responseOk;
    }
```

4.11.3.25 internal void uk.ac.soton.ses.SwordClientHandler.ResolveInbox () [private]

Resolves the inbox based on the currently-supplied endpoint.

Definition at line 150 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestResolveInbox().

```
{
    // if we're not supposed to resolve the inbox, skip this step
    if (!this._resolveInbox)
    {
        return;
    }

    string inbox = HtmlScraper.GetAttributeContent(this._endpoint, "link"
, "rel", "SwordDeposit", "href");

    if (!String.IsNullOrEmpty(inbox))
    {
        this._endpoint = inbox;
    }
}
```

4.11.3.26 void uk.ac.soton.ses.SwordClientHandler.WriteFileToRequest (string filename, HttpWebRequest wr) [private]

Writes the file in

filename

to the web request

wr

.

This uses a buffer whose size is stored statically in

`BUFFER_SIZE`

to speed up the transfer

Parameters

filename The absolute filename to send

wr The web request on which to send the file

Definition at line 204 of file SwordClientHandler.cs.

```
{
    wr.Timeout = 15000;
```

```
using (Stream requestStream = wr.GetRequestStream())
{
    using (FileStream fs = File.OpenRead(filename))
    {
        int readCount;
        byte[] buffer = new byte[BUFFER_SIZE];
        while ((readCount = fs.Read(buffer, 0, buffer.Length)) != 0)
        {
            Debug.WriteLine(String.Format("Doing a block, at {0}", fs
.Position));
            requestStream.Write(buffer, 0, readCount);
        }
        Debug.WriteLine("Finished with input file");
    }
    Debug.WriteLine("Finished with output stream");
}
```

4.11.4 Member Data Documentation

4.11.4.1 string uk.ac.soton.ses.SwordClientHandler._endpoint [private]

The main repository endpoint.

Definition at line 83 of file SwordClientHandler.cs.

4.11.4.2 string uk.ac.soton.ses.SwordClientHandler._password [private]

The repository password.

Definition at line 78 of file SwordClientHandler.cs.

4.11.4.3 internal bool uk.ac.soton.ses.SwordClientHandler._resolveInbox = false [private]

TODO: Whether the inbox URL should be resolved from the HTML of the supplied endpoint.

TODO

Definition at line 68 of file SwordClientHandler.cs.

Referenced by uk.ac.soton.ses.SwordClientHandlerTests.TestResolveInbox().

4.11.4.4 string uk.ac.soton.ses.SwordClientHandler._username [private]

The repository username.

Definition at line 73 of file SwordClientHandler.cs.

4.11.4.5 int uk.ac.soton.ses.SwordClientHandler.BUFFER_SIZE = 16 * 1024 [static, private]

Buffer size for uploads in bytes.

Definition at line 40 of file SwordClientHandler.cs.

4.11.4.6 `string uk.ac.soton.ses.SwordClientHandler.DOCX_CONTENTTYPE =
"application/vnd.openxmlformats-officedocument.wordprocessingml.document"
[static, private]`

.docx content type

Definition at line 50 of file SwordClientHandler.cs.

4.11.4.7 `string uk.ac.soton.ses.SwordClientHandler.EP2_PACKAGING =
"http://eprints.org/ep2/data/2.0" [static, private]`

EP2 packaging header value.

Definition at line 45 of file SwordClientHandler.cs.

4.11.4.8 `string uk.ac.soton.ses.SwordClientHandler.EXTRACT_MEDIA = "true" [static,
private]`

Should media be extracted by default, or ignored? Note that this is going into a header so it should be a string rather than a Boolean.

Definition at line 62 of file SwordClientHandler.cs.

4.11.4.9 `string uk.ac.soton.ses.SwordClientHandler.LIST_RECORD_PATH = "/id/records"
[static, private]`

The path for listing records.

Definition at line 55 of file SwordClientHandler.cs.

4.11.5 Property Documentation

4.11.5.1 `string uk.ac.soton.ses.SwordClientHandler.Endpoint [set]`

Sets the endpoint associated with the repository.

Definition at line 111 of file SwordClientHandler.cs.

4.11.5.2 `string uk.ac.soton.ses.SwordClientHandler.Password [set]`

Sets the password associated with the repository.

Definition at line 100 of file SwordClientHandler.cs.

4.11.5.3 `string uk.ac.soton.ses.SwordClientHandler.Username [set]`

Sets the username associated with the repository.

Definition at line 89 of file SwordClientHandler.cs.

The documentation for this class was generated from the following file:

- Q:/Projects/SwordHandler/SwordHandler/SwordClientHandler.cs

4.12 uk.ac.soton.ses.SwordClientHandlerTests Class Reference

A series of basic tests for the .NET API.

Public Member Functions

- [SwordClientHandlerTests](#) (string [sword2User](#), string [sword2Password](#), string [sword2Endpoint](#))
- void [Run](#) ()

Private Member Functions

- void [TestDelete](#) ([SwordClientHandler](#) sword2Handler, string targetToDelete)
- void [TestPutOnly](#) ([SwordClientHandler](#) sword2Handler)
- void [TestPutToDocument](#) ([SwordClientHandler](#) sword2Handler)
- void [TestResolveInbox](#) ([SwordClientHandler](#) sword2Handler)
- void [TestDepositZipToEprint](#) ([SwordClientHandler](#) sword2Handler)
- void [TestDepositEprintsXml](#) ([SwordClientHandler](#) sword2Handler)
- void [TestGetInfo](#) ([SwordClientHandler](#) sword2Handler)
- void [TestList](#) ([SwordClientHandler](#) sword2Handler)
- void [TestAtomReader](#) ()
- void [TestCreateContainer](#) ([SwordClientHandler](#) sword2Handler)

Private Attributes

- string [sword2User](#) = null
- string [sword2Password](#) = null
- string [sword2Endpoint](#) = null
- internal string [EPRINT_TO_DELETE](#) = "http://depositmo.eprints.org/id/eprint/58"
- XmlWriterSettings [xws](#) = new XmlWriterSettings()
- XmlWriter [consoleWriter](#) = null
- XmlDocument [response](#) = null

4.12.1 Detailed Description

A series of basic tests for the .NET API.

Definition at line 30 of file [SwordClientHandlerTests.cs](#).

4.12.2 Constructor & Destructor Documentation

4.12.2.1 uk.ac.soton.ses.SwordClientHandlerTests.SwordClientHandlerTests (string *sword2User*, string *sword2Password*, string *sword2Endpoint*)

Definition at line 42 of file [SwordClientHandlerTests.cs](#).

```

{
    this.sword2User = sword2User;
    this.sword2Password = sword2Password;
    this.sword2Endpoint = sword2Endpoint;
    this.xws.Indent = true;
    this.consoleWriter = XmlWriter.Create(Console.Out, this.xws);
}

```

4.12.3 Member Function Documentation

4.12.3.1 void uk.ac.soton.ses.SwordClientHandlerTests.Run ()

Definition at line 51 of file SwordClientHandlerTests.cs.

```

{
    bool runAllTests = false;
    bool testPutToDocument = true;
    bool testDepositZipToEprint = false;
    bool testDepositEprintsXml = false;
    bool testAtomReader = false;
    bool testDelete = false;
    bool testList = false;
    bool testResolveInbox = false;
    bool testGetInfo = false;
    bool testCreateContainer = false;
    bool testPutOnly = false;

    SwordClientHandler sword2Handler = new SwordClientHandler(this.
sword2User, this.sword2Password, this.sword2Endpoint);

    if (testResolveInbox || runAllTests)
    {
        this.TestResolveInbox(sword2Handler);
    }

    if (testAtomReader || runAllTests)
    {
        this.TestAtomReader();
    }

    if (testDelete || runAllTests)
    {
        this.TestDelete(sword2Handler, EPRINT_TO_DELETE);
    }

    if (testDepositZipToEprint || runAllTests)
    {
        this.TestDepositZipToEprint(sword2Handler);
    }

    if (testPutToDocument || runAllTests)
    {
        TestPutToDocument(sword2Handler);
    }

    if (testDepositEprintsXml || runAllTests)
    {
        this.TestDepositEprintsXml(sword2Handler);
    }

    if (testList || runAllTests)
    {
        this.TestList(sword2Handler);
    }
}

```

```

    if (testGetInfo || runAllTests)
    {
        this.TestGetInfo(sword2Handler);
    }

    if (testCreateContainer || runAllTests)
    {
        this.TestCreateContainer(sword2Handler);
    }

    if (testPutOnly)
    {
        this.TestPutOnly(sword2Handler);
    }

    if (this.response != null)
    {
        response.WriteTo(consoleWriter);
        consoleWriter.Flush();
    }
}

```

4.12.3.2 void uk.ac.soton.ses.SwordClientHandlerTests.TestAtomReader () [private]

Definition at line 244 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordAtomReader.AtomId, uk.ac.soton.ses.SwordAtomReader.EditHref, and uk.ac.soton.ses.SwordAtomReader.EditMediaHref.

```

{
    XmlDocument atomResponse = new XmlDocument();
    //atomResponse.LoadXml(@"<?xml version=""1.0"" encoding=""UTF-8""?><a
    tom:entry xmlns:atom=""http://www.w3.org/2005/Atom"" xmlns:sword=""http://purl.or
    g/net/sword/""> <atom:title>On Testing the Atom Protocol...</atom:title> <atom:
    id>http://depositmo.eprints.org/id/eprint/40</atom:id> <atom:updated>2010-11-04T
    05:35:21Z</atom:updated> <atom:published>2006-10-25T00:45:02Z</atom:published>
    <atom:author> <atom:name>admin</atom:name> <atom:email>davetaz@ecs.soton.ac
    .uk</atom:email> </atom:author> <atom:summary type=""text"" /> <atom:content t
    ype=""text/xml"" src=""http://depositmo.eprints.org/id/document/206"" /> <atom:li
    nk rel=""edit-media"" href=""http://depositmo.eprints.org/id/document/206"" />
    <atom:link rel=""edit"" href=""http://depositmo.eprints.org/sword-app/atom/40.ato
    m"" /> <atom:generator uri=""http://depositmo.eprints.org"" version=""1.3"">Depo
    sitMO / SWORD 2 Endpoint [eprints-build-2010-11-26-r5991]</atom:generator> <swor
    d:treatment>Deposited items will remain in your user inbox until you manually sen
    d them for reviewing.</sword:treatment> <sword:packaging>http://eprints.org/ep2/
    data/2.0</sword:packaging> <sword:noOp>false</sword:noOp></atom:entry>");
    atomResponse.LoadXml(@"<entry>
    <title>A magical and modified document</title>
    <link rel=""self"" href=""http://depositmo.eprints.org/cgi/export/eprint/311/At
    om/depositmo-eprint-311.xml""/>
    <link rel=""edit"" href=""http://depositmo.eprints.org/id/eprint/311""/>
    <link rel=""edit-media"" href=""http://depositmo.eprints.org/id/eprint/311/cont
    ents""/>
    <link rel=""alternate"" href=""http://depositmo.eprints.org/id/eprint/311""/>
    <summary>Q., Hercules (2011) A magical and modified document.</summary>
    <updated>2011-03-03T08:01:37Z</updated>
    <id>http://depositmo.eprints.org/id/eprint/311</id>
    <category term=""article"" scheme=""http://depositmo.eprints.org/data/eprint#ty
    pe""/>
    <author>
        <name>Hercules Q.</name>
    </author>
    </entry>

```

```
");

    XmlWriterSettings xws = new XmlWriterSettings();
    xws.Indent = true;
    XmlWriter xw = XmlWriter.Create(Console.Out);
    atomResponse.WriteTo(xw);
    xw.Flush();

    SwordAtomReader sar = new SwordAtomReader(atomResponse);
    Console.WriteLine("EditMediaHref: " + sar.EditMediaHref);
    Console.WriteLine("EditHref: " + sar.EditHref);
    Console.WriteLine("AtomId: " + sar.AtomId);
}
```

4.12.3.3 void uk.ac.soton.ses.SwordClientHandlerTests.TestCreateContainer (SwordClientHandler *sword2Handler*) [private]

Definition at line 276 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordClientHandler.CreateContainer().

```
{
    string response = sword2Handler.CreateContainer();
    return;
}
```

4.12.3.4 void uk.ac.soton.ses.SwordClientHandlerTests.TestDelete (SwordClientHandler *sword2Handler*, string *targetToDelete*) [private]

Definition at line 124 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordClientHandler.Delete().

```
{
    Debug.WriteLine(String.Format("Deleting document at {0}", targetToDelete));
    XmlDocument atomResponse = sword2Handler.Delete(targetToDelete);
    Debug.WriteLine("Finished deletion test");
}
```

4.12.3.5 void uk.ac.soton.ses.SwordClientHandlerTests.TestDepositEprintsXml (SwordClientHandler *sword2Handler*) [private]

Definition at line 190 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordAtomReader.AtomId, and uk.ac.soton.ses.SwordClientHandler.DepositEprintsXml.

```
{
    Debug.WriteLine("Depositing XML file");
    XmlDocument xmlDocument = new XmlDocument();
    xmlDocument.Load(@"P:\tmp\depositmo_sword2_test_scripts\test-import.xml");
    this.response = sword2Handler.DepositEprintsXml(xmlDocument);
    SwordAtomReader sar = new SwordAtomReader(this.response);
    Debug.WriteLine("ID was " + sar.AtomId);
}
```

4.12.3.6 void uk.ac.soton.ses.SwordClientHandlerTests.TestDepositZipToEprint (SwordClientHandler *sword2Handler*) [private]

Definition at line 182 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordAtomReader.AtomId, and uk.ac.soton.ses.SwordClientHandler.DepositZipToEprint.

```
{
    Debug.WriteLine("Depositing zip file");
    this.response = sword2Handler.DepositZipToEprint(@"P:\tmp\depositmo_s
word2_test_scripts\pics.tar.gz");
    SwordAtomReader sar = new SwordAtomReader(this.response);
    Debug.WriteLine("ID was " + sar.AtomId);
}
```

4.12.3.7 void uk.ac.soton.ses.SwordClientHandlerTests.TestGetInfo (SwordClientHandler *sword2Handler*) [private]

Definition at line 200 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordAtomReader.AtomTitle, uk.ac.soton.ses.SwordAtomReader.ContentsHref, and uk.ac.soton.ses.SwordClientHandler.GetEprintInfo().

```
{
    this.response = sword2Handler.GetEprintInfo("http://bazaar.eprints.org/id/eprint/23");
    SwordAtomReader sar = new SwordAtomReader(this.response);
    Console.WriteLine("Atom title is {0}", sar.AtomTitle);
    Console.WriteLine("Contents href is {0}", sar.ContentsHref);

    Debug.WriteLine("Got info!");
}
```

4.12.3.8 void uk.ac.soton.ses.SwordClientHandlerTests.TestList (SwordClientHandler *sword2Handler*) [private]

Definition at line 210 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordClientHandler.ListRecords(), and uk.ac.soton.ses.SwordListEntry.Title.

```
{
    Debug.WriteLine("Retrieving listing");
    //XmlDocument xmlDoc = new XmlDocument();
    //this.response = sword2Handler.ListRecords();
    //Uri uri = new Uri("http://yomiko.ecs.soton.ac.uk:8027/more/parts/to
/this/");
    //string leftPart = uri.GetLeftPart(UriPartial.Authority);

    //XmlReader xr = XmlTextReader.Create(@"C:\listresults.xml");
    //this.response = new XmlDocument();
    //this.response.Load(@"C:\listresults.xml");
    //SwordListReader slr2 = new SwordListReader(this.response);

    //return;

    this.response = sword2Handler.ListRecords(true);
    //this.response.WriteTo(this.consoleWriter);
}
```

```

SwordListReader slr = new SwordListReader(this.response);

//XmlWriter xw=XmlTextWriter.Create(@"C:\listresults.xml");
//this.response.WriteTo(xw);
//xw.Close();

foreach (SwordListEntry sle in slr.Entries)
{
    Console.WriteLine("Title: " + sle.Title);
}

this.consoleWriter.Flush();
Console.Out.Flush();
Console.ReadKey();
}

```

4.12.3.9 void uk.ac.soton.ses.SwordClientHandlerTests.TestPutOnly (SwordClientHandler sword2Handler) [private]

Definition at line 131 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordClientHandler.PutToDocument().

```

{
    bool result = sword2Handler.PutToDocument(@"P:\tmp\hyb.docx", "http://
/depositmo.eprints.org/id/document/1736664");//"http://depositmo.eprints.org/id/d
ocument/1736641");
    return;
}

```

4.12.3.10 void uk.ac.soton.ses.SwordClientHandlerTests.TestPutToDocument (SwordClientHandler sword2Handler) [private]

Definition at line 137 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordClientHandler.PostDocxToRepository(), and uk.ac.soton.ses.SwordClientHandler.PutToDocument().

```

{
    Debug.WriteLine("Depositing new .docx");
    //XmlDocument atomResponse = sword2Handler.DepositDocxToEprint(@"P:\t
mp\hy.docx");
    string locationHeader = sword2Handler.PostDocxToRepository(@"P:\tmp\h
y.docx");

    Debug.WriteLine("Initialising Atom response reader");
    /*
    SwordAtomReader sar = new SwordAtomReader(atomResponse);

    Debug.WriteLine("Title was " + sar.AtomTitle);
    Debug.WriteLine("Edit media href is " + sar.EditMediaHref);
    Debug.WriteLine("Contents href is " + sar.ContentsHref);*/
    /*
    XmlDocument dereference = sword2Handler.GetAtomXml(sar.EditMediaHref)
;
    XmlDocument subdocument = new XmlDocument();
    XmlNamespaceManager xmlns = new XmlNamespaceManager(dereference.NameT
able);
    //xmlns.AddNamespace("default", "");

```

```

        //xmlns.AddNamespace("atom", "http://www.w3.org/2005/Atom");
        xmlns.AddNamespace(String.Empty, "http://www.w3.org/2005/Atom");
        subdocument.AppendChild(dereference.SelectSingleNode("//feed", xmlns)
    );

    SwordAtomReader sar2 = new SwordAtomReader(subdocument);
    */

    Debug.WriteLine("Attempting to update document after a few seconds ..
.");
    Thread.Sleep(30 * 1000);
    //bool result = sword2Handler.PutToDocument(@"P:\tmp\hyb.docx", sar.E
ditMediaHref);
    bool result = sword2Handler.PutToDocument(@"P:\tmp\hyb.docx", locatio
nHeader); //sar.ContentHref);

    // note that until at least 15th December 2010, this response is not
Atom XML so
    // the following is/was not valid. However, the update to the title w
as occurring

    Debug.WriteLine("Update result: " + result.ToString());
}

```

4.12.3.11 void uk.ac.soton.ses.SwordClientHandlerTests.TestResolveInbox (SwordClientHandler sword2Handler) [private]

Definition at line 173 of file SwordClientHandlerTests.cs.

References uk.ac.soton.ses.SwordClientHandler._resolveInbox, and uk.ac.soton.ses.SwordClientHandler.ResolveInbox().

```

{
    bool origvalue = sword2Handler._resolveInbox;
    sword2Handler._resolveInbox = true;
    sword2Handler.ResolveInbox();
    // leave things as we found them
    sword2Handler._resolveInbox = origvalue;
}

```

4.12.4 Member Data Documentation

4.12.4.1 XmlWriter uk.ac.soton.ses.SwordClientHandlerTests.consoleWriter = null [private]

Definition at line 39 of file SwordClientHandlerTests.cs.

4.12.4.2 internal string uk.ac.soton.ses.SwordClientHandlerTests.EPRINT_TO_DELETE = "http://depositmo.eprints.org/id/eprint/58" [private]

Definition at line 36 of file SwordClientHandlerTests.cs.

4.12.4.3 XmlDocument uk.ac.soton.ses.SwordClientHandlerTests.response = null [private]

Definition at line 40 of file SwordClientHandlerTests.cs.

4.12.4.4 `string uk.ac.soton.ses.SwordClientHandlerTests.sword2Endpoint = null`
`[private]`

Definition at line 34 of file SwordClientHandlerTests.cs.

4.12.4.5 `string uk.ac.soton.ses.SwordClientHandlerTests.sword2Password = null`
`[private]`

Definition at line 33 of file SwordClientHandlerTests.cs.

4.12.4.6 `string uk.ac.soton.ses.SwordClientHandlerTests.sword2User = null` `[private]`

Definition at line 32 of file SwordClientHandlerTests.cs.

4.12.4.7 `XmlWriterSettings uk.ac.soton.ses.SwordClientHandlerTests.xws = new`
`XmlWriterSettings() [private]`

Definition at line 38 of file SwordClientHandlerTests.cs.

The documentation for this class was generated from the following file:

- Q:/Projects/SwordHandler/SwordHandler/SwordClientHandlerTests.cs

4.13 uk.ac.soton.ses.SwordListAuthor Class Reference

SWORD author.

Public Member Functions

- [SwordListAuthor](#) (string [name](#))
Author.

Properties

- string [Name](#) [get, set]
Gets or sets the author's name.

Private Attributes

- string [name](#)

4.13.1 Detailed Description

SWORD author.

Definition at line 28 of file SwordListReader.cs.

4.13.2 Constructor & Destructor Documentation

4.13.2.1 uk.ac.soton.ses.SwordListAuthor.SwordListAuthor (string *name*)

Author.

Parameters

name Author's name

Definition at line 41 of file SwordListReader.cs.

```
{
    this.Name = name;
}
```

4.13.3 Member Data Documentation

4.13.3.1 string uk.ac.soton.ses.SwordListAuthor.name [private]

Definition at line 30 of file SwordListReader.cs.

4.13.4 Property Documentation

4.13.4.1 string uk.ac.soton.ses.SwordListAuthor.Name [get, set]

Gets or sets the author's name.

Definition at line 35 of file SwordListReader.cs.

The documentation for this class was generated from the following file:

- Q:/Projects/SwordHandler/SwordHandler/SwordListReader.cs

4.14 uk.ac.soton.ses.SwordListEntry Class Reference

SWORD entry for the collection list.

Public Member Functions

- void [AddAuthor](#) (string *name*)
*Adds the author
name
to the entry.*
- [SwordListEntry](#) (string *title*)
Creates a new entry for the collection with the supplied title.

Properties

- string [Title](#) [get, set]
Title of the entry.
- string [Href](#) [get, set]
Href to the entry.
- string [Summary](#) [get, set]
Summary of the entry.
- DateTime [Updated](#) [get, set]
Update time of the entry.
- string [Id](#) [get, set]
ID of the entry.
- List< [SwordListAuthor](#) > [Authors](#) [get]
List of authors for the entry.

Private Attributes

- string [title](#)
- string [href](#)
- string [summary](#)
- DateTime [updated](#)
- string [id](#)
- List< [SwordListAuthor](#) > [authors](#)

4.14.1 Detailed Description

SWORD entry for the collection list.

Definition at line 50 of file SwordListReader.cs.

4.14.2 Constructor & Destructor Documentation

4.14.2.1 uk.ac.soton.ses.SwordListEntry.SwordListEntry (string *title*)

Creates a new entry for the collection with the supplied title.

Parameters

title Entry title

Definition at line 103 of file SwordListReader.cs.

```
{  
    this.authors = new List<SwordListAuthor>();  
    this.Title = title;  
}
```

4.14.3 Member Function Documentation

4.14.3.1 void uk.ac.soton.ses.SwordListEntry.AddAuthor (string *name*)

Adds the author

name

to the entry.

Parameters

name Author name

Definition at line 93 of file SwordListReader.cs.

Referenced by uk.ac.soton.ses.SwordListReader.ParseEntries().

```
{
    SwordListAuthor author = new SwordListAuthor(name);
    this.authors.Add(author);
}
```

4.14.4 Member Data Documentation

4.14.4.1 List<SwordListAuthor> uk.ac.soton.ses.SwordListEntry.authors [private]

Definition at line 57 of file SwordListReader.cs.

4.14.4.2 string uk.ac.soton.ses.SwordListEntry.href [private]

Definition at line 53 of file SwordListReader.cs.

4.14.4.3 string uk.ac.soton.ses.SwordListEntry.id [private]

Definition at line 56 of file SwordListReader.cs.

4.14.4.4 string uk.ac.soton.ses.SwordListEntry.summary [private]

Definition at line 54 of file SwordListReader.cs.

4.14.4.5 string uk.ac.soton.ses.SwordListEntry.title [private]

Definition at line 52 of file SwordListReader.cs.

4.14.4.6 DateTime uk.ac.soton.ses.SwordListEntry.updated [private]

Definition at line 55 of file SwordListReader.cs.

4.14.5 Property Documentation

4.14.5.1 `List<SwordListAuthor> uk.ac.soton.ses.SwordListEntry.Authors` [get]

List of authors for the entry.

Definition at line 87 of file `SwordListReader.cs`.

4.14.5.2 `string uk.ac.soton.ses.SwordListEntry.Href` [get, set]

Href to the entry.

Definition at line 67 of file `SwordListReader.cs`.

4.14.5.3 `string uk.ac.soton.ses.SwordListEntry.Id` [get, set]

ID of the entry.

Definition at line 82 of file `SwordListReader.cs`.

Referenced by `uk.ac.soton.ses.SwordListReader.GetEntryById()`, and `uk.ac.soton.ses.SwordListReader.ParseEntries()`.

4.14.5.4 `string uk.ac.soton.ses.SwordListEntry.Summary` [get, set]

Summary of the entry.

Definition at line 72 of file `SwordListReader.cs`.

Referenced by `uk.ac.soton.ses.SwordListReader.ParseEntries()`.

4.14.5.5 `string uk.ac.soton.ses.SwordListEntry.Title` [get, set]

Title of the entry.

Definition at line 62 of file `SwordListReader.cs`.

Referenced by `uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositaryControl.DumpListingToLog()`, and `uk.ac.soton.ses.SwordClientHandlerTests.TestList()`.

4.14.5.6 `DateTime uk.ac.soton.ses.SwordListEntry.Updated` [get, set]

Update time of the entry.

Definition at line 77 of file `SwordListReader.cs`.

Referenced by `uk.ac.soton.ses.Word2010DepositMOAddIn.DepositMORepositaryControl.DumpListingToLog()`, and `uk.ac.soton.ses.SwordListReader.ParseEntries()`.

The documentation for this class was generated from the following file:

- `Q:/Projects/SwordHandler/SwordHandler/SwordListReader.cs`

4.15 uk.ac.soton.ses.SwordListReader Class Reference

SWORD list reader.

Public Member Functions

- [SwordListReader](#) (XmlDocument [swordListXml](#))
Creates a new [SwordListReader](#) from the supplied listing document.
- [SwordListEntry GetEntryById](#) (string id)
Returns the entry that matches the supplied ID.

Properties

- List< [SwordListEntry](#) > [Entries](#) [get]
List of entries in the collection.

Private Member Functions

- internal void [ParseEntries](#) ()
Parses the entries in the supplied document and populates the list.

Private Attributes

- XmlDocument [swordListXml](#) = null
- XmlNamespaceManager [xnm](#) = null
- string [title](#)
- DateTime [updated](#)
- List< [SwordListEntry](#) > [entries](#) = new List<[SwordListEntry](#)>()

4.15.1 Detailed Description

SWORD list reader.

Definition at line 113 of file SwordListReader.cs.

4.15.2 Constructor & Destructor Documentation

4.15.2.1 uk.ac.soton.ses.SwordListReader.SwordListReader (XmlDocument *swordListXml*)

Creates a new [SwordListReader](#) from the supplied listing document.

Parameters

swordListXml XML document containing list of entries

Definition at line 132 of file SwordListReader.cs.

```
{
    this.swordListXml = swordListXml;
    if (this.swordListXml != null)
    {
        this.xnm = new XmlNamespaceManager(this.swordListXml.NameTable);

        this.xnm.AddNamespace("atom", "http://www.w3.org/2005/Atom");
    }
    this.ParseEntries();
}
```

4.15.3 Member Function Documentation

4.15.3.1 SwordListEntry uk.ac.soton.ses.SwordListReader.GetEntryById (string *id*)

Returns the entry that matches the supplied ID.

Parameters

id ID to match

Returns

Matching entry, else null

Definition at line 149 of file SwordListReader.cs.

References uk.ac.soton.ses.SwordListEntry.Id.

```
{
    foreach (SwordListEntry sle in this.Entries)
    {
        if (sle.Id.Equals(id))
        {
            return sle;
        }
    }
    return null;
}
```

4.15.3.2 internal void uk.ac.soton.ses.SwordListReader.ParseEntries () [private]

Parses the entries in the supplied document and populates the list.

Definition at line 164 of file SwordListReader.cs.

References uk.ac.soton.ses.SwordListEntry.AddAuthor(), uk.ac.soton.ses.SwordListEntry.Id, uk.ac.soton.ses.SwordListEntry.Summary, and uk.ac.soton.ses.SwordListEntry.Updated.

```
{
    if (this.swordListXml == null)
    {
        // don't parse a null document
        return;
    }
}
```

```
        this.title = this.swordListXml.SelectSingleNode("/atom:feed/atom:titl
e", this.xnm).InnerText;
        this.updated = DateTime.Parse(this.swordListXml.SelectSingleNode("/at
om:feed/atom:updated", this.xnm).InnerText);

        // get entries
        XmlNodeList nodeList = this.swordListXml.SelectNodes("/atom:feed/atom
:entry", this.xnm);
        foreach (XmlNode node in nodeList)
        {
            SwordListEntry sle = new SwordListEntry(node.SelectSingleNode("at
om:title", this.xnm).InnerText);
            sle.Updated = DateTime.Parse(node.SelectSingleNode("atom:updated"
, this.xnm).InnerText);
            sle.Id = node.SelectSingleNode("atom:id", this.xnm).InnerText;
            sle.Summary = node.SelectSingleNode("atom:summary", this.xnm).Inn
erText;
            XmlNodeList authorList = node.SelectNodes("atom:author", this.
xnm);
            foreach (XmlNode author in authorList)
            {
                sle.AddAuthor(author.SelectSingleNode("atom:name", this.xnm).
InnerText);
            }
            this.Entries.Add(sle);
        }
        return;
    }
```

4.15.4 Member Data Documentation

4.15.4.1 List<SwordListEntry> uk.ac.soton.ses.SwordListReader.entries = new List<SwordListEntry>() [private]

Definition at line 121 of file SwordListReader.cs.

4.15.4.2 XmlDocument uk.ac.soton.ses.SwordListReader.swordListXml = null [private]

Definition at line 115 of file SwordListReader.cs.

4.15.4.3 string uk.ac.soton.ses.SwordListReader.title [private]

Definition at line 118 of file SwordListReader.cs.

4.15.4.4 DateTime uk.ac.soton.ses.SwordListReader.updated [private]

Definition at line 119 of file SwordListReader.cs.

4.15.4.5 XmlNamespaceManager uk.ac.soton.ses.SwordListReader.xnm = null [private]

Definition at line 116 of file SwordListReader.cs.

4.15.5 Property Documentation

4.15.5.1 `List<SwordListEntry> uk.ac.soton.ses.SwordListReader.Entries` [get]

List of entries in the collection.

Definition at line 126 of file `SwordListReader.cs`.

The documentation for this class was generated from the following file:

- `Q:/Projects/SwordHandler/SwordHandler/SwordListReader.cs`

4.16 `uk.ac.soton.ses.Word2010DepositMOAddIn.ThisRibbonCollection` Class Reference

Properties

- internal `Word2010DepositMORibbon Word2010DepositMORibbon` [get]

Private Member Functions

- internal `ThisRibbonCollection` (`global::Microsoft.Office.Tools.Ribbon.RibbonFactory factory`)

4.16.1 Detailed Description

Definition at line 231 of file `Word2010DepositMOAddIn.Designer.cs`.

4.16.2 Constructor & Destructor Documentation

4.16.2.1 internal `uk.ac.soton.ses.Word2010DepositMOAddIn.ThisRibbonCollection.ThisRibbonCollection (global::Microsoft.Office.Tools.Ribbon.RibbonFactory factory) [private]`

Definition at line 234 of file `Word2010DepositMOAddIn.Designer.cs`.

```

        :
        base(factory) {
    }

```

4.16.3 Property Documentation

4.16.3.1 internal `Word2010DepositMORibbon uk.ac.soton.ses.Word2010DepositMOAddIn.ThisRibbonCollection.Word2010DepositMORibbon [get, private]`

Definition at line 196 of file `Word2010DepositMORibbon.Designer.cs`.

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMOAddIn.Design
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMORibbon.Design

4.17 uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn Class Reference

Entry point for the Microsoft Word 2010 DepositMO add-in.

Public Member Functions

- [Word2010DepositMOAddIn](#) (global::Microsoft.Office.Tools.Word.ApplicationFactory factory, global::System.IServiceProvider serviceProvider)

Protected Member Functions

- override void [Initialize](#) ()
- override void [FinishInitialization](#) ()
- override void [InitializeDataBindings](#) ()
- override void [OnShutdown](#) ()

Properties

- internal string [DefaultEndpoint](#) [get, set]
Gets or sets the default endpoint.
- internal string [DefaultUsername](#) [get, set]
Gets or sets the default username.
- internal string [DefaultPassword](#) [get, set]
Gets or sets the default password.
- internal uint [SubmissionThreadCount](#) [get]
Gets the number of active submission threads.

Private Member Functions

- internal Core.DocumentProperties [GetActiveDocumentProperties](#) ()
Gets the properties of the active document.
- internal void [IncrementSubmissionThreadCount](#) ()
Increments the thread count.
- internal void [DecrementSubmissionThreadCount](#) ()
Decrements the thread count.

- string [GetActiveSubmissionString](#) ()
Returns a formatted string containing the current pending submission summary.
- internal void [LogMessage](#) (string message)
Logs the message
message
to Word's status bar, any debug tracers and the log string list on this instance.
- void [AddMessageToLogStack](#) (string message)
Adds the message to the log stack, and purges the log stack if the size exceeds the maximum.
- internal string[] [GetAllLogMessages](#) ()
Returns the log stack as a string array.
- internal void [SetSingleLineTextBox](#) (string text, TextBox textBox)
Sets the value of
textBox
to
text
, in a thread-safe manner.
- delegate void [SetTextCallback](#) (string message, TextBox textBox)
Text set callback delegate for
textBox
.
- internal void [LogMessage](#) (string message, TextBox textBox)
Logs the message to the internal stack, debug output (if appropriate) and the supplied text box.
- internal void [MakeAllInvisible](#) ()
For every task pane that can be made invisible, make it invisible.
- internal void [MakeAllVisible](#) ()
Makes each available task pane and any child controls visible, and shows the associated control.
- void [ThisAddIn_Startup](#) (object sender, System.EventArgs e)
Called when the plug-in is started.
- void [AddRepositoryControl](#) ()
Adds a new repository control panel to the list and adds it to the custom task panes group.
- void [Application_DocumentOpen](#) (Word.Document Doc)
Event method to be called when a document is opened (or created, or focus switched, the latter of which is handled by the repository control add method.
- void [ThisAddIn_Shutdown](#) (object sender, System.EventArgs e)
Event triggered when the add-in is shut down.
- void [InternalStartup](#) ()
Required method for Designer support - do not modify the contents of this method with the code editor.
- void [InitializeCachedData](#) ()

- void [InitializeData](#) ()
- void [BindToData](#) ()
- void [StartCaching](#) (string MemberName)
- void [StopCaching](#) (string MemberName)
- bool [IsCached](#) (string MemberName)
- void [BeginInitialization](#) ()
- void [EndInitialization](#) ()
- void [InitializeControls](#) ()
- void [InitializeComponents](#) ()
- bool [NeedsFill](#) (string MemberName)

Private Attributes

- string [defaultEndpoint](#) = ""
The default endpoint for new controls (could be "").
- string [defaultUsername](#) = ""
The default username for new controls (could be "").
- string [defaultPassword](#) = ""
The default password for new controls (could be "").
- internal List< [DepositMORepositryControl](#) > [repositoryControls](#) = new List<[DepositMORepositryControl](#)>()
A list of all the repository controls the addin deals with.
- uint [submissionThreadCounter](#) = 0
The number of active submission threads.
- List< String > [log](#) = new List<string>()
Internal log buffer.
- internal Microsoft.Office.Tools.CustomTaskPaneCollection [CustomTaskPanels](#)
- internal Microsoft.Office.Tools.SmartTagCollection [VstoSmartTags](#)
- global::System.Object [missing](#) = global::System.Type.Missing
- internal Microsoft.Office.Interop.Word.Application [Application](#)

Static Private Attributes

- static readonly object [lockobj](#) = new object()
Lock object for threading.
- static int [MAX_LOG_LINES](#) = 32 * 1024
Maximum number of lines to store in the internal log buffer.
- static int [PURGE_NUMBER_OF_LOG_LINES](#) = 1 * 1024
*Number of lines by which to reduce the log buffer if
MAX_LOG_LINES
is reached.*

4.17.1 Detailed Description

Entry point for the Microsoft Word 2010 DepositMO add-in.

Definition at line 31 of file Word2010DepositMOAddIn.cs.

4.17.2 Constructor & Destructor Documentation

4.17.2.1 **uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.Word2010DepositMOAddIn** (**global::Microsoft.Office.Tools.Word.ApplicationFactory** *factory*, **global::System.IServiceProvider** *serviceProvider*)

Definition at line 33 of file Word2010DepositMOAddIn.Designer.cs.

```

        :
        base(factory, serviceProvider, "AddIn", "ThisAddIn") {
        Globals.Factory = factory;
    }

```

4.17.3 Member Function Documentation

4.17.3.1 **void** **uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.AddMessageToLogStack** (**string** *message*) [**private**]

Adds the message to the log stack, and purges the log stack if the size exceeds the maximum.

Parameters

message Message to log

Definition at line 164 of file Word2010DepositMOAddIn.cs.

```

{
    this.log.Add(message);
    if (this.log.Count > MAX_LOG_LINES)
    {
        this.log.RemoveRange(0, PURGE_NUMBER_OF_LOG_LINES);
    }
}

```

4.17.3.2 **void** **uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.AddRepositoryControl** () [**private**]

Adds a new repository control panel to the list and adds it to the custom task panes group.

Definition at line 307 of file Word2010DepositMOAddIn.cs.

```

{
    if (this.Application.Documents.Count == 0)
    {
        // COM will throw an exception if we try to do anything with Acti
    }
}

```

```
veWindow (even a test for null)
    // if there are no open documents
    return;
}

foreach (CustomTaskPane ctp in this.CustomTaskPanes)
{
    try
    {
        if (ctp != null && ctp.Window != null && ctp.Control != null
        && !ctp.Control.Disposing && ctp.Window == this.Application.ActiveWindow)
        {
            // we already have a control for this task pane so don't
            continue to add a new one
            return;
        }
    }
    catch (COMException cex)
    {
        this.LogMessage("Could not check for taskpane addition; full
        COM exception follows:");
        this.LogMessage(cex.ToString());
        this.LogMessage("You may wish to restart Microsoft Word");
        return;
    }
}

// create a new repository control, add it to the internal list and a
dd it to
// a custom task pane associated with this document window
DepositMORepositoryControl dmrc = new DepositMORepositoryControl();
this.repositoryControls.Add(dmrc);
this.CustomTaskPanes.Add(dmrc, "Repository control", this.
Application.ActiveWindow);
}
```

4.17.3.3 void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.Application_
DocumentOpen (Word.Document *Doc*) [private]

Event method to be called when a document is opened (or created, or focus switched, the latter of which is handled by the repository control add method.

Parameters

Doc The associated Word document

Definition at line 347 of file Word2010DepositMOAddIn.cs.

```
{
    // add a new repository control when a new document has been created
    // (not ideal, but Word will otherwise end up with multiple panels pe
r document)
    this.AddRepositoryControl();
}
```

4.17.3.4 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.BeginInitialization () [private]

Definition at line 124 of file Word2010DepositMOAddIn.Designer.cs.

```
        {  
            this.BeginInit();  
            this.CustomTaskPanels.BeginInit();  
            this.VstoSmartTags.BeginInit();  
        }
```

4.17.3.5 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.BindToData () [private]

Definition at line 96 of file Word2010DepositMOAddIn.Designer.cs.

```
        {  
        }
```

4.17.3.6 internal void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.DecrementSubmissionThrea () [private]

Decrements the thread count.

Definition at line 110 of file Word2010DepositMOAddIn.cs.

```
    {  
        lock (lockobj)  
        {  
            this.submissionThreadCounter--;  
            this.LogMessage(this.GetActiveSubmissionString());  
        }  
    }
```

4.17.3.7 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.EndInitialization () [private]

Definition at line 134 of file Word2010DepositMOAddIn.Designer.cs.

```
        {  
            this.VstoSmartTags.EndInit();  
            this.CustomTaskPanels.EndInit();  
            this.EndInit();  
        }
```

4.17.3.8 override void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.FinishInitialization
() [protected]

Definition at line 57 of file Word2010DepositMOAddIn.Designer.cs.

```
        {  
            this.InternalStartup();  
            this.OnStartup();  
        }
```

4.17.3.9 internal Core.DocumentProperties
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.GetActiveDocumentProperties
() [private]

Gets the properties of the active document.

Returns

Definition at line 74 of file Word2010DepositMOAddIn.cs.

```
{  
    return (Core.DocumentProperties)Globals.Word2010DepositMOAddIn.Applic  
ation.ActiveDocument.BuiltInDocumentProperties;  
}
```

4.17.3.10 string
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.GetActiveSubmissionString
() [private]

Returns a formatted string containing the current pending submission summary.

Returns

Definition at line 123 of file Word2010DepositMOAddIn.cs.

```
{  
    return String.Format("{0} submission{1} currently active", this.  
SubmissionThreadCount, (this.SubmissionThreadCount == 1) ? "" : "s");  
}
```

4.17.3.11 internal string []
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.GetAllLogMessages
() [private]

Returns the log stack as a string array.

Returns

String array of log messages

TODO: add some size management here

Definition at line 177 of file Word2010DepositMOAddIn.cs.

```
{
    return this.log.ToArray();
}
```

4.17.3.12 internal void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.IncrementSubmissionThreadCount() [**private**]

Increments the thread count.

Definition at line 98 of file Word2010DepositMOAddIn.cs.

```
{
    lock (lockobj)
    {
        this.submissionThreadCounter++;
        this.LogMessage(this.GetActiveSubmissionString());
    }
}
```

4.17.3.13 override void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.Initialize() [**protected**]

Definition at line 42 of file Word2010DepositMOAddIn.Designer.cs.

```
{
    base.Initialize();
    this.Application = this.GetHostItem<Microsoft.Office.Interop.Word.Application>(typeof(Microsoft.Office.Interop.Word.Application), "Application");
    Globals.Word2010DepositMOAddIn = this;
    global::System.Windows.Forms.Application.EnableVisualStyles();
    this.InitializeCachedData();
    this.InitializeControls();
    this.InitializeComponents();
    this.InitializeData();
}
```

4.17.3.14 void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.InitializeCachedData() [**private**]

Definition at line 76 of file Word2010DepositMOAddIn.Designer.cs.

```
{
    if ((this.DataHost == null)) {
```



```

        return;
    }
    if (this.DataHost.IsCacheInitialized) {
        this.DataHost.FillCachedData(this);
    }
}

```

4.17.3.15 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.InitializeComponents () [private]

Definition at line 153 of file Word2010DepositMOAddIn.Designer.cs.

```

{
}

```

4.17.3.16 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.InitializeControls () [private]

Definition at line 144 of file Word2010DepositMOAddIn.Designer.cs.

```

{
    this.CustomTaskPanels = Globals.Factory.CreateCustomTaskPaneCollection
(null, null, "CustomTaskPanels", "CustomTaskPanels", this);
    this.VstoSmartTags = Globals.Factory.CreateSmartTagCollection(null, null,
"VstoSmartTags", "VstoSmartTags", this);
}

```

4.17.3.17 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.InitializeData () [private]

Definition at line 89 of file Word2010DepositMOAddIn.Designer.cs.

```

{
}

```

4.17.3.18 override void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.InitializeDataBindings () [protected]

Definition at line 66 of file Word2010DepositMOAddIn.Designer.cs.

```

{
    this.BeginInitialization();
    this.BindToData();
    this.EndInitialization();
}

```

4.17.3.19 void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.InternalStartup
() [private]

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 379 of file Word2010DepositMOAddIn.cs.

```
{
    this.Startup += new System.EventHandler(ThisAddIn_Startup);
    this.Shutdown += new System.EventHandler(ThisAddIn_Shutdown);
}
```

4.17.3.20 bool
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.IsCached
(string MemberName) [private]

Definition at line 116 of file Word2010DepositMOAddIn.Designer.cs.

```
{
    return this.DataHost.IsCached(this, MemberName);
}
```

4.17.3.21 internal void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.LogMessage
(string message, TextBox textBox) [private]

Logs the message to the internal stack, debug output (if appropriate) and the supplied text box.

Thread-safe

Parameters

message The message to log

textBox The text box to which to log

Definition at line 216 of file Word2010DepositMOAddIn.cs.

```
{
    if (textBox.InvokeRequired)
    {
        SetTextCallback tc = new SetTextCallback(LogMessage);
        textBox.Invoke(tc, new Object[] { message, textBox });
    }
    else
    {
        if (textBox != null && !textBox.Disposing && !textBox.IsDisposed)
        {
            textBox.AppendText(message + Environment.NewLine);
        }

        // call the regular logger only if the invoke isn't required to
        // avoid multiple messages appearing in the other logs
        this.LogMessage(message);
    }
}
```

4.17.3.22 **internal void** **uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.LogMessage** **(string message) [private]**

Logs the message

message

to Word's status bar, any debug tracers and the log string list on this instance.

Parameters

message The log message

Definition at line 152 of file Word2010DepositMOAddIn.cs.

```
{
    Globals.Word2010DepositMOAddIn.Application.StatusBar = message;
    Debug.WriteLine(message);
    this.AddMessageToLogStack(message);
}
```

4.17.3.23 **internal void** **uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.MakeAllInvisible** **() [private]**

For every task pane that can be made invisible, make it invisible.

Definition at line 240 of file Word2010DepositMOAddIn.cs.

```
{
    foreach (CustomTaskPane c in this.CustomTaskPanes)
    {
        if (c != null)
        {
            c.Visible = false;
        }
    }
}
```

4.17.3.24 **internal void** **uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.MakeAllVisible** **() [private]**

Makes each available task pane and any child controls visible, and shows the associated control.

Also cleans up task panes where the child control is null.

Definition at line 256 of file Word2010DepositMOAddIn.cs.

```
{
    // make all of the custom task panes visible, along with their contro
ls
    foreach (CustomTaskPane c in this.CustomTaskPanes)
    {
        if (c != null)
```

```

        {
            c.Visible = true;
            if (c.Control != null)
            {
                c.Control.Show();
                c.Control.Visible = true;
            }
            else
            {
                // the control itself is null, so dispose of the pane
                c.Dispose();
            }
        }
    }
    // ensure the repository controls are also visible
    foreach (DepositMORepositoryControl dmrc in this.repositoryControls)
    {
        dmrc.Visible = true;
        dmrc.Show();
    }
}

```

4.17.3.25 bool

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.NeedsFill
(string *MemberName*) [private]

Definition at line 159 of file Word2010DepositMOAddIn.Designer.cs.

```

        {
            return this.DataHost.NeedsFill(this, MemberName);
        }

```

4.17.3.26 override void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.OnShutdown
() [protected]

Definition at line 167 of file Word2010DepositMOAddIn.Designer.cs.

```

        {
            this.VstoSmartTags.Dispose();
            this.CustomTaskPanels.Dispose();
            base.OnShutdown();
        }

```

4.17.3.27 internal void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.SetSingleLineTextBox
(string *text*, TextBox *textBox*) [private]

Sets the value of

`textBox`

to

`text`

, in a thread-safe manner.

Parameters

text The target value for

`textBox`

textBox The text box form control to set

Definition at line 189 of file Word2010DepositMOAddIn.cs.

```
{
    if (textBox.InvokeRequired)
    {
        SetTextCallback tc = new SetTextCallback(SetSingleLineTextBox);
        textBox.Invoke(tc, new Object[] { text, textBox });
    }
    else
    {
        textBox.Text = text;
    }
}
```

4.17.3.28 delegate void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.SetTextCallback
(string *message*, TextBox *textBox*) [**private**]

Text set callback delegate for

`textBox`

.

Needed for invocation by thread-safe text box value updater

Parameters

message

textBox

4.17.3.29 void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.StartCaching
(string *MemberName*) [**private**]

Definition at line 102 of file Word2010DepositMOAddIn.Designer.cs.

```
{
    this.DataHost.StartCaching(this, MemberName);
}
```

4.17.3.30 void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.StopCaching
(string *MemberName*) [private]

Definition at line 109 of file Word2010DepositMOAddIn.Designer.cs.

```
        {  
            this.DataHost.StopCaching(this, MemberName);  
        }
```

4.17.3.31 void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.ThisAddIn_
Shutdown (object *sender*, System.EventArgs *e*) [private]

Event triggered when the add-in is shut down.

Note that we will wait briefly for threads to clean up here, but this will 'lock' Word when the user tries to close if a submission is in limbo (and causing Task Manager-level 'force quits'). As at this point the user won't have received a 'successfully submitted' message, and there's no guarantee that the document has been submitted. Word itself will terminate the threads after a short while

Parameters

sender Sender object

e Event arguments

Definition at line 363 of file Word2010DepositMOAddIn.cs.

```
{  
    string statusText = "Shutting down DepositMO plugin";  
    if (this.SubmissionThreadCount > 0)  
    {  
        statusText += String.Format("; {0} - you will have to check these manually", this.GetActiveSubmissionString());  
    }  
    this.Application.StatusBar = statusText;  
}
```

4.17.3.32 void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.ThisAddIn_
Startup (object *sender*, System.EventArgs *e*) [private]

Called when the plug-in is started.

Parameters

sender Sender

e Event arguments

Definition at line 289 of file Word2010DepositMOAddIn.cs.

```
{
    // when the addin is started, create a new repository control
    // and place an event to repeat this when a document is opened
    this.AddRepositoryControl();

    // no independent event handler for a new document, only [new|open|fo
cus] or [open]
    //this.Application.DocumentOpen += new Word.ApplicationEvents4_Docume
ntOpenEventHandler(Application_DocumentOpen);
    this.Application.DocumentChange += new Word.ApplicationEvents4_Docume
ntChangeEventHandler(AddRepositoryControl);

    // log version and timestamp for diagnostics
    this.LogMessage("Started " + System.Reflection.Assembly.GetExecutingA
sssembly().FullName + " at " + DateTime.Now);
}
```

4.17.4 Member Data Documentation

4.17.4.1 internal Microsoft.Office.Interop.Word.Application uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.Application [private]

Definition at line 28 of file Word2010DepositMOAddIn.Designer.cs.

4.17.4.2 internal Microsoft.Office.Tools.CustomTaskPaneCollection uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.CustomTaskPanes [private]

Definition at line 20 of file Word2010DepositMOAddIn.Designer.cs.

4.17.4.3 string uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.defaultEndpoint = "" [private]

The default endpoint for new controls (could be "").

Definition at line 37 of file Word2010DepositMOAddIn.cs.

4.17.4.4 string uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.defaultPassword = "" [private]

The default password for new controls (could be "").

Definition at line 47 of file Word2010DepositMOAddIn.cs.

4.17.4.5 string uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.defaultUsername = "" [private]

The default username for new controls (could be "").

Definition at line 42 of file Word2010DepositMOAddIn.cs.

4.17.4.6 readonly object

```
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.lockobj =
new object() [static, private]
```

Lock object for threading.

Definition at line 83 of file Word2010DepositMOAddIn.cs.

4.17.4.7 List<String>

```
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.log = new
List<string>() [private]
```

Internal log buffer.

Definition at line 145 of file Word2010DepositMOAddIn.cs.

4.17.4.8 int uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.MAX_LOG_LINES = 32 * 1024 [static, private]

Maximum number of lines to store in the internal log buffer.

Definition at line 134 of file Word2010DepositMOAddIn.cs.

4.17.4.9 global::System.Object

```
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.missing =
global::System.Type.Missing [private]
```

Definition at line 25 of file Word2010DepositMOAddIn.Designer.cs.

4.17.4.10 int

```
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.PURGE_
NUMBER_OF_LOG_LINES = 1 * 1024 [static, private]
```

Number of lines by which to reduce the log buffer if

MAX_LOG_LINES

is reached.

Note this should be less than

MAX_LOG_LINES

.

Definition at line 140 of file Word2010DepositMOAddIn.cs.

4.17.4.11 internal List<DepositMOREpositoryControl>

```
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.repositoryControls
= new List<DepositMOREpositoryControl>() [private]
```

A list of all the repository controls the addin deals with.

Definition at line 68 of file Word2010DepositMOAddIn.cs.

4.17.4.12 `uint`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.submissionThreadCounter`
`= 0 [private]`

The number of active submission threads.

Definition at line 88 of file Word2010DepositMOAddIn.cs.

4.17.4.13 `internal Microsoft.Office.Tools.SmartTagCollection`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.VstoSmartTags`
`[private]`

Definition at line 22 of file Word2010DepositMOAddIn.Designer.cs.

4.17.5 Property Documentation

4.17.5.1 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.DefaultEndpoint`
`[get, set, private]`

Gets or sets the default endpoint.

Definition at line 52 of file Word2010DepositMOAddIn.cs.

4.17.5.2 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.DefaultPassword`
`[get, set, private]`

Gets or sets the default password.

Definition at line 62 of file Word2010DepositMOAddIn.cs.

4.17.5.3 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.DefaultUsername`
`[get, set, private]`

Gets or sets the default username.

Definition at line 57 of file Word2010DepositMOAddIn.cs.

4.17.5.4 `internal uint`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMOAddIn.SubmissionThreadCount`
`[get, private]`

Gets the number of active submission threads.

Definition at line 93 of file Word2010DepositMOAddIn.cs.

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMOAddIn.cs
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMOAddIn.Designer.cs

4.18 uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon Class Reference

Ribbon interface for Microsoft Word 2010 DepositMO add-in.

Public Member Functions

- [Word2010DepositMORibbon \(\)](#)
The constructor for the DepositMO Word ribbon.

Protected Member Functions

- override void [Dispose](#) (bool disposing)
Clean up any resources being used.

Private Member Functions

- void [Word2010DepositMORibbon_Load](#) (object sender, RibbonUIEventArgs e)
Event triggered when the ribbon is loaded.
- void [Word2010DepositMOMainGroup_DialogLauncherClick](#) (object sender, RibbonControlEventArgs e)
Event triggered when the first group's dialogue launcher is selected (bottom-right miniature icon).
- void [quickSubmissionRibbonGroup_DialogLauncherClick](#) (object sender, RibbonControlEventArgs e)
Event triggered when the quick submission dialogue launcher is selected (bottom-right miniature icon).
- void [Word2010DepositMOREpositoryButton_Click](#) (object sender, RibbonControlEventArgs e)
Event triggered when the show panel button is clicked.
- void [Word2010DepositMOREpositoryHideButton_Click](#) (object sender, RibbonControlEventArgs e)
Event triggered when the hide panel button is clicked.
- void [quickSubmitButton_Click](#) (object sender, RibbonControlEventArgs e)
Event triggered when the quick submit button is clicked.
- void [aboutRibbonButton_Click](#) (object sender, RibbonControlEventArgs e)
Event triggered when the about button is clicked.
- void [InitializeComponent](#) ()
Required method for Designer support - do not modify the contents of this method with the code editor.

Private Attributes

- internal string [quickUsername](#) = null
- internal string [quickPassword](#) = null
- System.ComponentModel.IContainer [components](#) = null
Required designer variable.
- internal Microsoft.Office.Tools.Ribbon.RibbonTab [tab1](#)
- Microsoft.Office.Tools.Ribbon.RibbonTab [Word2010DepositMORibbonTab](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonGroup [Word2010DepositMOMainGroup](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonButton [Word2010DepositMORepositaryButton](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonButton [Word2010DepositMORepositaryHideButton](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonGroup [quickSubmissionRibbonGroup](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonEditBox [endpointEditBox](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonButton [quickSubmitButton](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonGroup [aboutRibbonGroup](#)
- internal Microsoft.Office.Tools.Ribbon.RibbonButton [aboutRibbonButton](#)

4.18.1 Detailed Description

Ribbon interface for Microsoft Word 2010 DepositMO add-in.

Definition at line 28 of file Word2010DepositMORibbon.cs.

4.18.2 Constructor & Destructor Documentation

4.18.2.1 uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMORibbon ()

The constructor for the DepositMO Word ribbon.

Definition at line 29 of file Word2010DepositMORibbon.Designer.cs.

```
        : base(Globals.Factory.GetRibbonFactory())
    {
        InitializeComponent();
    }
```

4.18.3 Member Function Documentation

4.18.3.1 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.aboutRibbonButton_Click (object sender, RibbonControlEventArgs e) [private]

Event triggered when the about button is clicked.

Launches the about box

Parameters

sender Event sender

e Event arguments

Definition at line 105 of file Word2010DepositMORibbon.cs.

```
{
    AboutBox aboutBox = new AboutBox();
    aboutBox.ShowDialog((System.Windows.Forms.IWin32Window)Globals.Ribbon
s.GetRibbon<Word2010DepositMORibbon>().Container);
}
```

4.18.3.2 override void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Dispose (
bool disposing) [protected]

Clean up any resources being used.

Parameters

disposing true if managed resources should be disposed; otherwise, false.

Definition at line 39 of file Word2010DepositMORibbon.Designer.cs.

```
{
    if (disposing && (components != null))
    {
        components.Dispose();
    }
    base.Dispose(disposing);
}
```

4.18.3.3 void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.InitializeComponent
() [private]

Required method for Designer support - do not modify the contents of this method with the code editor.

Definition at line 54 of file Word2010DepositMORibbon.Designer.cs.

```
{
    Microsoft.Office.Tools.Ribbon.RibbonDialogLauncher ribbonDialogLaunch
erImpl1 = this.Factory.CreateRibbonDialogLauncher();
    Microsoft.Office.Tools.Ribbon.RibbonDialogLauncher ribbonDialogLaunch
erImpl2 = this.Factory.CreateRibbonDialogLauncher();
    System.ComponentModel.ComponentResourceManager resources = new System
.ComponentModel.ComponentResourceManager(typeof(Word2010DepositMORibbon));
    this.tab1 = this.Factory.CreateRibbonTab();
    this.Word2010DepositMORibbonTab = this.Factory.CreateRibbonTab();
    this.Word2010DepositMOMainGroup = this.Factory.CreateRibbonGroup();
    this.Word2010DepositMORepositaryButton = this.Factory.CreateRibbonBut
ton();
    this.Word2010DepositMORepositaryHideButton = this.Factory.CreateRibbon
Button();
    this.quickSubmissionRibbonGroup = this.Factory.CreateRibbonGroup();
    this.endpointEditBox = this.Factory.CreateRibbonEditBox();
    this.quickSubmitButton = this.Factory.CreateRibbonButton();
    this.aboutRibbonGroup = this.Factory.CreateRibbonGroup();
    this.aboutRibbonButton = this.Factory.CreateRibbonButton();
    this.tab1.SuspendLayout();
}
```

```
this.Word2010DepositMORibbonTab.SuspendLayout();
this.Word2010DepositMOMainGroup.SuspendLayout();
this.quickSubmissionRibbonGroup.SuspendLayout();
this.aboutRibbonGroup.SuspendLayout();
//
// tab1
//
this.tab1.ControlId.ControlIdType = Microsoft.Office.Tools.Ribbon.RibbonControlIdType.Office;
this.tab1.Label = "TabAddIns";
this.tab1.Name = "tab1";
//
// Word2010DepositMORibbonTab
//
this.Word2010DepositMORibbonTab.Groups.Add(this.Word2010DepositMOMainGroup);
this.Word2010DepositMORibbonTab.Groups.Add(this.quickSubmissionRibbonGroup);
this.Word2010DepositMORibbonTab.Groups.Add(this.aboutRibbonGroup);
this.Word2010DepositMORibbonTab.KeyTip = "DEP";
this.Word2010DepositMORibbonTab.Label = "DepositMO 2010";
this.Word2010DepositMORibbonTab.Name = "Word2010DepositMORibbonTab";
//
// Word2010DepositMOMainGroup
//
this.Word2010DepositMOMainGroup.DialogLauncher = ribbonDialogLauncherImpl1;
this.Word2010DepositMOMainGroup.Items.Add(this.Word2010DepositMORepositoryButton);
this.Word2010DepositMOMainGroup.Items.Add(this.Word2010DepositMORepositoryHideButton);
this.Word2010DepositMOMainGroup.Label = "Repository control";
this.Word2010DepositMOMainGroup.Name = "Word2010DepositMOMainGroup";
//
// Word2010DepositMORepositoryButton
//
this.Word2010DepositMORepositoryButton.ControlSize = Microsoft.Office.Core.RibbonControlSize.RibbonControlSizeLarge;
this.Word2010DepositMORepositoryButton.Image = global::uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.DocumentImage;
this.Word2010DepositMORepositoryButton.Label = "Show";
this.Word2010DepositMORepositoryButton.Name = "Word2010DepositMORepositoryButton";
this.Word2010DepositMORepositoryButton.ScreenTip = "Displays the repository control panels if they aren't already shown";
this.Word2010DepositMORepositoryButton.ShowImage = true;
this.Word2010DepositMORepositoryButton.Click += new Microsoft.Office.Tools.Ribbon.RibbonControlEventHandler(this.Word2010DepositMORepositoryButton_Click);
//
// Word2010DepositMORepositoryHideButton
//
this.Word2010DepositMORepositoryHideButton.ControlSize = Microsoft.Office.Core.RibbonControlSize.RibbonControlSizeLarge;
this.Word2010DepositMORepositoryHideButton.Image = global::uk.ac.soton.ses.Word2010DepositMOAddIn.Properties.Resources.DocumentImage;
this.Word2010DepositMORepositoryHideButton.Label = "Hide";
this.Word2010DepositMORepositoryHideButton.Name = "Word2010DepositMORepositoryHideButton";
this.Word2010DepositMORepositoryHideButton.ScreenTip = "Hides the repository controls if they're visible";
this.Word2010DepositMORepositoryHideButton.ShowImage = true;
this.Word2010DepositMORepositoryHideButton.Click += new Microsoft.Office.Tools.Ribbon.RibbonControlEventHandler(this.Word2010DepositMORepositoryHideButton_Click);
//
// quickSubmissionRibbonGroup
```

```

        //
        this.quickSubmissionRibbonGroup.DialogLauncher = ribbonDialogLauncher
Impl2;
        this.quickSubmissionRibbonGroup.Items.Add(this.endpointEditBox);
        this.quickSubmissionRibbonGroup.Items.Add(this.quickSubmitButton);
        this.quickSubmissionRibbonGroup.Label = "Quick submission";
        this.quickSubmissionRibbonGroup.Name = "quickSubmissionRibbonGroup";
        //
        // endpointEditBox
        //
        this.endpointEditBox.Label = "Endpoint";
        this.endpointEditBox.Name = "endpointEditBox";
        this.endpointEditBox.SizeString = "http://depositmo.eprints.org/sword
-app/deposit/inbox";
        this.endpointEditBox.SuperTip = "The endpoint against which submissio
n will occur";
        this.endpointEditBox.Text = null;
        //
        // quickSubmitButton
        //
        this.quickSubmitButton.Image = global::uk.ac.soton.ses.Word2010Deposi
tMOAddIn.Properties.Resources.DocumentImage;
        this.quickSubmitButton.Label = "Submit";
        this.quickSubmitButton.Name = "quickSubmitButton";
        this.quickSubmitButton.ShowImage = true;
        this.quickSubmitButton.SuperTip = resources.GetString("quickSubmitBut
ton.SuperTip");
        this.quickSubmitButton.Click += new Microsoft.Office.Tools.Ribbon.Rib
bonControlEventHandler(this.quickSubmitButton_Click);
        //
        // aboutRibbonGroup
        //
        this.aboutRibbonGroup.Items.Add(this.aboutRibbonButton);
        this.aboutRibbonGroup.Label = "About";
        this.aboutRibbonGroup.Name = "aboutRibbonGroup";
        //
        // aboutRibbonButton
        //
        this.aboutRibbonButton.ControlSize = Microsoft.Office.Core.RibbonCont
rolSize.RibbonControlSizeLarge;
        this.aboutRibbonButton.Image = global::uk.ac.soton.ses.Word2010Deposi
tMOAddIn.Properties.Resources.DocumentImage;
        this.aboutRibbonButton.Label = "About DepositMO 2010";
        this.aboutRibbonButton.Name = "aboutRibbonButton";
        this.aboutRibbonButton.ShowImage = true;
        this.aboutRibbonButton.SuperTip = "Displays some information about th
e DepositMO Word author add-in";
        this.aboutRibbonButton.Click += new Microsoft.Office.Tools.Ribbon.Rib
bonControlEventHandler(this.aboutRibbonButton_Click);
        //
        // Word2010DepositMORibbon
        //
        this.Name = "Word2010DepositMORibbon";
        this.RibbonType = "Microsoft.Word.Document";
        this.Tabs.Add(this.tab1);
        this.Tabs.Add(this.Word2010DepositMORibbonTab);
        this.Load += new Microsoft.Office.Tools.Ribbon.RibbonUIEventHandler(t
his.Word2010DepositMORibbon_Load);
        this.tab1.ResumeLayout(false);
        this.tab1.PerformLayout();
        this.Word2010DepositMORibbonTab.ResumeLayout(false);
        this.Word2010DepositMORibbonTab.PerformLayout();
        this.Word2010DepositMOMainGroup.ResumeLayout(false);
        this.Word2010DepositMOMainGroup.PerformLayout();
        this.quickSubmissionRibbonGroup.ResumeLayout(false);
        this.quickSubmissionRibbonGroup.PerformLayout();
        this.aboutRibbonGroup.ResumeLayout(false);

```

```
        this.aboutRibbonGroup.PerformLayout();  
    }
```

4.18.3.4 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.quickSubmissionRibbonGroup. DialogLauncherClick (object sender, RibbonControlEventArgs e) [private]

Event triggered when the quick submission dialogue launcher is selected (bottom-right miniature icon).

Brings up the quick submission form

Parameters

sender Event sender

e Event arguments

Definition at line 63 of file Word2010DepositMORibbon.cs.

```
{  
    QuickSubmitForm qsf = new QuickSubmitForm();  
    // this really can't find the parent window!  
    qsf.ShowDialog((System.Windows.Forms.IWin32Window)Globals.RibbonGroup.  
Ribbon<Word2010DepositMORibbon>().Container);  
}
```

4.18.3.5 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.quickSubmitButton_ Click (object sender, RibbonControlEventArgs e) [private]

Event triggered when the quick submit button is clicked.

Parameters

sender Event sender

e Event arguments

Definition at line 95 of file Word2010DepositMORibbon.cs.

```
{  
    this.quickSubmissionRibbonGroup.DialogLauncherClick(sender, e);  
}
```

4.18.3.6 void uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMOMainGroup. DialogLauncherClick (object sender, RibbonControlEventArgs e) [private]

Event triggered when the first group's dialogue launcher is selected (bottom-right miniature icon).

Brings up the log viewer

Parameters

sender Event sender

e Event arguments

Definition at line 51 of file Word2010DepositMORibbon.cs.

```
{
    LogViewerForm lvf = new LogViewerForm();
    lvf.Show();
}
```

4.18.3.7 void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMORepos
Click (object *sender*, RibbonControlEventArgs *e*) [private]

Event triggered when the show panel button is clicked.

Parameters

sender Event sender

e Event arguments

Definition at line 75 of file Word2010DepositMORibbon.cs.

```
{
    Globals.Word2010DepositMOAddIn.MakeAllVisible();
}
```

4.18.3.8 void

uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMORepos
Click (object *sender*, RibbonControlEventArgs *e*) [private]

Event triggered when the hide panel button is clicked.

Parameters

sender Event sender

e Event arguments

Definition at line 85 of file Word2010DepositMORibbon.cs.

```
{
    Globals.Word2010DepositMOAddIn.MakeAllInvisible();
}
```


4.18.3.9 void
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMORibbon
Load (object *sender*, RibbonEventArgs *e*) [private]

Event triggered when the ribbon is loaded.

Parameters

sender Event sender

e Event arguments

Definition at line 38 of file Word2010DepositMORibbon.cs.

```
{
    this.endpointEditBox.Text = Globals.Word2010DepositMOAddIn.DefaultEnd
point;
    this.quickSubmissionRibbonGroup.DialogLauncherClick += new RibbonCont
rolEventHandler (quickSubmissionRibbonGroup_DialogLauncherClick);
    this.Word2010DepositMOMainGroup.DialogLauncherClick += new RibbonCont
rolEventHandler (Word2010DepositMOMainGroup_DialogLauncherClick);
}
```

4.18.4 Member Data Documentation

4.18.4.1 internal Microsoft.Office.Tools.Ribbon.RibbonButton
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.aboutRibbonButton
[private]

Definition at line 190 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.2 internal Microsoft.Office.Tools.Ribbon.RibbonGroup
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.aboutRibbonGroup
[private]

Definition at line 189 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.3 System.ComponentModel.IContainer
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.components
= null [private]

Required designer variable.

Definition at line 24 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.4 internal Microsoft.Office.Tools.Ribbon.RibbonEditBox
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.endpointEditBox
[private]

Definition at line 187 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.5 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.quickPassword`
`= null [private]`

Definition at line 31 of file Word2010DepositMORibbon.cs.

4.18.4.6 `internal Microsoft.Office.Tools.Ribbon.RibbonGroup`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.quickSubmissionRibbonGr`
`[private]`

Definition at line 186 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.7 `internal Microsoft.Office.Tools.Ribbon.RibbonButton`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.quickSubmitButton`
`[private]`

Definition at line 188 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.8 `internal string`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.quickUsername`
`= null [private]`

Definition at line 30 of file Word2010DepositMORibbon.cs.

4.18.4.9 `internal Microsoft.Office.Tools.Ribbon.RibbonTab`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.tab1`
`[private]`

Definition at line 181 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.10 `internal Microsoft.Office.Tools.Ribbon.RibbonGroup`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMOMain`
`[private]`

Definition at line 183 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.11 `internal Microsoft.Office.Tools.Ribbon.RibbonButton`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMOREpo`
`[private]`

Definition at line 184 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.12 `internal Microsoft.Office.Tools.Ribbon.RibbonButton`
`uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMOREpo`
`[private]`

Definition at line 185 of file Word2010DepositMORibbon.Designer.cs.

4.18.4.13 Microsoft.Office.Tools.Ribbon.RibbonTab
uk.ac.soton.ses.Word2010DepositMOAddIn.Word2010DepositMORibbon.Word2010DepositMORibbon
[private]

Definition at line 182 of file Word2010DepositMORibbon.Designer.cs.

The documentation for this class was generated from the following files:

- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMORibbon.cs
- Q:/Projects/Word2010DepositMOAddIn/Word2010DepositMOAddIn/Word2010DepositMORibbon.Designer.cs

Index

[_SubmitDocument](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, [18](#)

[_ThisRibbonCollection](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::GlobalApplication, [38](#)

[_Word2010DepositMOAddIn](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::GlobalApplication_DocumentOpen, [38](#)

[_endpoint](#)
uk::ac::soton::ses::SwordClientHandler, [89](#)

[_factory](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::GlobalAssemblyCompany, [38](#)

[_password](#)
uk::ac::soton::ses::SwordClientHandler, [89](#)

[_resolveInbox](#)
uk::ac::soton::ses::SwordClientHandler, [89](#)

[_username](#)
uk::ac::soton::ses::SwordClientHandler, [89](#)

[AboutBox](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, [10](#)

[aboutRibbonButton](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, [131](#)

[aboutRibbonButton_Click](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, [125](#)

[aboutRibbonGroup](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, [131](#)

[AddAuthor](#)
uk::ac::soton::ses::SwordListEntry, [101](#)

[AddMessageToLogStack](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, [110](#)

[addRepository](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, [21](#)

[AddRepositoryControl](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, [110](#)

[addToGroupButton](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, [111](#)

[AssemblyCopyright](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, [15](#)

[AssemblyDescription](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, [15](#)

[AssemblyProduct](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, [15](#)

[AssemblyTitle](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, [15](#)

[AssemblyVersion](#)
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, [15](#)

[AtomContentSrc](#)
uk::ac::soton::ses::SwordAtomReader, [67](#)

[AtomContentType](#)
uk::ac::soton::ses::SwordAtomReader, [67](#)

[AtomGenerator](#)
uk::ac::soton::ses::SwordAtomReader, [67](#)

[AtomGeneratorUri](#)
uk::ac::soton::ses::SwordAtomReader, [67](#)

[AtomGeneratorVersion](#)
uk::ac::soton::ses::SwordAtomReader, [67](#)

[AtomId](#)
uk::ac::soton::ses::SwordAtomReader, [67](#)

[AtomPublished](#)
uk::ac::soton::ses::SwordAtomReader, [68](#)

[AtomSummary](#)

uk::ac::soton::ses::SwordAtomReader, 68	uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 48
AtomTitle	48
uk::ac::soton::ses::SwordAtomReader, 68	copyButton_Click
AtomUpdated	uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 46
uk::ac::soton::ses::SwordAtomReader, 68	46
AtomXml	CreateContainer
uk::ac::soton::ses::SwordAtomReader, 68	uk::ac::soton::ses::SwordClientHandler, 74
atomXml	Culture
uk::ac::soton::ses::SwordAtomReader, 67	uk::ac::soton::ses::Word2010DepositMOAddIn::Properties::RepositoryControl, 62
Authors	62
uk::ac::soton::ses::SwordListEntry, 102	CustomTaskPanels
authors	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 121
uk::ac::soton::ses::SwordListEntry, 101	121
BeginInitialization	DecrementSubmissionThreadCount
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 111	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 112
111	112
BindToData	Default
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 111	uk::ac::soton::ses::Word2010DepositMOAddIn::Properties::RepositoryControl, 63
111	63
BUFFER_SIZE	DefaultEndpoint
uk::ac::soton::ses::SwordClientHandler, 89	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 123
89	123
cancelButton	defaultEndpoint
uk::ac::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 54	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 121
54	121
cancelButton_Click	defaultInstance
uk::ac::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 50	uk::ac::soton::ses::Word2010DepositMOAddIn::Properties::RepositoryControl, 63
50	63
closeButton	DefaultPassword
uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 48	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 123
48	123
closeButton_Click	defaultPassword
uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 45	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 121
45	121
components	DefaultUsername
uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, 14	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 123
14	123
uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 34	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 121
34	121
uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 48	48
uk::ac::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 54	uk::ac::soton::ses::SwordClientHandler, 74
54	74
uk::ac::soton::ses::Word2010DepositMOAddIn::RepositoryControl, 59	uk::ac::soton::ses::SwordClientHandler, 75
59	75
uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 131	uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 75, 76
131	75, 76
consoleWriter	DepositMORepositoryControl
uk::ac::soton::ses::SwordClientHandlerTests, 97	uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 18
97	18
ContentsHref	DepositMORepositoryControl_Load
uk::ac::soton::ses::SwordAtomReader, 68	uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 23
68	23
copyButton	23

- DepositXml
 - uk::ac::soton::ses::SwordClientHandler, 76, 77
- DepositZipToEprint
 - uk::ac::soton::ses::SwordClientHandler, 77, 78
- Dispose
 - uk::ac::soton::ses::Word2010DepositMOAddIn::ActiveSubmissionForm, 10
 - uk::ac::soton::ses::Word2010DepositMOAddIn::FastDepositMORepositoryControl, 23
 - uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 46
 - uk::ac::soton::ses::Word2010DepositMOAddIn::QuickSubmissionForm, 50
 - uk::ac::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 56
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, 125
- DocumentImage
 - uk::ac::soton::ses::Word2010DepositMOAddIn::PropertiesResources, 62
- documentLocationLabel
 - uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 34
- documentLocationTextBox
 - uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 35
- DOCX_CONTENTTYPE
 - uk::ac::soton::ses::SwordClientHandler, 89
- DumpListingToLog
 - uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 24
- EditHref
 - uk::ac::soton::ses::SwordAtomReader, 68
- EditMediaHref
 - uk::ac::soton::ses::SwordAtomReader, 69
- EndInitialization
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddInClientHandler, 112
- Endpoint
 - uk::ac::soton::ses::SwordClientHandler, 90
- endpoint
 - uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 37
 - uk::ac::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 60
- endpointEditBox
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, 131
- Entries
 - uk::ac::soton::ses::SwordListReader, 106
- entries
 - uk::ac::soton::ses::SwordListReader, 105
 - EP2_PACKAGING
 - uk::ac::soton::ses::SwordClientHandler, 90
 - EPRINT_TO_DELETE
 - uk::ac::soton::ses::SwordClientHandlerTests, 97
 - EXTRACT_MEDIA
 - uk::ac::soton::ses::SwordClientHandler, 90
 - FastDepositMORepositoryControl, uk::ac::soton::ses::Word2010DepositMOAddIn::Globals, 39
 - LogViewerForm, FinishInitialization
 - QuickSubmissionForm, Word2010DepositMOAddIn::Word2010DepositMORibbon, 112
 - RepositoryGroupUserControl, GetActiveDocumentProperties
 - Word2010DepositMORibbon, Word2010DepositMOAddIn::Word2010DepositMOAddInClientHandler, 112
 - GetActiveSubmissionString
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddInClientHandler, 113
 - GetAllLogMessages
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddInClientHandler, 113
 - GetAttributeContent
 - uk::ac::soton::ses::HtmlScraper, 40
 - GetBasicAuthAtomWebRequest
 - uk::ac::soton::ses::SwordClientHandler, 78, 79
 - GetEntryById
 - uk::ac::soton::ses::SwordListReader, 104
 - GetEprintInfo
 - uk::ac::soton::ses::SwordClientHandler, 80
 - GetMetaContent
 - uk::ac::soton::ses::HtmlScraper, 43, 44
 - GetMultipleNodes
 - uk::ac::soton::ses::SwordAtomReader, 65
 - GetResponseLocation
 - uk::ac::soton::ses::Word2010DepositMOAddInClientHandler, 80
 - GetSingleNode
 - uk::ac::soton::ses::SwordAtomReader, 65
 - GetXmlResponse
 - uk::ac::soton::ses::SwordClientHandler, 80
 - DepositMORepositoryControl, uk::ac::soton::ses::SwordAtomReader, 66
 - RepositoryGroupUserControl, uk::ac::soton::ses::SwordAtomReader, 66
 - GetXPathValue
 - uk::ac::soton::ses::Word2010DepositMORibbon, 131
 - Globals
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Globals, 38
 - groupRepositoryGroupBox

- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 35
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 115
- Href
 - uk::acc::soton::ses::SwordListEntry, 102
- href
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- labelCopyright
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- labelProductName
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- labelVersion
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- identLabel
 - uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 59
- IncrementSubmissionThreadCount
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 113
- Initialize
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 114
- InitializeCachedData
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 114
- InitializeComponent
 - log
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 10
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 24
 - uk::acc::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 46
 - uk::acc::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 50
 - uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 57
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, 126
- InitializeComponents
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 114
- InitializeControls
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 115
- InitializeData
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 115
- InitializeDataBindings
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 115
- InternalStartup
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 115
- labelCompanyName
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- labelProductVersion
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- labelVersion
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- LIST_RECORD_PATH
 - uk::acc::soton::ses::SwordClientHandler, 90
- listRecords
 - uk::acc::soton::ses::SwordClientHandler, 81, 82
- lockWord
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 35
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 121
- log
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 10
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORepositoryControl, 24
 - uk::acc::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 46
 - uk::acc::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 50
 - uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 57
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon, 126
- logoPictureBox
 - uk::acc::soton::ses::Word2010DepositMOAddIn::AboutBox, 14
- logTextBox
 - uk::acc::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 46
- LogViewerForm
 - uk::acc::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 46
- MakeAllInvisible
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 117
- MakeAllVisible
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 117

- uk::acc::soton::ses::Word2010DepositMOAddInRepositoryGroupUserControl, 59
- uk::acc::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 54
- repositoryLocationTextBox 36
- uk::acc::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 54
- uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 59
- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORE, 31
- ResolveInbox 59
- uk::acc::soton::ses::SwordClientHandler, 87
- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORE, 32
- resourceCulture 61
- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORE, 36
- resourceMan 61
- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORE, 33
- ResourceManager 62
- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORE, 36
- Resources 61
- uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMORE, 33
- response 97
- uk::acc::soton::ses::SwordClientHandlerTests, Summary 102
- Ribbons 39
- uk::acc::soton::ses::Word2010DepositMOAddIn::Globals, 101
- Run 92
- uk::acc::soton::ses::SwordClientHandlerTests, sword2Endpoint 97
- uk::acc::soton::ses::SwordClientHandlerTests, sword2Password 98
- SetSingleLineTextBox 118
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 98
- SetTextCallback 119
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 65
- StartCaching 119
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddInClientHandler, 73
- StopCaching 119
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 99
- submissionLogTextBox 36
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddInRepositoryControl, 100
- SubmissionThreadCount 123
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddInReader, 103
- submissionThreadCounter 122
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 105
- uk::acc::soton::ses::SwordAtomReader, 69

- Endpoint, 90
- EP2_PACKAGING, 90
- EXTRACT_MEDIA, 90
- GetBasicAuthAtomWebRequest, 78, 79
- GetEprintInfo, 80
- GetResponseLocation, 80
- GetXmlResponse, 80
- LIST_RECORD_PATH, 90
- ListRecords, 81, 82
- Password, 90
- PostDocxToContainer, 83, 84
- PostDocxToRepository, 85
- PutToDocument, 86
- ResolveInbox, 87
- SwordClientHandler, 73
- Username, 90
- WriteFileToRequest, 88
- uk::ac::soton::ses::SwordClientHandlerTests, 91
 - consoleWriter, 97
 - EPRINT_TO_DELETE, 97
 - response, 97
 - Run, 92
 - sword2Endpoint, 97
 - sword2Password, 98
 - sword2User, 98
 - SwordClientHandlerTests, 91
 - TestAtomReader, 93
 - TestCreateContainer, 94
 - TestDelete, 94
 - TestDepositEprintsXml, 94
 - TestDepositZipToEprint, 94
 - TestGetInfo, 95
 - TestList, 95
 - TestPutOnly, 96
 - TestPutToDocument, 96
 - TestResolveInbox, 97
 - xws, 98
- uk::ac::soton::ses::SwordListAuthor, 98
 - Name, 99
 - name, 99
 - SwordListAuthor, 99
- uk::ac::soton::ses::SwordListEntry, 99
 - AddAuthor, 101
 - Authors, 102
 - authors, 101
 - Href, 102
 - href, 101
 - Id, 102
 - id, 101
 - Summary, 102
 - summary, 101
 - SwordListEntry, 100
 - Title, 102
 - title, 101
 - Updated, 102
 - updated, 101
- uk::ac::soton::ses::SwordListReader, 103
 - Entries, 106
 - entries, 105
 - GetEntryById, 104
 - ParseEntries, 104
 - SwordListReader, 103
 - swordListXml, 105
 - title, 105
 - updated, 105
 - xnm, 105
- uk::ac::soton::ses::Word2010DepositMOAddIn::AboutBox, 9
 - AboutBox, 10
 - AssemblyCompany, 15
 - AssemblyCopyright, 15
 - AssemblyDescription, 15
 - AssemblyProduct, 15
 - AssemblyTitle, 15
 - AssemblyVersion, 15
 - components, 14
 - Dispose, 10
 - InitializeComponent, 10
 - labelCompanyName, 14
 - labelCopyright, 14
 - labelProductName, 14
 - labelVersion, 14
 - logoPictureBox, 14
 - okButton, 14
 - okButton_Click, 13
 - tableLayoutPanel, 14
 - textBoxDescription, 14
- uk::ac::soton::ses::Word2010DepositMOAddIn::DepositMORepository, 15
 - _SubmitDocument, 18
 - addRepository, 21
 - addToGroupButton, 34
 - addToGroupButton_Click, 22
 - components, 34
 - DepositMORepositoryControl, 18
 - DepositMORepositoryControl_Load, 23
 - Dispose, 23
 - documentLocationLabel, 34
 - documentLocationTextBox, 35
 - DumpListingToLog, 24
 - endpoint, 37
 - groupRepositoryGroupBox, 35
 - InitializeComponent, 24
 - lockobj, 35
 - logException, 30
 - logMessage, 30
 - messagesGroupBox, 35

- password, 37
- passwordLabel, 35
- passwordTextBox, 35
- removeFromGroupButton, 35
- removeFromGroupButton_Click, 30
- repositoryCollectionTabControl, 35
- repositoryControlGroupBox, 36
- repositoryLocationLabel, 36
- repositoryLocationTextBox, 36
- submissionLogTextBox, 36
- SubmitDocument, 31
- submitToAll, 32
- submitToAllButton, 36
- submitToAllButton_Click, 33
- submitToThisRepositoryButton, 36
- submitToThisRepositoryButton_Click, 33
- updateEprintButton, 36
- updateEprintButton_Click, 33
- username, 37
- usernameLabel, 36
- usernameTextBox, 37
- WarningBox, 34
- uk::ac::soton::ses::Word2010DepositMOAddIn::GlobalIdentLabel, 37
 - _ThisRibbonCollection, 38
 - _Word2010DepositMOAddIn, 38
 - _factory, 38
 - Factory, 39
 - Globals, 38
 - Ribbons, 39
 - Word2010DepositMOAddIn, 39
- uk::ac::soton::ses::Word2010DepositMOAddIn::LogViewerForm, 44
 - closeButton, 48
 - closeButton_Click, 45
 - components, 48
 - copyButton, 48
 - copyButton_Click, 46
 - Dispose, 46
 - InitializeComponent, 46
 - logTextBox, 48
 - LogViewerForm, 45
- uk::ac::soton::ses::Word2010DepositMOAddIn::PropertyResource, 61
 - Culture, 62
 - DocumentImage, 62
 - resourceCulture, 61
 - resourceMan, 61
 - ResourceManager, 62
 - Resources, 61
- uk::ac::soton::ses::Word2010DepositMOAddIn::PropertyResource, 62
 - Default, 63
 - defaultInstance, 63
- uk::ac::soton::ses::Word2010DepositMOAddIn::QuickSubmitForm, 48
 - cancelButton, 54
 - cancelButton_Click, 50
 - components, 54
 - Dispose, 50
 - InitializeComponent, 50
 - passwordLabel, 54
 - passwordTextBox, 54
 - QuickSubmitForm, 49
 - repositoryLocationLabel, 54
 - repositoryLocationTextBox, 54
 - submitButton, 54
 - submitButton_Click, 52
 - usernameLabel, 54
 - usernameTextBox, 55
- uk::ac::soton::ses::Word2010DepositMOAddIn::RepositoryGroupUserControl, 55
 - components, 59
 - Dispose, 56
 - endpoint, 60
 - id, 60
 - identLabel, 59
 - InitializeComponent, 57
 - password, 60
 - passwordLabel, 59
 - passwordTextBox, 59
 - RepositoryGroupUserControl, 56
 - repositoryLocationLabel, 59
 - repositoryLocationTextBox, 59
 - username, 60
 - usernameLabel, 59
 - usernameTextBox, 59
- uk::ac::soton::ses::Word2010DepositMOAddIn::ThisRibbonCollection, 106
 - ThisRibbonCollection, 106
 - Word2010DepositMORibbon, 106
- uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, 107
 - AddMessageToLogStack, 110
 - AddRepositoryControl, 110
 - Application, 121
 - ApplicationResource, 111
 - BeginInitialization, 111
 - BindToData, 111
 - CustomTaskPanels, 121
 - DecrementSubmissionThreadCount, 112
 - DefaultEndpoint, 123
 - defaultEndpoint, 121
 - DefaultPassword, 123
 - defaultPassword, 121
 - DefaultUsername, 123
 - defaultUsername, 121
 - EndInitialization, 112

- FinishInitialization, [112](#)
- GetActiveDocumentProperties, [112](#)
- GetActiveSubmissionString, [113](#)
- GetAllLogMessages, [113](#)
- IncrementSubmissionThreadCount, [113](#)
- Initialize, [114](#)
- InitializeCachedData, [114](#)
- InitializeComponents, [114](#)
- InitializeControls, [115](#)
- InitializeData, [115](#)
- InitializeDataBindings, [115](#)
- InternalStartup, [115](#)
- IsCached, [115](#)
- lockobj, [121](#)
- log, [121](#)
- LogMessage, [116](#)
- MakeAllInvisible, [117](#)
- MakeAllVisible, [117](#)
- MAX_LOG_LINES, [122](#)
- missing, [122](#)
- NeedsFill, [118](#)
- OnShutdown, [118](#)
- PURGE_NUMBER_OF_LOG_LINES, [122](#)
- repositoryControls, [122](#)
- SetSingleLineTextBox, [118](#)
- SetTextCallback, [119](#)
- StartCaching, [119](#)
- StopCaching, [119](#)
- SubmissionThreadCount, [123](#)
- submissionThreadCounter, [122](#)
- ThisAddIn_Shutdown, [119](#)
- ThisAddIn_Startup, [120](#)
- VstoSmartTags, [122](#)
- Word2010DepositMOAddIn, [110](#)
- uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn, [123](#)
 - aboutRibbonButton, [131](#)
 - aboutRibbonButton_Click, [125](#)
 - aboutRibbonGroup, [131](#)
 - components, [131](#)
 - Dispose, [125](#)
 - endpointEditBox, [131](#)
 - InitializeComponent, [126](#)
 - quickPassword, [131](#)
 - quickSubmissionRibbonGroup, [131](#)
 - quickSubmissionRibbonGroup_ -
DialogLauncherClick, [128](#)
 - quickSubmitButton, [132](#)
 - quickSubmitButton_Click, [129](#)
 - quickUsername, [132](#)
 - tab1, [132](#)
 - Word2010DepositMOMainGroup, [132](#)
 - Word2010DepositMOMainGroup_ -
DialogLauncherClick, [129](#)
 - Word2010DepositMOREpositoryButton, [132](#)
 - Word2010DepositMOREpositoryButton_ -
Click, [130](#)
 - Word2010DepositMOREpositoryHideButton, [132](#)
 - Word2010DepositMOREpositoryHideButton_ -
Click, [130](#)
 - Word2010DepositMORibbon, [125](#)
 - Word2010DepositMORibbon_Load, [130](#)
 - Word2010DepositMORibbonTab, [132](#)
- Updated
 - uk::acc::soton::ses::SwordListEntry, [102](#)
- updated
 - uk::acc::soton::ses::SwordListEntry, [101](#)
 - uk::acc::soton::ses::SwordListReader, [105](#)
- updateEprintButton
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMOREpositoryGr, [36](#)
- updateEprintButton_Click
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMOREpositoryGr, [33](#)
- Username
 - uk::acc::soton::ses::SwordClientHandler, [90](#)
- username
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMOREpositoryGr, [37](#)
 - uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGr, [60](#)
- usernameLabel
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMOREpositoryGr, [36](#)
 - uk::acc::soton::ses::Word2010DepositMOAddIn::QuickSubmitt, [54](#)
 - uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGr, [59](#)
- usernameTextBox
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMOREpositoryGr, [37](#)
 - uk::acc::soton::ses::Word2010DepositMOAddIn::QuickSubmitt, [55](#)
 - uk::acc::soton::ses::Word2010DepositMOAddIn::RepositoryGr, [59](#)
- VstoSmartTags
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Word2010Dep, [122](#)
- WarningBox
 - uk::acc::soton::ses::Word2010DepositMOAddIn::DepositMOREpositoryGr, [34](#)
- Word2010DepositMOAddIn
 - uk::acc::soton::ses::Word2010DepositMOAddIn::Globals, [39](#)

- uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMOAddIn,
110
- Word2010DepositMOMainGroup
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
132
- Word2010DepositMOMainGroup_-
 - DialogLauncherClick
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
129
- Word2010DepositMOREpositoryButton
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
132
- Word2010DepositMOREpositoryButton_Click
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
130
- Word2010DepositMOREpositoryHideButton
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
132
- Word2010DepositMOREpositoryHideButton_-
 - Click
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
130
- Word2010DepositMORibbon
 - uk::ac::soton::ses::Word2010DepositMOAddIn::ThisRibbonCollection,
106
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
125
- Word2010DepositMORibbon_Load
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
130
- Word2010DepositMORibbonTab
 - uk::ac::soton::ses::Word2010DepositMOAddIn::Word2010DepositMORibbon,
132
- WriteFileToRequest
 - uk::ac::soton::ses::SwordClientHandler, 88
- xnm
 - uk::ac::soton::ses::SwordAtomReader, 67
 - uk::ac::soton::ses::SwordListReader, 105
- xws
 - uk::ac::soton::ses::SwordClientHandlerTests,
98