

Eprints Archive Software System Documentation

Robert Tansley Christopher Gutteridge

February 1, 2001

Contents

1	Introduction	2
1.1	Further Help and Bug Reports	2
2	Overview	2
2.1	Directory Structure	3
2.2	The html Directory	4
2.3	Eprint and Document File Storage	5
3	<i>Eprints</i> Metadata Handling	6
3.1	Verbose Metadata Field Specification	7
3.2	Terse Metadata Field Specification	8
3.3	The MetaField Class	9
4	The MySQL Database	9
4.1	Metadata Storage	10
4.2	Relationships	10
5	The Searching Mechanism	11
5.1	Searching Metadata Fields	11

10 Scripted Importing of Data	18
11 Customisation Examples	19
11.1 Listing All Files in a Format	19

1 Introduction

This document describes the workings of the Eprints archive software, and how it interacts with the other components to provide services.




Figure 1: Overview of the Components of an *Eprints* arc9.47hiv9.47e

2.1 Directory Structure

This section lists and describes the directories in an installed *Eprints* system.

bin

and run `generate_static` (or `update_laf`.) The file will be added to the archive Web server.

In order to reduce processor load, and to enable search engines such as

boolean	true or false
date	a date (day, month and year)
email	an e-mail address
enum	one of a specified set of values
eprinttype	a type of eprint (generally only used by system)
intc	64.6eger /F8 9.963 Tf 04.656 0 pmunsigned eprint (generally only used by system)

Argument	Types it applies to	Description
type	ALL	the type of field, from table 1
required	ALL	

Miscellaneous arguments:
subjects

documents. Contains information about the eprint document files (e.g. PDFs,

Field Type	Stored as MySQL Type	Internal Representation (MySQL & <i>Eprints</i> code)
boolean	SET('TRUE','FALSE')	'TRUE' or 'FALSE'
date	DATE	YYYY-MM-DD
email	VARCHAR(255)	as-is
enum	VARCHAR(255)	tag of the selected value
eprinttype	VARCHAR(255)	tag of the eprint type
int	INT UNSIGNED	the number
multitext	TEXT	as-is
multiurl	TEXT	as-is
username	TEXT	: username1: username2:
name	VARCHAR(255)	: surname, fi rstname mi ddl ename: surname Jr. , fi rstname, mi ddl ename:
pagerange	VARCHAR(255)	ext-yyy,Td((VARCHA(255)n'80 Td((xaxis)TJ/F8 9.963 Tf 320. usr VARCHAR(255) as-is

The `make_meta_fields` method in `SearchExpression.pm`

tag1: tag2: tag3: ANY

This will retrieve records where the field has any one of the values tag1, tag2 or tag3.

In SQL: Each tag is turned into a LIKE "%: tag: %" clause. Multiple tags are then combined with AND or OR in order to construct the SQL query.

5.1.7 year fields

HTML Form: Rendered as a text input

This sorts results by descending year, then authors, then title. The default order if ASCending or DESCending are not specified is ascending.

SearchExpression.pm can also produce a text string which, at a later time, can be fed back into SearchExpression.pm to recreate the same search. This technique is used by the subscriptions mechanism to store and retrieve user subscriptions.

This usually results in a chain of versions, but may result in a 'tree' of

Remove email based user registration.

The code which creates the link to each format from the abstract page is in
SiteRoutines.pm