KEYSTONE: Auditable Dispute-Key Availability for Encrypted AI Rollups

Zubaer Mahmood Zubraj
School of Engineering, East Delta University
Chittagong, Bangladesh
zmzubraj@gmail.com

Abstract

Encrypted optimistic rollups can keep ciphertext and execution receipts available and still fail when a dispute needs timely authorized decryption. We call the missing property *dispute-key availability* (DKA): the conditional ability of an authorized verifier to obtain at least t valid threshold-decryption contributions before a dispute deadline, while confidentiality holds before authorization. KEYSTONE composes established threshold-KEM and verifiable partial-decryption components with an unpredictable *canary* audit that exercises custodians' shares without touching a production ciphertext, plus a public request and deadline transcript. For a committee of n custodians, threshold t, sample size s and acceptance threshold q, we give an exact false-accept expression for static catastrophic states; at $n = 32$, $t = 22$, $s = q = 8$ the worst-case detection probability is 0.980654. We evaluate the design with (i) three prespecified simulation cells of 131,072 draws each, (ii) exact correlated-failure and acceptance-rule analysis, (iii) cryptographic microbenchmarks at RFC 7919 group sizes, and (iv) a single-host emulated testbed of 32 custodian processes running real ffdhe2048 cryptography under eight frozen latency, loss and crash profiles. The audit's strict acceptance rule detects catastrophic states but also fails benignly in most draws under 10% independent unavailability (audit pass 43.1% while reconstruction succeeds in 99.98%); larger samples with a relaxed rule recover a better trade-off. Eleven selective withholders pass every audit and defeat every dispute, so an audit is evidence of present sampled serviceability, not of future cooperation. In the emulated testbed every reconstructable dispute decrypted the correct plaintext within 5 s (medians 3.69–3.88 s across profiles) and none within the 2 s primary deadline: serial verification of 22 proofs in the pure-Python prototype, not network delay, dominates completion time, and eleven crashes defeat every dispute. KEYSTONE is not a new threshold-encryption primitive and the prototype is not production software.

Keywords: dispute-key availability; threshold decryption; encrypted rollups; readiness sampling; selective withholding; accountability.

1 Introduction

Private or encrypted optimistic execution introduces an operational dependency that public data-availability mechanisms do not remove. A ciphertext can remain retrievable while the threshold service needed to open its record key is unavailable, late, invalid, or selectively uncooperative. In an optimistic dispute, that difference is decisive: the system must recover enough valid contributions after authorization and before a deadline, not merely prove that encrypted bytes exist.

KEYSTONE studies this distinction in the setting of encrypted AI-rollup disputes. Each inference record is encrypted under a fresh symmetric key that is wrapped under an epoch threshold public key. A routine audit samples custodians using post-commit randomness

and asks each sampled custodian to operate on a canonical, non-production group element. A valid response demonstrates current access to the custodian's epoch share. An authorized dispute instead requests partial decryptions of the target record's KEM component. The two paths share cryptographic machinery but measure different behavior.

The research question is: *how can an encrypted AI rollup obtain publicly auditable, non-revealing evidence that at least t valid threshold-decryption contributions are currently serviceable for an authorized dispute before deadline Δ_d, under explicit churn and correlated-failure assumptions, without releasing a production key or plaintext before authorization?*

The contribution is deliberately narrow:

1. a decomposition separating ciphertext availability, valid-share registration, audit-time readiness, authorized decryptability and deadline liveness (Section 3, Table 1);
2. a non-production canary audit built from established threshold-decryption and equality-of-discrete-log techniques (Section 4);
3. an exact false-accept expression for static catastrophic states, its scaling, and an acceptance-rule trade-off between detection and benign alarms (Section 5);
4. an evaluation combining prespecified simulation, exact correlated-failure analysis, measured cryptographic cost at standard group sizes, and an emulated deadline testbed, including a selective-withholding counterexample (Section 6).

We do not claim a new threshold-encryption, VSS/PVSS, DLEQ, proactive-sharing, context-dependent-decryption or bulletin-board primitive, nor that a successful audit proves future availability, adaptive selective-withholding resistance or production security.

2 Background and Related Work

Data-availability sampling, including PeerDAS, concerns the retrievability of encoded public data and is therefore a contrast class rather than a solution to threshold-key serviceability [1]. Threshold encryption establishes that a ciphertext can be opened only with sufficiently many decryption contributions [2]. Verifiable, publicly verifiable and proactive secret sharing address correct distribution, refresh and changing committees [3–6], but do not by themselves measure whether a dispute service will meet a future deadline.

Threshold-release systems already cover much of the design space. ETHTID studies deployable threshold information disclosure on Ethereum; Ferveo and BEAT-MEV apply threshold decryption to encrypted transaction ordering; vetKeys and time-lock encrypted storage address controlled blockchain disclosure; and context-dependent threshold decryption provides context-isolation machinery [7–12]. EigenAI is adjacent verifiable AI execution rather than evidence for the present availability claim [13]. Accountability for

threshold-decryption misbehavior and accountable liveness constrain what public evidence can establish [14, 15].

Our prior-art search therefore rejects broad primitive novelty. The hypothesis we test is narrower: whether the rollup-dispute framing (ciphertext versus serviceability separation, a pre-authorization canary exercise, explicit catastrophic false-accept analysis, correlated-failure qualification, and deadline evidence) is a useful systems contribution. Not finding a single combined predecessor in a bounded search is not proof of novelty.

3 System and Threat Model

3.1 Entities and records

An epoch E contains n custodians and a threshold t. Custodian i holds share x_i and registers public share $Y_i = g^{x_i}$. A rollup worker encrypts record r with a fresh key K_r under AES-256-GCM, wraps K_r through a threshold Diffie–Hellman KEM under the epoch public key PK_E, and publishes the encrypted record to a data-availability layer. The settlement layer records commitment, policy, request and deadline events and supplies an ordered public clock. Figure 1 shows the three paths.




Figure 1. KEYSTONE architecture. Sealing, routine canary auditing and authorized dispute release are separate paths over one custodian committee. The audit uses a beacon-derived canary, never a production ciphertext; only an authorized dispute requests partial decryptions of a record's KEM component C_1. Dashed arrows are public evidence written to the bulletin board.

3.2 Readiness and security properties

For request type $u \in \{\text{audit}, \text{dispute}\}$, $\text{Ready}_i(E, \tau, u, \Delta) = 1$ iff custodian i can access its valid current share, execute the required operation, produce a valid proof and deliver its response by $\tau + \Delta$. Audit and dispute readiness differ on purpose: a target-aware custodian may answer a canary and refuse a particular dispute. Table 1 lists the properties and where this paper assesses each.

Table 1. Properties separated by KEYSTONE, how each is assessed in this paper, and the evidence type.

Property	Meaning	Assessed by	Evidence type
Ciphertext availability (CA)	Encrypted record and receipt bytes are retrievable from the DA layer	Assumed (provided by the DA layer); contrast class	Assumption
Valid-share registration	Registered shares are consistent with one epoch key (DKG/VSS/PVSS)	Feldman commitment checks at keygen	Prototype tests
Audit-time readiness (AKR)	At least q of s sampled custodians return valid canary partials by the audit deadline	Eq. (1); Tables 5, 2	Exact; simulation; emulation
Authorized decryptability	After authorization, the combiner obtains t distinct valid partials of C_1	Prototype open path; Table 5	Tests; emulation
Deadline liveness (DDL)	Authorized decryptability completes by Δ_d	Figure 3; Table 5(b)	Single-host emulation
Pre-authorization confidentiality (PAC)	With fewer than t shares, an adversary learns nothing about K_r beyond base-scheme leakage	Inherited from the threshold KEM [2]; canary never touches C_1	Design argument
(ε, Δ_d)-DKA	With probability $\geq 1 - \varepsilon$ the combiner obtains t valid partials by $\tau + \Delta_d$, and PAC holds before	Composition of the rows above	Conditional

3.3 Adversaries and exclusions

The model covers independent crash faults, provider, region or software-domain correlated outages, invalid or equivocal responses, changing compromise across epochs, selective withholding, beacon prediction or substitution, and unauthorized requests. Confidentiality assumes fewer than t current shares are compromised. Production DKG/PVSS security, malicious authorized verifiers, arbitrary asynchronous partitions and fully adaptive selective-withholding resistance are out of scope. Invalid proofs and equivocation are positive cryptographic evidence; attributing a missed deadline to malice additionally requires the declared synchrony and delivery assumption.

4 KEYSTONE Protocol

Epoch setup and sealing. The committee is formed under identity, stake and failure-domain placement policy. A production system would use an authenticated DKG or PVSS; the prototype uses a dealer with Feldman commitments [3] as a substitution boundary. The worker encrypts the record under K_r, publishes $C_1 = g^{\rho}$, derives PK_E^{ρ} and uses it to wrap K_r. The envelope binds epoch, record identifier, ciphertext, metadata and DA pointer.

Non-production readiness audit. The coordinator commits epoch and audit slot before the beacon is known. The finalized beacon then fixes a uniform or domain-stratified sample S of size s, and all parties derive

$$X = H_G(\text{KEYSTONE-CANARY} \parallel E \parallel \text{slot} \parallel \text{beacon}),$$

where H_G is domain separated and does not expose $\log_g X$. Sampled custodian i returns $D_i = X^{x_i}$ with a Chaum–Pedersen proof that $\log_g Y_i = \log_X D_i$, bound to the request context [16, 17]. The verifier checks membership, freshness, uniqueness, proof validity and deadline, and accepts after q valid responses. Because X is fresh and derived, the audit exercises share access without opening a production record, and a coordinator cannot substitute a record's C_1 as a challenge.

Authorized dispute release. A dispute starts only after the policy contract binds a record, epoch, authorized verifier set and deadline. Custodians verify the authorization and return $C_1^{x_i}$ with a DLEQ proof. The combiner verifies t distinct responses and interpolates in the exponent, $\prod_{i \in I} (C_1^{x_i})^{\lambda_i} = C_1^{x} = PK_E^{\rho}$, then unwraps K_r, decrypts and runs the authorized verification. The public transcript records valid, invalid, equivocal, stale, unauthorized and missing responses; plaintext release policy stays separate.

5 Analysis

5.1 Static catastrophic false acceptance

Let exactly $r < t$ custodians be audit-ready throughout one request. If s custodians are sampled uniformly without replacement and acceptance requires q valid responses,

$$\Pr[\text{accept} \mid r] = \sum_{j=q}^{\min(s,r)} \frac{\binom{r}{j}\binom{n-r}{s-j}}{\binom{n}{s}}.$$

This is non-decreasing in r, so the worst catastrophic state is $r = t - 1$, and for $q = s$

$$\varepsilon_a = \Pr[\text{false accept}] \leq \frac{\binom{t-1}{s}}{\binom{n}{s}}.$$

For $n = 32, t = 22, s = q = 8, \varepsilon_a = 0.0193462822$ and detection $1 - \varepsilon_a = 0.9806537178$. These are exact under the static model, not field-calibrated probabilities. If the catastrophic ready set is fixed and samples are independent and unpredictable, m audits all falsely accept with probability at most ε_a^m; this does not hold for time-varying or adaptive readiness without a temporal model. Figure 2 shows how detection grows with s and how the bound scales with committee size under $t = n - \lfloor (n-1)/3 \rfloor$.




Figure 2. Exact worst-case detection $1 - \binom{t-1}{s} / \binom{n}{s}$ *versus sample size with* $q = s$. *(a) Thresholds* $t \in \{17,22,27\}$ *at* $n = 32$*; the baseline* $s = 8$, $t = 22$ *is annotated. (b) Committee sizes* 16–128. *Values for* $(n, s) \in \{(16,4), (32,8), (64,12), (128,16)\}$ *are listed in Table 6.*

5.2 Three non-implication witnesses

1. CA does not imply DKA: ciphertext stays available while only $t - 1$ custodians are dispute-ready.

2. AKR does not imply target-dispute success: selective custodians answer the canary and withhold the target response. With $w = n - t + 1$ withholders the dispute fails deterministically while every audit passes (Figure 5).

3. A finite sequence of accepted audits does not imply future DKA: enough custodians may become unavailable after the last audit.

5.3 The acceptance-rule trade-off

Requiring $q = s$ maximizes detection but turns every benign miss in the sample into an alarm. Under independent unavailability f, a healthy committee passes with probability $\Pr[\mathrm{Bin}(s, 1 - f) \geq q]$, which for $s = q = 8$ and $f = 0.10$ is only 0.43 although t of 32 shares are almost surely reachable. Table 2 and Figure 6 give the exact trade-off. At $s = 8$ no rule achieves both: $q = 7$ lowers detection to 85.9% while benign pass rises to 81.3%. A larger sample recovers the trade-off: $s = 16, q = 14$ detects 98.8% of worst-case catastrophic

states with benign pass 95.7% at $f = 0.05$ and 78.9% at $f = 0.10$. This analysis was added after observing the high benign alarm rate in exploratory runs and is reported as design guidance, not as a prespecified result.

Table 2. Exact acceptance-rule trade-off at $n = 32$, $t = 22$: worst-case catastrophic detection ($r = t - 1$) versus the probability that a healthy committee passes under IID unavailability f. Post hoc analysis.

		Worst-case	Benign audit pass under IID unavailability		
s	q	detection	$f = 0.05$	$f = 0.10$	$f = 0.20$
8	6	57.5%	99.4%	96.2%	79.7%
8	7	85.9%	94.3%	81.3%	50.3%
8	8	98.1%	66.3%	43.0%	16.8%
12	10	89.6%	98.0%	88.9%	55.8%
12	11	98.2%	88.2%	65.9%	27.5%
12	12	99.9%	54.0%	28.2%	6.9%
16	13	93.2%	99.3%	93.2%	59.8%
16	14	98.8%	95.7%	78.9%	35.2%
16	15	99.9%	81.1%	51.5%	14.1%

6 Evaluation

6.1 Method and evidence labels

Table 3 lists every experiment. We separate four evidence types and label each result with one of them. *Exact* values are closed-form under a declared model. *Simulation* results come from three cells whose parameters, endpoints, precision targets and seed schedule were written and hashed before execution: 32 seed blocks of 4,096 independent draws each (131,072 draws per cell), which exceeds the Hoeffding requirement of 73,778 draws for the stated half-widths [18]. The sampling-policy cell uses common random numbers, so uniform and stratified samples are compared on the same failure draw. *Microbenchmarks* are single-process wall-clock medians. *Emulation* is a testbed of 32 custodian operating-system processes on one host. Proportions carry 95% Wilson intervals [19]. The emulated testbed is not a geo-distributed deployment.

Table 3. Experimental configuration. The baseline committee is $n = 32$, $t = 22$, $s = q = 8$ with four failure domains of eight custodians.

Experiment family	Parameters	Execution and evidence label
Static bound (Eq. 2)	$n \in \{16,32,64,128\}$, $t = n - \lfloor (n-1)/3 \rfloor$, $s \in \{1, \ldots, 16\}$, $q = s$; baseline $n = 32, t = 22, s = q = 8$	Exact closed form
PC03 prespecified cells	$n = 32, t = 22, s = q = 8$, 4 domains of 8. IID: $p_{\text{off}} = 0.10$. STRAT: $p_{\text{dom}} = 0.20$, $p_{\text{off}} = 0.02$, uniform vs. 2-per-domain quota. SW: $w = 11$	32 seed blocks × 4,096 draws $= 131{,}072$ per cell; seeds frozen before execution; simulation
Correlation model	$f \in \{0, 0.025, \ldots, 0.40\}$; IID vs. 2/4/8 equal domains	Exact; declared synthetic model
Acceptance rule	$s \in \{8,12,16\}$, $q \in [\lceil s/2 \rceil, s]$, IID $f \in \{0.05, 0.10, 0.20\}$	Exact; post hoc
Cryptographic cost	ffdhe2048, ffdhe3072 (RFC 7919) and the 256-bit prototype group; $n \leq 128$	Local microbenchmark, CPython 3.13, Apple M4 Pro
Deadline testbed	ffdhe2048, $n = 32, t = 22$; 8 profiles × 300 traces; one-way delay lognormal (median 0/40/120 ms); 2% loss; 10 or 11 crashes; one-domain outage; $\Delta_d \in \{0.25, 0.5, 1, 2, 5\}$ s	32 custodian processes on one host, loopback TCP, real cryptography; emulation

6.2 Comparison with readiness baselines

Table 4 compares the canary audit with the obvious alternatives. A heartbeat confirms only that a process responds; a custodian that has lost its share still answers, so a static catastrophic state of $t - 1$ share-holders is invisible to it. Share registration is checked once and says nothing about later share loss. Decrypting a real record would test the right capability but discloses a production record. A full-committee canary probe detects every static catastrophic state at four times KEYSTONE's per-round cost at $n = 32$; KEYSTONE trades that cost for the detection probability of Eq. (2).

Table 4. Readiness checks compared. Costs are measured medians for ffdhe2048 in the prototype (Table 7); bytes are canonical request plus response transcripts.

Readiness check	Exercises the secret share?	Touches production ciphertext?	Detects a static state with $r = t - 1$ ready shares	Cost per check ($n = 32$, ffdhe2048, measured)
Liveness heartbeat	No	No	No: a node that lost its share still answers	1 message per node; no group operations
Share registration (Feldman/PVSS check)	Once, at setup	No	No: says nothing about later share loss	One-time $O(nt)$ exponentiations at epoch setup
Full-committee canary probe	Yes	No (canary)	Yes, with probability 1	32 proofs + 32 verifications; 8501 ms CPU; 36,991 B
KEYSTONE sampled canary ($s = q = 8$)	Yes, for the sampled members	No (canary)	Yes, with probability 0.9807 (Eq. 2)	8 proofs + 8 verifications; 2125 ms CPU; 9,415 B
Decrypt a real record as a test	Yes	Yes: exposes a production record	Yes	t verifications plus a real disclosure; excluded by design

6.3 Deadline liveness in an emulated testbed

The testbed runs 32 custodian processes, each an asyncio TCP server holding only its own ffdhe2048 share, and one combiner on the same host. Each trace performs one canary audit and one authorized dispute over a freshly sealed 1 KiB record. The combiner verifies each DLEQ proof on arrival, stops at $t = 22$ valid partials, combines, unwraps K_r and checks the decrypted plaintext. One-way delays are drawn per message from a lognormal law with the profile's median; loss drops a message with no retransmission; crashed custodians never answer. Each of eight profiles ran 300 traces with seeds fixed before execution.

Figure 3 and Table 5(b) report the results. The prespecified primary endpoint, success by $\Delta_d = 2$ s, was 0% in every profile: no dispute finished in under 3.5 s. Every reconstructable dispute finished within 5 s, with medians from 3.69 to 3.88 s and a slowest success of 4.48 s. Completion time is dominated by computation, not by the network. With no injected delay the median is 3818 ms, close to 22 serial proof verifications at the 135.4 ms measured in Table 7; adding a 120 ms-median one-way delay moved the median only to 3875 ms, because responses arrive while the combiner is still verifying earlier ones. A heavy-tailed delay law ($\sigma = 1.2$) did not lengthen completion (95th percentile 3850 ms).

Ten crashes (median 3692 ms) and a full domain outage (median 3700 ms) completed slightly faster than the fault-free global profile, which we attribute to fewer custodian processes competing for the shared host CPU. Eleven crashes defeated every dispute (0/300 succeeded).




Figure 3. Empirical probability that an authorized dispute decrypts the correct plaintext by deadline Δ_d, single-host emulation with real ffdhe2048 cryptography, 300 traces per profile. (a) Latency profiles. (b) Faults under the 120 ms-median profile; with eleven crashed custodians no dispute succeeds. Vertical lines mark the evaluated deadlines 0.25, 0.5, 1, 2 *and* 5 *s.*

The audit side reproduces Eq. (1) on real cryptography. A single audit took 1.24–1.43 s at the median. With ten crashed custodians the strict audit passed in 2.3% of traces against an exact expectation of 3.0%; with one domain down, 5.7% against 7.0%; with 2% message loss, 71.7% against 72.4%. In the crash and outage profiles the dispute nevertheless succeeded in every trace, the benign-alarm pattern of Section 5. One control trace timed out because the combiner was slowed by unrelated activity on the shared host; it is counted as a failure.

The design implication is that Δ_d must budget for verifying t proofs at the combiner. We did not measure optimized, batched or parallel verification, which would shorten this term.

6.4 Robustness under failure scenarios

Table 5(a) reports the prespecified simulation cells. Under 10% independent unavailability the committee reconstructs in 99.98% of draws, yet the strict audit passes in only 43.1%: the audit is a sensitive alarm, not an accurate health score. Under 20% domain outages, fixed-quota stratified sampling raised conditional detection of catastrophic draws from 99.89% to 100.00% and lowered the benign pass rate from 37.3% to 34.9%. The prespecified primary endpoint, the paired difference in detected catastrophes per draw, was 0.00021 (Hoeffding half-width 0.0075; all 28 discordant pairs favored stratification), so

stratification’s benefit is real but small in this cell. With eleven selective withholders, audits passed in 100.0% of draws and disputes succeeded in 0.0% (upper 95% bound 0.0029%), confirming the second non-implication witness at the prespecified sample size.

Table 5. Robustness under failure scenarios. (a) Prespecified simulation; dispute success equals reconstructability because the simulator has no network. (b) Emulated testbed: audit pass is $q = 8$ valid responses within the 6 s timeout; dispute success requires correct plaintext within $\Delta_d = 2$ s; times are over successful disputes, from first request to decrypted plaintext.

Scenario	Audit pass	Dispute success	By $\Delta_d =$ 5 s	Median time	p95 time
(a) PC03 prespecified simulation, 131,072 draws per cell, 95% Wilson intervals					
IID 10% unavailable	43.1% [42.8, 43.3]	99.98% [99.97, 99.99]	–	–	–
Domain outage 20%, uniform sample	37.3% [37.0, 37.6]	81.3% [81.1, 81.6]	–	–	–
Domain outage 20%, stratified sample	34.9% [34.7, 35.2]	81.3% [81.1, 81.6]	–	–	–
selective withholders	100.0% [99.997, 100.000]	0.0% [0.000, 0.003]	–	–	–
(b) Emulated deadline testbed, ffdhe2048; dispute success by the primary $\Delta_d = 2$ s and by 5 s, 95% Wilson intervals					
control	100.0% [98.7, 100.0]	0.0% [0.0, 1.3]	99.7%	3818 ms	3936 ms
regional	100.0% [98.7, 100.0]	0.0% [0.0, 1.3]	100.0%	3841 ms	3908 ms
global	100.0% [98.7, 100.0]	0.0% [0.0, 1.3]	100.0%	3875 ms	4016 ms
global loss2	71.7% [66.3, 76.5]	0.0% [0.0, 1.3]	100.0%	3829 ms	3886 ms
global crash10	2.3% [1.1, 4.7]	0.0% [0.0, 1.3]	100.0%	3692 ms	3775 ms

Scenario	Audit pass	Dispute success	By Δ_d = 5 s	Median time	p95 time
global crash11	1.7% [0.7, 3.8]	0.0% [0.0, 1.3]	0.0%	–	–
global domain outage	5.7% [3.6, 8.9]	0.0% [0.0, 1.3]	100.0%	3700 ms	3780 ms
heavy tail	98.3% [96.2, 99.3]	0.0% [0.0, 1.3]	100.0%	3772 ms	3850 ms

Figure 4 shows why placement matters. At equal per-unit unavailability $f = 0.10$, an IID committee reconstructs with probability 99.98%, four domains of eight (each under the placement cap $n - t = 10$) with 94.8%, and two domains of sixteen, which violate the cap, with only 81.0%. These are exact values under a declared synthetic model; real domain labels and their independence are assumptions.




Figure 4. IID versus domain-correlated unavailability at $n = 32$, $t = 22$. A domain fails with probability f and takes all its members; in the IID model each custodian fails independently with probability f. (a) Reconstructability. (b) Audit pass with $s = q = 8$. Exact; a 20,000-draw Monte Carlo check agrees within 0.009.




Figure 5. Audit pass versus dispute success as the number of selective withholders w grows, with no other failures. Lines are exact; markers at $w = 11$ are the prespecified 131,072-draw simulation cell.




Figure 6. Detection versus benign alarm rate (audit fails while the committee is healthy, $f = 0.10$) for each acceptance threshold q; one curve per sample size. Exact values from Table 2 and its full source grid.

6.5 Performance and scalability

Table 7 gives per-operation costs in the pure-Python prototype; these are upper bounds, and optimized libraries are substantially faster. At ffdhe2048 a custodian's partial decryption with proof takes 130.3 ms and its verification 135.4 ms; verifying 22 partials and combining takes 3213 ms (10201 ms at ffdhe3072). The 256-bit prototype group is listed for reference only and is not a secure size. Table 6 scales the committee: audit cost grows with s, not n, while dispute cost grows with t. Table 8 reports the bulletin-board gas costs measured in the Foundry harness.

Table 6. Scalability with $t = n - \lfloor (n-1)/3 \rfloor$. Detection is exact (Eq. (2), $q = s$). Audit CPU is s proofs plus s verifications; bytes are one request plus s responses. Dispute time is measured verification of t partials plus combination.

n	t	s	Detection	Audit, ffdhe2048 CPU	Bytes	Dispute: verify t + combine ffdhe2048	ffdhe3072
16	11	4	88.46%	1063 ms	4,819	1585 ms	5040 ms
32	22	8	98.07%	2125 ms	9,415	3213 ms	10201 ms
64	43	12	99.66%	3188 ms	14,011	6230 ms	20086 ms
128	86	16	99.92%	4250 ms	18,607	12534 ms	40201 ms

Table 7. Median wall time per operation, CPython 3.13 on an Apple M4 Pro; RFC 7919 groups [20] with $q = (p-1)/2$ and generator 4. Pure-Python reference implementation.

Operation (median, ms)	256-bit prototype	ffdhe2048	ffdhe3072
Canary derivation H_G	0.08	16.99	54.32
Partial decryption + DLEQ proof	0.58	130.30	420.54
DLEQ verification	0.75	135.36	430.58
Seal 1 KiB record	0.22	48.32	156.48
Partial response size (bytes)	253	1149	1661

Table 8. Bulletin-board gas per operation, re-measured for this revision with Foundry 1.5.1 and Solidity 0.8.24 (test-body gas; fixture setup excluded). Each operation was measured in the small harness committee named in the scope column; values are deterministic and identical to the earlier snapshot.

Bulletin-board operation	Gas	Harness scope
Register epoch	223,629	n=5, t=3; duplicate-identity validation enabled
Open audit	125,107	three sampled members; q=3
Submit audit response	57,882	first commitment from one sampled custodian
Mark invalid response	27,704	admin records a non-zero evidence hash
Record equivocation	51,710	second conflicting commitment from one custodian
Finalize audit	29,142	two responses for a three-member sample after deadline
Open dispute	144,149	n=5, t=3; all members eligible
Cancel request	5,709	admin cancels one open audit

7 Discussion

Availability is layered. Data availability answers whether encrypted bytes can be retrieved; share registration whether a key was formed consistently; a readiness audit whether sampled custodians can now perform a non-production share operation; an authorized dispute whether t custodians will serve a specific target before a deadline. Treating these as interchangeable hides distinct failure modes, and the evaluation shows each one separating in practice: high reconstructability with low audit pass under benign failures, perfect audit pass with zero dispute success under selective withholding, and dispute completion governed by verification work at the combiner rather than by average network latency.

Three design consequences follow. First, the acceptance rule should be chosen for a target benign alarm rate, which in our analysis favors larger samples with $q < s$ over $s = q$. Second, failure-domain placement under the cap $n - t$ matters more than sampling policy: violating the cap cost far more reconstructability than stratification changed detection. Third, deadlines must budget for verifying t proofs at the combiner; in our prototype that term exceeded the injected network delay by more than an order of magnitude. Non-response proves absence from the transcript, not malice, so penalties should distinguish warning, temporary inactivity, replacement and slashing.

8 Limitations

1. **Novelty.** Broad component novelty is defeated by prior work; the narrow composition has not been independently reviewed for novelty.
2. **Future cooperation.** The audit does not prove it; selective withholding is a counterexample, not a solved problem.
3. **Temporal inference.** Repeated-audit multiplication requires a static ready set or a justified temporal model.
4. **Emulation, not deployment.** The deadline testbed runs on one host with loopback TCP and synthetic delay laws; geo-distributed behavior, congestion and clock skew are not measured, and host scheduling caused one control-trace timeout. Completion times reflect a pure-Python implementation and would differ for optimized code.
5. **Non-production prototype.** A dealer replaces DKG/PVSS; the pure-Python code and the bulletin-board contract have not been externally audited.
6. **Post hoc analysis.** The simulation design was prespecified and hashed before execution; one analysis (Table 2) was added afterwards and is labeled post hoc.
7. **External validity.** Failure models are synthetic; no claim is made about real provider, region or operator behavior.

The hypothesis should be rejected or reframed if a predecessor already makes the same dispute-specific property and readiness probe explicit, or if independent reproduction fails to recover the property separations reported here.

9 Conclusion

KEYSTONE isolates a failure mode that ciphertext data availability does not address: the threshold service needed for an authorized encrypted-rollup dispute may be unavailable, slow or uncooperative at the deadline. It decomposes the relevant properties, instantiates a non-production canary audit from established components, and gives an exact static detection bound. The evaluation shows that the audit detects catastrophic states, that its acceptance rule needs tuning to avoid benign alarms, that it cannot detect selective withholding, and that in an emulated 32-custodian committee every reconstructable dispute completes within five seconds, a budget set by proof verification rather than by the network. KEYSTONE measures present sampled serviceability under declared assumptions; it does not prove future availability or introduce a new threshold-decryption primitive.

Declarations

Study type and ethics. Non-human computational research using synthetic data, simulation, locally generated prototype outputs and smart-contract tests; no personal data, participants, production secrets or live systems.

Data and code availability. Source code, frozen designs with SHA-256 hashes, seed schedules, raw per-block and per-trace outputs, and the scripts that generate every table and figure are publicly available at https://github.com/zmzubraj/KeyStone under the MIT License.

Funding and conflicts of interest. This work was self-funded. The author declares no conflicts of interest.

AI-assisted preparation. AI assistance was used for drafting, code integration, experiment scripting and figure generation. The author is responsible for the scientific content, verification and submission.

[1] D. Ryan, D. Feist, F. D'Amato, H.-W. Wang, and A. Stokes. EIP-7594: PeerDAS – Peer Data Availability Sampling. Ethereum Improvement Proposal. 2024. https://eips.ethereum.org/EIPS/eip-7594

[2] D. Boneh, X. Boyen, and S. Halevi. Chosen ciphertext secure public key threshold encryption without random oracles. *Topics in cryptology – CT-RSA 2006*. 2006, 226–243. doi: 10.1007/11605805_15

[3] P. Feldman. A practical scheme for non-interactive verifiable secret sharing. *28th annual symposium on foundations of computer science (FOCS)*. 1987, 427–438. doi: 10.1109/SFCS.1987.4

[4] B. Schoenmakers. A simple publicly verifiable secret sharing scheme and its application to electronic voting. *CRYPTO*. 1999, 148–164. doi: 10.1007/3-540-48405-1_10

[5] A. Herzberg, S. Jarecki, H. Krawczyk, and M. Yung. Proactive secret sharing or: How to cope with perpetual leakage. *CRYPTO*. 1995, 339–352

[6] T. Yurek, Z. Xiang, Y. Xia, and A. Miller. Long live the honey badger: Robust asynchronous DPSS and its applications. *32nd USENIX security symposium (USENIX security 23)*. 2023, 5413–5430. https://www.usenix.org/conference/usenixsecurity23/presentation/yurek

[7] O. Stengele, M. Raiber, J. Müller-Quade, and H. Hartenstein. ETHTID: Deployable threshold information disclosure on Ethereum. *2021 3rd international conference on blockchain computing and applications (BCCA)*. 2021, 127–134. doi: 10.1109/BCCA53669.2021.9657019

[8] J. Bebel, and D. Ojha. Ferveo: Threshold decryption for mempool privacy in BFT networks. Cryptology ePrint Archive, Paper 2022/898. 2022. https://eprint.iacr.org/2022/898

[9] J. Bormet, S. Faust, H. Othman, and Z. Qu. BEAT-MEV: Epochless approach to batched threshold encryption for MEV prevention. *34th USENIX security symposium (USENIX security 25)*. 2025. https://www.usenix.org/conference/usenixsecurity25/presentation/bormet

[10] A. Cerulli, A. Connolly, G. Neven, F.-S. Preiss, and V. Shoup. vetKeys: How a blockchain can keep many secrets. Cryptology ePrint Archive, Paper 2023/616. 2023. https://eprint.iacr.org/2023/616

[11] A. Agarwal, K. Babel, S. Das, and B. Poorebrahim Gilkalaye. Time-lock encrypted storage for blockchains. Cryptology ePrint Archive, Paper 2025/2048. 2025. https://eprint.iacr.org/2025/2048

[12] D. Boneh, B. Bünz, K. Nayak, L. Rotem, and V. Shoup. Context-dependent threshold decryption and its applications. Cryptology ePrint Archive, Paper 2025/279; extended abstract in ASIACRYPT 2025. 2025. https://eprint.iacr.org/2025/279

[13] D. R. Alves, V. Patankar, M. Pereira, J. Stephens, N. Vaziri, and S. Kannan. EigenAI: Deterministic Inference, Verifiable Results. *arXiv preprint arXiv:2602.00182*. 2026. https://arxiv.org/abs/2602.00182

[14] D. Boneh, A. Partap, and L. Rotem. Accountability for misbehavior in threshold decryption via threshold traitor tracing. Cryptology ePrint Archive, Paper 2023/1724. 2023. https://eprint.iacr.org/2023/1724

[15] A. Lewis-Pye, J. Neu, T. Roughgarden, and L. Zanolini. Accountable liveness. *arXiv preprint arXiv:2504.12218*. 2025. https://arxiv.org/abs/2504.12218

[16] D. Chaum, and T. P. Pedersen. Wallet databases with observers. *Advances in cryptology – CRYPTO '92*. 1993, 89–105. doi: 10.1007/3-540-48071-4_7

[17] A. Faz-Hernandez, S. Scott, N. Sullivan, R. S. Wahby, and C. A. Wood. Hashing to elliptic curves. Internet Engineering Task Force. 2023. doi: 10.17487/RFC9380

[18] W. Hoeffding. Probability inequalities for sums of bounded random variables. *Journal of the American Statistical Association*. 1963, 58, 13–30. doi: 10.1080/01621459.1963.10500830

[19] E. B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*. 1927, 22, 209–212. doi: 10.1080/01621459.1927.10502953

[20] D. K. Gillmor. Negotiated finite field Diffie-Hellman ephemeral parameters for transport layer security (TLS). Internet Engineering Task Force. 2016. doi: 10.17487/RFC7919