

# Hw5

- Q1 (5 pts): run Mallet
- Q2 (25 pts): MaxEnt decoder
- Q3 (15 pts): calculate empirical expectation
- Q4 (30 pts): calculate model expectations
- standard portion: 25 points

---

Total: 100 pts

# Q1: run Mallet MaxEnt learner

- The format of the model file:

FEATURES FOR CLASS c1

<default> 0.3243

t1 0.245

t2 0.491

....

FEATURES FOR CLASS c2

<default> 0.3243

t1 -30.412

t2 1.349

....

## Q2: write a MaxEnt decoder

The formula for  $P(y \mid x)$ :

$$p(y|x) = \frac{e^{\lambda_0(y) + \sum_{k=1}^K \lambda_k f_k(x, y)}}{Z}$$

$\lambda_0(y)$  is the weight of the default feature for  $y$ .

The  $k$  in  $f_k$  corresponds to a (class, feature) pair  $(c_i, t_j)$

$f_k(x, y) = 1$  iff  $t_j$  is present in  $x$  and  $y = c_i$ .

## Q2: calculate $P(y|x)$

- The format of the model file:

Suppose  $x$  is "t1 t3"

FEATURES FOR CLASS  $c_1$

<default> 0.324

t1 0.245

t2 0.491

t3 -0.22

FEATURES FOR CLASS  $c_2$

<default> 0.456

t1 -30.4

t2 1.349

t3 2.42

$$p(c_1|x) = \frac{e^{\lambda_0(c_1) + \sum_{k=1}^K \lambda_k f_k(x, c_1)}}{Z}$$

$$p(c_1|x) = \frac{e^{0.324 + 0.245 - 0.22}}{Z}$$

$$p(c_2|x) = \frac{e^{\lambda_0(c_2) + \sum_{k=1}^K \lambda_k f_k(x, c_2)}}{Z}$$

$$p(c_2|x) = \frac{e^{0.456 - 30.4 + 2.42}}{Z}$$

...

$$P(c1 \mid x) = \frac{A}{Z}$$

$$P(c2 \mid x) = \frac{B}{Z}$$

$$P(c3 \mid x) = \frac{C}{Z}$$

$$Z = A + B + C$$

$$P(c1 \mid x) = \frac{A}{A+B+C}$$

$$P(c2 \mid x) = \frac{B}{A+B+C}$$

$$P(c3 \mid x) = \frac{C}{A+B+C}$$

Q3-Q4: calculate expectation

$$E_{\tilde{p}} f_j = \sum_{(x,y) \in X \times Y} \tilde{p}(x, y) f_j(x, y)$$

$$E_p f_j = \sum_{(x,y) \in X \times Y} p(x, y) f_j(x, y)$$