Sequence Report

Summary

Mic500 200k Termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep MIC 500	FAILED
Mic 2k 200k termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep MIC 2K	FAILED
Mic 2k 15dB PAD 200k termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep 15dB PAD	FAILED
Line Gain -10 200kTermination	
Signal Path Setup	PASSED
Stepped Frequency Sweep -10	FAILED
Line Gain -10 600 Termination	
Signal Path Setup	PASSED
Level and Gain -10	FAILED
Line Gain +5 200kTermination	
Signal Path Setup	PASSED
Stepped Frequency Sweep +5	PASSED
Line Gain +5 600 Termination	
Signal Path Setup	PASSED
Level and Gain +5	PASSED
Line Gain -5 600 Termination	
Signal Path Setup	PASSED
Level and Gain -5	PASSED
Line Gain 0 600 Termination	
Signal Path Setup	PASSED
Level and Gain 0	PASSED
Line Gain +10 600 Termination	
Signal Path Setup	PASSED
Level and Gain +10	PASSED
Line Gain +10 200k Termination Level Hi	
Signal Path Setup	PASSED
Noise Recorder (RMS) CW	FAILED
Line Gain +10 200k Termination Level Low	
Signal Path Setup	PASSED
Noise Recorder (RMS) CCW	FAILED
Hi Z Gain -10 2.2M 200k Termination	

Signal Path Setup	PASSED
Level and Gain 2.2M	PASSED
Hi Z Gain -10 47k 200k Termination	
Signal Path Setup	PASSED
Level and Gain 47K	FAILED
Dummy Signal Path For Report	
Signal Path Setup	PASSED
Sequence Result:	
Sequence Result:	FAILED

Mic500 200k Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Mic500 200k Termination : Verify Connections

Waveform:	Sine
Generator Level:	-42.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:04:11.384 PM)

Ch1 71.11 mVrms

Gain (5/7/2023 5:04:11.384 PM)

Ch1 21.558 dB

THD+N Ratio (5/7/2023 5:04:11.384 PM)

Ch1 ---- %

Frequency (5/7/2023 5:04:11.384 PM)

Ch1 ---- Hz

Mic500 200k Termination : Stepped Frequency Sweep MIC 500

Generator Level:	-42.300 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	5/7/2023 5:04:25 PM

RMS Level (5/7/2023 5:04:25.740 PM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (5/7/2023 5:04:25.740 PM)



Result: PASSED

THD Ratio (5/7/2023 5:04:25.740 PM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Mic 2k 200k termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Mic 2k 200k termination : Verify Connections

Waveform:	Sine
Generator Level:	-42.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:04:31.360 PM)

Ch1 71.12 mVrms

Gain (5/7/2023 5:04:31.360 PM)

Ch1 21.554 dB

THD+N Ratio (5/7/2023 5:04:31.360 PM)

Ch1 ---- %

Frequency (5/7/2023 5:04:31.360 PM)

Ch1 ---- Hz

Mic 2k 200k termination : Stepped Frequency Sweep MIC 2K

Generator Level:	-42.300 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	5/7/2023 5:04:45 PM

RMS Level (5/7/2023 5:04:45.921 PM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD Ratio (5/7/2023 5:04:45.921 PM)



Ch1 Failed Upper Limit

Result: FAILED

Mic 2k 15dB PAD 200k termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Mic 2k 15dB PAD 200k termination : Verify Connections

Waveform:	Sine
Generator Level:	-42.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:04:51.437 PM)

Ch1 71.07 mVrms

Gain (5/7/2023 5:04:51.437 PM)

Ch1 21.551 dB

THD+N Ratio (5/7/2023 5:04:51.437 PM)

Ch1 ---- %

Frequency (5/7/2023 5:04:51.437 PM)

Ch1 ---- Hz

Mic 2k 15dB PAD 200k termination : Stepped Frequency Sweep 15dB PAD

Generator Level:	-42.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	5/7/2023 5:05:07 PM

RMS Level (5/7/2023 5:05:07.581 PM)



Ch1 PASSED

Result: PASSED

THD Ratio (5/7/2023 5:05:07.581 PM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain -10 200kTermination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain -10 200kTermination : Verify Connections

Waveform:	Sine
Generator Level:	0.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:05:13.713 PM)

Ch1 8.402 Vrms

Gain (5/7/2023 5:05:13.713 PM)

Ch1 20.731 dB

THD+N Ratio (5/7/2023 5:05:13.713 PM)

Ch1 5.650031 %

Frequency (5/7/2023 5:05:13.713 PM)

Ch1 1.00000 kHz

Line Gain -10 200kTermination : Stepped Frequency Sweep -10

Generator Level:	0.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	15
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	5/7/2023 5:05:34 PM

RMS Level (5/7/2023 5:05:34.191 PM)



Ch1 ⚠ Failed Upper Limit

Result: FAILED

THD+N Ratio (5/7/2023 5:05:34.191 PM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain -10 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain -10 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:05:40.126 PM)

Ch1 2.464 Vrms

Gain (5/7/2023 5:05:40.126 PM)

Ch1 20.053 dB

THD+N Ratio (5/7/2023 5:05:40.126 PM)

Ch1 0.667448 %

Frequency (5/7/2023 5:05:40.126 PM)

Ch1 1.00000 kHz

Line Gain -10 600 Termination : Level and Gain -10

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:05:45.301 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-11.500 dBu	+10.053 dBu	-8.500 dBu	⚠

Result: ⚠ FAILED

Line Gain +5 200kTermination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +5 200kTermination : Verify Connections

Waveform:	Sine
Generator Level:	0.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:05:51.126 PM)

Ch1 5.010 Vrms

Gain (5/7/2023 5:05:51.126 PM)

Ch1 16.217 dB

THD+N Ratio (5/7/2023 5:05:51.126 PM)

Ch1 0.263096 %

Frequency (5/7/2023 5:05:51.126 PM)

Ch1 1.00000 kHz

Line Gain +5 200kTermination : Stepped Frequency Sweep +5

Generator Level:	0.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	15
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	5/7/2023 5:06:00 PM

RMS Level (5/7/2023 5:06:00.179 PM)



Ch1 PASSED

Result: PASSED

THD+N Ratio (5/7/2023 5:06:00.179 PM)



Ch1 PASSED

Result: PASSED

Line Gain +5 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +5 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:06.298 PM)

Ch1 1.395 Vrms

Gain (5/7/2023 5:06:06.298 PM)

Ch1 15.112 dB

THD+N Ratio (5/7/2023 5:06:06.298 PM)

Ch1 0.276856 %

Frequency (5/7/2023 5:06:06.298 PM)

Ch1 1.00000 kHz

Line Gain +5 600 Termination : Level and Gain +5

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:09.474 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	+3.500 dBu	+5.111 dBu	+6.500 dBu	✓

Result: ✓ PASSED

Line Gain -5 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain -5 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:15.372 PM)

Ch1 432.2 mVrms

Gain (5/7/2023 5:06:15.372 PM)

Ch1 4.933 dB

THD+N Ratio (5/7/2023 5:06:15.372 PM)

Ch1 0.183953 %

Frequency (5/7/2023 5:06:15.372 PM)

Ch1 1.00000 kHz

Line Gain -5 600 Termination : Level and Gain -5

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:18.689 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-6.500 dBu	-5.067 dBu	-3.500 dBu	✓

Result: ✓ PASSED

Line Gain 0 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain 0 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:24.669 PM)

Ch1 754.1 mVrms

Gain (5/7/2023 5:06:24.669 PM)

Ch1 9.767 dB

THD+N Ratio (5/7/2023 5:06:24.669 PM)

Ch1 0.165846 %

Frequency (5/7/2023 5:06:24.669 PM)

Ch1 1.00000 kHz

Line Gain 0 600 Termination : Level and Gain 0

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:27.951 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-1.500 dBu	-0.233 dBu	+1.500 dBu	✓

Result: ✓ PASSED

Line Gain +10 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +10 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:33.863 PM)

Ch1 2.465 Vrms

Gain (5/7/2023 5:06:33.863 PM)

Ch1 20.055 dB

THD+N Ratio (5/7/2023 5:06:33.863 PM)

Ch1 0.663292 %

Frequency (5/7/2023 5:06:33.863 PM)

Ch1 1.00000 kHz

Line Gain +10 600 Termination : Level and Gain +10

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:37.189 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	+8.500 dBu	+10.053 dBu	+11.500 dBu	✓

Result: ✓ PASSED

Line Gain +10 200k Termination Level Hi : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +10 200k Termination Level Hi : Verify Connections

Waveform:	Sine
Generator Level:	-20.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:06:43.248 PM)

Ch1 888.0 mVrms

Gain (5/7/2023 5:06:43.248 PM)

Ch1 21.187 dB

THD+N Ratio (5/7/2023 5:06:43.248 PM)

Ch1 2.277261 %

Frequency (5/7/2023 5:06:43.248 PM)

Ch1 1.00000 kHz

Line Gain +10 200k Termination Level Hi : Noise Recorder (RMS) CW

Waveform:	None
Low-pass Filter:	20 kHz
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Sweep Time:	0.00:00:03.000
Reading Rate:	10/sec
Input Bandwidth:	Use Signal Path
Record Acquisition:	False
Measured 1	5/7/2023 5:06:54 PM

RMS Level (5/7/2023 5:06:54.855 PM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Line Gain +10 200k Termination Level Low : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +10 200k Termination Level Low : Verify Connections

Waveform:	Sine
Generator Level:	-20.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:07:01.039 PM)

Ch1 888.0 mVrms

Gain (5/7/2023 5:07:01.039 PM)

Ch1 21.187 dB

THD+N Ratio (5/7/2023 5:07:01.039 PM)

Ch1 2.269391 %

Frequency (5/7/2023 5:07:01.039 PM)

Ch1 1.00000 kHz

Line Gain +10 200k Termination Level Low : Noise Recorder (RMS) CCW

Waveform:	None
Low-pass Filter:	20 kHz
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Sweep Time:	0.00:00:03.000
Reading Rate:	10/sec
Input Bandwidth:	Use Signal Path
Record Acquisition:	False
Measured 1	5/7/2023 5:07:14 PM

RMS Level (5/7/2023 5:07:14.377 PM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Hi Z Gain -10 2.2M 200k Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	2
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Hi Z Gain -10 2.2M 200k Termination : Verify Connections

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:07:20.085 PM)

Ch1 20.05 mVrms

Gain (5/7/2023 5:07:20.085 PM)

Ch1 -9.450 dB

THD+N Ratio (5/7/2023 5:07:20.085 PM)

Ch1 ---- %

Frequency (5/7/2023 5:07:20.085 PM)

Ch1 ---- Hz

Hi Z Gain -10 2.2M 200k Termination : Level and Gain 2.2M

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:07:23.842 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-2.000 dBu	-1.112 dBu	+2.000 dBu	✓

Result: ✓ PASSED

Hi Z Gain -10 47k 200k Termination : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Hi Z Gain -10 47k 200k Termination : Verify Connections

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:07:29.920 PM)

Ch1 20.12 mVrms

Gain (5/7/2023 5:07:29.920 PM)

Ch1 -9.369 dB

THD+N Ratio (5/7/2023 5:07:29.920 PM)

Ch1 ---- %

Frequency (5/7/2023 5:07:29.920 PM)

Ch1 ---- Hz

Hi Z Gain -10 47k 200k Termination : Level and Gain 47K

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:07:35.288 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-8.000 dBu	-31.754 dBu	-4.000 dBu	⚠

Result: ⚠ FAILED

Dummy Signal Path For Report : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Unbalanced
Channels:	2
Termination:	100 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Dummy Signal Path For Report : Verify Connections

Waveform:	Sine
Generator Level:	100.0 mVrms
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (5/7/2023 5:07:39.515 PM)

Ch1 14.32 uVrms

Ch2 7.346 uVrms