Sequence Report

Audio precision

Summary

Mic500 200k Termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep MIC 500	FAILED
Mic 2k 200k termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep MIC 2K	FAILED
Mic 2k 15dB PAD 200k termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep 15dB PAD	FAILED
Line Gain -10 200kTermination	
Signal Path Setup	PASSED
Stepped Frequency Sweep -10	FAILED
Line Gain -10 600 Termination	
Signal Path Setup	PASSED
Level and Gain -10	FAILED
Line Gain +5 200kTermination	
Signal Path Setup	PASSED
Stepped Frequency Sweep +5	FAILED
Line Gain +5 600 Termination	
Signal Path Setup	PASSED
Level and Gain +5	PASSED
Line Gain -5 600 Termination	
Signal Path Setup	PASSED
Level and Gain -5	PASSED
Line Gain 0 600 Termination	
Signal Path Setup	PASSED
Level and Gain 0	PASSED
Line Gain +10 600 Termination	
Signal Path Setup	PASSED
Level and Gain +10	PASSED
Line Gain +10 200k Termination Level Hi	
Signal Path Setup	PASSED
Noise Recorder (RMS) CW	FAILED
Line Gain +10 200k Termination Level Low	
Signal Path Setup	PASSED
Noise Recorder (RMS) CCW	PASSED
Hi Z Gain -10 2.2M 200k Termination	

Signal Path Setup	PASSED
Level and Gain 2.2M	PASSED
Hi Z Gain -10 47k 200k Termination	
Signal Path Setup	PASSED
Level and Gain 47K	PASSED
Dummy Signal Path For Report	
Signal Path Setup	PASSED
Sequence Result:	
Sequence Result:	FAILED

Mic500 200k Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Mic500 200k Termination : Verify Connections

Waveform:	Sine
Generator Level:	-42.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:10:50.224 AM)

Ch1 1.065 mVrms

Gain (6/1/2023 11:10:50.224 AM)

Ch1 -14.929 dB

THD+N Ratio (6/1/2023 11:10:50.224 AM)

Ch1 58.041292 %

Frequency (6/1/2023 11:10:50.224 AM)

Ch1 120.011 Hz

Mic500 200k Termination : Stepped Frequency Sweep MIC 500

Generator Level:	-42.300 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	6/1/2023 11:10:56 AM

RMS Level (6/1/2023 11:10:56.565 AM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (6/1/2023 11:10:56.565 AM)



Result: PASSED

THD Ratio (6/1/2023 11:10:56.565 AM)

Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Mic 2k 200k termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Mic 2k 200k termination : Verify Connections

Waveform:	Sine
Generator Level:	-42.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:11:02.024 AM)

Ch1 1.029 mVrms

Gain (6/1/2023 11:11:02.024 AM)

Ch1 -15.260 dB

THD+N Ratio (6/1/2023 11:11:02.024 AM)

Ch1 58.627921 %

Frequency (6/1/2023 11:11:02.024 AM)

Ch1 120.024 Hz

Mic 2k 200k termination : Stepped Frequency Sweep MIC 2K

Generator Level:	-42.300 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	6/1/2023 11:11:08 AM

RMS Level (6/1/2023 11:11:08.422 AM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD Ratio (6/1/2023 11:11:08.422 AM)



Ch1 Failed Upper Limit

Result: FAILED

Mic 2k 15dB PAD 200k termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Mic 2k 15dB PAD 200k termination : Verify Connections

Waveform:	Sine
Generator Level:	-42.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:11:13.925 AM)

Ch1 1.127 mVrms

Gain (6/1/2023 11:11:13.925 AM)

Ch1 -14.452 dB

THD+N Ratio (6/1/2023 11:11:13.925 AM)

Ch1 57.426691 %

Frequency (6/1/2023 11:11:13.925 AM)

Ch1 120.001 Hz

Mic 2k 15dB PAD 200k termination : Stepped Frequency Sweep 15dB PAD

Generator Level:	-42.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	6/1/2023 11:11:20 AM

RMS Level (6/1/2023 11:11:20.329 AM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD Ratio (6/1/2023 11:11:20.329 AM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain -10 200kTermination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain -10 200kTermination : Verify Connections

Waveform:	Sine
Generator Level:	0.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:11:26.164 AM)

Ch1 1.212 mVrms

Gain (6/1/2023 11:11:26.164 AM)

Ch1 -56.118 dB

THD+N Ratio (6/1/2023 11:11:26.164 AM)

Ch1 55.836574 %

Frequency (6/1/2023 11:11:26.164 AM)

Ch1 119.970 Hz

Line Gain -10 200kTermination : Stepped Frequency Sweep -10

Generator Level:	0.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	15
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	6/1/2023 11:11:34 AM

RMS Level (6/1/2023 11:11:34.541 AM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (6/1/2023 11:11:34.541 AM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain -10 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain -10 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:11:40.608 AM)

Ch1 1.061 mVrms

Gain (6/1/2023 11:11:40.608 AM)

Ch1 -47.270 dB

THD+N Ratio (6/1/2023 11:11:40.608 AM)

Ch1 55.772939 %

Frequency (6/1/2023 11:11:40.608 AM)

Ch1 120.016 Hz

Line Gain -10 600 Termination : Level and Gain -10

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:11:43.768 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-11.500 dBu	-57.267 dBu	-8.500 dBu	⚠

Result: ⚠ FAILED

Line Gain +5 200kTermination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +5 200kTermination : Verify Connections

Waveform:	Sine
Generator Level:	0.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:11:49.592 AM)

Ch1 6.848 mVrms

Gain (6/1/2023 11:11:49.592 AM)

Ch1 -41.060 dB

THD+N Ratio (6/1/2023 11:11:49.592 AM)

Ch1 54.830889 %

Frequency (6/1/2023 11:11:49.592 AM)

Ch1 120.025 Hz

Line Gain +5 200kTermination : Stepped Frequency Sweep +5

Generator Level:	0.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	15
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	6/1/2023 11:11:59 AM

RMS Level (6/1/2023 11:11:59.806 AM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (6/1/2023 11:11:59.806 AM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain +5 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +5 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:05.898 AM)

Ch1 1.383 Vrms

Gain (6/1/2023 11:12:05.898 AM)

Ch1 15.034 dB

THD+N Ratio (6/1/2023 11:12:05.898 AM)

Ch1 0.491287 %

Frequency (6/1/2023 11:12:05.898 AM)

Ch1 1.00000 kHz

Line Gain +5 600 Termination : Level and Gain +5

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:09.107 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	+3.500 dBu	+5.033 dBu	+6.500 dBu	✓

Result: ✓ PASSED

Line Gain -5 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain -5 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:15.074 AM)

Ch1 428.4 mVrms

Gain (6/1/2023 11:12:15.074 AM)

Ch1 4.855 dB

THD+N Ratio (6/1/2023 11:12:15.074 AM)

Ch1 0.426363 %

Frequency (6/1/2023 11:12:15.074 AM)

Ch1 1.00000 kHz

Line Gain -5 600 Termination : Level and Gain -5

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:18.364 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-6.500 dBu	-5.145 dBu	-3.500 dBu	✓

Result: ✓ PASSED

Line Gain 0 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain 0 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:24.359 AM)

Ch1 747.5 mVrms

Gain (6/1/2023 11:12:24.359 AM)

Ch1 9.690 dB

THD+N Ratio (6/1/2023 11:12:24.359 AM)

Ch1 0.440110 %

Frequency (6/1/2023 11:12:24.359 AM)

Ch1 1.00000 kHz

Line Gain 0 600 Termination : Level and Gain 0

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:27.667 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-1.500 dBu	-0.310 dBu	+1.500 dBu	✓

Result: ✓ PASSED

Line Gain +10 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +10 600 Termination : Verify Connections

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:33.710 AM)

Ch1 2.438 Vrms

Gain (6/1/2023 11:12:33.710 AM)

Ch1 19.959 dB

THD+N Ratio (6/1/2023 11:12:33.710 AM)

Ch1 0.596800 %

Frequency (6/1/2023 11:12:33.710 AM)

Ch1 1.00000 kHz

Line Gain +10 600 Termination : Level and Gain +10

Waveform:	Sine
Generator Level:	-10.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:37.055 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	+8.500 dBu	+9.957 dBu	+11.500 dBu	✓

Result: ✓ PASSED

Line Gain +10 200k Termination Level Hi : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +10 200k Termination Level Hi : Verify Connections

Waveform:	Sine
Generator Level:	-20.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:43.022 AM)

Ch1 877.2 mVrms

Gain (6/1/2023 11:12:43.022 AM)

Ch1 21.080 dB

THD+N Ratio (6/1/2023 11:12:43.022 AM)

Ch1 1.323537 %

Frequency (6/1/2023 11:12:43.022 AM)

Ch1 1.00000 kHz

Line Gain +10 200k Termination Level Hi : Noise Recorder (RMS) CW

Waveform:	None
Low-pass Filter:	20 kHz
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Sweep Time:	0.00:00:03.000
Reading Rate:	10/sec
Input Bandwidth:	Use Signal Path
Record Acquisition:	False
Measured 1	6/1/2023 11:12:48 AM

RMS Level (6/1/2023 11:12:48.082 AM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Line Gain +10 200k Termination Level Low : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Line Gain +10 200k Termination Level Low : Verify Connections

Waveform:	Sine
Generator Level:	-20.000 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:12:54.270 AM)

Ch1 23.02 uVrms

Gain (6/1/2023 11:12:54.270 AM)

Ch1 -70.559 dB

THD+N Ratio (6/1/2023 11:12:54.270 AM)

Ch1 ---- %

Frequency (6/1/2023 11:12:54.270 AM)

Ch1 ---- Hz

Line Gain +10 200k Termination Level Low : Noise Recorder (RMS) CCW

Waveform:	None
Low-pass Filter:	20 kHz
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Sweep Time:	0.00:00:03.000
Reading Rate:	10/sec
Input Bandwidth:	Use Signal Path
Record Acquisition:	False
Measured 1	6/1/2023 11:12:59 AM

RMS Level (6/1/2023 11:12:59.982 AM)



Ch1 PASSED

Result: PASSED

Hi Z Gain -10 2.2M 200k Termination : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Hi Z Gain -10 2.2M 200k Termination : Verify Connections

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:13:05.991 AM)

Ch1 3.615 mVrms

Gain (6/1/2023 11:13:05.991 AM)

Ch1 -24.319 dB

THD+N Ratio (6/1/2023 11:13:05.991 AM)

Ch1 71.978540 %

Frequency (6/1/2023 11:13:05.991 AM)

Ch1 59.9918 Hz

Hi Z Gain -10 2.2M 200k Termination : Level and Gain 2.2M

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:13:10.046 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-2.000 dBu	+0.209 dBu	+2.000 dBu	✓

Result: ✓ PASSED

Hi Z Gain -10 47k 200k Termination : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Hi Z Gain -10 47k 200k Termination : Verify Connections

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:13:15.972 AM)

Ch1 405.8 mVrms

Gain (6/1/2023 11:13:15.972 AM)

Ch1 16.684 dB

THD+N Ratio (6/1/2023 11:13:15.972 AM)

Ch1 0.574557 %

Frequency (6/1/2023 11:13:15.972 AM)

Ch1 1.00000 kHz

Hi Z Gain -10 47k 200k Termination : Level and Gain 47K

Waveform:	Sine
Generator Level:	-22.300 dBu
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:13:19.338 AM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-8.000 dBu	-5.616 dBu	-4.000 dBu	✓

Result: ✓ PASSED

Dummy Signal Path For Report : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Unbalanced
Channels:	2
Termination:	100 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None

• References

dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm

• DCX

DCX is not detected.

Dummy Signal Path For Report : Verify Connections

Waveform:	Sine
Generator Level:	100.0 mVrms
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (6/1/2023 11:13:23.346 AM)

Ch1 78.16 uVrms
Ch2 7.469 uVrms