Sequence Report

Audio precision

Summary

Mic500 200k Termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep MIC 500	FAILED
Mic 2k 200k termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep MIC 2K	FAILED
Mic 2k 15dB PAD 200k termination	
Signal Path Setup	PASSED
Stepped Frequency Sweep 15dB PAD	FAILED
Line Gain -10 200kTermination	
Signal Path Setup	PASSED
Stepped Frequency Sweep -10	FAILED
Line Gain -10 600 Termination	
Signal Path Setup	PASSED
Level and Gain -10	PASSED
Line Gain +5 200kTermination	
Signal Path Setup	PASSED
Stepped Frequency Sweep +5	FAILED
Line Gain +5 600 Termination	
Signal Path Setup	PASSED
Level and Gain +5	FAILED
Line Gain -5 600 Termination	
Signal Path Setup	PASSED
Level and Gain -5	FAILED
Line Gain 0 600 Termination	
Signal Path Setup	PASSED
Level and Gain 0	FAILED
Line Gain +10 600 Termination	
Signal Path Setup	PASSED
Level and Gain +10	FAILED
Line Gain +10 200k Termination Level Hi	
Signal Path Setup	PASSED
Noise Recorder (RMS) CW	FAILED
Line Gain +10 200k Termination Level Low	
Signal Path Setup	PASSED
Noise Recorder (RMS) CCW	FAILED
Hi Z Gain -10 2.2M 200k Termination	

Signal Path Setup	PASSED
Level and Gain 2.2M	FAILED
Hi Z Gain -10 47k 200k Termination	
Signal Path Setup	PASSED
Level and Gain 47K	FAILED
DummyPathForReport	
Signal Path Setup	PASSED

Sequence Result:

Sequence Result:	FAILED

Mic500 200k Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Mic500 200k Termination : Verify Connections

Waveform: Sine

Generator Level: -42.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:45:15.609 PM)

Ch1 282.1 mVrms

Gain (4/29/2023 10:45:15.609 PM)

Ch1 33.526 dB

THD+N Ratio (4/29/2023 10:45:15.609 PM)

Ch1 ---- %

Frequency (4/29/2023 10:45:15.609 PM)

Ch1 ---- Hz

Mic500 200k Termination : Stepped Frequency Sweep MIC 500

Generator Level:	-42.300 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	4/29/2023 10:45:23 PM

RMS Level (4/29/2023 10:45:23.720 PM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (4/29/2023 10:45:23.720 PM)



Result: PASSED

THD Ratio (4/29/2023 10:45:23.720 PM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Mic 2k 200k termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Mic 2k 200k termination : Verify Connections

Waveform: Sine

Generator Level: -42.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:45:28.898 PM)

Ch1 288.8 mVrms

Gain (4/29/2023 10:45:28.898 PM)

Ch1 33.729 dB

THD+N Ratio (4/29/2023 10:45:28.898 PM)

Ch1 ---- %

Frequency (4/29/2023 10:45:28.898 PM)

Ch1 ---- Hz

Mic 2k 200k termination : Stepped Frequency Sweep MIC 2K

Generator Level:	-42.300 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	4/29/2023 10:45:36 PM

RMS Level (4/29/2023 10:45:36.790 PM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD Ratio (4/29/2023 10:45:36.790 PM)



Ch1 Failed Upper Limit

Result: FAILED

Mic 2k 15dB PAD 200k termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Mic 2k 15dB PAD 200k termination : Verify Connections

Waveform: Sine

Generator Level: -42.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:45:42.375 PM)

Ch1 273.1 mVrms

Gain (4/29/2023 10:45:42.375 PM)

Ch1 33.245 dB

THD+N Ratio (4/29/2023 10:45:42.375 PM)

Ch1 ---- %

Frequency (4/29/2023 10:45:42.375 PM)

Ch1 ---- Hz

Mic 2k 15dB PAD 200k termination : Stepped Frequency Sweep 15dB PAD

Generator Level:	-42.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	10
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	4/29/2023 10:45:51 PM

RMS Level (4/29/2023 10:45:51.509 PM)



Ch1 ⚠ Failed Upper Limit

Result: FAILED

THD Ratio (4/29/2023 10:45:51.509 PM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain -10 200kTermination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain -10 200kTermination : Verify Connections

Waveform: Sine

Generator Level: 0.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:45:56.755 PM)

Ch1 289.3 mVrms

Gain (4/29/2023 10:45:56.755 PM)

Ch1 -8.554 dB

THD+N Ratio (4/29/2023 10:45:56.755 PM)

Ch1 ---- %

Frequency (4/29/2023 10:45:56.755 PM)

Ch1 ---- Hz

Line Gain -10 200kTermination : Stepped Frequency Sweep -10

Generator Level:	0.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	15
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	4/29/2023 10:46:07 PM

RMS Level (4/29/2023 10:46:07.133 PM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (4/29/2023 10:46:07.133 PM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain -10 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain -10 600 Termination : Verify Connections

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:12.534 PM)

Ch1 291.8 mVrms

Gain (4/29/2023 10:46:12.534 PM)

Ch1 1.519 dB

THD+N Ratio (4/29/2023 10:46:12.534 PM)

Ch1 ---- %

Frequency (4/29/2023 10:46:12.534 PM)

Ch1 ---- Hz

Line Gain -10 600 Termination : Level and Gain -10

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:16.474 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-11.500 dBu	-8.697 dBu	-8.500 dBu	✔

Result: ✔ PASSED

Line Gain +5 200kTermination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain +5 200kTermination : Verify Connections

Waveform: Sine

Generator Level: 0.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:21.911 PM)

Ch1 296.3 mVrms

Gain (4/29/2023 10:46:21.911 PM)

Ch1 -8.348 dB

THD+N Ratio (4/29/2023 10:46:21.911 PM)

Ch1 ---- %

Frequency (4/29/2023 10:46:21.911 PM)

Ch1 ---- Hz

Line Gain +5 200kTermination : Stepped Frequency Sweep +5

Generator Level:	0.000 dBu
DC Offset:	0.000 V
EQ:	None
Start Frequency:	20.0000 kHz
Stop Frequency:	20.0000 Hz
Step Type:	Logarithmic
Number of Points:	15
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Phase Ref Channel:	Ch1
Measured 1	4/29/2023 10:46:32 PM

RMS Level (4/29/2023 10:46:32.313 PM)



Ch1 ⚠ Failed Lower Limit

Result: FAILED

THD+N Ratio (4/29/2023 10:46:32.313 PM)



Ch1 Failed Upper Limit

Result: FAILED

Line Gain +5 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain +5 600 Termination : Verify Connections

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:38.025 PM)

Ch1 290.2 mVrms

Gain (4/29/2023 10:46:38.025 PM)

Ch1 1.471 dB

THD+N Ratio (4/29/2023 10:46:38.025 PM)

Ch1 ---- %

Frequency (4/29/2023 10:46:38.025 PM)

Ch1 ---- Hz

Line Gain +5 600 Termination : Level and Gain +5

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:41.912 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	+3.500 dBu	-8.484 dBu	+6.500 dBu	⚠

Result: ⚠ FAILED

Line Gain -5 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain -5 600 Termination : Verify Connections

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:47.326 PM)

Ch1 285.1 mVrms

Gain (4/29/2023 10:46:47.326 PM)

Ch1 1.319 dB

THD+N Ratio (4/29/2023 10:46:47.326 PM)

Ch1 ---- %

Frequency (4/29/2023 10:46:47.326 PM)

Ch1 ---- Hz

Line Gain -5 600 Termination : Level and Gain -5

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:51.245 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-6.500 dBu	-8.557 dBu	-3.500 dBu	⚠

Result: ⚠ FAILED

Line Gain 0 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain 0 600 Termination : Verify Connections

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:46:56.679 PM)

Ch1 289.9 mVrms

Gain (4/29/2023 10:46:56.679 PM)

Ch1 1.463 dB

THD+N Ratio (4/29/2023 10:46:56.679 PM)

Ch1 ---- %

Frequency (4/29/2023 10:46:56.679 PM)

Ch1 ---- Hz

Line Gain 0 600 Termination : Level and Gain 0

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:00.549 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-1.500 dBu	-8.550 dBu	+1.500 dBu	⚠

Result: ⚠ FAILED

Line Gain +10 600 Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	600 ohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain +10 600 Termination : Verify Connections

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:05.967 PM)

Ch1 285.8 mVrms

Gain (4/29/2023 10:47:05.967 PM)

Ch1 1.339 dB

THD+N Ratio (4/29/2023 10:47:05.967 PM)

Ch1 ---- %

Frequency (4/29/2023 10:47:05.967 PM)

Ch1 ---- Hz

Line Gain +10 600 Termination : Level and Gain +10

Waveform: Sine

Generator Level: -10.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:10.110 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	+8.500 dBu	-8.646 dBu	+11.500 dBu	⚠

Result: ⚠ FAILED

Line Gain +10 200k Termination Level Hi : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain +10 200k Termination Level Hi : Verify Connections

Waveform: Sine

Generator Level: -20.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:15.834 PM)

Ch1 291.9 mVrms

Gain (4/29/2023 10:47:15.834 PM)

Ch1 11.523 dB

THD+N Ratio (4/29/2023 10:47:15.834 PM)

Ch1 ---- %

Frequency (4/29/2023 10:47:15.834 PM)

Ch1 ---- Hz

Line Gain +10 200k Termination Level Hi : Noise Recorder (RMS) CW

Waveform:	None
Low-pass Filter:	20 kHz
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Sweep Time:	0.00:00:03.000
Reading Rate:	10/sec
Input Bandwidth:	Use Signal Path
Record Acquisition:	False
Measured 1	4/29/2023 10:47:28 PM

RMS Level (4/29/2023 10:47:28.257 PM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Line Gain +10 200k Termination Level Low : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	1
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Line Gain +10 200k Termination Level Low : Verify Connections

Waveform: Sine

Generator Level: -20.000 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:33.745 PM)

Ch1 295.5 mVrms

Gain (4/29/2023 10:47:33.745 PM)

Ch1 11.631 dB

THD+N Ratio (4/29/2023 10:47:33.745 PM)

Ch1 ---- %

Frequency (4/29/2023 10:47:33.745 PM)

Ch1 ---- Hz

Line Gain +10 200k Termination Level Low : Noise Recorder (RMS) CCW

Waveform:	None
Low-pass Filter:	20 kHz
Weighting Filter:	Signal Path
High-pass Filter:	20 Hz
Sweep Time:	0.00:00:03.000
Reading Rate:	10/sec
Input Bandwidth:	Use Signal Path
Record Acquisition:	False
Measured 1	4/29/2023 10:47:47 PM

RMS Level (4/29/2023 10:47:47.899 PM)



Ch1 ⚠ Failed Upper Limit

Result: ⚠ FAILED

Hi Z Gain -10 2.2M 200k Termination : Signal Path Setup

Output Connector:	Analog Balanced
Channels:	2
Source Impedance:	100 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Hi Z Gain -10 2.2M 200k Termination : Verify Connections

Waveform: Sine

Generator Level: -22.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:53.239 PM)

Ch1 292.1 mVrms

Gain (4/29/2023 10:47:53.239 PM)

Ch1 13.829 dB

THD+N Ratio (4/29/2023 10:47:53.239 PM)

Ch1 ---- %

Frequency (4/29/2023 10:47:53.239 PM)

Ch1 ---- Hz

Hi Z Gain -10 2.2M 200k Termination : Level and Gain 2.2M

Waveform: Sine

Generator Level: -22.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:47:58.721 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-2.000 dBu	-8.709 dBu	+2.000 dBu	⚠

Result: ⚠ FAILED

Hi Z Gain -10 47k 200k Termination : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Balanced
Channels:	1
Channel:	Ch1
Termination:	200 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00

Port D (hex): 00

Hi Z Gain -10 47k 200k Termination : Verify Connections

Waveform: Sine

Generator Level: -22.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:48:04.221 PM)

Ch1 279.5 mVrms

Gain (4/29/2023 10:48:04.221 PM)

Ch1 13.445 dB

THD+N Ratio (4/29/2023 10:48:04.221 PM)

Ch1 ---- %

Frequency (4/29/2023 10:48:04.221 PM)

Ch1 ---- Hz

Hi Z Gain -10 47k 200k Termination : Level and Gain 47K

Waveform: Sine

Generator Level: -22.300 dBu

DC Offset: 0.000 V

Frequency: 1.00000 kHz

RMS Level (4/29/2023 10:48:08.482 PM)

Channel	Lower Limit	Value	Upper Limit	
Ch1	-8.000 dBu	-8.634 dBu	-4.000 dBu	⚠

Result: ⚠ FAILED

DummyPathForReport : Signal Path Setup

Output Connector:	Analog Unbalanced
Channels:	2
Source Impedance:	50 ohm
Output EQ:	None
Input Connector:	Analog Unbalanced
Channels:	2
Termination:	100 kohm
Input Bandwidth:	AC (<10 Hz) - 90k (192 kHz SR)
Device Delay:	0.000 s
Input EQ:	None
• References	
dBr G:	100.0 mVrms
dBm (Output Power):	600.0 ohm
W(watts) (Output Power):	8.000 ohm
Shared Frequency Reference:	1.00000 kHz
dBrA:	1.000 Vrms
dBrB:	1.000 Vrms
dBrA Offset:	0.000 dB
dBrB Offset:	0.000 dB
dBSPL1:	10.00 mVrms
dBSPL2:	10.00 mVrms
dBSPL1 Calibrator Level:	94.000 dBSPL
dBSPL2 Calibrator Level:	94.000 dBSPL
dBm (Input Power):	600.0 ohm
W(watts) (Input Power):	8.000 ohm
• DCX	
DC Output 1:	0.000 V
DC Output 1:	Off
DC Output 2:	0.000 V
DC Output 2:	Off
Port A (hex):	00
Port B (hex):	00
Port C (hex):	00
Port D (hex):	00

DummyPathForReport : Verify Connections

Waveform:	Sine
Generator Level:	100.0 mVrms
DC Offset:	0.000 V
Frequency:	1.00000 kHz

RMS Level (4/29/2023 10:48:12.128 PM)

Ch1 285.8 mVrms

Ch2 288.4 mVrms