NPF: a new packet filter

Zoltán Arnold Nagy The NetBSD Foundation zoltan@netbsd.org • What is a packet filter?

- What is a packet filter?
 - A boolean valued function $(f : \mathbb{P} \to \mathbb{B})$

- What is a packet filter?
 - A boolean valued function $(f : \mathbb{P} \to \mathbb{B})$
- How can it be implemented?

- What is a packet filter?
 - A boolean valued function $(f : \mathbb{P} \to \mathbb{B})$
- How can it be implemented?
 - boolean expression tree
 - directed acyclic control flow graph
 - if-then-else hell

A sea of firewalls

- IPFilter (ipf)
- FreeBSD's ipfw
- OpenBSD's pf
- NetBSD's npf

How NPF started out

- Sponsored by The NetBSD Foundation
- Written by Mindaugas Rasiukevicius (rmind@) from scratch, altought the design was inspired by the Berkeley Packet Filter
- First imported to -current in August 2010

 Goal: The program's goal is to promote open-source software development among students and get them actually involved

- Goal: The program's goal is to promote open-source software development among students and get them actually involved
- Mentoring organizations apply with a set of proposed projects

- Goal: The program's goal is to promote open-source software development among students and get them actually involved
- Mentoring organizations apply with a set of proposed projects
- Students apply for organizations with a proposal based either on a proposed project or a new one

- Goal: The program's goal is to promote open-source software development among students and get them actually involved
- Mentoring organizations apply with a set of proposed projects
- Students apply for organizations with a proposal based either on a proposed project or a new one
- Organizations get a number of slots for students

- Goal: The program's goal is to promote open-source software development among students and get them actually involved
- Mentoring organizations apply with a set of proposed projects
- Students apply for organizations with a proposal based either on a proposed project or a new one
- Organizations get a number of slots for students
- Mentoring organizations get \$500 per student, students get \$5000

- Goal: The program's goal is to promote open-source software development among students and get them actually involved
- Mentoring organizations apply with a set of proposed projects
- Students apply for organizations with a proposal based either on a proposed project or a new one
- Organizations get a number of slots for students
- Mentoring organizations get \$500 per student, students get \$5000
- It has been running since 2005
 - 2011: 175 mentoring organizations, 1115 students
- NetBSD has participated every year so far with a high success rate
 - 2011: 9 projects, 8 projects ended with success
 - Already accepted for 2012 as a mentoring organization
- My GSoC proposal for 2011 was to add IPv6 support to NPF
 - committed to -current in November 2011



Motivations and goals

- There a few existing firewalls
- It's easier to design a new firewall from ground up than to clean up existing codebases
- Design goals for NPF:
 - MP-safety and locklessness for scalable MP performance
 - Fast tree- and hash-based lookup support for tables
 - Stateful packet filtering
 - N-Code processor, a general bytecode engine
 - Keep configuration syntax changes to a minimum
 - Modularity, extensibility: an extension API for developers, hooking support
 - Last but not least: simplicity
- Of course it's portable, uses pfil(9) hooks; DragonFlyBSD is considering adoption
- Work in progress



Usage

- npfct1 can be used to communicate with /dev/npf via ioctls
 start, stop, reload, flush, stats, tables, sessions, ...
- Rules are translated into bytecode, and pushed down to the kernel
- The parser has been recently rewritten by christos@ based on martin@'s code

Features - variables and groups

```
ext_if = "wm0"
int_if = "wm1"
group (name "external", interface $ext_if) {
group (name "internal", interface $int_if) {
group (default) {
   block all
```

Features - rule procedures

Allows connection-based packet transformation

```
procedure "rid" {
    normalize (random-id)
}

procedure "log" {
    log npflog0
}
```

Features - tables

```
table "1" type tree dynamic
table "2" type hash file "/etc/npf_backlist"
group (default) {
   block in quick from <1>
   block out quick to <2>
}
```

What can it do today?

- Rule syntax is nearly identical to other firewalls
- Group support
- Rule procedures (connection-based packet transformations)
 - IP ID randomization
 - enforcement of TCP minimum TTL
 - enforcement of TCP Maximum Segment Size (MSS)
 - logging
- Tables support
- Application-level gateways (ALGs)

```
ext if = "wm0"
int_if = "wm1"
table "1" type "tree" dynamic
procedure "rid" { normalize (random-id) }
procedure "log" { log npflog0 }
group (name "external", interface $ext_if) {
    block in quick from <1>
    pass out quick from $ext_if keep state apply "rid"
    pass in quick proto tcp to $ext_if port ssh apply "log"
    . . .
}
group (name "internal", interface $int_if) {
    block in all
   pass in quick from <1>
   pass out quick all
}
group (default) { block all }
```

Inside

N-code engine:

- General purpose bytecode engine, 32-bit words, 4 registers available
- The firewall configuration is compiled to our bytecode format, then loaded
- CISC and RISC-like instructions
- The packets are processed as a byte-stream

Efficient internal structures

- npf_addr (in6_addr, 128-bit) for addresses (the first 32 bit is used for IPv4 addresses)
- uint8 t for masks
 - instead of generating the appropriate npf_addr value from 255.255.255.0 or /24, we just store the mask (<=128)
 - tradeoff: CPU for memory



Inside

Let's see what we can work with...

```
typedef struct {
        /* Information flags. */
        uint32 t
                                npc info:
        /* Pointers to the IP v4/v6 addresses. */
        npf_addr_t *
                                npc_srcip;
        npf_addr_t *
                                npc_dstip;
        /* Size (v4 or v6) of IP addresses. */
        int
                                npc_ipsz;
        size_t
                                npc_hlen;
        int
                                npc_next_proto;
        /* IPv4, IPv6. */
        union {
                struct ip
                                v4:
                struct ip6_hdr v6;
        } npc_ip;
        /* TCP, UDP, ICMP. */
        union {
                struct tcphdr
                               tcp;
                struct udphdr
                                udp;
                struct icmp
                                icmp;
        } npc_14;
} npf_cache_t;
```

• Replace red-black trees with Patricia (radix) trees for tables

- Replace red-black trees with Patricia (radix) trees for tables
- Pregenerate an array for masks

- Replace red-black trees with Patricia (radix) trees for tables
- Pregenerate an array for masks
- Support per-rule statistics

- Replace red-black trees with Patricia (radix) trees for tables
- Pregenerate an array for masks
- Support per-rule statistics
- Multiple address per interface support on interface-based rules
- Dynamic interface tracking
 - Let's say you have a rule based on an interface instead of an address...
 - ...you compile and load the rules...
 - ...then change the interface's address?
- Control fragmentation on a per-interface basis

- Replace red-black trees with Patricia (radix) trees for tables
- Pregenerate an array for masks
- Support per-rule statistics
- Multiple address per interface support on interface-based rules
- Dynamic interface tracking
 - Let's say you have a rule based on an interface instead of an address...
 - ...you compile and load the rules...
 - ...then change the interface's address?
- Control fragmentation on a per-interface basis
- Stateful NAT64 [RFC 6146]
- IPv6-to-IPv6 Network Prefix Translation (NPTv6) [RFC 6296]

- Replace red-black trees with Patricia (radix) trees for tables
- Pregenerate an array for masks
- Support per-rule statistics
- Multiple address per interface support on interface-based rules
- Dynamic interface tracking
 - Let's say you have a rule based on an interface instead of an address...
 - ...you compile and load the rules...
 - ...then change the interface's address?
- Control fragmentation on a per-interface basis
- Stateful NAT64 [RFC 6146]
- IPv6-to-IPv6 Network Prefix Translation (NPTv6) [RFC 6296]
- Write more documentation and bug-fix...



Questions and answers?

Thank you! Arigatou gozaimashita!