

Owanbe — Railway Staging Guide

Staging deploy - Supabase migrations first

Document date: 30 July 2026

Owanbe Planner v6 - internal / developer documentation

Table of Contents

Overview

1. Supabase (do this first)
2. Connect repository
3. Environment variables
4. Build and start commands
5. Custom domain (optional)
6. Post-deploy verification
7. Redeploy workflow

Related docs

Version: 6.0.0

Date: 2026-07-30

Overview

Railway hosts the built static site or a static file server for staging. Supabase remains the database - link the same project and apply migrations before the first staging deploy.

1. Supabase (do this first)

```
cd owanbe-6
npx supabase login
npx supabase link --project-ref YOUR_PROJECT_REF
npx supabase db push
```

Or run supabase/APPLY_ALL.sql in the Supabase SQL Editor.

Verify tables: events, brands, user_roles, admin_permissions.

2. Connect repository

1. Railway -> New Project -> Deploy from GitHub repo (`owanbe-6`).
 2. Select branch used for staging (e.g. `main` or `staging`).
-

3. Environment variables

In Railway -> Service -> Variables, set (for build):

Variable	Value
VITE_SUPABASE_URL	Your Supabase URL
VITE_SUPABASE_ANON_KEY	Anon key
NODE_VERSION	20 (optional)

Add any other VITE_* keys your app expects.

4. Build and start commands

Static SPA (recommended):

- Build command: npm install && npm run build
 - Start command: npx serve dist -s -l \$PORT
- (-s enables SPA fallback to index.html)

Add serve to package.json dependencies or use npx serve as above.

Alternative: Railway Static Site template if available - build npm run build, publish dist/.

5. Custom domain (optional)

Railway -> Settings -> Generate domain or attach custom domain. Rebuild after env changes.

6. Post-deploy verification

1. Open staging URL - landing page loads.
 2. Sign in as `oadeagbo@gmail.com` - super admin / admin tabs on `/admin`.
 3. `/dashboard` - no `public.event` / `public.brand` schema errors (plural tables `events`, `brands`).
 4. New reviewer signups receive admin permissions (migration behavior).
-

7. Redeploy workflow

1. Push code to connected branch.
 2. Railway rebuilds automatically.
 3. If only SQL changed, run migrations in Supabase - no Railway rebuild required.
-

Related docs

- docs/OWANBE-FIX-REPORT.pdf - root cause and fixes
- docs/AWS_DEPLOY_GUIDE.pdf - production AWS path
- supabase/migrations/ - full migration chain