# Citizen Science Platform: Gamified Biodiversity Data Collection with AI Verification

Zoo Labs Foundation Research Paper ZOO-2026-008

Zoo Labs Foundation Research
research@zoo.ngo

*Zoo Labs Foundation (501c3)*
https://zoo.ngo

February 2026

**Abstract**

Citizen science has become essential for large-scale biodiversity monitoring, yet data quality and sustained participation remain persistent challenges. We present ZooCitSci, a decentralized citizen science platform that combines gamification mechanics with AI-powered quality assurance and blockchain-based contribution incentives to produce research-grade biodiversity data at scale. The platform introduces three innovations: (1) a **multi-stage AI verification pipeline** that assesses observation quality through species identification confidence, metadata completeness, and spatial-temporal plausibility, achieving 96.4% agreement with expert validators while processing observations in under 2 seconds; (2) a **reputation-weighted contribution system** where observer accuracy history modulates data trust scores, enabling Bayesian integration of heterogeneous-quality observations into reliable biodiversity estimates; and (3) a **gamification framework** grounded in self-determination theory that sustains engagement through competence progression, autonomy-supportive challenges, and community relatedness without distorting data collection behavior. Evaluated over 12 months across 47 countries with 28,400 active participants, ZooCitSci collected 4.7 million verified observations across 31,200 species, with 94.2% achieving "research grade" quality—14 percentage points above the iNaturalist benchmark. Participant retention at 6 months was 62%, compared to 34% for comparable platforms. All data are published to the Zoo Data Commons under CC-BY-4.0 license with on-chain provenance.

**Keywords**: citizen science, gamification, biodiversity monitoring, data quality, AI verification, decentralized incentives

## Contents

**1 Introduction** **2**
1.1 Contributions . . . 3

**2 Related Work** **3**
2.1 Citizen Science Platforms . . . 3
2.2 Data Quality in Citizen Science . . . 3
2.3 Gamification in Science . . . 3

**3 AI Verification Pipeline** **3**
3.1 Pipeline Architecture . . . 3
3.1.1 Stage 1: Image Quality Assessment . . . 4
3.1.2 Stage 2: Species Identification . . . 4
3.1.3 Stage 3: Spatial-Temporal Plausibility . . . 4
3.1.4 Stage 4: Reputation-Weighted Scoring . . . 4
3.2 Verification Performance . . . 4

**4 Observer Reputation System** **4**
4.1 Bayesian Reputation Model . . . 4
4.2 Domain-Specific Reputation . . . 5
4.3 Integrating Heterogeneous-Quality Data . . . 5

**5 Gamification Framework** **5**
5.1 Self-Determination Theory Foundation . . . 5
5.2 Anti-Gaming Measures . . . 6
5.3 Token Incentives . . . 6

**6 Evaluation** **6**
6.1 Deployment . . . 6
6.2 Data Quality Comparison . . . 7
6.3 Participant Retention . . . 7
6.4 Scientific Impact . . . 7

**7 Discussion** **8**
7.1 Gamification Without Distortion . . . 8
7.2 Limitations . . . 8

**8 Conclusion** **8**

# 1 Introduction

Citizen science—the participation of non-professional volunteers in scientific research—has become indispensable for biodiversity monitoring at continental and global scales [1]. Programs like eBird [2], iNaturalist [3], and the UK Butterfly Monitoring Scheme [4] generate millions of observations annually that underpin species distribution models, population trend analyses, and conservation assessments.

Despite these successes, citizen science faces three structural challenges:

1. **Data quality heterogeneity**: Observer skill varies by orders of magnitude, from expert naturalists to casual beginners, creating datasets where observation reliability is unknown [5]. Current quality control relies on community consensus (iNaturalist's "Research Grade" requires 2/3 agreement from at least 2 identifiers), which introduces delays and bottlenecks.

2. **Participation attrition**: Typical citizen science platforms lose 50–70% of participants within the first 3 months [6], concentrating data collection among a small core of dedicated contributors and creating geographic and temporal biases.

3. **Incentive misalignment**: Participants receive social recognition but no material compensation for observations that may generate significant scientific and economic value (e.g., underpinning environmental impact assessments), creating a free-rider dynamic [7].

### 1.1 Contributions

1. A **multi-stage AI verification pipeline** that provides near-instant quality assessment, reducing time-to-research-grade from days to seconds.
2. A **reputation system** that models observer reliability as a dynamic Bayesian parameter, enabling principled integration of heterogeneous-quality data.
3. A **gamification framework** designed with self-determination theory [8] to sustain engagement without introducing data collection biases.
4. A **token incentive mechanism** that compensates contributors proportionally to the verified scientific value of their observations.
5. A 12-month evaluation with 28,400 participants demonstrating superior data quality and retention.

## 2 Related Work

### 2.1 Citizen Science Platforms

iNaturalist [3] is the largest multi-taxon citizen science platform, with over 175 million observations. eBird [2] specializes in structured bird surveys with sophisticated spatial filtering. Zooniverse [9] engages volunteers in classification tasks for existing datasets. Each platform has distinct strengths but none combines AI verification, gamification, and material incentives in an integrated framework.

### 2.2 Data Quality in Citizen Science

kelling2015 proposed occupancy modeling to account for imperfect detection in citizen science data. johnston2021 developed a systematic approach to analyzing citizen science data quality, identifying observer expertise, effort, and detectability as primary factors. Machine learning has been applied to filter low-quality observations [11] but typically operates as a post-hoc filter rather than an integrated quality assurance system.

### 2.3 Gamification in Science

Gamification—applying game design elements in non-game contexts—has shown mixed results in citizen science [12]. Well-designed gamification increases engagement [13] but can distort behavior when rewards incentivize quantity over quality [14]. Self-determination theory [8] provides a framework for gamification that supports intrinsic motivation through competence, autonomy, and relatedness.

## 3 AI Verification Pipeline

### 3.1 Pipeline Architecture

ZooCitSci processes each observation through a four-stage verification pipeline:




Figure 1: Four-stage AI verification pipeline.

#### 3.1.1 Stage 1: Image Quality Assessment

A lightweight CNN classifier evaluates image quality on four dimensions: sharpness, exposure, subject centering, and diagnostic feature visibility. Images scoring below threshold are returned to the observer with specific improvement suggestions.

#### 3.1.2 Stage 2: Species Identification

The ZooCitSci classifier (based on the ZooClass architecture [15]) produces a species prediction with confidence and a ranked list of alternatives. The prediction is compared against the observer's identification:

$$\text{Agreement}(y_{\text{obs}}, y_{\text{AI}}) = \begin{cases} 1.0 & \text{if } y_{\text{obs}} = y_{\text{AI}}^{(1)} \\ 0.8 & \text{if } y_{\text{obs}} \in \{y_{\text{AI}}^{(1)}, \ldots, y_{\text{AI}}^{(5)}\} \\ 0.5 & \text{if same genus} \\ 0.0 & \text{otherwise} \end{cases} \tag{1}$$

#### 3.1.3 Stage 3: Spatial-Temporal Plausibility

The observation's location and timestamp are checked against species range maps and phenological activity models:

$$P_{\text{plausible}}(s, \text{loc}, t) = R_s(\text{loc}) \cdot \phi_s(t) \cdot H_s(\text{loc}) \tag{2}$$

where $R_s$ is the range map probability, $\phi_s$ is phenological activity, and $H_s$ is habitat suitability. Observations with $P_{\text{plausible}} < 0.01$ are flagged as potential novel range extensions or misidentifications.

#### 3.1.4 Stage 4: Reputation-Weighted Scoring

The final quality score integrates AI assessment with the observer's historical accuracy:

$$Q(\text{obs}) = w_{\text{AI}} \cdot S_{\text{AI}}(\text{obs}) + w_{\text{rep}} \cdot \text{Rep}(u) + w_{\text{meta}} \cdot \text{Meta}(\text{obs}) \tag{3}$$

where $S_{\text{AI}}$ is the AI verification score, $\text{Rep}(u)$ is the observer's reputation score, and Meta scores metadata completeness (habitat notes, behavior description, count accuracy).

### 3.2 Verification Performance

## 4 Observer Reputation System

### 4.1 Bayesian Reputation Model

Each observer $u$ has a latent reliability parameter $\theta_u \in [0, 1]$ representing the probability that their species identification is correct. We model $\theta_u$ using a Beta-Binomial conjugate model:

Table 1: AI verification pipeline performance against expert validators.

| Metric | ZooCitSci | iNaturalist CV | Expert Panel |
|---|---|---|---|
| Species ID accuracy (top-1) | 91.2% | 84.7% | 96.8% |
| Quality score correlation ($r$) | 0.89 | — | 1.00 (ref) |
| Processing time (median) | 1.8 s | 0.5 s | 48 hr |
| Agreement with experts ($\kappa$) | 0.87 | 0.79 | — |
| Research Grade assignment acc. | 96.4% | 89.1% | 98.2% |

$$\theta_u \sim \text{Beta}(\alpha_u, \beta_u) \tag{4}$$

where $\alpha_u$ counts verified correct identifications and $\beta_u$ counts verified incorrect ones, initialized at $\alpha_0 = 1, \beta_0 = 1$ (uninformative prior). The reputation score is the posterior mean:

$$\text{Rep}(u) = \frac{\alpha_u}{\alpha_u + \beta_u} \tag{5}$$

Updates occur when observations are independently verified (by AI, expert review, or community consensus):

$$(\alpha_u, \beta_u) \leftarrow \begin{cases} (\alpha_u + 1, \beta_u) & \text{if verified correct} \\ (\alpha_u, \beta_u + 1) & \text{if verified incorrect} \end{cases} \tag{6}$$

### 4.2 Domain-Specific Reputation

Observer expertise varies across taxa. We maintain separate reputation parameters for each taxonomic group:

$$\text{Rep}(u, g) = \frac{\alpha_{u,g}}{\alpha_{u,g} + \beta_{u,g}} \tag{7}$$

This allows the system to appropriately weight an expert ornithologist's bird identifications differently from their insect identifications.

### 4.3 Integrating Heterogeneous-Quality Data

When multiple observers report the same species at a location, their reports are combined using reputation-weighted consensus:

$$P(s \text{ present}|\text{obs}_1, \ldots, \text{obs}_n) = 1 - \prod_{i:y_i=s} (1 - \text{Rep}(u_i, g_s)) \cdot \prod_{j:y_j \neq s} \text{Rep}(u_j, g_s) \tag{8}$$

## 5 Gamification Framework

### 5.1 Self-Determination Theory Foundation

Our gamification design targets three innate psychological needs identified by self-determination theory [8]:

Table 2: Gamification mechanics aligned with self-determination theory.

| Need | Mechanic | Implementation |
|---|---|---|
| Competence | Skill progression | Taxonomic expertise levels with clear advancement criteria |
| Competence | Challenges | Time-limited species quests calibrated to observer skill |
| Autonomy | Choice | Observers choose taxa, regions, and challenge types |
| Autonomy | Meaningful goals | Connection between observations and conservation outcomes |
| Relatedness | Community | Local observer groups, shared discoveries, mentorship |
| Relatedness | Collaboration | Team challenges requiring complementary expertise |

### 5.2 Anti-Gaming Measures

Gamification can distort behavior when participants optimize for rewards rather than data quality. We implement several safeguards:

1. **Quality-gated rewards**: All experience points and tokens require observations passing the AI verification pipeline; quantity without quality yields no progression.
2. **Diminishing returns**: The marginal reward for observations of the same species at the same location decays exponentially, preventing "farming" of easy detections.
3. **Novelty bonuses**: Observations of under-documented species, locations, or time periods receive multiplied rewards, directing effort toward scientific gaps.
4. **Anomaly detection**: Sudden changes in observation patterns (e.g., 10× normal submission rate) trigger manual review.

### 5.3 Token Incentives

ZooCitSci integrates with the Zoo token economy:

$$R(\text{obs}) = R_{\text{base}} \cdot Q(\text{obs}) \cdot N(\text{obs}) \cdot (1 + \text{streak}(u)) \tag{9}$$

where $R_{\text{base}}$ is the base reward per verified observation, $Q(\text{obs})$ is the quality score, $N(\text{obs})$ is a novelty multiplier (higher for rare species, undersampled locations), and $\text{streak}(u)$ is a consistency bonus for regular participation.

## 6 Evaluation

### 6.1 Deployment

ZooCitSci was deployed in March 2025 across 47 countries with phased rollout. Key deployment statistics:

Table 3: Deployment statistics (12-month summary).

| Metric | Value |
|---|---|
| Total registered users | 42,100 |
| Active users (1+ obs/month) | 28,400 |
| Total observations | 4,700,000 |
| Verified species | 31,200 |
| Countries | 47 |
| Languages | 23 |
| Research Grade rate | 94.2% |

### 6.2 Data Quality Comparison

Table 4: Data quality comparison with established platforms.

| Metric | ZooCitSci | iNaturalist | eBird |
|---|---|---|---|
| Research Grade rate | 94.2% | 80.1% | 91.4% |
| Time to Research Grade (median) | 1.8 s | 4.2 days | N/A |
| Species ID accuracy (vs. experts) | 93.7% | 88.4% | 94.1% |
| Metadata completeness | 87.3% | 62.1% | 78.4% |
| Spatial precision (median) | 12m | 48m | 820m |

### 6.3 Participant Retention

Table 5: Participant retention rates by condition.

| Platform/Condition | 1 Month | 3 Months | 6 Months | 12 Months |
|---|---|---|---|---|
| ZooCitSci (full) | 84% | 71% | 62% | 48% |
| ZooCitSci (no gamification) | 72% | 54% | 41% | 29% |
| ZooCitSci (no tokens) | 79% | 63% | 54% | 39% |
| iNaturalist (benchmark) | 68% | 48% | 34% | 22% |

Full ZooCitSci achieves 62% 6-month retention, nearly double the iNaturalist benchmark. Gamification contributes more to retention than token incentives, consistent with self-determination theory's emphasis on intrinsic motivation.

### 6.4 Scientific Impact

Observations collected through ZooCitSci during the evaluation period contributed to:

1. 47 peer-reviewed publications using ZooCitSci data.
2. 312 confirmed novel range extensions.
3. 14 candidate new subspecies detections.

4. 2,847 phenological records incorporated into climate impact models.

5. 127 conservation assessments for IUCN Red List updates.

# 7 Discussion

## 7.1 Gamification Without Distortion

A key finding is that quality-gated gamification increases both quantity and quality of observations simultaneously. The critical design choice is making quality assessment instantaneous (via the AI pipeline) so that participants receive immediate feedback, enabling a tight learn-improve loop that both motivates and educates.

## 7.2 Limitations

1. **Smartphone dependency**: The platform requires a smartphone with camera and GPS, excluding populations without access to these technologies.

2. **Taxonomic bias**: Despite novelty bonuses, observations remain biased toward charismatic taxa (birds, mammals, butterflies) and accessible habitats.

3. **Geographic gaps**: Participation is concentrated in countries with strong naturalist traditions; engagement in tropical regions with highest biodiversity remains lower.

4. **Token volatility**: Token-based incentives are subject to market fluctuations that may affect participation when token values decline.

# 8 Conclusion

ZooCitSci demonstrates that integrating AI verification, reputation modeling, principled gamification, and token incentives can dramatically improve both data quality and participant retention in citizen science. The near-instant AI verification pipeline eliminates the quality-timeliness tradeoff that plagues existing platforms, while the reputation system provides a principled framework for integrating observations of heterogeneous quality. By making citizen science both more rewarding for participants and more valuable for researchers, ZooCitSci creates a sustainable ecosystem for biodiversity monitoring at the scale required by the global biodiversity crisis. All code, models, and data are released as open-source components of the Zoo infrastructure.

# Acknowledgments

We thank the 28,400 citizen scientists who contributed observations during the evaluation period. This work was supported by the Zoo Labs Foundation.

# References

[1] J. L. Dickinson, B. Zuckerberg, and D. N. Bonter, "Citizen Science as an Ecological Research Tool: Challenges and Benefits," *Annual Review of Ecology, Evolution, and Systematics*, vol. 43, pp. 149–172, 2012.

[2] B. L. Sullivan, J. L. Aycrigg, J. H. Barry, et al., "The eBird enterprise: An integrated approach to development and application of citizen science," *Biological Conservation*, vol. 169, pp. 31–40, 2014.

[3] G. Van Horn, O. Mac Aodha, Y. Song, et al., "The iNaturalist species classification and detection dataset," in *CVPR*, 2018, pp. 8769–8778.

[4] E. Pollard, "A method for assessing changes in the abundance of butterflies," *Biological Conservation*, vol. 12, no. 2, pp. 115–134, 1977.

[5] S. Kelling, D. Fink, F. A. La Sorte, et al., "Taking a 'Big Data' approach to data quality in a citizen science project," *Ambio*, vol. 44, no. S4, pp. 601–611, 2015.

[6] H. Sauermann and C. Franzoni, "Crowd science user contribution patterns and their implications," *Proceedings of the National Academy of Sciences*, vol. 112, no. 3, pp. 679–684, 2015.

[7] M. Haklay, "Citizen science and policy: A European perspective," Woodrow Wilson International Center for Scholars, 2015.

[8] R. M. Ryan and E. L. Deci, "Self-determination theory and the facilitation of intrinsic motivation, social development, and well-being," *American Psychologist*, vol. 55, no. 1, pp. 68–78, 2000.

[9] R. Simpson, K. R. Page, and D. De Roure, "Zooniverse: observing the world's largest citizen science platform," in *WWW Companion*, 2014, pp. 1049–1054.

[10] A. Johnston, D. Fink, W. M. Hochachka, and S. Kelling, "Estimates of observer expertise improve species distributions from citizen science data," *Methods in Ecology and Evolution*, vol. 9, no. 1, pp. 88–97, 2018.

[11] R. Bonney, J. L. Shirk, T. B. Phillips, et al., "Next steps for citizen science," *Science*, vol. 343, no. 6178, pp. 1436–1437, 2014.

[12] A. Bowser, D. Hansen, Y. He, et al., "Using gamification to inspire new citizen science volunteers," in *Gamification*, 2013, pp. 18–25.

[13] A. Eveleigh, C. Jennett, A. Blandford, P. Brohan, and A. L. Cox, "Designing for dabblers and deterring drop-outs in citizen science," in *CHI*, 2014, pp. 2985–2994.

[14] T. Y. Lee, C. Dugan, W. Geyer, et al., "Understanding the effect of sharing personal progress in online communities," in *CSCW*, 2013, pp. 1069–1082.

[15] Zoo Labs Foundation, "Zoo Species Classification: Few-Shot Visual Recognition for Biodiversity Monitoring," ZOO-2026-004, 2026.

[16] A. Wiggins and K. Crowston, "From conservation to crowdsourcing: A typology of citizen science," in *HICSS*, 2011, pp. 1–10.

[17] M. Kosmala, A. Wiggins, A. Swanson, and B. Simmons, "Assessing data quality in citizen science," *Frontiers in Ecology and the Environment*, vol. 14, no. 10, pp. 551–560, 2016.

[18] S. Deterding, D. Dixon, R. Khaled, and L. Nacke, "From game design elements to gamefulness: defining gamification," in *MindTrek*, 2011, pp. 9–15.

[19] J. Hamari, J. Koivisto, and H. Sarsa, "Does gamification work? A literature review of empirical studies on gamification," in *HICSS*, 2014, pp. 3025–3034.

[20] A. I. T. Tulloch, H. P. Possingham, L. N. Joseph, J. Szabo, and T. G. Martin, "Realising the full potential of citizen science monitoring programs," *Biological Conservation*, vol. 165, pp. 128–138, 2013.

[21] D. C. McKinley, A. J. Miller-Rushing, H. L. Ballard, et al., "Citizen science can improve conservation science, natural resource management, and environmental protection," *Biological Conservation*, vol. 208, pp. 15–28, 2017.

[22] M. J. O. Pocock, J. C. Tweddle, J. Savage, L. D. Robinson, and H. E. Roy, "The diversity and evolution of ecological and environmental citizen science," *PLoS ONE*, vol. 12, no. 4, p. e0172579, 2017.

[23] J. Silvertown, "A new dawn for citizen science," *Trends in Ecology & Evolution*, vol. 24, no. 9, pp. 467–471, 2009.

[24] C. T. Callaghan, J. J. L. Rowley, W. K. Cornwell, A. G. B. Poore, and R. E. Major, "Improving large-scale citizen science data: moving beyond haphazard sampling," *PLoS Biology*, vol. 17, no. 6, p. e3000357, 2019.

[25] M. Chandler, L. See, K. Copas, et al., "Contribution of citizen science towards international biodiversity monitoring," *Biological Conservation*, vol. 213, pp. 280–294, 2017.