

maix.touchscreen

maix.touchscreen module

You can use `maix.touchscreen` to access this module with MaixPy

This module is generated from `MaixPy` and `MaixCDK`

1. Module

No module

2. Enum

3. Variable

4. Function

5. Class

5.1. TouchScreen

TouchScreen class

C++ definition code:

```
1 | class TouchScreen
```

5.1.1. __init__

```
1 | def __init__(self, device: str = '',  
    open: bool = True) -> None
```

Construct a new TouchScreen object

item	description
type	func
param	device: touchscreen device path, you can get devices by list_devices method, by default(value is NULL(None in MaixPy)) means the first device open: If true, touchscreen will automatically call open() after creation. default is true.
static	False

C++ defination code:

```
1 | TouchScreen(const std::string  
    &device = "", bool open = true)
```

5.1.2. open

```
1 | def open(self) -> maix.err.Err
```

open touchscreen device

item	description
type	func
return	error code, err::ERR_NONE means success, others means failed
static	False

C++ definition code:

```
1 | err::Err open()
```

5.1.3. close

```
1 | def close(self) -> maix.err.Err
```

close touchscreen device

item	description
type	func
return	error code, err::ERR_NONE means success, others means failed
static	False

C++ definition code:

```
1 | err::Err close()
```

5.1.4. read

```
1 | def read(self) -> list[int]
```

read touchscreen device

item	description
type	func
attention	This method will discard same event in buffer, that is: if too many move event in buffer when call this method, it will only return the last one, and if read pressed or released event, it will return immediately.
return	Returns a list include x, y, pressed state
static	False

C++ definition code:

```
1 | std::vector<int> read()
```

5.1.5. read0

```
1 | def read0(self) -> list[int]
```

read touchscreen device

item	description
type	func
attention	This method will return immediately if have event, so it's better to use available() to check if

item	description
	have more event in buffer, or too much event in buffer when your program call this read() interval is too long will make your program slow.
return	Returns a list include x, y, pressed state
static	False

C++ defination code:

```
1 | std::vector<int> read0()
```

5.1.6. available

```
1 | def available(self, timeout: int =  
   | 0) -> bool
```

If we need to read from touchscreen, for event
driven touchscreen means have event or not

item	description
type	func
param	timeout: -1 means block, 0 means no block, >0 means timeout, default is 0, unit is ms.
return	true if need to read(have event), false if not

item	description
static	False
C++ definition code:	
<pre>1 bool available(int timeout = 0)</pre>	

5.1.7. is_opened

```
1 | def is_opened(self) -> bool
```

Check if touchscreen is opened

item	description
type	func
return	true if touchscreen is opened, false if not
static	False
C++ definition code:	
<pre>1 bool is_opened()</pre>	