28-Lead Very Thin Plastic Quad Flat, No Lead Package (PBA) - 5x5 mm Body [VQFN] With Multiple Fused Exposed Pads

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Microchip Technology Drawing C04-1038 Rev A Sheet 1 of 2

28-Lead Very Thin Plastic Quad Flat, No Lead Package (PBA) - 5x5 mm Body [VQFN] With Multiple Fused Exposed Pads

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		28	
Pitch	e		0.50 BSC	
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3		0.203 REF	
Overall Length	D		5.00 BSC	
Overall Width	E		5.00 BSC	
Terminal Width	b	0.20	0.25	0.30
Terminal Length	L	0.55	0.60	0.65

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Exposed Pad Length	D2	0.97	1.02	1.07
Exposed Pad Length	D3	0.57	0.62	0.67
Exposed Pad Length	D4		0.106 REF	
Exposed Pad Width	E2	0.71	0.735	0.76
Exposed Pad Width	E3	0.40	0.45	0.50
Exposed Pad Width	E4		1.28 REF	
Exposed Pad Width	E5		2.79 REF	

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

   REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1038 Rev A Sheet 2 of 2

28-Lead Very Thin Plastic Quad Flat, No Lead Package (PBA) - 5x5 mm Body [VQFN] With Multiple Fused Exposed Pads

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

	Units	MILLIMETERS		
	Dimension Limits	MIN	NOM	MAX
Contact Pitch	E		0.50	
Center Pad Width	X2			1.02
Center Pad Width (X2)	X3			0.62
Center Pad Length	Y2			0.72
Center Pad Length (X2)	Y3			0.45
Contact Pad Spacing	C1		5.20	
Contact Pad Spacing	C2		5.20	
Contact Pad Width (X28)	X1			0.25
Contact Pad Length (X28)	Y1			0.65
Contact Pad to Center Pad (X2)	G1		0.35 REF	
Contact Pad to Contact Pad (X24)	G2	0.25		
Thermal Via Diameter	V		0.33	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3038 Rev A