Packaging Diagrams and Parameters

32-Lead Very-Thin Panel Quad Flatpack No-Leads (9GW) 3.5x3.5x0.9mm Body [VPQFN] Panel Level Package with 1.8x1.8mm Exposed Pad

Note:	For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Microchip Technology Drawing C04-00684 Rev A Sheet 1 of 2

© 2025 Microchip Technology Inc.

32-Lead Very-Thin Panel Quad Flatpack No-Leads (9GW) 3.5x3.5x0.9mm Body [VPQFN] Panel Level Package with 1.8x1.8mm Exposed Pad

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		32	
Pitch	e		0.35 BSC	
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.025	0.035	0.045
Protective Layer	A3		0.025 REF	
Overall Length	D		3.50 BSC	
Exposed Pad Length	D2	1.70	1.80	1.90
Overall Width	E		3.50 BSC	
Exposed Pad Width	E2	1.70	1.80	1.90
Terminal Width	b	0.12	-	0.18
Terminal Length	L	0.22	0.30	0.38
Terminal-to-Exposed-Pad	K	0.43	-	-

Notes:

1. The Pin 1 visual index feature may vary, but it must be located within the hatched area.
2. The package is saw singulated.
3. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. The theoretically exact value is shown without tolerances.
   REF: Reference Dimension, usually without tolerances, is for information purposes only.

Microchip Technology Drawing C04-00684 Rev A Sheet 2 of 2

© 2025 Microchip Technology Inc.

32-Lead Very-Thin Panel Quad Flatpack No-Leads (9GW) 3.5x3.5x0.9mm Body [VPQFN] Panel Level Package with 1.8x1.8mm Exposed Pad

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

	Units	MILLIMETERS		
	Dimension Limits	MIN	NOM	MAX
Contact Pitch	E		0.35 BSC	
Center Pad Width	X2			1.90
Center Pad Length	Y2			1.90
Contact Pad Spacing	C1		3.20	
Contact Pad Spacing	C2		3.20	
Contact Pad Width (X32)	X1			0.15
Contact Pad Length (X32)	Y1			0.40
Contact Pad to Center Pad (X32)	G1	0.50		
Contact Pad to Contact Pad (X28)	G2	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. The theoretically exact value is shown without tolerances.
2. For best soldering results, please refer to the current industry standard IPC-7093.

Microchip Technology Drawing C04-02684 Rev A

© 2025 Microchip Technology Inc.