


Packaging Diagrams and Parameters

48-Leads Extremely Thin Fine Pitch Land Grid Array (CF) - 4x6 mm Body [XFLGA] SST LEGACY C1QE and C1QF

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing C04-163-CF Rev A Sheet 1 of 2

Packaging Diagrams and Parameters

48-Leads Extremely Thin Fine Pitch Land Grid Array (CF) - 4x6 mm Body [XFLGA] SST LEGACY C1QE and C1QF

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



		Units	MILLIMETERS		
Dimension Limits			MIN	NOM	MAX
Number of Terminals	N		48		
Pitch	e		0.50 BSC		
Overall Height	A	-		0.473	0.520
Standoff	A1		0.025	0.04	0.065
Overall Length	D		4.00 BSC		
Overall Terminal Spacing	D1			2.50 BSC	
Overall Width	E		6.00 BSC		
Exposed Pad Width	E2			5.00 BSC	
Terminal Width	b		0.24	0.29	0.34


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

Land Pattern

48-Leads Extremely Thin Fine Pitch Land Grid Array (CF) - 4x6 mm Body [XFLGA] SST LEGACY C1QE and C1QF

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Contact Pad Spacing	C1		2.50	
Contact Pad Spacing	C2		5.00	
Contact Pad Diameter (X48)	X			0.29

Notes:


- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2163-CF Rev A

Packaging Diagrams and Parameters

48-Leads Extremely Thin Fine Pitch Land Grid Array (CJ) - 4x6 mm Body [XFLGA] SST LEGACY CAQE and CAQF

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing C04-163-CJ Rev A Sheet 1 of 2

Packaging Diagrams and Parameters

48-Leads Extremely Thin Fine Pitch Land Grid Array (CJ) - 4x6 mm Body [XFLGA] SST LEGACY CAQE and CAQF

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	48		
Pitch	e	0.50 BSC		
Overall Height	A	-	0.473	0.520
Standoff	A1	0.025	0.04	0.065
Overall Length	D	4.00 BSC		
Overall Terminal Spacing	D1		2.50 BSC	
Overall Width	E	6.00 BSC		
Exposed Pad Width	E2		5.00 BSC	
Terminal Width	b	0.24	0.29	0.34


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

Land Pattern

48-Leads Extremely Thin Fine Pitch Land Grid Array (CJ) - 4x6 mm Body [XFLGA] SST LEGACY CAQE and CAQF

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.50 BSC	
Contact Pad Spacing	C1		2.50	
Contact Pad Spacing	C2		5.00	
Contact Pad Diameter (X48)	X			0.29

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2163-CJ Rev A