



# 12-Lead Very, Very Thin Plastic Quad Flat, No Lead (2PX) - 3x3x0.8 mm Body [WQFN] Supertex Legacy Package K7

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



## 12-Lead Very, Very Thin Plastic Quad Flat, No Lead (2PX) - 3x3x0.8 mm Body [WQFN] Supertex Legacy Package K7

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




|                         |    | Units | MILLIMETERS |      |      |
|-------------------------|----|-------|-------------|------|------|
| Dimension Limits        |    |       | MIN         | NOM  | MAX  |
| Number of Terminals     | N  |       | 12          |      |      |
| Pitch                   | e  |       | 0.50 BSC    |      |      |
| Overall Height          | A  |       | 0.70        | 0.75 | 0.80 |
| Standoff                | A1 |       | 0.00        | 0.02 | 0.05 |
| Terminal Thickness      | A3 |       | 0.20 REF    |      |      |
| Overall Length          | D  |       | 3.00 BSC    |      |      |
| Exposed Pad Length      | D2 |       | 1.25        | 1.45 | 1.65 |
| Overall Width           | E  |       | 3.00 BSC    |      |      |
| Exposed Pad Width       | E2 |       | 1.25        | 1.45 | 1.65 |
| Terminal Width          | b  |       | 0.18        | 0.25 | 0.30 |
| Terminal Length         | L  |       | 0.30        | 0.40 | 0.50 |
| Pullback (Note 3)       | L1 |       | —           | —    | 0.15 |
| Terminal-to-Exposed-Pad | K  |       | 0.38 REF    |      |      |

### Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Depending on the method of manufacturing, a maximum of 0.15mm pullback (L1) may be present.
- Dimensioning and tolerancing per ASME Y14.5M
  - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
  - REF: Reference Dimension, usually without tolerance, for information purposes only.

## 12-Lead Very, Very Thin Plastic Quad Flat, No Lead (2PX) - 3x3x0.8 mm Body [WQFN] Supertex Legacy Package K7

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



### RECOMMENDED LAND PATTERN

| Units                            |    | MILLIMETERS |      |      |
|----------------------------------|----|-------------|------|------|
| Dimension Limits                 |    | MIN         | NOM  | MAX  |
| Contact Pitch                    | E  | 0.50 BSC    |      |      |
| Optional Center Pad Width        | X2 |             |      | 1.65 |
| Optional Center Pad Length       | Y2 |             |      | 1.65 |
| Contact Pad Spacing              | C1 |             | 3.00 |      |
| Contact Pad Spacing              | C2 |             | 3.00 |      |
| Contact Pad Width (Xnn)          | X1 |             |      | 0.30 |
| Contact Pad Length (Xnn)         | Y1 |             |      | 0.85 |
| Contact Pad to Center Pad (Xnn)  | G1 | 0.25        |      |      |
| Contact Pad to Contact Pad (Xnn) | G2 | 0.20        |      |      |
| Thermal Via Diameter             | V  |             | 0.30 |      |
| Thermal Via Pitch                | EV |             | 1.00 |      |

#### Notes:

- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2302 Rev A